

PAVEMENT SCHEDULE	
B1	Prop. Var. Depth Leveling Course Type S-4.75A at an Average Rate of 100 lbs. Per Square Yard Per 1" of Depth. The Avg. Wheel Path Width Shall be Approx. 4'.
B2	Proposed Approximately 5-1/2" of Asphalt Concrete Base Course, Type B-25.0B at an Average Rate of 627 lbs. per square yard.
C1	Proposed Approximately 1-1/2" of Asphalt Concrete Surface Course, Type S-9.5B at an Average Rate of 168 lbs. per square yard
C2	Proposed Approximately 1-1/2" of Asphalt Concrete Surface Course, Type SF-9.5A at an Average Rate of 165 lbs. per square yard
M1	Milling Depth 0" - 1.5" at the Edge of Curb & Gutter. Milling Shall Extend Below the Lip of the Curb & Gutter by the Thickness of the Proposed Overlay or as Directed by the Engineer.
M2	Milling Depth 1.5" for Entire Width of Roadway. Milling at Edge of Curb & Gutter Shall Extend Below the Lip of the Curb & Gutter by the Thickness of the Proposed Overlay or as Directed by the Engineer.
S	Shoulder Reconstruction as Directed by the Engineer
DRAWINGS NOT TO SCALE	