PROJ. REFERENCE NO. SHEET NO. R-2568B TCP-16

PHASE II

STEP 1. PLACE PAVEMENT MARKINGS AND MARKERS AS MUCH AS POSSIBLE AWAY FROM TRAFFIC ON -L- (NORTHBOUND LANES) FROM STA. 58+60+/- TO STA. 73+20+/- AS SHOWN ON TCP-18 THRU TCP-22.

WORK IN A CONTINUOUS MANNER TO COMPLETE THE FOLLOWING WORK IN STEP 2 THRU STEP 4:

USING ROADWAY STANDARD DRAWING NO. 1101.02 AND FLAGGERS, PLACE EXISTING NC 109 TRAFFIC IN THE LEFT LANE IN A ONE-LANE, TWO-WAY PATTERN FROM STA. 58+60+/- TO STA. 73+20+/-.

PLACE PAVEMENT MARKINGS AND MARKERS AS MUCH AS POSSIBLE ON NEW -L- NORTH BOUND LANES FOR THE TEMPORARY TRAFFIC PATTERN AS SHOWN ON TCP-18 THRU TCP-22.

USING FLAGGERS, SHIFT EXISTING NC 109 TRAFFIC ONTO THE RIGHT LANE OF -L- IN A ONE-LANE, TWO-WAY PATTERN. INSTALL TEMPORARY CONCRETE BARRIER AND CRASH CUSHION FROM STA. 58+40+/- TO STA. 61+05+/- (ATTACH CONCRETE BARRIER TO THE NEW -L- NORTHBOUND STRUCTURE RAIL).

PLACE REMAINING PAVEMENT MARKINGS AND MARKERS ON NEW -L- NORTH BOUND LANES FOR THE TEMPORARY TRAFFIC PATTERN AS SHOWN ON TCP-18 THRU TCP-22.

OPEN -L- (NORTHBOUND LANES) TO THE TEMORARY TRAFFIC PATTERN AS SHOWN ON TCP-18 THRU TCP-22. INSTALL TYPE III BARRICADES TO CLOSE EXISTING NC 109 ROADWAY TO TRAFFIC.

USING ROADWAY STANDARD DRAWING NO. 1101.02 AND FLAGGERS, INSTALL TEMPORARY CONCRETE BARRIER AND CRASH CUSHIONS AT THE FOLLOWING LOCATION AS SHOWN ON TCP-21 THRU TCP-22:

-L- STA. 71+30+/- TO-STA. 73+40+/- (LEFT)

GRADE AND CONSTRUCT -L- (SOUTHBOUND LANES) UP TO, BUT NOT INCLUDING, THE FINAL LAYER AND PROPOSED STRUCTURE THROUGH THE FOLLOWING LOCATIONS AS SHOWN ON TCP-18 THRU TCP-19 AND TCP-21 THRU TCP-22:

-L- STA. 58+60+/- TO STA. 62+20+/--L- STA. 69+70+/- TO STA. 73+30+/-

CONSTRUCT THE FOLLOWING PROPOSED ROADWAYS UP TO, BUT NOT INCLUDING, THE FINAL LAYER AS SHOWN ON TCP-21 AND TCP-22 AND CONSTRUCTION PLANS:

-Y14A--Y12DET-

COMPLETE ALL ROADWAY AND STRUCTURE WORK FOR PHASE II

APPROVED: DATE: 9/1/04

PHASE II

NONE 01/04 DWG. BY: SJS DESIGN BY: SJS REVIEWED BY: CLM

REVISIONS