

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL UNIT



SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION		GRADATION		ROCK DESCRIPTION		TERMS AND DEFINITIONS																																																																											
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER 30 cm ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:</p> <p align="center"><i>VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGH PLASTIC, A-7-6</i></p>		<p>WELL GRADED- INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE UNIFORM- INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE (ALSO POORLY GRADED). GAP-GRADED- INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p align="center">ANGULARITY OF GRAINS</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS: <u>ANGULAR</u>, <u>SUBANGULAR</u>, <u>SUBROUNDED</u>, OR <u>ROUNDED</u>.</p>		<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 2.5 cm PER 50 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>		<p>ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOOD - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOADED FROM PARENT MATERIAL. FLOOD PLAIN (F.P.) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.</p>																																																																											
SOIL LEGEND AND AASHTO CLASSIFICATION				MINERALOGICAL COMPOSITION																																																																													
<p>GENERAL CLASS.</p> <table border="1"> <tr> <th colspan="2">GRANULAR MATERIALS (>85% PASSING #200)</th> <th colspan="2">SILT-CLAY MATERIALS (>85% PASSING #200)</th> <th colspan="2">ORGANIC MATERIALS</th> </tr> <tr> <td>A-1</td><td>A-3</td><td>A-2</td><td>A-4</td><td>A-5</td><td>A-7</td> </tr> <tr> <td>A-1-a</td><td>A-1-b</td><td>A-2-4</td><td>A-2-5</td><td>A-2-6</td><td>A-2-7</td> </tr> </table>		GRANULAR MATERIALS (>85% PASSING #200)		SILT-CLAY MATERIALS (>85% PASSING #200)		ORGANIC MATERIALS		A-1	A-3	A-2	A-4	A-5	A-7	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p>		<p>CRYSTALLINE ROCK (CR)</p> <p>NON-CRYSTALLINE ROCK (NCR)</p> <p>COASTAL PLAIN SEDIMENTARY ROCK (CP)</p>		<p>WEATHERED ROCK (WR)</p> <p>CRYSTALLINE ROCK (CR)</p> <p>NON-CRYSTALLINE ROCK (NCR)</p> <p>COASTAL PLAIN SEDIMENTARY ROCK (CP)</p>																																																									
GRANULAR MATERIALS (>85% PASSING #200)		SILT-CLAY MATERIALS (>85% PASSING #200)		ORGANIC MATERIALS																																																																													
A-1	A-3	A-2	A-4	A-5	A-7																																																																												
A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7																																																																												
<p>GROUP CLASS.</p> <table border="1"> <tr> <th colspan="2">GRANULAR MATERIALS (>85% PASSING #200)</th> <th colspan="2">SILT-CLAY MATERIALS (>85% PASSING #200)</th> <th colspan="2">ORGANIC MATERIALS</th> </tr> <tr> <td>A-1</td><td>A-3</td><td>A-2</td><td>A-4</td><td>A-5</td><td>A-7</td> </tr> <tr> <td>A-1-a</td><td>A-1-b</td><td>A-2-4</td><td>A-2-5</td><td>A-2-6</td><td>A-2-7</td> </tr> </table>		GRANULAR MATERIALS (>85% PASSING #200)		SILT-CLAY MATERIALS (>85% PASSING #200)		ORGANIC MATERIALS		A-1	A-3	A-2	A-4	A-5	A-7	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	<p>COMPRESSIBILITY</p> <p>SLIGHTLY COMPRESSIBLE LIQUID LIMIT LESS THAN 30 MODERATELY COMPRESSIBLE LIQUID LIMIT 31-50 HIGHLY COMPRESSIBLE LIQUID LIMIT GREATER THAN 50</p>		<p>PERCENTAGE OF MATERIAL</p> <table border="1"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT-CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>>10%</td> <td>>20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </table>		ORGANIC MATERIAL	GRANULAR SOILS	SILT-CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	>10%	>20%	HIGHLY 35% AND ABOVE	<p>GROUND WATER</p> <p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>SOUNDING ROD</p>		<p>WEATHERING</p> <p>FRESH</p> <p>VERY SLIGHT (V. SL.)</p> <p>SLIGHT (SL.)</p> <p>MODERATE (MOD.)</p> <p>MODERATELY SEVERE (MOD. SEV.)</p> <p>SEVERE (SEV.)</p> <p>VERY SEVERE (V. SEV.)</p> <p>COMPLETE</p>																																			
GRANULAR MATERIALS (>85% PASSING #200)		SILT-CLAY MATERIALS (>85% PASSING #200)		ORGANIC MATERIALS																																																																													
A-1	A-3	A-2	A-4	A-5	A-7																																																																												
A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7																																																																												
ORGANIC MATERIAL	GRANULAR SOILS	SILT-CLAY SOILS	OTHER MATERIAL																																																																														
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																														
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																														
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																														
HIGHLY ORGANIC	>10%	>20%	HIGHLY 35% AND ABOVE																																																																														
<p>SOIL LEGEND AND AASHTO CLASSIFICATION (CONT.)</p> <table border="1"> <tr> <th>GENERAL CLASS.</th> <th>GROUP CLASS.</th> <th>SYMBOL</th> <th>% PASSING</th> <th>LIQUID LIMIT</th> <th>PLASTIC INDEX</th> <th>GROUP INDEX</th> <th>USUAL TYPES OF MAJOR MATERIALS</th> <th>GEN. RATING AS A SUBGRADE</th> </tr> <tr> <td>GRANULAR MATERIALS (>85% PASSING #200)</td> <td>A-1, A-3, A-2, A-4, A-5, A-7</td> <td>Diagonal lines, horizontal lines, etc.</td> <td>50 MX, 30 MX, 15 MX, 10 MX, 5 MX, 2 MX</td> <td>40 MX, 30 MX, 20 MX, 15 MX, 10 MX, 5 MX</td> <td>4, 3, 2, 1, 0, 0, 0</td> <td>0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10</td> <td>GRAVEL AND SAND, SAND, SILTY OR CLAYEY GRAVEL AND SAND, SILTY SOILS, CLAYEY SOILS</td> <td>EXCELLENT TO GOOD, FAIR TO POOR, FAIR TO POOR, POOR, UNSUITABLE</td> </tr> </table>		GENERAL CLASS.	GROUP CLASS.	SYMBOL	% PASSING	LIQUID LIMIT	PLASTIC INDEX	GROUP INDEX	USUAL TYPES OF MAJOR MATERIALS	GEN. RATING AS A SUBGRADE	GRANULAR MATERIALS (>85% PASSING #200)	A-1, A-3, A-2, A-4, A-5, A-7	Diagonal lines, horizontal lines, etc.	50 MX, 30 MX, 15 MX, 10 MX, 5 MX, 2 MX	40 MX, 30 MX, 20 MX, 15 MX, 10 MX, 5 MX	4, 3, 2, 1, 0, 0, 0	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10	GRAVEL AND SAND, SAND, SILTY OR CLAYEY GRAVEL AND SAND, SILTY SOILS, CLAYEY SOILS	EXCELLENT TO GOOD, FAIR TO POOR, FAIR TO POOR, POOR, UNSUITABLE	<p>CONSISTENCY OR DENSENESS</p> <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (IN-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (KN/m²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE, LOOSE, MEDIUM DENSE, DENSE, VERY DENSE</td> <td><4, 4 TO 10, 10 TO 30, 30 TO 50, >50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT, SOFT, MEDIUM STIFF, STIFF, VERY STIFF, HARD</td> <td><2, 2 TO 4, 4 TO 8, 8 TO 15, 15 TO 30, >30</td> <td><25, 25 TO 50, 50 TO 100, 100 TO 200, 200 TO 400, >400</td> </tr> </table>		PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (IN-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (KN/m ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE, LOOSE, MEDIUM DENSE, DENSE, VERY DENSE	<4, 4 TO 10, 10 TO 30, 30 TO 50, >50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT, SOFT, MEDIUM STIFF, STIFF, VERY STIFF, HARD	<2, 2 TO 4, 4 TO 8, 8 TO 15, 15 TO 30, >30	<25, 25 TO 50, 50 TO 100, 100 TO 200, 200 TO 400, >400	<p>TEXTURE OR GRAIN SIZE</p> <table border="1"> <tr> <th>U.S. STD. SIEVE SIZE</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <th>OPENING (MM)</th> <td>4.75</td> <td>2.0</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table>		U.S. STD. SIEVE SIZE	4	10	40	60	200	270	OPENING (MM)	4.75	2.0	0.42	0.25	0.075	0.053	<p>ABBREVIATIONS</p> <table border="1"> <tr> <td>AR - AUGER REFUSAL</td> <td>FRAC. - FRACTURED</td> <td>SL. - SILT, SILTY</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>FRAGS. - FRAGMENTS</td> <td>SLI. - SLIGHTLY</td> </tr> <tr> <td>CL. - CLAY</td> <td>HL. - HIGHLY</td> <td>TCR - TRICONE REFUSAL</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>MED. - MEDIUM</td> <td>W. - MOISTURE CONTENT</td> </tr> <tr> <td>CSE. - COARSE</td> <td>MICA. - MICA</td> <td>V. - VERY</td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>MOD. - MODERATELY</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>NP. - NON PLASTIC</td> <td>U. - UNIT WEIGHT</td> </tr> <tr> <td>e - VOID RATIO</td> <td>PMT - PRESSUREMETER TEST</td> <td>W_d - DRY UNIT WEIGHT</td> </tr> <tr> <td>F. - FINE</td> <td>SAP. - SAPROLITIC</td> <td></td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td>SD. - SAND, SANDY</td> <td></td> </tr> </table>		AR - AUGER REFUSAL	FRAC. - FRACTURED	SL. - SILT, SILTY	BT - BORING TERMINATED	FRAGS. - FRAGMENTS	SLI. - SLIGHTLY	CL. - CLAY	HL. - HIGHLY	TCR - TRICONE REFUSAL	CPT - CONE PENETRATION TEST	MED. - MEDIUM	W. - MOISTURE CONTENT	CSE. - COARSE	MICA. - MICA	V. - VERY	DMT - DILATOMETER TEST	MOD. - MODERATELY	VST - VANE SHEAR TEST	DPT - DYNAMIC PENETRATION TEST	NP. - NON PLASTIC	U. - UNIT WEIGHT	e - VOID RATIO	PMT - PRESSUREMETER TEST	W _d - DRY UNIT WEIGHT	F. - FINE	SAP. - SAPROLITIC		FOSS. - FOSSILIFEROUS	SD. - SAND, SANDY	
GENERAL CLASS.	GROUP CLASS.	SYMBOL	% PASSING	LIQUID LIMIT	PLASTIC INDEX	GROUP INDEX	USUAL TYPES OF MAJOR MATERIALS	GEN. RATING AS A SUBGRADE																																																																									
GRANULAR MATERIALS (>85% PASSING #200)	A-1, A-3, A-2, A-4, A-5, A-7	Diagonal lines, horizontal lines, etc.	50 MX, 30 MX, 15 MX, 10 MX, 5 MX, 2 MX	40 MX, 30 MX, 20 MX, 15 MX, 10 MX, 5 MX	4, 3, 2, 1, 0, 0, 0	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10	GRAVEL AND SAND, SAND, SILTY OR CLAYEY GRAVEL AND SAND, SILTY SOILS, CLAYEY SOILS	EXCELLENT TO GOOD, FAIR TO POOR, FAIR TO POOR, POOR, UNSUITABLE																																																																									
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (IN-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (KN/m ²)																																																																														
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE, LOOSE, MEDIUM DENSE, DENSE, VERY DENSE	<4, 4 TO 10, 10 TO 30, 30 TO 50, >50	N/A																																																																														
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT, SOFT, MEDIUM STIFF, STIFF, VERY STIFF, HARD	<2, 2 TO 4, 4 TO 8, 8 TO 15, 15 TO 30, >30	<25, 25 TO 50, 50 TO 100, 100 TO 200, 200 TO 400, >400																																																																														
U.S. STD. SIEVE SIZE	4	10	40	60	200	270																																																																											
OPENING (MM)	4.75	2.0	0.42	0.25	0.075	0.053																																																																											
AR - AUGER REFUSAL	FRAC. - FRACTURED	SL. - SILT, SILTY																																																																															
BT - BORING TERMINATED	FRAGS. - FRAGMENTS	SLI. - SLIGHTLY																																																																															
CL. - CLAY	HL. - HIGHLY	TCR - TRICONE REFUSAL																																																																															
CPT - CONE PENETRATION TEST	MED. - MEDIUM	W. - MOISTURE CONTENT																																																																															
CSE. - COARSE	MICA. - MICA	V. - VERY																																																																															
DMT - DILATOMETER TEST	MOD. - MODERATELY	VST - VANE SHEAR TEST																																																																															
DPT - DYNAMIC PENETRATION TEST	NP. - NON PLASTIC	U. - UNIT WEIGHT																																																																															
e - VOID RATIO	PMT - PRESSUREMETER TEST	W _d - DRY UNIT WEIGHT																																																																															
F. - FINE	SAP. - SAPROLITIC																																																																																
FOSS. - FOSSILIFEROUS	SD. - SAND, SANDY																																																																																
<p>SOIL MOISTURE - CORRELATION OF TERMS</p> <table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>		SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>EQUIPMENT USED ON SUBJECT PROJECT</p> <table border="1"> <tr> <td>DRILL UNITS:</td> <td>ADVANCING TOOLS:</td> <td>HAMMER TYPE:</td> </tr> <tr> <td><input type="checkbox"/> MOBILE B-</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input checked="" type="checkbox"/> 152 mm CONTINUOUS FLIGHT AUGER</td> <td>CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input checked="" type="checkbox"/> 203 mm HOLLOW AUGERS</td> <td><input type="checkbox"/> -B</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input checked="" type="checkbox"/> -N <u>XWL</u></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td><input type="checkbox"/> -H</td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input checked="" type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td>HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> TRICONE _____ mm STEEL TEETH</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE _____ mm TUNG-CARB.</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td></td> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> OTHER</td> </tr> </table>		DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input checked="" type="checkbox"/> 152 mm CONTINUOUS FLIGHT AUGER	CORE SIZE:	<input type="checkbox"/> CME-45C	<input checked="" type="checkbox"/> 203 mm HOLLOW AUGERS	<input type="checkbox"/> -B	<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS	<input checked="" type="checkbox"/> -N <u>XWL</u>	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input type="checkbox"/> -H	<input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	HAND TOOLS:	<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE _____ mm STEEL TEETH	<input type="checkbox"/> POST HOLE DIGGER		<input type="checkbox"/> TRICONE _____ mm TUNG-CARB.	<input type="checkbox"/> HAND AUGER		<input type="checkbox"/> CORE BIT	<input type="checkbox"/> SOUNDING ROD		<input type="checkbox"/> OTHER	<input type="checkbox"/> VANE SHEAR TEST			<input type="checkbox"/> OTHER																											
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																															
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																															
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																															
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																															
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																															
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																															
<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																															
<input type="checkbox"/> BK-51	<input checked="" type="checkbox"/> 152 mm CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																																															
<input type="checkbox"/> CME-45C	<input checked="" type="checkbox"/> 203 mm HOLLOW AUGERS	<input type="checkbox"/> -B																																																																															
<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS	<input checked="" type="checkbox"/> -N <u>XWL</u>																																																																															
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input type="checkbox"/> -H																																																																															
<input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	HAND TOOLS:																																																																															
<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE _____ mm STEEL TEETH	<input type="checkbox"/> POST HOLE DIGGER																																																																															
	<input type="checkbox"/> TRICONE _____ mm TUNG-CARB.	<input type="checkbox"/> HAND AUGER																																																																															
	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> SOUNDING ROD																																																																															
	<input type="checkbox"/> OTHER	<input type="checkbox"/> VANE SHEAR TEST																																																																															
		<input type="checkbox"/> OTHER																																																																															
<p>PLASTICITY</p> <table border="1"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>		NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p>ROCK HARDNESS</p> <table border="1"> <tr> <th>VERY HARD</th> <th>HARD</th> <th>MODERATELY HARD</th> <th>MEDIUM HARD</th> <th>SOFT</th> <th>VERY SOFT</th> </tr> <tr> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGISTS PICK.</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 6 mm DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGISTS PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> <td>CAN BE GROOVED OR GOUGED 1 mm DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 25 mm MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGISTS PICK.</td> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL CENTIMETERS IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 25 mm OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> </tr> </table>		VERY HARD	HARD	MODERATELY HARD	MEDIUM HARD	SOFT	VERY SOFT	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGISTS PICK.	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 6 mm DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGISTS PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	CAN BE GROOVED OR GOUGED 1 mm DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 25 mm MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGISTS PICK.	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL CENTIMETERS IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 25 mm OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.																																																			
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																															
LOW PLASTICITY	0-5	VERY LOW																																																																															
MED. PLASTICITY	6-15	SLIGHT																																																																															
HIGH PLASTICITY	16-25	MEDIUM																																																																															
	26 OR MORE	HIGH																																																																															
VERY HARD	HARD	MODERATELY HARD	MEDIUM HARD	SOFT	VERY SOFT																																																																												
CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGISTS PICK.	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 6 mm DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGISTS PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	CAN BE GROOVED OR GOUGED 1 mm DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 25 mm MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGISTS PICK.	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL CENTIMETERS IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 25 mm OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.																																																																												
<p>COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>		<p>INDURATION</p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <table border="1"> <tr> <th>FRAGILE</th> <th>MODERATELY INDURATED</th> <th>INDURATED</th> <th>EXTREMELY INDURATED</th> </tr> <tr> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>		FRAGILE	MODERATELY INDURATED	INDURATED	EXTREMELY INDURATED	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																						
FRAGILE	MODERATELY INDURATED	INDURATED	EXTREMELY INDURATED																																																																														
RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																														
<p>NOTES:</p> <p align="right">ELEVATION: 251.996 METERS</p>		<p>FRACTURE SPACING</p> <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 3 m</td> <td>VERY THICKLY BEDDED</td> <td>> 1 m</td> </tr> <tr> <td>WIDE</td> <td>1 TO 3 m</td> <td>THICKLY BEDDED</td> <td>0.5 - 1 m</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>30 TO 100 cm</td> <td>THINLY BEDDED</td> <td>0.05 - 0.5 m</td> </tr> <tr> <td>CLOSE</td> <td>5 TO 30 cm</td> <td>VERY THINLY BEDDED</td> <td>10 - 50 mm</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 5 cm</td> <td>THICKLY LAMINATED</td> <td>2.5 - 10 mm</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 2.5 mm</td> </tr> </table>		TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 3 m	VERY THICKLY BEDDED	> 1 m	WIDE	1 TO 3 m	THICKLY BEDDED	0.5 - 1 m	MODERATELY CLOSE	30 TO 100 cm	THINLY BEDDED	0.05 - 0.5 m	CLOSE	5 TO 30 cm	VERY THINLY BEDDED	10 - 50 mm	VERY CLOSE	LESS THAN 5 cm	THICKLY LAMINATED	2.5 - 10 mm			THINLY LAMINATED	< 2.5 mm																																																		
TERM	SPACING	TERM	THICKNESS																																																																														
VERY WIDE	MORE THAN 3 m	VERY THICKLY BEDDED	> 1 m																																																																														
WIDE	1 TO 3 m	THICKLY BEDDED	0.5 - 1 m																																																																														
MODERATELY CLOSE	30 TO 100 cm	THINLY BEDDED	0.05 - 0.5 m																																																																														
CLOSE	5 TO 30 cm	VERY THINLY BEDDED	10 - 50 mm																																																																														
VERY CLOSE	LESS THAN 5 cm	THICKLY LAMINATED	2.5 - 10 mm																																																																														
		THINLY LAMINATED	< 2.5 mm																																																																														