| COMPUTED BY: | DATE: |
|--------------|-------|
| CHECKED BY: | DATE: |

STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

INDEX OF SHEETS

C200911 (R-2206C) CATAWBA / LINCOLN COUNTY

| SHEET NUMBER | INDEX OF SHEETS |
|-------------------|--|
| | SHEET |
| 1 | TITLE SHEET |
| 1-A | INDEX OF SHEETS, LIST OF STANDARDS DRAWINGS, AND GENERAL NOTES |
| 1-B | CONVENTIONAL SYMBOLS |
| 1-C | CENTERLINE COORDINATE LIST |
| 2 THRU 2-F | TYPICAL SECTIONS AND PAVEMENT SCHEDULE |
| 2-G THRU 2-I | DITCH DETAIL |
| 2-J THRU 2-O | GUARDRAIL DETAILS |
| 2-P THRU 2-Q | DETAILS OF REINFORCED BRIDGE APPROACH FILLS |
| 2-R | ROCK EMBANKMENT DETAIL |
| 2-S | CHANNEL CHANGE DETAIL |
| 2-T | SCOUR HOLE DETAIL |
| 2-U | TEMPORARY STEEL COVER DETAIL |
| 2-V | CONCRETE ENDWALL FOR TAPERED INLET DETAIL |
| 2-W | REINFORCED TAPERED INLET DETAIL |
| 2-X | CONCRETE FLUME DETAIL |
| 2-Y | JUNCTION BOX DETAIL |
| 2-Z | GUIDE FOR GRADING SUBGRADE – INTERSTATE & FREEWAY |
| 2-AA | DETAIL FOR CONCRETE BRIDGE APPROACH DROP INLET |
| 3 (2 SHEETS) | SUMMARY OF QUANTITIES |
| 3-A THRU 3-N | DRAINAGE SUMMARIES |
| 3-0 | EARTHWORK SUMMARY |
| 3-P | GUARDRAIL SUMMARY |
| 3-Q | ASPHALT PAVEMENT REMOVAL & WOVEN WIRE FENCE & CHAIN LINK |
| 2.5 | FENCE SUMMARIES |
| 3-R | PARCEL INDEX SHEET |
| 4 THRU 49 | PLAN SHEETS |
| 50 THRU 83 | PROFILE SHEETS |
| TCP-1 THRU TCP-20 | TRAFFIC CONTROL, MARKING AND DELINEATION |
| PM-1 THRU PM-4 | PAVEMENT MARKING PLANS |
| EC-1 THRU EC-89 | EROSION CONTROL PLANS |
| RF-1 THRU RF-2 | REFORESTATION DETAILS |
| UC-1 THRU UC-10 | UTILITY CONSTRUCITON PLANS |
| UO-1 THRU UO-19 | UTILITIES BY OTHERS PLANS |
| X-1 THRU X-1B | CROSS-SECTION SUMMARY |
| X-2 THRU X-333 | CROSS SECTIONS |
| C-1 THRU C-11 | CULVERT PLANS |
| S-1 THRU S-374 | STRUCTURE PLANS |
| | |

GENERAL NOTES:

2002 SPECIFICATIONS EFFECTIVE: 01-15-02

GRADE LINE:

GRADING AND SURFACING OR RESURFACING AND WIDENING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. WHERE NO GRADE LINES ARE SHOWN, THE PROFILES SHOWN DENOTE THE TOP ELEVATION OF THE EXISTING PAVEMENT ALONG THE CENTER LINE OF SURVEY ON WHICH THE PROPOSED RESURFACING WILL BE PLACED. GRADE LINES MAY BE ADJUSTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD _______.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 OR 225.05 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

SHOULDER CONSTRUCTION ON HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN

ACCORDANCE WITH STD. NO. 560.01 OR 560.02.

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

BERM DITCHES:

BERM DITCHES SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 240.01 AT LOCATIONS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER.

UNDERDRAINS:

UNDERDRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 815.03 AT LOCATIONS DIRECTED BY THE ENGINEER.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC WILL BE PAID FOR AS "EXTRA WORK"

IN ACCORDANCE WITH SECTION 104-7.

END BENTS:

THE ENGINEER SHALL CHECK THE STRUCTURE END BENT PLANS, DETAILS, AND CROSS-SECTION PRIOR TO SETTING OF THE SLOPE STAKES FOR THE EMBANKMENT OR EXCAVATION APPROACHING A BRIDGE.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE:

WATER & SEWER - LINCOLN COUNTY

ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS, EXCEPT AS SHOWN ON THE PLANS.

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY OTHERS.



PROJECT REFERENCE NO. SHEET NO.

> ROADWAY DESIGN **ENGINEER**

EFF. 01-15-02

ROADWAY METRIC STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch -N. C. Department of Transportation - Raleigh, N. C., Dated January 15, 2002 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO. TITLE

DIVISION 2 - EARTHWORK

200.03 Method of Clearing - Method III

225.02 Guide for Grading Subgrade - Secondary and Local

225.04 Method of Obtaining Superelevation - Two Lane Pavement

225.05 Method of Obtaining Superelevation - Divided Highways

225.07 Grading for False Cut at Grade Separations

225.09 Guide for Shoulder and Ditch Transition at Grade Separations

240.01 Guide for Berm Ditch Construction

DIVISION 3 - PIPE CULVERTS

300.01 Method of Pipe Installation - Method 'A'

300.02 Method of Pipe Installation - Method 'B'

310.10 Driveway Pipe Construction

DIVISION 5 - SUBGRADE, BASES AND SHOULDERS

560.01 Method of Shoulder Construction - High Side of Superelevated Curve - Method I

560.02 Method of Shoulder Construction - High Side of Superelevated Curve - Method II

DIVISION 6 - ASPHALT BASES AND PAVEMENTS

610.03 Guide for Paving Shoulders Under Bridges - Method III

654.01 Pavement Repairs

DIVISION 8 - INCIDENTALS

815.03 Pipe Underdrain and Blind Drain

820.04 Drain Installation in Shoulder Berm Gutter

838.01 Conc. Endwall for Single and Double Pipe Culverts - 375mm thru 1200mm Pipe 90° Skew

838.11 Brick Endwall for Single and Double Pipe Culverts - 375mm thru 1200mm Pipe 90° Skew

838.39 Reinforced Concrete Endwall - for Single 1800mm Pipe 90° Skew

838.69 Reinforced Brick Endwall - for Single 1800mm Pipe 90° Skew

840.00 Concrete Base Pad for Drainage Structures

840.17 Concrete Median Drop Inlet Type 'A' - 300mm thru 1800mm Pipe

840.18 Concrete Median Drop Inlet Type 'B' - 300mm thru 900mm Pipe

840.19 Concrete Median Drop Inlet Type 'D' - 300mm thru 900mm Pipe

840.22 Frames and Wide Slot Sag Grates

840.26 Brick Median Drop Inlet Type 'A' - 300mm thru 1800mm Pipe

840.27 Brick Median Drop Inlet Type 'B' - 300mm thru 900mm Pipe

840.28 Brick Median Drop Inlet Type 'D' - 300mm thru 900mm Pipe

840.29 Frames and Narrow Slot Flat Grates

840.31 Concrete Junction Box - 300mm thru 1650mm Pipe

840.32 Brick Junction Box - 300mm thru 1650mm Pipe

840.34 Traffic Bearing Junction Box - for Use with Pipes 1050mm and Under

840.35 Traffic Bearing Drop Inlet - for Cast Iron Double Frame and Grates

840.41 Spring Box - Concrete or Brick

840.54 Manhole Frame and Cover

840.66 Drainage Structure Steps

840.72 Pipe Collar

850.10 Guide for Berm Drainage Outlet - 400mm and 450mm Pipe

850.11 Guide for Berm Drainage Outlet - 600mm and 800mm Pipe

862.01 Guardrail Placement

866.01 Chain Link Fence - 1.2m, 1.5m and 1.8m High Fence

866.02 Woven Wire Fence - with Wood Post

866.04 Barbed Wire Fence with Wood Posts (2 - 7 Strands)

876.01 Rip Rap in Channels

876.02 Guide for Rip Rap at Pipe Outlets

876.04 Drainage Ditches with Class 'B' Rip Rap