

SIGN NUMBER: SP04364      BACKG COLOR: Orange  
 TYPE: D      COPY COLOR: Black  
 QUANTITY: 1

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 4'-0"  
 HEIGHT: 2'-6"  
 TOTAL AREA: 10.0 Sq.Ft.

BORDER TYPE: RECESSED  
 RECESS: 0.5"  
 WIDTH: 0.75"  
 RADII: 1.88"

NO. Z BARS:      MAT'L: 0.125" (3.2 mm) ALUMINUM  
 LENGTH:

DESIGN BY: LKD      CHECKED BY: CHECKED      STD #:  
 PROJECT ID: R-2237B      DIV: 11      DATE: Jul 14, 2004

USE NOTES: 2,5  
 1. Legend and border shall be direct applied Type III reflective sheeting.  
 2. Legend and border shall be direct applied non-reflective sheeting.  
 3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
 4. Background shall be Type III reflective sheeting.  
 5. Background shall be Type I reflective sheeting.  
 6. Center arrow(s) vertically on sign.  
 7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

LETTER POSITIONS

Letter spacings are to start of next letter													Series/Size	
													Text Length	
N	O	O	V	E	R	S	I	Z	E	D			C5	
3.8	3.8	2.9	4	3.7	3.9	3.4	3.6	3.8	1.8	3.6	3.4	2.7	3.8	40.4
V	E	H	I	C	L	E	S							C5
11.1	3.9	3.4	3.8	1.8	3.6	3.4	3.4	2.8	11.1					25.8
U	S													C5
3.9	3.8	2.8	4	3.6	3.8	1	4	3.8	4	3.6	3.4	2.7	3.9	40.3

Spacing Factor is 1 unless specified otherwise

SIGN NUMBER: SP04365      BACKG COLOR: Orange  
 TYPE: D      COPY COLOR: Black  
 QUANTITY: 1

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 5'-0"  
 HEIGHT: 2'-6"  
 TOTAL AREA: 12.5 Sq.Ft.

BORDER TYPE: RECESSED  
 RECESS: 0.5"  
 WIDTH: 0.75"  
 RADII: 1.88"

NO. Z BARS:      MAT'L: 0.125" (3.2 mm) ALUMINUM  
 LENGTH:

DESIGN BY: LKD      CHECKED BY: CHECKED      STD #:  
 PROJECT ID: R-2237B      DIV: 11      DATE: Jul 14, 2004

USE NOTES: 2,5  
 1. Legend and border shall be direct applied Type III reflective sheeting.  
 2. Legend and border shall be direct applied non-reflective sheeting.  
 3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
 4. Background shall be Type III reflective sheeting.  
 5. Background shall be Type I reflective sheeting.  
 6. Center arrow(s) vertically on sign.  
 7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

LETTER POSITIONS

Letter spacings are to start of next letter													Series/Size							
													Text Length							
O	V	E	R	S	I	Z	E	D	V	E	H	I	C	L	E	S	C5			
2.8	3.5	3.6	3.1	3.3	3.5	1.4	3.3	3.1	2.7	3	3.6	3.1	3.5	1.4	3.3	3.1	3.1	2.8	2.8	54.5
F	O	R	U	S																C5
5.7	3.1	3.6	2.7	3	3.5	2.8	3	3.3	3.5	1	3	3.5	3.6	3.3	3.1	2.7	5.7			48.7
U	S	E	N	C																C5
16.9	3.5	3.5	2.5	3	3.5	2.8	3	1.8	2.7	16.9										26.1

Spacing Factor is 0.7 unless specified otherwise

SIGN NUMBER: SP04366      BACKG COLOR: Orange  
 TYPE: D      COPY COLOR: Black  
 QUANTITY: 1

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 4'-3"  
 HEIGHT: 2'-6"  
 TOTAL AREA: 10.0 Sq.Ft.

BORDER TYPE: RECESSED  
 RECESS: 0.5"  
 WIDTH: 0.75"  
 RADII: 1.88"

NO. Z BARS:      MAT'L: 0.125" (3.2 mm) ALUMINUM  
 LENGTH:

DESIGN BY: LKD      CHECKED BY: CHECKED      STD #:  
 PROJECT ID: R-2237B      DIV: 11      DATE: Jul 14, 2004

USE NOTES: 2,5  
 1. Legend and border shall be direct applied Type III reflective sheeting.  
 2. Legend and border shall be direct applied non-reflective sheeting.  
 3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
 4. Background shall be Type III reflective sheeting.  
 5. Background shall be Type I reflective sheeting.  
 6. Center arrow(s) vertically on sign.  
 7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

LETTER POSITIONS

Letter spacings are to start of next letter													Series/Size	
													Text Length	
N	O	O	V	E	R	S	I	Z	E	D			C5	
4.5	3.5	2.9	5	3.5	3.6	3.1	3.3	3.5	1.4	3.3	3.1	2.7	4.5	38.9
V	E	H	I	C	L	E	S							C5
11.1	3.9	3.4	3.8	1.8	3.6	3.4	3.3	2.8	11.1					25.8
U	S													C5
3.7	3.5	2.8	5.2	3.3	3.5	1	5.2	3.3	3.6	3.3	3.1	2.7	3.7	40.6

Spacing Factor is 1 unless specified otherwise

APPROVED: \_\_\_\_\_ DATE: \_\_\_\_\_

SEAL:

SCALE: NONE  
 DATE: 07/04  
 DWG. BY: DAP  
 DESIGN BY: DAP  
 REVIEWED BY: JWW

DETOUR ROUTE SIGN DESIGNS

REVISIONS	

CADD FILE

02-SEP-2004 14:50  
 R:\TCP\R2237B\TC\top\_detour.dgn  
 ddparker AT TETC206426