

SIGN NUMBER: SP04358 TYPE: D QUANTITY: 1 SIGN WIDTH: 2'-6" HEIGHT: 1'-0" TOTAL AREA: 2.5 Sq.Ft. BORDER TYPE: RECESSED RECESS: 0.38" WIDTH: 0.63" RADIUS: 1.5" NO. Z BARS: 1 LENGTH:	BACKG COLOR: Orange COPY COLOR: Black SYMBOL	DESIGN BY: LKD PROJECT ID: R-2237B	CHECKED BY: CHECKED DIV: 11	STD #: DATE: Jul 14, 2004
--	--	---------------------------------------	--------------------------------	---------------------------

USE NOTES: 2,5  
1. Legend and border shall be direct applied Type III reflective sheeting.  
2. Legend and border shall be direct applied non-reflective sheeting.  
3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
4. Background shall be Type III reflective sheeting.  
5. Background shall be Type I reflective sheeting.  
6. Center arrow(s) vertically on sign.  
7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

LETTER POSITIONS										
Letter spacings are to start of next letter										
	U	S	3	2	1					Series/Size Text Length
	3.1	4.5	3.3	6	4.3	4.5	1.2	3.1		C6 23.9

Spacing Factor is 1 unless specified otherwise

SIGN NUMBER: SP04359 TYPE: D QUANTITY: 1 SIGN WIDTH: 2'-6" HEIGHT: 2'-0" TOTAL AREA: 5.0 Sq.Ft. BORDER TYPE: RECESSED RECESS: 0.38" WIDTH: 0.63" RADIUS: 1.5" NO. Z BARS: 1 LENGTH:	BACKG COLOR: Orange COPY COLOR: Black SYMBOL	DESIGN BY: LKD PROJECT ID: R-2237B	CHECKED BY: CHECKED DIV: 11	STD #: DATE: Jul 14, 2004
--	--	---------------------------------------	--------------------------------	---------------------------

USE NOTES: 2,5  
1. Legend and border shall be direct applied Type III reflective sheeting.  
2. Legend and border shall be direct applied non-reflective sheeting.  
3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
4. Background shall be Type III reflective sheeting.  
5. Background shall be Type I reflective sheeting.  
6. Center arrow(s) vertically on sign.  
7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

LETTER POSITIONS										
Letter spacings are to start of next letter										
	S	O	U	T	H					Series/Size Text Length
	4.9	3.3	0.7	4.7	4.3	4	3.3	4.9		C6 20.3
	U	S	3	2	1					C6 22.8
	3.6	4.5	3.3	4.9	4.3	4.5	1.2	3.6		

Spacing Factor is 1 unless specified otherwise

SIGN NUMBER: SP04360 TYPE: D QUANTITY: 1 SIGN WIDTH: 2'-6" HEIGHT: 2'-0" TOTAL AREA: 5.0 Sq.Ft. BORDER TYPE: RECESSED RECESS: 0.38" WIDTH: 0.63" RADIUS: 1.5" NO. Z BARS: 1 LENGTH:	BACKG COLOR: Orange COPY COLOR: Black SYMBOL	DESIGN BY: LKD PROJECT ID: R-2237B	CHECKED BY: CHECKED DIV: 11	STD #: DATE: Jul 14, 2004
--	--	---------------------------------------	--------------------------------	---------------------------

USE NOTES: 2,5  
1. Legend and border shall be direct applied Type III reflective sheeting.  
2. Legend and border shall be direct applied non-reflective sheeting.  
3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
4. Background shall be Type III reflective sheeting.  
5. Background shall be Type I reflective sheeting.  
6. Center arrow(s) vertically on sign.  
7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

LETTER POSITIONS										
Letter spacings are to start of next letter										
	N	O	R	T	H					Series/Size Text Length
	4.8	3.3	0.8	4.7	4.3	4	3.3	4.8		C6 20.4
	U	S	3	2	1					C6 22.8
	3.6	4.5	3.3	4.9	4.3	4.5	1.2	3.6		

Spacing Factor is 1 unless specified otherwise

SIGN NUMBER: SP04376 TYPE: D QUANTITY: 1 SIGN WIDTH: 5'-0" HEIGHT: 2'-0" TOTAL AREA: 10.0 Sq.Ft. BORDER TYPE: RECESSED RECESS: 0.38" WIDTH: 0.63" RADIUS: 1.5" NO. Z BARS: 1 LENGTH:	BACKG COLOR: Orange COPY COLOR: Black SYMBOL	DESIGN BY: LKD PROJECT ID: R-2237B	CHECKED BY: CHECKED DIV: 11	STD #: DATE: Jul 23, 2004
---	--	---------------------------------------	--------------------------------	---------------------------

USE NOTES: 2,5  
1. Legend and border shall be direct applied Type III reflective sheeting.  
2. Legend and border shall be direct applied non-reflective sheeting.  
3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
4. Background shall be Type III reflective sheeting.  
5. Background shall be Type I reflective sheeting.  
6. Center arrow(s) vertically on sign.  
7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

LETTER POSITIONS																			
Letter spacings are to start of next letter																			
	H	O	R	I	Z	O	N	T	A	L					Series/Size Text Length				
	13.2	3.8	4	3.8	1.8	3.6	4	3.6	2.8	4	2.5	13.2			C5 33.6				
	C	L	E	A	R	A	N	C	E	1	0	F	T		C5 50.1				
	5	3.6	3.4	3.1	4	3.6	4	3.8	3.6	2.5	4.1	2.1	2.9	4.1	3.1	2.5	5		

Spacing Factor is 1 unless specified otherwise

02-SEP-2004 11:49  
R:\TCP\R2237B\TC\TCp\_detour.dgn  
doparker AT 11/11/2004

APPROVED: _____ DATE: _____	<b>DETOUR ROUTE SIGN DESIGNS</b>									
SCALE: NONE	DATE: 07/04	<table border="1"> <tr> <th colspan="2">REVISIONS</th> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </table>	REVISIONS							
REVISIONS										
DWG. BY: DAP	DESIGN BY: DAP									
REVIEWED BY: JWW										
		CAD FILE								