



PROJECT NOTES

SIGNS SUMMARY OF QUANTITIES

ITEM NO.		ITEM DESCRIPTION	QUANTITY	UNIT
DESC. NO.	SECT. NO.			
4048000000	902	REINFORCED CONCRETE SIGN FOOTINGS.....	5	C.Y.
4054000000	902	PLAIN CONCRETE SIGN FOOTINGS.....	1	C.Y.
4060000000	903	SUPPORTS, BREAKAWAY STEEL BEAM.....	3179	LB.
4072000000	903	SUPPORTS, 3 LB STEEL U-CHANNEL.....	435	L.F.
4078000000	903	SUPPORTS, 2 LB STEEL U-CHANNEL.....	10	EA.
4110000000	904	SIGN ERECTION, TYPE A (GROUND MOUNTED).....	12	EA.
4110000000	904	SIGN ERECTION, TYPE B (GROUND MOUNTED).....	4	EA.
4102000000	904	SIGN ERECTION, TYPE E.....	20	EA.
4108000000	904	SIGN ERECTION, TYPE F.....	3	EA.
4114000000	904	SIGN ERECTION, MILEMARKERS.....	10	EA.
4129000000	906	RELOCATE SIGN, TYPE A (GROUND MOUNTED).....	2	EA.
4138000000	907	DISPOSAL OF SUPPORT, STEEL BEAM.....	4	EA.
4152000000	907	DISPOSAL OF SIGN SYSTEM, STEEL BEAM.....	4	EA.
4155000000	907	DISPOSAL OF SIGN SYSTEM, U-CHANNEL.....	26	EA.
4236000000	907	DISPOSAL OF SIGN, A OR B (GROUND MOUNTED).....	7	EA.

Pay Item Notes:

- | | |
|---|---|
| 1 | DISPOSAL OF SIGN SYSTEM, STEEL BEAM |
| 2 | DISPOSAL OF SIGN SYSTEM, U-CHANNEL |
| 3 | DISPOSAL OF SIGN, A OR B (GROUND MOUNTED) |
| 4 | SIGN ERECTION, TYPE A (GROUND MOUNTED) |
| 5 | SIGN ERECTION, TYPE B (GROUND MOUNTED) |
| 6 | DISPOSAL OF SUPPORT, STEEL BEAM |
| 7 | RELOCATE SIGN, TYPE A (GROUND MOUNTED) |

General Notes:

- . SIGNS FURNISHED BY STATE
- . IF REMOVAL OR RELOCATION OF SIGNS ON PRIVATE STREET (NON-STATE MAINTAINED) IS REQUIRED DUE TO CONSTRUCTION, THE CONTRACTOR SHALL INFORM THE ENGINEER. THE WORK WILL BE COMPLETED BY OTHERS.
- . SIGNING PLANS DO NOT INCLUDE TEMPORARY CONSTRUCTION SIGNING OR PAVEMENT MARKINGS. SEE TRAFFIC CONTROL PLANS.
- . WHEN NOT STATIONED OR DIMENSIONED ON PLANS, ALL 'E' AND 'F' SIGNS SHALL BE FIELD LOCATED BY THE ENGINEER
- . ALL EXISTING SIGNS ON "U" CHANNEL POST WITHIN THE PROJECT LIMITS SHALL BE REMOVED AND DISPOSED OF UNLESS OTHERWISE NOTED ON PLANS.
- . WHEN EXISTING SIGNS ARE REMOVED AND INSTALLED ON NEW SUPPORTS, THE RE-ERECTION SHALL IMMEDIATELY FOLLOW THE REMOVAL.
- . THE BACKGROUND FOR TYPE E & F SIGNS SHALL BE TYPE III REFLECTIVE SHEETING.
- DO NOT BEGIN FABRICATION FOR TYPES A & B SIGNS MOUNTED ON OVERHEAD STRUCTURES OR STEEL SUPPORTS UNTIL "S" DIMENSIONS HAVE BEEN FIELD VERIFIED.
- SEE ROADWAY PLANS FOR GUARD/GUIDE RAIL DETAILS.

Proejct Notes:

- | | |
|---|--|
| A | ERECT PROPOSED SIGN(S) ON EXISITING SUPPORTS |
|---|--|

**ROADWAY STANDARD DRAWINGS
APPLICABLE TO THESE SIGNING PLANS**

901.10	904.10
901.20	904.20
901.50	904.40
903.10	904.50