

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**  
**GEOTECHNICAL UNIT**

<b>ID</b> B-3685	<b>STATE PROJECT NO.</b> 33226.1.1	<b>SHEET NO.</b> 2	<b>TOTAL SHEETS</b> 14
---------------------	---------------------------------------	-----------------------	---------------------------

**SUBSURFACE INVESTIGATION**

**SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION				GRADATION				ROCK DESCRIPTION				TERMS AND DEFINITIONS																																																																																																																																																																				
SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE: VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGH PLASTICITY, A-7-6				WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.				HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:				ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARGILLACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (F.P.) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (IN OR B.P.F.) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS LESS THAN 0.1 FOOT PENETRATION WITH 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																																																																																																				
<b>SOIL LEGEND AND AASHTO CLASSIFICATION</b>				<b>MINERALOGICAL COMPOSITION</b>				<b>WEATHERING</b>																																																																																																																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="4">GRANULAR MATERIALS (&lt; 75% PASSING #200)</th> <th colspan="4">SILT-CLAY MATERIALS (&gt; 75% PASSING #200)</th> <th colspan="4">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th colspan="4"></th> </tr> <tr> <th>SYMBOL</th> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="4"></td> </tr> <tr> <th>% PASSING</th> <td>10 30 40 200</td> <td>10 30 40 200</td> <td>10 30 40 200</td> <td>10 30 40 200</td> <td>10 30 40 200</td> <td>10 30 40 200</td> <td>10 30 40 200</td> <td>10 30 40 200</td> <td>10 30 40 200</td> <td>10 30 40 200</td> <td colspan="4"></td> </tr> <tr> <th>LIQUID LIMIT PLASTIC INDEX</th> <td colspan="2">6 MX</td> <td colspan="2">N.P.</td> <td colspan="2">4 MX</td> <td colspan="2">8 MX</td> <td colspan="2">12 MX</td> <td colspan="2">16 MX</td> <td colspan="2">No MX</td> <td colspan="2"></td> </tr> <tr> <th>GROUP INDEX</th> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2"></td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td colspan="2">STONE FRAGS, GRAVEL AND SAND</td> <td colspan="2">FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="2">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="2">HIGHLY ORGANIC SOILS</td> <td colspan="2"></td> </tr> <tr> <th>GRADING AS A SUBGRADE</th> <td colspan="4">EXCELLENT TO GOOD</td> <td colspan="4">FAIR TO POOR</td> <td colspan="2">FAIR TO POOR</td> <td colspan="2">POOR</td> <td colspan="2">UNSATISFACTORY</td> <td colspan="2"></td> </tr> </table>				GENERAL CLASS.	GRANULAR MATERIALS (< 75% PASSING #200)				SILT-CLAY MATERIALS (> 75% PASSING #200)				ORGANIC MATERIALS				GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7					SYMBOL															% PASSING	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200					LIQUID LIMIT PLASTIC INDEX	6 MX		N.P.		4 MX		8 MX		12 MX		16 MX		No MX				GROUP INDEX	0		0		0		0		0		0		0				USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS				GRADING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR		POOR		UNSATISFACTORY				MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.				<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3">COMPRESSION</th> </tr> <tr> <td>SLIGHTLY COMPRESSIBLE</td> <td colspan="2">LIQUID LIMIT LESS THAN 30</td> </tr> <tr> <td>MODERATELY COMPRESSIBLE</td> <td colspan="2">LIQUID LIMIT 31-50</td> </tr> <tr> <td>HIGHLY COMPRESSIBLE</td> <td colspan="2">LIQUID LIMIT GREATER THAN 50</td> </tr> </table>				COMPRESSION			SLIGHTLY COMPRESSIBLE	LIQUID LIMIT LESS THAN 30		MODERATELY COMPRESSIBLE	LIQUID LIMIT 31-50		HIGHLY COMPRESSIBLE	LIQUID LIMIT GREATER THAN 50		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3">PERCENTAGE OF MATERIAL</th> </tr> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT-CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>&gt;10%</td> <td>&gt;20%</td> <td>HIGHLY</td> </tr> </table>				PERCENTAGE OF MATERIAL			ORGANIC MATERIAL	GRANULAR SOILS	SILT-CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	>10%	>20%	HIGHLY
GENERAL CLASS.	GRANULAR MATERIALS (< 75% PASSING #200)				SILT-CLAY MATERIALS (> 75% PASSING #200)				ORGANIC MATERIALS																																																																																																																																																																							
GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7																																																																																																																																																																						
SYMBOL																																																																																																																																																																																
% PASSING	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200	10 30 40 200																																																																																																																																																																						
LIQUID LIMIT PLASTIC INDEX	6 MX		N.P.		4 MX		8 MX		12 MX		16 MX		No MX																																																																																																																																																																			
GROUP INDEX	0		0		0		0		0		0		0																																																																																																																																																																			
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS																																																																																																																																																																			
GRADING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR		POOR		UNSATISFACTORY																																																																																																																																																																			
COMPRESSION																																																																																																																																																																																
SLIGHTLY COMPRESSIBLE	LIQUID LIMIT LESS THAN 30																																																																																																																																																																															
MODERATELY COMPRESSIBLE	LIQUID LIMIT 31-50																																																																																																																																																																															
HIGHLY COMPRESSIBLE	LIQUID LIMIT GREATER THAN 50																																																																																																																																																																															
PERCENTAGE OF MATERIAL																																																																																																																																																																																
ORGANIC MATERIAL	GRANULAR SOILS	SILT-CLAY SOILS	OTHER MATERIAL																																																																																																																																																																													
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																																																																													
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																																																																													
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																																																																													
HIGHLY ORGANIC	>10%	>20%	HIGHLY																																																																																																																																																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="4">GROUND WATER</th> </tr> <tr> <td></td> <td colspan="3">WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING.</td> </tr> <tr> <td></td> <td colspan="3">STATIC WATER LEVEL AFTER 24 HOURS.</td> </tr> <tr> <td></td> <td colspan="3">PERCHED WATER, SATURATED ZONE OR WATER BEARING STRATA</td> </tr> <tr> <td></td> <td colspan="3">SPRING OR SEEPAGE</td> </tr> </table>				GROUND WATER					WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING.				STATIC WATER LEVEL AFTER 24 HOURS.				PERCHED WATER, SATURATED ZONE OR WATER BEARING STRATA				SPRING OR SEEPAGE			<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3">MISCELLANEOUS SYMBOLS</th> </tr> <tr> <td></td> <td colspan="2">ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</td> </tr> <tr> <td></td> <td colspan="2">SOIL SYMBOL</td> </tr> <tr> <td></td> <td colspan="2">ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</td> </tr> <tr> <td></td> <td colspan="2">INFERRED SOIL BOUNDARIES</td> </tr> <tr> <td></td> <td colspan="2">INFERRED ROCK LINE</td> </tr> <tr> <td></td> <td colspan="2">ALLUVIAL SOIL BOUNDARY</td> </tr> <tr> <td></td> <td colspan="2">DIP/DIP DIRECTION OF ROCK STRUCTURES</td> </tr> <tr> <td></td> <td colspan="2">SOUNDING ROD</td> </tr> <tr> <td></td> <td colspan="2">TEST BORING</td> </tr> <tr> <td></td> <td colspan="2">AUGER BORING</td> </tr> <tr> <td></td> <td colspan="2">CORE BORING</td> </tr> <tr> <td></td> <td colspan="2">MONITORING WELL</td> </tr> <tr> <td></td> <td colspan="2">PIEZOMETER INSTALLATION</td> </tr> <tr> <td></td> <td colspan="2">SLOPE INDICATOR INSTALLATION</td> </tr> <tr> <td></td> <td colspan="2">SPT N-VALUE</td> </tr> <tr> <td></td> <td colspan="2">SPT REFUSAL</td> </tr> </table>				MISCELLANEOUS SYMBOLS				ROADWAY EMBANKMENT WITH SOIL DESCRIPTION			SOIL SYMBOL			ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS			INFERRED SOIL BOUNDARIES			INFERRED ROCK LINE			ALLUVIAL SOIL BOUNDARY			DIP/DIP DIRECTION OF ROCK STRUCTURES			SOUNDING ROD			TEST BORING			AUGER BORING			CORE BORING			MONITORING WELL			PIEZOMETER INSTALLATION			SLOPE INDICATOR INSTALLATION			SPT N-VALUE			SPT REFUSAL																																																																																																			
GROUND WATER																																																																																																																																																																																
	WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING.																																																																																																																																																																															
	STATIC WATER LEVEL AFTER 24 HOURS.																																																																																																																																																																															
	PERCHED WATER, SATURATED ZONE OR WATER BEARING STRATA																																																																																																																																																																															
	SPRING OR SEEPAGE																																																																																																																																																																															
MISCELLANEOUS SYMBOLS																																																																																																																																																																																
	ROADWAY EMBANKMENT WITH SOIL DESCRIPTION																																																																																																																																																																															
	SOIL SYMBOL																																																																																																																																																																															
	ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS																																																																																																																																																																															
	INFERRED SOIL BOUNDARIES																																																																																																																																																																															
	INFERRED ROCK LINE																																																																																																																																																																															
	ALLUVIAL SOIL BOUNDARY																																																																																																																																																																															
	DIP/DIP DIRECTION OF ROCK STRUCTURES																																																																																																																																																																															
	SOUNDING ROD																																																																																																																																																																															
	TEST BORING																																																																																																																																																																															
	AUGER BORING																																																																																																																																																																															
	CORE BORING																																																																																																																																																																															
	MONITORING WELL																																																																																																																																																																															
	PIEZOMETER INSTALLATION																																																																																																																																																																															
	SLOPE INDICATOR INSTALLATION																																																																																																																																																																															
	SPT N-VALUE																																																																																																																																																																															
	SPT REFUSAL																																																																																																																																																																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="4">CONSISTENCY OR DENSENESS</th> </tr> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 &gt; 4</td> </tr> </table>				CONSISTENCY OR DENSENESS				PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 > 4	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="7">ROCK HARDNESS</th> </tr> <tr> <td>VERY HARD</td> <td colspan="6">CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> </tr> <tr> <td>HARD</td> <td colspan="6">CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> </tr> <tr> <td>MODERATELY HARD</td> <td colspan="6">CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> </tr> <tr> <td>MEDIUM HARD</td> <td colspan="6">CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> </tr> <tr> <td>SOFT</td> <td colspan="6">CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> </tr> <tr> <td>VERY SOFT</td> <td colspan="6">CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> </tr> </table>				ROCK HARDNESS							VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.						HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.						MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.						MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.						SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.						VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.																																																																																																													
CONSISTENCY OR DENSENESS																																																																																																																																																																																
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )																																																																																																																																																																													
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																													
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 > 4																																																																																																																																																																													
ROCK HARDNESS																																																																																																																																																																																
VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.																																																																																																																																																																															
HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.																																																																																																																																																																															
MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.																																																																																																																																																																															
MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.																																																																																																																																																																															
SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.																																																																																																																																																																															
VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.																																																																																																																																																																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="7">TEXTURE OR GRAIN SIZE</th> </tr> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.0</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CS.SD.)</th> <th>FINE SAND (F.SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td>GRAIN SIZE</td> <td>MM 305 IN. 12"</td> <td>75 3"</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> </table>				TEXTURE OR GRAIN SIZE							U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.0	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS.SD.)	FINE SAND (F.SD.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE	MM 305 IN. 12"	75 3"	2.0	0.25	0.05	0.005	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3">ABBREVIATIONS</th> </tr> <tr> <td>AR - AUGER REFUSAL</td> <td colspan="2">PMT - PRESSUREMETER TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td colspan="2">SD. - SAND, SANDY</td> </tr> <tr> <td>CL. - CLAY</td> <td colspan="2">SL. - SILT, SILTY</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td colspan="2">SLI. - SLIGHTLY</td> </tr> <tr> <td>CSE. - COARSE</td> <td colspan="2">TCR - TRICONE REFUSAL</td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td colspan="2">γ - UNIT WEIGHT</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td colspan="2">γ<sub>d</sub> - DRY UNIT WEIGHT</td> </tr> <tr> <td>e - VOID RATIO</td> <td colspan="2">w - MOISTURE CONTENT</td> </tr> <tr> <td>F. - FINE</td> <td colspan="2">v. - VERY</td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td colspan="2">VST - VANE SHEAR TEST</td> </tr> <tr> <td>FRAC. - FRACTURED</td> <td colspan="2"></td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td colspan="2"></td> </tr> <tr> <td>MED. - MEDIUM</td> <td colspan="2"></td> </tr> </table>				ABBREVIATIONS			AR - AUGER REFUSAL	PMT - PRESSUREMETER TEST		BT - BORING TERMINATED	SD. - SAND, SANDY		CL. - CLAY	SL. - SILT, SILTY		CPT - CONE PENETRATION TEST	SLI. - SLIGHTLY		CSE. - COARSE	TCR - TRICONE REFUSAL		DMT - DILATOMETER TEST	γ - UNIT WEIGHT		DPT - DYNAMIC PENETRATION TEST	γ <sub>d</sub> - DRY UNIT WEIGHT		e - VOID RATIO	w - MOISTURE CONTENT		F. - FINE	v. - VERY		FOSS. - FOSSILIFEROUS	VST - VANE SHEAR TEST		FRAC. - FRACTURED			FRAGS. - FRAGMENTS			MED. - MEDIUM																																																																																														
TEXTURE OR GRAIN SIZE																																																																																																																																																																																
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																										
	4.76	2.0	0.42	0.25	0.075	0.053																																																																																																																																																																										
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS.SD.)	FINE SAND (F.SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																										
GRAIN SIZE	MM 305 IN. 12"	75 3"	2.0	0.25	0.05	0.005																																																																																																																																																																										
ABBREVIATIONS																																																																																																																																																																																
AR - AUGER REFUSAL	PMT - PRESSUREMETER TEST																																																																																																																																																																															
BT - BORING TERMINATED	SD. - SAND, SANDY																																																																																																																																																																															
CL. - CLAY	SL. - SILT, SILTY																																																																																																																																																																															
CPT - CONE PENETRATION TEST	SLI. - SLIGHTLY																																																																																																																																																																															
CSE. - COARSE	TCR - TRICONE REFUSAL																																																																																																																																																																															
DMT - DILATOMETER TEST	γ - UNIT WEIGHT																																																																																																																																																																															
DPT - DYNAMIC PENETRATION TEST	γ <sub>d</sub> - DRY UNIT WEIGHT																																																																																																																																																																															
e - VOID RATIO	w - MOISTURE CONTENT																																																																																																																																																																															
F. - FINE	v. - VERY																																																																																																																																																																															
FOSS. - FOSSILIFEROUS	VST - VANE SHEAR TEST																																																																																																																																																																															
FRAC. - FRACTURED																																																																																																																																																																																
FRAGS. - FRAGMENTS																																																																																																																																																																																
MED. - MEDIUM																																																																																																																																																																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="4">SOIL MOISTURE - CORRELATION OF TERMS</th> </tr> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th colspan="2">GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td colspan="2">USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td colspan="2">SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td colspan="2">SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td colspan="2">REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>				SOIL MOISTURE - CORRELATION OF TERMS				SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION		LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE		PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE		OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE		SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3">EQUIPMENT USED ON SUBJECT PROJECT</th> </tr> <tr> <td>DRILL UNITS:</td> <td>ADVANCING TOOLS:</td> <td>HAMMER TYPE:</td> </tr> <tr> <td><input type="checkbox"/> MOBILE B-47</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td>CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-45B</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> -B</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -N</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td><input type="checkbox"/> -H</td> </tr> <tr> <td><input type="checkbox"/> OTHER _____</td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td>HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/> OTHER _____</td> <td><input checked="" type="checkbox"/> TRICONE 2 1/16" STEEL TEETH</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE _____ TUNG-CARB.</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td></td> <td><input type="checkbox"/> OTHER _____</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> OTHER _____</td> </tr> </table>				EQUIPMENT USED ON SUBJECT PROJECT			DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> MOBILE B-47	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:	<input type="checkbox"/> CME-45B	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B	<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input type="checkbox"/> -H	<input type="checkbox"/> OTHER _____	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	HAND TOOLS:	<input type="checkbox"/> OTHER _____	<input checked="" type="checkbox"/> TRICONE 2 1/16" STEEL TEETH	<input type="checkbox"/> POST HOLE DIGGER		<input type="checkbox"/> TRICONE _____ TUNG-CARB.	<input type="checkbox"/> HAND AUGER		<input type="checkbox"/> CORE BIT	<input type="checkbox"/> SOUNDING ROD		<input type="checkbox"/> OTHER _____	<input type="checkbox"/> VANE SHEAR TEST			<input type="checkbox"/> OTHER _____																																																																																																										
SOIL MOISTURE - CORRELATION OF TERMS																																																																																																																																																																																
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																														
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																														
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																														
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																														
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																														
EQUIPMENT USED ON SUBJECT PROJECT																																																																																																																																																																																
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																																																																														
<input type="checkbox"/> MOBILE B-47	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																														
<input type="checkbox"/> BK-51	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																																																																																																																																														
<input type="checkbox"/> CME-45B	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B																																																																																																																																																																														
<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N																																																																																																																																																																														
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input type="checkbox"/> -H																																																																																																																																																																														
<input type="checkbox"/> OTHER _____	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	HAND TOOLS:																																																																																																																																																																														
<input type="checkbox"/> OTHER _____	<input checked="" type="checkbox"/> TRICONE 2 1/16" STEEL TEETH	<input type="checkbox"/> POST HOLE DIGGER																																																																																																																																																																														
	<input type="checkbox"/> TRICONE _____ TUNG-CARB.	<input type="checkbox"/> HAND AUGER																																																																																																																																																																														
	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> SOUNDING ROD																																																																																																																																																																														
	<input type="checkbox"/> OTHER _____	<input type="checkbox"/> VANE SHEAR TEST																																																																																																																																																																														
		<input type="checkbox"/> OTHER _____																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">PLASTICITY</th> </tr> <tr> <td>PLASTIC PLASTICITY</td> <td>PLASTICITY INDEX (PI)</td> </tr> <tr> <td>PLASTICITY</td> <td>DRY STRENGTH</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>0-5 VERY LOW</td> </tr> <tr> <td></td> <td>6-15 SLIGHT</td> </tr> <tr> <td></td> <td>16-25 MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE HIGH</td> </tr> </table>				PLASTICITY		PLASTIC PLASTICITY	PLASTICITY INDEX (PI)	PLASTICITY	DRY STRENGTH	HIGH PLASTICITY	0-5 VERY LOW		6-15 SLIGHT		16-25 MEDIUM		26 OR MORE HIGH	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">FRACTURE SPACING</th> <th colspan="2">BEDDING</th> </tr> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>&gt; 4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table>				FRACTURE SPACING		BEDDING		TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	> 4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET																																																																																																																											
PLASTICITY																																																																																																																																																																																
PLASTIC PLASTICITY	PLASTICITY INDEX (PI)																																																																																																																																																																															
PLASTICITY	DRY STRENGTH																																																																																																																																																																															
HIGH PLASTICITY	0-5 VERY LOW																																																																																																																																																																															
	6-15 SLIGHT																																																																																																																																																																															
	16-25 MEDIUM																																																																																																																																																																															
	26 OR MORE HIGH																																																																																																																																																																															
FRACTURE SPACING		BEDDING																																																																																																																																																																														
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																													
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	> 4 FEET																																																																																																																																																																													
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																													
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																													
CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																													
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																													
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">INDURATION</th> </tr> <tr> <td colspan="2">FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</td> </tr> <tr> <td>FRIABLE</td> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>				INDURATION		FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.		FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>BENCH MARK:</td> <td><b>TBM #2 RAILROAD SPIKE IN 14" HICKORY TREE</b></td> </tr> <tr> <td></td> <td><b>163 FEET RIGHT OF -BL- STA. 11+40</b></td> </tr> <tr> <td></td> <td><b>ELEVATION: 29.11 FEET</b></td> </tr> <tr> <td>NOTES:</td> <td></td> </tr> </table>				BENCH MARK:	<b>TBM #2 RAILROAD SPIKE IN 14" HICKORY TREE</b>		<b>163 FEET RIGHT OF -BL- STA. 11+40</b>		<b>ELEVATION: 29.11 FEET</b>	NOTES:																																																																																																																																																						
INDURATION																																																																																																																																																																																
FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.																																																																																																																																																																																
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																																																																															
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																															
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																															
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																															
BENCH MARK:	<b>TBM #2 RAILROAD SPIKE IN 14" HICKORY TREE</b>																																																																																																																																																																															
	<b>163 FEET RIGHT OF -BL- STA. 11+40</b>																																																																																																																																																																															
	<b>ELEVATION: 29.11 FEET</b>																																																																																																																																																																															
NOTES:																																																																																																																																																																																
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.																																																																																																																																																																																