

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**  
**GEOTECHNICAL UNIT**

ID	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
B-3427	8.1770801	2	

## SUBSURFACE INVESTIGATION

### SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION	TERMS AND DEFINITIONS																																																																																																																																																																																																																																									
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (ASHSTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:</p> <p style="text-align: center;"><i>VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>	<p><b>WELL GRADED</b>- INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE <b>UNIFORM</b>- INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO <b>POORLY GRADED</b>)  <b>GAP-GRADED</b>- INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p style="text-align: center;"><b>ANGULARITY OF GRAINS</b></p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS: <b>ANGULAR</b>, <b>SUBANGULAR</b>, <b>SUBROUNDED</b>, OR <b>ROUNDED</b>.</p>	<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p> <p><b>WEATHERED ROCK (WR)</b> </p> <p><b>CRYSTALLINE ROCK (CR)</b> </p> <p><b>NON-CRYSTALLINE ROCK (NCR)</b> </p> <p><b>COASTAL PLAIN SEDIMENTARY ROCK (CP)</b> </p>	<p><b>ALLUVIUM (ALLUV.)</b>- SOILS WHICH HAVE BEEN TRANSPORTED BY WATER.  <b>AQUIFER</b>- A WATER BEARING FORMATION OR STRATA.  <b>ARENACEOUS</b>- APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.  <b>ARGILLACEOUS</b>- APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC.  <b>ARTESIAN</b>- GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.  <b>CALCAREOUS (CALC.)</b>- SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.  <b>COLLUVIUM</b>- ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.  <b>CORE RECOVERY (REC.)</b>- TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.  <b>DIKE</b>- A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.  <b>DIP</b>- THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.  <b>DIP DIRECTION (DIP AZIMUTH)</b>- THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.  <b>FAULT</b>- A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.  <b>FISSILE</b>- A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.  <b>FLOAT</b>- ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL.  <b>FLOOD PLAIN (F.P.)</b>- LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.  <b>FORMATION (FM.)</b>- A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.  <b>JOINT</b>- FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.  <b>LEDGE</b>- A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.  <b>LENS</b>- A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.  <b>MOTTLED (MOT.)</b>- IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.  <b>PERCHED WATER</b>- WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.  <b>RESIDUAL SOIL</b>- SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.  <b>ROCK QUALITY DESIGNATION (R.Q.D.)</b>- A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.  <b>SAPROLITE (SAP.)</b>- RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.  <b>SILL</b>- AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.  <b>SLICKENSIDE</b>- POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.  <b>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT)</b>- NUMBER OF BLOWS (IN OR B.P.F.) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS LESS THAN 0.1 FOOT PENETRATION WITH 60 BLOWS.  <b>STRATA CORE RECOVERY (SREC.)</b>- TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.  <b>STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.)</b>- A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.  <b>TOPSOIL (T.S.)</b>- SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																																																																																									
<p style="text-align: center;"><b>SOIL LEGEND AND AASHTO CLASSIFICATION</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th rowspan="2">GENERAL CLASS.</th> <th colspan="7">GRANULAR MATERIALS (&lt;35% PASSING #200)</th> <th colspan="7">SILT-CLAY MATERIALS (&gt;85% PASSING #200)</th> <th colspan="3">ORGANIC MATERIALS</th> </tr> <tr> <th>A-1</th> <th>A-3</th> <th colspan="2">A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th colspan="2">A-7-5</th> <th colspan="2">A-7-6</th> <th colspan="3"></th> </tr> <tr> <td>GROUP CLASS.</td> <td>A-1-a</td> <td>A-1-b</td> <td>A-2-4</td> <td>A-2-5</td> <td>A-2-6</td> <td>A-2-7</td> <td>A-4</td> <td>A-5</td> <td>A-6</td> <td>A-7</td> <td>A-1, A-2</td> <td>A-4, A-5</td> <td>A-6, A-7</td> <td colspan="2"></td> <td colspan="3"></td> </tr> <tr> <td>SYMBOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> <td colspan="3"></td> </tr> <tr> <td>% PASSING</td> <td>50 MX</td> <td>30 MX</td> <td>50 MX</td> <td>51 MN</td> <td>35 MX</td> <td>35 MX</td> <td>35 MX</td> <td>35 MX</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> </tr> <tr> <td>LIQUID LIMIT</td> <td>6 MX</td> <td>N.P.</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> </tr> <tr> <td>PLASTIC INDEX</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>4 MX</td> <td>8 MX</td> <td>12 MX</td> <td>16 MX</td> <td>10 MX</td> <td>11 MN</td> <td>11 MN</td> <td>11 MN</td> <td>11 MN</td> <td>11 MN</td> <td>11 MN</td> <td>11 MN</td> <td>11 MN</td> <td>11 MN</td> </tr> <tr> <td>GROUP INDEX</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td>STONE FRAGS. GRAVEL AND SAND</td> <td>FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td>SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="2">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="2">GRANULAR SOILS</td> <td>SILT-CLAY SOILS</td> <td colspan="2">MUCK, PEAT</td> <td colspan="3">HIGHLY ORGANIC SOILS</td> </tr> <tr> <td>GENERAL RATING AS A SUBGRADE</td> <td colspan="4">EXCELLENT TO GOOD</td> <td colspan="4">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td colspan="3">UNSUITABLE</td> <td colspan="3"></td> </tr> </table> <p style="text-align: center;">P.I. OF A-7-5 ≤ L.L. - 30 : P.I. OF A-7-6 &gt; L.L. - 30</p>	GENERAL CLASS.	GRANULAR MATERIALS (<35% PASSING #200)							SILT-CLAY MATERIALS (>85% PASSING #200)							ORGANIC MATERIALS			A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7	A-7-5		A-7-6					GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7						SYMBOL																			% PASSING	50 MX	30 MX	50 MX	51 MN	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	LIQUID LIMIT	6 MX	N.P.	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	PLASTIC INDEX	0	0	0	0	4 MX	8 MX	12 MX	16 MX	10 MX	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	GROUP INDEX	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS	CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		GRANULAR SOILS		SILT-CLAY SOILS	MUCK, PEAT		HIGHLY ORGANIC SOILS			GENERAL RATING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR	POOR	UNSUITABLE						<p style="text-align: center;"><b>MINERALOGICAL COMPOSITION</b></p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p> <p style="text-align: center;"><b>COMPRESSIBILITY</b></p> <p>SLIGHTLY COMPRESSIBLE LIQUID LIMIT LESS THAN 30          MODERATELY COMPRESSIBLE LIQUID LIMIT 31-50          HIGHLY COMPRESSIBLE LIQUID LIMIT GREATER THAN 50</p> <p style="text-align: center;"><b>PERCENTAGE OF MATERIAL</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th rowspan="2"></th> <th colspan="2">GRANULAR SOILS</th> <th colspan="2">SILT-CLAY SOILS</th> <th colspan="2">OTHER MATERIAL</th> </tr> <tr> <th>TRACE</th> <th>&gt;10%</th> <th>TRACE</th> <th>&gt;20%</th> <th>TRACE</th> <th>&gt;35%</th> </tr> <tr> <td>ORGANIC MATERIAL</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> <td>10 - 20%</td> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 10%</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> <td>20 - 35%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>5 - 10%</td> <td>&gt;10%</td> <td>&gt;10%</td> <td>&gt;20%</td> <td>HIGHLY</td> <td>35% AND ABOVE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>		GRANULAR SOILS		SILT-CLAY SOILS		OTHER MATERIAL		TRACE	>10%	TRACE	>20%	TRACE	>35%	ORGANIC MATERIAL	2 - 3%	3 - 5%	3 - 5%	5 - 12%	LITTLE	10 - 20%	TRACE OF ORGANIC MATTER	3 - 5%	5 - 10%	5 - 10%	12 - 20%	SOME	20 - 35%	LITTLE ORGANIC MATTER	5 - 10%	>10%	>10%	>20%	HIGHLY	35% AND ABOVE	MODERATELY ORGANIC							HIGHLY ORGANIC							<p style="text-align: center;"><b>WEATHERING</b></p> <p><b>FRESH</b> ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> <p><b>VERY SLIGHT (V. SLI.)</b> ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY, ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> <p><b>SLIGHT (SLI.)</b> ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> <p><b>MODERATE (MOD.)</b> SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> <p><b>MODERATELY SEVERE (MOD. SEV.)</b> ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK.  <i>IF TESTED, WOULD YIELD SPT REFUSAL</i></p> <p><b>SEVERE (SEV.)</b> ALL ROCKS EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN.  <i>IF TESTED, YIELDS SPT N VALUES &gt; 100 BPF</i></p> <p><b>VERY SEVERE (V. SEV.)</b> ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, YIELDS SPT N VALUES &lt; 100 BPF</i></p> <p><b>COMPLETE</b> ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>	<p style="text-align: center;"><b>ROCK HARDNESS</b></p> <p><b>VERY HARD</b> CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGISTS PICK.</p> <p><b>HARD</b> CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p> <p><b>MODERATELY HARD</b> CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGISTS PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p> <p><b>MEDIUM HARD</b> CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGISTS PICK.</p> <p><b>SOFT</b> CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p> <p><b>VERY SOFT</b> CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</p>
GENERAL CLASS.		GRANULAR MATERIALS (<35% PASSING #200)							SILT-CLAY MATERIALS (>85% PASSING #200)							ORGANIC MATERIALS																																																																																																																																																																																																																												
	A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7	A-7-5		A-7-6																																																																																																																																																																																																																														
GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7																																																																																																																																																																																																																															
SYMBOL																																																																																																																																																																																																																																												
% PASSING	50 MX	30 MX	50 MX	51 MN	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN	36 MN																																																																																																																																																																																																																										
LIQUID LIMIT	6 MX	N.P.	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN																																																																																																																																																																																																																										
PLASTIC INDEX	0	0	0	0	4 MX	8 MX	12 MX	16 MX	10 MX	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN	11 MN																																																																																																																																																																																																																										
GROUP INDEX	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																																																																																																																																										
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS	CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		GRANULAR SOILS		SILT-CLAY SOILS	MUCK, PEAT		HIGHLY ORGANIC SOILS																																																																																																																																																																																																																													
GENERAL RATING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR	POOR	UNSUITABLE																																																																																																																																																																																																																																	
	GRANULAR SOILS		SILT-CLAY SOILS		OTHER MATERIAL																																																																																																																																																																																																																																							
	TRACE	>10%	TRACE	>20%	TRACE	>35%																																																																																																																																																																																																																																						
ORGANIC MATERIAL	2 - 3%	3 - 5%	3 - 5%	5 - 12%	LITTLE	10 - 20%																																																																																																																																																																																																																																						
TRACE OF ORGANIC MATTER	3 - 5%	5 - 10%	5 - 10%	12 - 20%	SOME	20 - 35%																																																																																																																																																																																																																																						
LITTLE ORGANIC MATTER	5 - 10%	>10%	>10%	>20%	HIGHLY	35% AND ABOVE																																																																																																																																																																																																																																						
MODERATELY ORGANIC																																																																																																																																																																																																																																												
HIGHLY ORGANIC																																																																																																																																																																																																																																												
<p style="text-align: center;"><b>CONSISTENCY OR DENSENESS</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th rowspan="2">PRIMARY SOIL TYPE</th> <th rowspan="2">COMPACTNESS OR CONSISTENCY</th> <th colspan="2">RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th rowspan="2">RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/F<sup>2</sup>)</th> </tr> <tr> <th>&lt;4</th> <th>4 TO 10</th> </tr> <tr> <td rowspan="3">GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE</td> <td>4</td> <td>10</td> <td rowspan="3">N/A</td> </tr> <tr> <td>LOOSE</td> <td>10</td> <td>30</td> </tr> <tr> <td>MEDIUM DENSE</td> <td>30</td> <td>50</td> </tr> <tr> <td rowspan="3">GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT</td> <td>&lt;2</td> <td>&lt;0.25</td> <td rowspan="3">0.25 TO 0.5</td> </tr> <tr> <td>SOFT</td> <td>2 TO 4</td> <td>0.5 TO 1</td> </tr> <tr> <td>MEDIUM STIFF</td> <td>4 TO 8</td> <td>1 TO 2</td> </tr> <tr> <td rowspan="3"></td> <td>STIFF</td> <td>8 TO 15</td> <td>2 TO 4</td> <td rowspan="3">&gt;4</td> </tr> <tr> <td>VERY STIFF</td> <td>15 TO 30</td> <td></td> </tr> <tr> <td>HARD</td> <td>&gt;30</td> <td></td> </tr> </table>	PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)		RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/F <sup>2</sup> )	<4	4 TO 10	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	4	10	N/A	LOOSE	10	30	MEDIUM DENSE	30	50	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	<2	<0.25	0.25 TO 0.5	SOFT	2 TO 4	0.5 TO 1	MEDIUM STIFF	4 TO 8	1 TO 2		STIFF	8 TO 15	2 TO 4	>4	VERY STIFF	15 TO 30		HARD	>30		<p style="text-align: center;"><b>MISCELLANEOUS SYMBOLS</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td></td> <td>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</td> <td></td> <td>SPT TEST BORING</td> <td></td> <td>SAMPLE DESIGNATIONS</td> </tr> <tr> <td></td> <td>SOIL SYMBOL</td> <td></td> <td>AUGER BORING</td> <td></td> <td>S- BULK SAMPLE</td> </tr> <tr> <td></td> <td>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</td> <td></td> <td>CORE BORING</td> <td></td> <td>SS- SPLIT SPOON SAMPLE</td> </tr> <tr> <td></td> <td>INFERRED SOIL BOUNDARIES</td> <td></td> <td>SHELBY TUBE SAMPLE</td> <td></td> <td>RS- ROCK SAMPLE</td> </tr> <tr> <td></td> <td>INFERRED ROCK LINE</td> <td></td> <td>MONITORING WELL</td> <td></td> <td>RT- RECOMPACTED TRIAXIAL SAMPLE</td> </tr> <tr> <td></td> <td>ALLUVIAL SOIL BOUNDARY</td> <td></td> <td>PIEZOMETER INSTALLATION</td> <td></td> <td>CBR - CBR SAMPLE</td> </tr> <tr> <td></td> <td>DIP/DIP DIRECTION OF ROCK STRUCTURES</td> <td></td> <td>SLOPE INDICATOR INSTALLATION</td> <td></td> <td></td> </tr> <tr> <td></td> <td>SOUNDING ROD</td> <td></td> <td>SPT N-VALUE</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SPT REFUSAL</td> <td></td> <td></td> </tr> </table>		ROADWAY EMBANKMENT WITH SOIL DESCRIPTION		SPT TEST BORING		SAMPLE DESIGNATIONS		SOIL SYMBOL		AUGER BORING		S- BULK SAMPLE		ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS		CORE BORING		SS- SPLIT SPOON SAMPLE		INFERRED SOIL BOUNDARIES		SHELBY TUBE SAMPLE		RS- ROCK SAMPLE		INFERRED ROCK LINE		MONITORING WELL		RT- RECOMPACTED TRIAXIAL SAMPLE		ALLUVIAL SOIL BOUNDARY		PIEZOMETER INSTALLATION		CBR - CBR SAMPLE		DIP/DIP DIRECTION OF ROCK STRUCTURES		SLOPE INDICATOR INSTALLATION				SOUNDING ROD		SPT N-VALUE						SPT REFUSAL			<p style="text-align: center;"><b>ABBREVIATIONS</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>AR - AUGER REFUSAL</td> <td>PMT - PRESSUREMETER TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>SD - SAND, SANDY</td> </tr> <tr> <td>CL - CLAY</td> <td>SL - SILT, SILTY</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>SLI - SLIGHTLY</td> </tr> <tr> <td>CSE - COARSE</td> <td>TCR - TRICONE REFUSAL</td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>U - UNIT WEIGHT</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>U<sub>d</sub> - DRY UNIT WEIGHT</td> </tr> <tr> <td>e - VOID RATIO</td> <td>W - MOISTURE CONTENT</td> </tr> <tr> <td>F - FINE</td> <td>V - VERY</td> </tr> <tr> <td>FOSS - FOSSILIFEROUS</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>FRAC. - FRACTURED</td> <td></td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td></td> </tr> <tr> <td>MED. - MEDIUM</td> <td></td> </tr> </table>	AR - AUGER REFUSAL	PMT - PRESSUREMETER TEST	BT - BORING TERMINATED	SD - SAND, SANDY	CL - CLAY	SL - SILT, SILTY	CPT - CONE PENETRATION TEST	SLI - SLIGHTLY	CSE - COARSE	TCR - TRICONE REFUSAL	DMT - DILATOMETER TEST	U - UNIT WEIGHT	DPT - DYNAMIC PENETRATION TEST	U <sub>d</sub> - DRY UNIT WEIGHT	e - VOID RATIO	W - MOISTURE CONTENT	F - FINE	V - VERY	FOSS - FOSSILIFEROUS	VST - VANE SHEAR TEST	FRAC. - FRACTURED		FRAGS. - FRAGMENTS		MED. - MEDIUM		<p style="text-align: center;"><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td> <p>DRILL UNITS:</p> <input type="checkbox"/> MOBILE B- _____</td> <td> <p>ADVANCING TOOLS:</p> <input type="checkbox"/> CLAY BITS</td> <td> <p>HAMMER TYPE:</p> <input checked="" type="checkbox"/> AUTOMATIC   <input type="checkbox"/> MANUAL</td> </tr> <tr> <td> <input type="checkbox"/> BK-51</td> <td> <input checked="" type="checkbox"/> 8" HOLLOW AUGERS</td> <td> <p>CORE SIZE:</p> <input type="checkbox"/> B- _____</td> </tr> <tr> <td> <input type="checkbox"/> CME-45</td> <td> <input type="checkbox"/> HARD FACED FINGER BITS</td> <td> <input checked="" type="checkbox"/> N- X _____</td> </tr> <tr> <td> <input checked="" type="checkbox"/> CME-550</td> <td> <input type="checkbox"/> TUNG.-CARBIDE INSERTS</td> <td> <input type="checkbox"/> H- _____</td> </tr> <tr> <td> <input type="checkbox"/> PORTABLE HOIST</td> <td> <input checked="" type="checkbox"/> CASING   <input checked="" type="checkbox"/> W/ ADVANCER</td> <td> <p>HAND TOOLS:</p> <input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td> <input type="checkbox"/> OTHER _____</td> <td> <input type="checkbox"/> TRICONE _____ * STEEL TEETH</td> <td> <input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td> <input type="checkbox"/> OTHER _____</td> <td> <input type="checkbox"/> TRICONE _____ * TUNG.-CARB.</td> <td> <input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td> <input type="checkbox"/> OTHER _____</td> <td> <input checked="" type="checkbox"/> CORE BIT</td> <td> <input type="checkbox"/> VANE SHEAR TEST</td> </tr> <tr> <td></td> <td> <input type="checkbox"/> OTHER _____</td> <td> <input type="checkbox"/> OTHER _____</td> </tr> </table>	<p>DRILL UNITS:</p> <input type="checkbox"/> MOBILE B- _____	<p>ADVANCING TOOLS:</p> <input type="checkbox"/> CLAY BITS	<p>HAMMER TYPE:</p> <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input checked="" type="checkbox"/> 8" HOLLOW AUGERS	<p>CORE SIZE:</p> <input type="checkbox"/> B- _____	<input type="checkbox"/> CME-45	<input type="checkbox"/> HARD FACED FINGER BITS	<input checked="" type="checkbox"/> N- X _____	<input checked="" type="checkbox"/> CME-550	<input type="checkbox"/> TUNG.-CARBIDE INSERTS	<input type="checkbox"/> H- _____	<input type="checkbox"/> PORTABLE HOIST	<input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> W/ ADVANCER	<p>HAND TOOLS:</p> <input type="checkbox"/> POST HOLE DIGGER	<input type="checkbox"/> OTHER _____	<input type="checkbox"/> TRICONE _____ * STEEL TEETH	<input type="checkbox"/> HAND AUGER	<input type="checkbox"/> OTHER _____	<input type="checkbox"/> TRICONE _____ * TUNG.-CARB.	<input type="checkbox"/> SOUNDING ROD	<input type="checkbox"/> OTHER _____	<input checked="" type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST		<input type="checkbox"/> OTHER _____	<input type="checkbox"/> OTHER _____	<p style="text-align: center;"><b>FRACTURE SPACING</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table> <p style="text-align: center;"><b>BEDDING</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>&gt; 4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table>	TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FEET	VERY CLOSE	LESS THAN 0.16 FEET	TERM	THICKNESS	VERY THICKLY BEDDED	> 4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET	<p style="text-align: center;"><b>INDURATION</b></p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p><b>FRIABLE</b> RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p><b>MODERATELY INDURATED</b> GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p><b>INDURATED</b> GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p><b>EXTREMELY INDURATED</b> SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>																																																										
PRIMARY SOIL TYPE			COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)		RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/F <sup>2</sup> )																																																																																																																																																																																																																																						
	<4	4 TO 10																																																																																																																																																																																																																																										
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	4	10	N/A																																																																																																																																																																																																																																								
	LOOSE	10	30																																																																																																																																																																																																																																									
	MEDIUM DENSE	30	50																																																																																																																																																																																																																																									
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	<2	<0.25	0.25 TO 0.5																																																																																																																																																																																																																																								
	SOFT	2 TO 4	0.5 TO 1																																																																																																																																																																																																																																									
	MEDIUM STIFF	4 TO 8	1 TO 2																																																																																																																																																																																																																																									
	STIFF	8 TO 15	2 TO 4	>4																																																																																																																																																																																																																																								
	VERY STIFF	15 TO 30																																																																																																																																																																																																																																										
	HARD	>30																																																																																																																																																																																																																																										
	ROADWAY EMBANKMENT WITH SOIL DESCRIPTION		SPT TEST BORING		SAMPLE DESIGNATIONS																																																																																																																																																																																																																																							
	SOIL SYMBOL		AUGER BORING		S- BULK SAMPLE																																																																																																																																																																																																																																							
	ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS		CORE BORING		SS- SPLIT SPOON SAMPLE																																																																																																																																																																																																																																							
	INFERRED SOIL BOUNDARIES		SHELBY TUBE SAMPLE		RS- ROCK SAMPLE																																																																																																																																																																																																																																							
	INFERRED ROCK LINE		MONITORING WELL		RT- RECOMPACTED TRIAXIAL SAMPLE																																																																																																																																																																																																																																							
	ALLUVIAL SOIL BOUNDARY		PIEZOMETER INSTALLATION		CBR - CBR SAMPLE																																																																																																																																																																																																																																							
	DIP/DIP DIRECTION OF ROCK STRUCTURES		SLOPE INDICATOR INSTALLATION																																																																																																																																																																																																																																									
	SOUNDING ROD		SPT N-VALUE																																																																																																																																																																																																																																									
			SPT REFUSAL																																																																																																																																																																																																																																									
AR - AUGER REFUSAL	PMT - PRESSUREMETER TEST																																																																																																																																																																																																																																											
BT - BORING TERMINATED	SD - SAND, SANDY																																																																																																																																																																																																																																											
CL - CLAY	SL - SILT, SILTY																																																																																																																																																																																																																																											
CPT - CONE PENETRATION TEST	SLI - SLIGHTLY																																																																																																																																																																																																																																											
CSE - COARSE	TCR - TRICONE REFUSAL																																																																																																																																																																																																																																											
DMT - DILATOMETER TEST	U - UNIT WEIGHT																																																																																																																																																																																																																																											
DPT - DYNAMIC PENETRATION TEST	U <sub>d</sub> - DRY UNIT WEIGHT																																																																																																																																																																																																																																											
e - VOID RATIO	W - MOISTURE CONTENT																																																																																																																																																																																																																																											
F - FINE	V - VERY																																																																																																																																																																																																																																											
FOSS - FOSSILIFEROUS	VST - VANE SHEAR TEST																																																																																																																																																																																																																																											
FRAC. - FRACTURED																																																																																																																																																																																																																																												
FRAGS. - FRAGMENTS																																																																																																																																																																																																																																												
MED. - MEDIUM																																																																																																																																																																																																																																												
<p>DRILL UNITS:</p> <input type="checkbox"/> MOBILE B- _____	<p>ADVANCING TOOLS:</p> <input type="checkbox"/> CLAY BITS	<p>HAMMER TYPE:</p> <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																																																																																										
<input type="checkbox"/> BK-51	<input checked="" type="checkbox"/> 8" HOLLOW AUGERS	<p>CORE SIZE:</p> <input type="checkbox"/> B- _____																																																																																																																																																																																																																																										
<input type="checkbox"/> CME-45	<input type="checkbox"/> HARD FACED FINGER BITS	<input checked="" type="checkbox"/> N- X _____																																																																																																																																																																																																																																										
<input checked="" type="checkbox"/> CME-550	<input type="checkbox"/> TUNG.-CARBIDE INSERTS	<input type="checkbox"/> H- _____																																																																																																																																																																																																																																										
<input type="checkbox"/> PORTABLE HOIST	<input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> W/ ADVANCER	<p>HAND TOOLS:</p> <input type="checkbox"/> POST HOLE DIGGER																																																																																																																																																																																																																																										
<input type="checkbox"/> OTHER _____	<input type="checkbox"/> TRICONE _____ * STEEL TEETH	<input type="checkbox"/> HAND AUGER																																																																																																																																																																																																																																										
<input type="checkbox"/> OTHER _____	<input type="checkbox"/> TRICONE _____ * TUNG.-CARB.	<input type="checkbox"/> SOUNDING ROD																																																																																																																																																																																																																																										
<input type="checkbox"/> OTHER _____	<input checked="" type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST																																																																																																																																																																																																																																										
	<input type="checkbox"/> OTHER _____	<input type="checkbox"/> OTHER _____																																																																																																																																																																																																																																										
TERM	SPACING																																																																																																																																																																																																																																											
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																																																																																																											
WIDE	3 TO 10 FEET																																																																																																																																																																																																																																											
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																																																																																																											
CLOSE	0.16 TO 1 FEET																																																																																																																																																																																																																																											
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																																																																																																											
TERM	THICKNESS																																																																																																																																																																																																																																											
VERY THICKLY BEDDED	> 4 FEET																																																																																																																																																																																																																																											
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																																																											
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																																																											
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																																																											
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																																																											
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																																																											
<p style="text-align: center;"><b>TEXTURE OR GRAIN SIZE</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.0</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F. SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td>GRAIN SIZE</td> <td>MM 305</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> <tr> <td></td> <td>IN. 12"</td> <td>3"</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.0	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE	MM 305	75	2.0	0.25	0.05	0.005		IN. 12"	3"					<p style="text-align: center;"><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>	SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p style="text-align: center;"><b>PLASTICITY</b></p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>	NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p style="text-align: center;"><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL.-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>	<p style="text-align: center;"><b>FRAC. MARK: -T10- *306 LOCATED AT -L- STA.236+62.44; OFFSET 178.11' (LEFT)</b></p> <p style="text-align: right;">ELEVATION: 754.87</p> <p>NOTES:</p>																																																																																																																																																																							
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																																																																						
	4.76	2.0	0.42	0.25	0.075	0.053																																																																																																																																																																																																																																						
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																																																																						
GRAIN SIZE	MM 305	75	2.0	0.25	0.05	0.005																																																																																																																																																																																																																																						
	IN. 12"	3"																																																																																																																																																																																																																																										
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																																																										
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																																																																										
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																										
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																																																																										
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																										
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																																																																										
LOW PLASTICITY	0-5	VERY LOW																																																																																																																																																																																																																																										
MED. PLASTICITY	6-15	SLIGHT																																																																																																																																																																																																																																										
HIGH PLASTICITY	16-25	MEDIUM																																																																																																																																																																																																																																										
	26 OR MORE	HIGH																																																																																																																																																																																																																																										