PROJECT REFERENCE NO.	SHEET NO.
R-2610 A	10
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 17691 ENGINEER RICHARD A SHILLINGLAW — 12-11-03

HYDRAULICS ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 12786 ENGINEER STEVEN M BONDON — 12.15.03

CONST.REV.

R/W REV.

-L-	-Y7B-	-Y9-	-Y9-
PI Sta 30+60.891	PI Sta 10+18.280	PI Sta 10+48.343	PI Sta 11+78.775
Δ = 19° 48' 16.9" (LT)	Δ = 6° 52' 07.8" (LT)	Δ = 21° 09' 24.4" (RT)	Δ = 77° 20' 16.2" (LT)
L = 411.332	L = 36.517	L = 36.926	L = 40.494
T = 207.739	T = 18.280	T = 18.675	T = 24.008
R = 1,190.000	R = 304.602	R = 100.000	R = 30.000
SE = 0.041		SEE SHEET 2G FOR SE	SEE SHEET 2G FOR SE
Runoff = 36m			

-BL-
PI Sta 29+81.348
D = 19° 48' 17.0" (LT)
L = 411.332
T = 207.739
R = 1,190.000

SEE SHEET 30 FOR -L- PROFILE
SEE SHEET 43 FOR -Y9- PROFILE
SEE SHEET 2-G FOR -L- & -Y9- INTERSECTION DETAILS
SEE SHEETS 2-H & 2-I FOR DITCH DETAILS
SEE SHEET 48 FOR DITCH PROFILES
SEE CROSS-SECTIONS AND ROADWAY STANDARD DRAWINGS STD. No. 862.01 SHEET 2 FOR SPECIAL MEDIAN GRADING

REVISIONS

8/17/99

MATCHLINE -L- 28+90 SEE SHEET 9

MATCHLINE -L- 32+20 SEE SHEET 11

-L- +41.745
116.883m
(383.47 ft)

-L- +35.470
96.07lm
(315.19ft)

-L- +58.916
98.75lm
(323.99 ft)

-L- +67.413
104.356m
(342.38 ft)

-L- +43.045
87.974m
(288.63 ft)

-L- +58.000
61.000m
(200.13ft)

-L- +54.000
41.000m
(134.51ft)

-L- +81.000
40.000m
(131.23ft)

-L- +86.000
28.041m
(92.00 ft)

-Y9- +57.685
14.166m (46.48ft)

-L- +42.710
28.042m
(92.00 ft)

-L- +80.770
28.042m
(92.00 ft)

-L- +00.000
32.687m
(107.24ft)

-Y9- +00.000
8.522m (27.96 ft)
12.000m (39.37ft)

-Y9- +29.668
8.193m
(26.88 ft)

-Y9- +40.000
16.000m
(52.49ft)

-Y9- +60.000
11.000m
(36.09ft)

-Y9- +66.593
8.196m
(26.89ft)

-Y9- +20.000
15.000m
(49.21ft)

-Y9- +54.767
8.196m
(26.89ft)

-Y9- +60.000
11.000m
(36.09ft)

-Y9- +72.646
8.196m
(26.89ft)

-L- 31+57.200
32.919m

-L- 31+57.200
42.063m

-L- +99.844
32.919m
(108.00 ft)

-Y7B- +57.658
8.832m
(28.98 ft)

-Y9- POT Sta. 12+82.829=
-Y7B- POC Sta. 10+38.854

-Y7B- PT Sta. 10+36.517

END CONST.
-Y7B- POT 10+72.336

BEG. CONST.
-Y7B- PC Sta. 10+00.000

-L- STA 31+48.721 =
-Y9- STA 12+12.178

-Y9- PT Sta. 11+95.261

-Y9- PC Sta. 11+54.767

-Y9- PT Sta. 10+66.593

-L- POC 30+00.000 =
-BL- 30+79.544
0.0m OFFSET
REBAR, NO CAP

END SPECIAL GRADING
-L- STA. 30+05.930

BEGIN CONST.
-Y9- POT Sta. 10+00.000

N 51° 30' 10.2" W

N 53° 50' 28.0" W

N 48° 49' 15.8" W

N 69° 58' 40.2" W

CUT BACK GULLY SLOPES TO 2:1 MAX DO NOT CLEAR TREES

REMOVE VERTICAL HEADCUT, SET DITCH GRADE AT 10% MAX

DITCH REPAIR SEE DETAIL 10G

RIP RAP BASIN #1 SEE SHEET 2-K FOR DETAIL

0.6m TAIL DITCH SEE DETAIL 10F

SPECIAL DITCH GRADE SLOPE = 0.44% SEE DETAIL 10D

0.6m LATERAL BASE DITCH SEE DETAIL 10A

LINE TOE SEE DETAIL 10B

CHANNEL IMPROVEMENT SEE DETAIL 10E

"V" DITCH CLEANOUT SEE DETAIL 10C

CLEANOUT 4M³ SEDIMENT

RETAIN DI & DO NOT DISTURB

BEG FENCE
BEG C/A
-Y7B- +57.658

END FENCE -L- +16.590
END C/A 59.692m
(195.84 ft)

END SHLDR BERM GTR.
STA. 30+80 -L- LT

SHLDR BERM GTR.

REMOVE G/R

REMOVE 600 mm CMP

REMOVE 375 mm CONC

REMOVE 450 mm CONC

REMOVE 600 mm CONC

REMOVE 450 mm CONC

REMOVE 375 mm CMP

REMOVE 600 mm CONC

REMOVE 450 mm CONC

REMOVE 600 mm CONC

REMOVE 450 mm CONC

REMOVE 375 mm CONC

REMOVE 600 mm CONC

REMOVE 450 mm CONC

REMOVE 450 mm CONC

REMOVE 375 mm CONC

REMOVE 450 mm CONC

REMOVE 450 mm CONC

REMOVE 375 mm CMP

REMOVE 450 mm CONC

REMOVE 450 mm CONC

REMOVE 375 mm CONC