PROJ. REFERENCE NO.	SHEET NO.
U-0620	45

0 10

LEGEND

[X] N60 EQUIVALENT

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

130 120

CPT 22
122+89
18.61' LT -L-
122+50.00
122.44
0.0250
WETLANDS 122.69
3:1
122.00
WETLANDS
ALLUVIUM: SOFT, GRAY, FINE SANDY CLAY (M)
MEDIUM STIFF, GRAY, FINE SANDY SILT (M TO W)
VERY LOOSE, GRAY, SILTY FINE SAND (W TO SAT)
SOFT, GRAY, FINE TO COARSE SANDY, SILTY CLAY (M)
VERY LOOSE, GRAY, SILTY FINE SAND (M TO SAT)
SOFT, GRAY, FINE TO COARSE SANDY, SILTY CLAY (M)
MEDIUM STIFF, GRAY, FINE SANDY SILT (M TO W)
3 5 3 3 3 5
B-27
122+41
66.5' RT -L-
122+41.67
WETLANDS 121.28
ALLUVIUM: SOFT, GRAY, FINE SANDY, SILTY CLAY (M)
LOOSE, GRAY, SILTY, CLAYEY, FINE SAND (SAT)
LOOSE, BLACK TO GRAY, SLIGHTLY CLAYEY, SILTY, FINE SAND WITH TRACE OF ORGANIC MATTER (SAT)
SOFT, GRAY, FINE TO COARSE SANDY, SILTY CLAY (M)
2 4 4 2
CAPE FEAR FORMATION:
MEDIUM STIFF TO STIFF, LIGHT GRAY, FINE SANDY, SILTY CLAY WITH TRACE OF MICA (M)
7 10 8
STIFF, LIGHT GRAY, COARSE TO FINE, SANDY, CLAYEY SILT WITH TRACE OF MICA (M)
WETLANDS 121.14
121.07
WETLANDS
122+00.00

130 120

122+00.00
21.55
121.44
0.0250
121.50
3:1
121.92
WETLANDS

121+50.00

AP-6
121+00
CENTERLINE
121+00.00
21.92
0.0250
121.42
3:1
121.42
116.52
ALLUVIUM: VERY LOOSE, BLACK, HIGHLY ORGANIC, SILTY, FINE SAND, MUCK (M)
VERY LOOSE, GRAY, SILTY, FINE SAND (W TO SAT)
SOFT, GRAY, FINE TO COARSE, SANDY, SILTY CLAY (M)
VERY LOOSE, GRAY, SILTY, FINE SAND (W TO SAT)

120+50.00
12.55
0.0250
122.50
3:1
121.30
119.67

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150