

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION												GRADATION						ROCK DESCRIPTION						TERMS AND DEFINITIONS																																																																										
SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE: VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGH PLASTIC, A-7-6												WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE (ALSO POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.						HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS: <div style="display: flex; align-items: center;"> <p>NON-COASTAL PLAIN MATERIAL THAT YIELDS SPT N VALUES > 100 BLOWS PER FOOT.</p> </div>						ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOOD PLAIN (F.P.) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR B.P.F.) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS LESS THAN 0.1 FOOT PENETRATION WITH 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																										
												SOIL LEGEND AND AASHTO CLASSIFICATION <table border="1" style="width:100%; font-size: small;"> <thead> <tr> <th rowspan="2">GENERAL CLASS.</th> <th colspan="4">GRANULAR MATERIALS (< 35% PASSING #200)</th> <th colspan="3">SILT-CLAY MATERIALS (> 85% PASSING #200)</th> <th colspan="3">ORGANIC MATERIALS</th> </tr> <tr> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th> </th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-4, A-5</th> </tr> </thead> <tbody> <tr> <td>GROUP CLASS.</td> <td>A-1-a</td> <td>A-1-b</td> <td>A-2-4</td> <td>A-2-5</td> <td>A-2-6</td> <td>A-2-7</td> <td> </td> <td> </td> <td>A-7-a</td> <td>A-7-b</td> <td>A-3</td> <td>A-6, A-7</td> <td> </td> </tr> <tr> <td>SYMBOL</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> <td>[Symbol]</td> </tr> <tr> <td>% PASSING</td> <td>50 MX</td> <td>30 MX</td> <td>10 MN</td> <td>15 MN</td> <td>10 MN</td> <td>10 MN</td> <td>10 MN</td> <td>10 MN</td> <td>10 MN</td> <td>10 MN</td> <td>10 MN</td> <td>10 MN</td> <td>10 MN</td> </tr> </tbody> </table>												GENERAL CLASS.	GRANULAR MATERIALS (< 35% PASSING #200)				SILT-CLAY MATERIALS (> 85% PASSING #200)			ORGANIC MATERIALS			A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7			A-7-a	A-7-b	A-3	A-6, A-7		SYMBOL	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	% PASSING	50 MX	30 MX	10 MN	15 MN	10 MN	10 MN	10 MN	10 MN	10 MN	10 MN	10 MN	10 MN	10 MN	MINERALOGICAL COMPOSITION MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.						WEATHERING FRESH - ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER HAMMER IF CRYSTALLINE. VERY SLIGHT (V. SL.) - ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY, ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE. SLIGHT (SL.) - ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH, OPEN JOINTS MAY CONTAIN CLAY, IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED, CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. MODERATE (MOD.) - SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK. MODERATELY SEVERE (MOD. SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION, ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK, ROCK GIVES "CLUNK" SOUND WHEN STRUCK, IF TESTED, WOULD YIELD SPT REFUSAL. SEVERE (SEV.) - ALL ROCKS EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL, IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT, SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN, IF TESTED, YIELDS SPT N VALUES > 100 BPF. VERY SEVERE (V. SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING, SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN, IF TESTED, YIELDS SPT N VALUES < 100 BPF. COMPLETE - ROCK REDUCED TO SOIL, ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS, QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS, SAPROLITE IS ALSO AN EXAMPLE.					
																									GENERAL CLASS.	GRANULAR MATERIALS (< 35% PASSING #200)				SILT-CLAY MATERIALS (> 85% PASSING #200)			ORGANIC MATERIALS																																																																	
												A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5																																																																													
GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7			A-7-a	A-7-b	A-3	A-6, A-7																																																																																						
SYMBOL	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]	[Symbol]																																																																																					
% PASSING	50 MX	30 MX	10 MN	15 MN	10 MN	10 MN	10 MN	10 MN	10 MN	10 MN	10 MN	10 MN	10 MN																																																																																					
CONSISTENCY OR DENSITY <table border="1" style="width:100%; font-size: x-small;"> <thead> <tr> <th rowspan="2">PRIMARY SOIL TYPE</th> <th colspan="2">COMPACTION OR CONSISTENCY</th> <th colspan="2">RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th colspan="2">RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/SQ. FT.)</th> </tr> </thead> <tbody> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE</td> <td>LOOSE</td> <td>< 4</td> <td>4 TO 10</td> <td></td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT</td> <td>SOFT</td> <td>< 2</td> <td>2 TO 4</td> <td>< 0.25</td> <td>0.25 TO 0.5</td> </tr> <tr> <td></td> <td>MEDIUM STIFF</td> <td>STIFF</td> <td>4 TO 8</td> <td>8 TO 15</td> <td>0.5 TO 1</td> <td>1 TO 2</td> </tr> <tr> <td></td> <td>VERY STIFF</td> <td>HARD</td> <td>15 TO 30</td> <td>> 30</td> <td>2 TO 4</td> <td>> 4</td> </tr> </tbody> </table>												PRIMARY SOIL TYPE	COMPACTION OR CONSISTENCY		RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)		RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/SQ. FT.)		GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	LOOSE	< 4	4 TO 10		N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	SOFT	< 2	2 TO 4	< 0.25	0.25 TO 0.5		MEDIUM STIFF	STIFF	4 TO 8	8 TO 15	0.5 TO 1	1 TO 2		VERY STIFF	HARD	15 TO 30	> 30	2 TO 4	> 4	GROUND WATER <div style="display: flex; align-items: center; gap: 10px;"> <div style="text-align: center;"> WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING. </div> <div style="text-align: center;"> STATIC WATER LEVEL AFTER 24 HOURS. </div> <div style="text-align: center;"> PERCHED WATER, SATURATED ZONE OR WATER BEARING STRATA </div> <div style="text-align: center;"> SPRING OR SEEPAGE </div> </div>						MISCELLANEOUS SYMBOLS <table border="0" style="width:100%; font-size: x-small;"> <tr> <td>[Symbol] ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</td> <td>[Symbol] TEST BORING</td> <td>[Symbol] SAMPLE DESIGNATIONS</td> </tr> <tr> <td>[Symbol] SOIL SYMBOL</td> <td>[Symbol] AUGER BORING</td> <td>S - BULK SAMPLE</td> </tr> <tr> <td>[Symbol] ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</td> <td>[Symbol] CORE BORING</td> <td>SS - SPLIT SPOON SAMPLE</td> </tr> <tr> <td>[Symbol] INFERRED SOIL BOUNDARIES</td> <td>[Symbol] MONITORING WELL</td> <td>ST - SHELBY TUBE SAMPLE</td> </tr> <tr> <td>[Symbol] INFERRED ROCK LINE</td> <td>[Symbol] PIEZOMETER INSTALLATION</td> <td>RS - ROCK SAMPLE</td> </tr> <tr> <td>[Symbol] ALLUVIAL SOIL BOUNDARY</td> <td>[Symbol] SLOPE INDICATOR INSTALLATION</td> <td>RT - RECOMPACTED TRIAXIAL SAMPLE</td> </tr> <tr> <td>[Symbol] DIP/DIP DIRECTION OF ROCK STRUCTURES</td> <td>[Symbol] SPT N-VALUE</td> <td>CBR - CBR SAMPLE</td> </tr> <tr> <td>[Symbol] SOUNDING ROD</td> <td>[Symbol] SPT REFUSAL</td> <td></td> </tr> </table>						[Symbol] ROADWAY EMBANKMENT WITH SOIL DESCRIPTION	[Symbol] TEST BORING	[Symbol] SAMPLE DESIGNATIONS	[Symbol] SOIL SYMBOL	[Symbol] AUGER BORING	S - BULK SAMPLE	[Symbol] ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS	[Symbol] CORE BORING	SS - SPLIT SPOON SAMPLE	[Symbol] INFERRED SOIL BOUNDARIES	[Symbol] MONITORING WELL	ST - SHELBY TUBE SAMPLE	[Symbol] INFERRED ROCK LINE	[Symbol] PIEZOMETER INSTALLATION	RS - ROCK SAMPLE	[Symbol] ALLUVIAL SOIL BOUNDARY	[Symbol] SLOPE INDICATOR INSTALLATION	RT - RECOMPACTED TRIAXIAL SAMPLE	[Symbol] DIP/DIP DIRECTION OF ROCK STRUCTURES	[Symbol] SPT N-VALUE	CBR - CBR SAMPLE	[Symbol] SOUNDING ROD	[Symbol] SPT REFUSAL																	
PRIMARY SOIL TYPE	COMPACTION OR CONSISTENCY		RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)		RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/SQ. FT.)																																																																																													
	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	LOOSE	< 4	4 TO 10		N/A																																																																																											
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	SOFT	< 2	2 TO 4	< 0.25	0.25 TO 0.5																																																																																												
	MEDIUM STIFF	STIFF	4 TO 8	8 TO 15	0.5 TO 1	1 TO 2																																																																																												
	VERY STIFF	HARD	15 TO 30	> 30	2 TO 4	> 4																																																																																												
[Symbol] ROADWAY EMBANKMENT WITH SOIL DESCRIPTION	[Symbol] TEST BORING	[Symbol] SAMPLE DESIGNATIONS																																																																																																
[Symbol] SOIL SYMBOL	[Symbol] AUGER BORING	S - BULK SAMPLE																																																																																																
[Symbol] ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS	[Symbol] CORE BORING	SS - SPLIT SPOON SAMPLE																																																																																																
[Symbol] INFERRED SOIL BOUNDARIES	[Symbol] MONITORING WELL	ST - SHELBY TUBE SAMPLE																																																																																																
[Symbol] INFERRED ROCK LINE	[Symbol] PIEZOMETER INSTALLATION	RS - ROCK SAMPLE																																																																																																
[Symbol] ALLUVIAL SOIL BOUNDARY	[Symbol] SLOPE INDICATOR INSTALLATION	RT - RECOMPACTED TRIAXIAL SAMPLE																																																																																																
[Symbol] DIP/DIP DIRECTION OF ROCK STRUCTURES	[Symbol] SPT N-VALUE	CBR - CBR SAMPLE																																																																																																
[Symbol] SOUNDING ROD	[Symbol] SPT REFUSAL																																																																																																	
TEXTURE OR GRAIN SIZE <table border="1" style="width:100%; font-size: x-small;"> <thead> <tr> <th>U.S. STD. SIEVE SIZE</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> </thead> <tbody> <tr> <td>OPENING (MM)</td> <td>4.76</td> <td>2.0</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </tbody> </table>												U.S. STD. SIEVE SIZE	4	10	40	60	200	270	OPENING (MM)	4.76	2.0	0.42	0.25	0.075	0.053	ABBREVIATIONS <table border="0" style="width:100%; font-size: x-small;"> <tr> <td>AR - AUGER REFUSAL</td> <td>PMT - PRESSUREMETER TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>SD. - SAND, SANDY</td> </tr> <tr> <td>CL. - CLAY</td> <td>SL. - SILT, SILTY</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>SLI. - SLIGHTLY</td> </tr> <tr> <td>CSE. - COARSE</td> <td>TCR - TRICONE REFUSAL</td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>γ - UNIT WEIGHT</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>γ_d - DRY UNIT WEIGHT</td> </tr> <tr> <td>o - VOID RATIO</td> <td>w - MOISTURE CONTENT</td> </tr> <tr> <td>F. - FINE</td> <td>v - VERY</td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>FRAC. - FRACTURED</td> <td></td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td></td> </tr> <tr> <td>MED. - MEDIUM</td> <td></td> </tr> </table>						AR - AUGER REFUSAL	PMT - PRESSUREMETER TEST	BT - BORING TERMINATED	SD. - SAND, SANDY	CL. - CLAY	SL. - SILT, SILTY	CPT - CONE PENETRATION TEST	SLI. - SLIGHTLY	CSE. - COARSE	TCR - TRICONE REFUSAL	DMT - DILATOMETER TEST	γ - UNIT WEIGHT	DPT - DYNAMIC PENETRATION TEST	γ _d - DRY UNIT WEIGHT	o - VOID RATIO	w - MOISTURE CONTENT	F. - FINE	v - VERY	FOSS. - FOSSILIFEROUS	VST - VANE SHEAR TEST	FRAC. - FRACTURED		FRAGS. - FRAGMENTS		MED. - MEDIUM																																										
U.S. STD. SIEVE SIZE	4	10	40	60	200	270																																																																																												
OPENING (MM)	4.76	2.0	0.42	0.25	0.075	0.053																																																																																												
AR - AUGER REFUSAL	PMT - PRESSUREMETER TEST																																																																																																	
BT - BORING TERMINATED	SD. - SAND, SANDY																																																																																																	
CL. - CLAY	SL. - SILT, SILTY																																																																																																	
CPT - CONE PENETRATION TEST	SLI. - SLIGHTLY																																																																																																	
CSE. - COARSE	TCR - TRICONE REFUSAL																																																																																																	
DMT - DILATOMETER TEST	γ - UNIT WEIGHT																																																																																																	
DPT - DYNAMIC PENETRATION TEST	γ _d - DRY UNIT WEIGHT																																																																																																	
o - VOID RATIO	w - MOISTURE CONTENT																																																																																																	
F. - FINE	v - VERY																																																																																																	
FOSS. - FOSSILIFEROUS	VST - VANE SHEAR TEST																																																																																																	
FRAC. - FRACTURED																																																																																																		
FRAGS. - FRAGMENTS																																																																																																		
MED. - MEDIUM																																																																																																		
SOIL MOISTURE - CORRELATION OF TERMS <table border="1" style="width:100%; font-size: x-small;"> <thead> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </tbody> </table>												SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	EQUIPMENT USED ON SUBJECT PROJECT <table border="1" style="width:100%; font-size: x-small;"> <thead> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> </thead> <tbody> <tr> <td><input checked="" type="checkbox"/> MOBILE B-57</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> AUTOMATIC <input checked="" type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input checked="" type="checkbox"/> 8" HOLLOW AUGERS</td> <td>CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -N <input type="checkbox"/> -H</td> </tr> <tr> <td><input type="checkbox"/> CME-45</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td>HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> OTHER</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input checked="" type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td></td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH</td> <td></td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.</td> <td></td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> CORE BIT</td> <td></td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> OTHER</td> <td></td> </tr> </tbody> </table>						DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input checked="" type="checkbox"/> MOBILE B-57	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> AUTOMATIC <input checked="" type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input checked="" type="checkbox"/> 8" HOLLOW AUGERS	CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -N <input type="checkbox"/> -H	<input type="checkbox"/> CME-45	<input type="checkbox"/> HARD FACED FINGER BITS	HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> OTHER	<input type="checkbox"/> CME-550	<input checked="" type="checkbox"/> TUNG-CARBIDE INSERTS		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER		<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH		<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.		<input type="checkbox"/> OTHER	<input type="checkbox"/> CORE BIT		<input type="checkbox"/> OTHER	<input type="checkbox"/> OTHER																																					
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																
<input checked="" type="checkbox"/> MOBILE B-57	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> AUTOMATIC <input checked="" type="checkbox"/> MANUAL																																																																																																
<input type="checkbox"/> BK-51	<input checked="" type="checkbox"/> 8" HOLLOW AUGERS	CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -N <input type="checkbox"/> -H																																																																																																
<input type="checkbox"/> CME-45	<input type="checkbox"/> HARD FACED FINGER BITS	HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> OTHER																																																																																																
<input type="checkbox"/> CME-550	<input checked="" type="checkbox"/> TUNG-CARBIDE INSERTS																																																																																																	
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER																																																																																																	
<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH																																																																																																	
<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.																																																																																																	
<input type="checkbox"/> OTHER	<input type="checkbox"/> CORE BIT																																																																																																	
<input type="checkbox"/> OTHER	<input type="checkbox"/> OTHER																																																																																																	
PLASTICITY <table border="1" style="width:100%; font-size: x-small;"> <thead> <tr> <th>NONPLASTIC</th> <th>VERY LOW</th> <th>SLIGHT</th> <th>MEDIUM</th> <th>HIGH</th> </tr> </thead> <tbody> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> <td></td> </tr> </tbody> </table>												NONPLASTIC	VERY LOW	SLIGHT	MEDIUM	HIGH	0-5	6-15	16-25	26 OR MORE		FRACTURE SPACING <table border="1" style="width:100%; font-size: x-small;"> <thead> <tr> <th>TERM</th> <th>SPACING</th> </tr> </thead> <tbody> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </tbody> </table>						TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FEET	VERY CLOSE	LESS THAN 0.16 FEET	BEDDING <table border="1" style="width:100%; font-size: x-small;"> <thead> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> </thead> <tbody> <tr> <td>VERY THICKLY BEDDED</td> <td>> 4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </tbody> </table>						TERM	THICKNESS	VERY THICKLY BEDDED	> 4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET																																							
NONPLASTIC	VERY LOW	SLIGHT	MEDIUM	HIGH																																																																																														
0-5	6-15	16-25	26 OR MORE																																																																																															
TERM	SPACING																																																																																																	
VERY WIDE	MORE THAN 10 FEET																																																																																																	
WIDE	3 TO 10 FEET																																																																																																	
MODERATELY CLOSE	1 TO 3 FEET																																																																																																	
CLOSE	0.16 TO 1 FEET																																																																																																	
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																	
TERM	THICKNESS																																																																																																	
VERY THICKLY BEDDED	> 4 FEET																																																																																																	
THICKLY BEDDED	1.5 - 4 FEET																																																																																																	
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																	
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																	
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																	
THINLY LAMINATED	< 0.008 FEET																																																																																																	
COLOR DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.												INDURATION FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC. <table border="1" style="width:100%; font-size: x-small;"> <tbody> <tr> <td>FRIABLE</td> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </tbody> </table>						FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																									
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																	
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																	
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																	
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																	
BENCH MARK: NCGS MONUMENT "ROYAL" 11700.38 - 841 - 58.63' LT ELEVATION: 763.83 NOTES:																																																																																																		