

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL UNIT



SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION		GRADATION		ROCK DESCRIPTION		TERMS AND DEFINITIONS																																																																																																																																																																																																																																			
SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER 30 cm ACCORDING TO STANDARD PENETRATION TEST (AASHTO T208, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE: <i>VERY STIFF, GRAY SILT CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, MEDIUM PLASTIC, A-7-6</i>		WELL-GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE (ALSO POORLY GRADED). GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.		HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 2.5 cm PER 50 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:		ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FESSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL FLOOD PLAIN (F.P.) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIORUS STRATUM. RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N) OF A 63.5 kg HAMMER FALLING 0.76 METERS REQUIRED TO PRODUCE A PENETRATION OF 30 cm INTO SOIL WITH A 5 cm OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS LESS THAN 2.5 cm PENETRATION WITH 50 BLOWS. STRATA CORE RECOVERY (SREC) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																																																																																																																																																																			
<table border="1"> <tr> <th colspan="10">SOIL LEGEND AND AASHTO CLASSIFICATION</th> </tr> <tr> <th rowspan="2">GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (< 75% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (> 75% PASSING #200)</th> <th colspan="2">ORGANIC MATERIALS</th> </tr> <tr> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th></th> <th></th> </tr> <tr> <th>GROUP CLASS.</th> <td>A-1-a</td> <td>A-1-b</td> <td>A-2-4</td> <td>A-2-5</td> <td>A-2-6</td> <td>A-2-7</td> <td>A-4-4</td> <td>A-4-5</td> <td>A-6-4</td> <td>A-6-5</td> <td>A-7-4</td> <td>A-7-5</td> </tr> <tr> <th>SYMBOL</th> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>% PASSING</th> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> </tr> <tr> <th>LIQUID LIMIT PLASTIC INDEX</th> <td>6 MX</td> <td>N.P.</td> <td>40 MX/41 MN 10 MX/10 MN</td> <td>40 MX/41 MN 11 MN/11 MN</td> <td>40 MX/41 MN 10 MX/10 MN</td> <td>40 MX/41 MN 11 MN/11 MN</td> <td>40 MX/41 MN 10 MX/10 MN</td> <td>40 MX/41 MN 11 MN/11 MN</td> <td>40 MX/41 MN 10 MX/10 MN</td> <td>40 MX/41 MN 11 MN/11 MN</td> <td>40 MX/41 MN 10 MX/10 MN</td> <td>40 MX/41 MN 11 MN/11 MN</td> </tr> <tr> <th>GROUP INDEX</th> <td>0</td> <td>0</td> <td>0</td> <td>4 MX</td> <td>8 MX</td> <td>12 MX</td> <td>16 MX</td> <td>20 MX</td> <td>24 MX</td> <td>28 MX</td> <td>32 MX</td> <td>36 MX</td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td colspan="2">FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="2">MUCK, PEAT</td> <td colspan="2">HIGHLY ORGANIC SOILS</td> </tr> <tr> <th>GEN. RATING AS A SUBGRADE</th> <td colspan="4">EXCELLENT TO GOOD</td> <td colspan="4">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td colspan="2">UNSUITABLE</td> </tr> <tr> <td colspan="13">P.I. OF A-7-5 ≤ L.L. - 30 ; P.I. OF A-7-6 > L.L. - 30</td> </tr> </table>		SOIL LEGEND AND AASHTO CLASSIFICATION										GENERAL CLASS.	GRANULAR MATERIALS (< 75% PASSING #200)					SILT-CLAY MATERIALS (> 75% PASSING #200)					ORGANIC MATERIALS		A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7			GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-4-4	A-4-5	A-6-4	A-6-5	A-7-4	A-7-5	SYMBOL													% PASSING	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	LIQUID LIMIT PLASTIC INDEX	6 MX	N.P.	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	20 MX	24 MX	28 MX	32 MX	36 MX	USUAL TYPES OF MAJOR MATERIALS	FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		MUCK, PEAT		HIGHLY ORGANIC SOILS		GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR	POOR	UNSUITABLE		P.I. OF A-7-5 ≤ L.L. - 30 ; P.I. OF A-7-6 > L.L. - 30													<table border="1"> <tr> <th colspan="3">CONSISTENCY OR DENSENESS</th> </tr> <tr> <th>PRIMARY SOIL TYPE</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (kN/m²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>< 4 4 TO 10 10 TO 30 30 TO 50 > 50</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>< 25 25 TO 50 50 TO 100 100 TO 200 200 TO 400 > 400</td> </tr> </table>		CONSISTENCY OR DENSENESS			PRIMARY SOIL TYPE	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (kN/m ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 25 25 TO 50 50 TO 100 100 TO 200 200 TO 400 > 400	<table border="1"> <tr> <th colspan="3">TEXTURE OR GRAIN SIZE</th> </tr> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.0</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F. SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td>GRAIN SIZE</td> <td>MM 305 IN. 12"</td> <td>75 3"</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> </table>		TEXTURE OR GRAIN SIZE			U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.0	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE	MM 305 IN. 12"	75 3"	2.0	0.25	0.05	0.005	<table border="1"> <tr> <th colspan="3">SOIL MOISTURE - CORRELATION OF TERMS</th> </tr> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td rowspan="2">LL PLASTIC RANGE (PI) PL</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td rowspan="2">OM SL</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>		SOIL MOISTURE - CORRELATION OF TERMS			SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL PLASTIC RANGE (PI) PL	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM SL	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<table border="1"> <tr> <th colspan="3">PLASTICITY</th> </tr> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>		PLASTICITY			NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<table border="1"> <tr> <th colspan="3">COLOR</th> </tr> <tr> <td colspan="3">DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</td> </tr> </table>		COLOR			DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		
SOIL LEGEND AND AASHTO CLASSIFICATION																																																																																																																																																																																																																																									
GENERAL CLASS.	GRANULAR MATERIALS (< 75% PASSING #200)					SILT-CLAY MATERIALS (> 75% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																																																																														
	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7																																																																																																																																																																																																																															
GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-4-4	A-4-5	A-6-4	A-6-5	A-7-4	A-7-5																																																																																																																																																																																																																													
SYMBOL																																																																																																																																																																																																																																									
% PASSING	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200																																																																																																																																																																																																																													
LIQUID LIMIT PLASTIC INDEX	6 MX	N.P.	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN	40 MX/41 MN 10 MX/10 MN	40 MX/41 MN 11 MN/11 MN																																																																																																																																																																																																																													
GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	20 MX	24 MX	28 MX	32 MX	36 MX																																																																																																																																																																																																																													
USUAL TYPES OF MAJOR MATERIALS	FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		MUCK, PEAT		HIGHLY ORGANIC SOILS																																																																																																																																																																																																																														
GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR	POOR	UNSUITABLE																																																																																																																																																																																																																														
P.I. OF A-7-5 ≤ L.L. - 30 ; P.I. OF A-7-6 > L.L. - 30																																																																																																																																																																																																																																									
CONSISTENCY OR DENSENESS																																																																																																																																																																																																																																									
PRIMARY SOIL TYPE	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (kN/m ²)																																																																																																																																																																																																																																							
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50																																																																																																																																																																																																																																							
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 25 25 TO 50 50 TO 100 100 TO 200 200 TO 400 > 400																																																																																																																																																																																																																																							
TEXTURE OR GRAIN SIZE																																																																																																																																																																																																																																									
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																																																																			
	4.76	2.0	0.42	0.25	0.075	0.053																																																																																																																																																																																																																																			
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																																																																			
GRAIN SIZE	MM 305 IN. 12"	75 3"	2.0	0.25	0.05	0.005																																																																																																																																																																																																																																			
SOIL MOISTURE - CORRELATION OF TERMS																																																																																																																																																																																																																																									
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																																																							
LL PLASTIC RANGE (PI) PL	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																																																																							
	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																							
OM SL	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																																																																							
	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																							
PLASTICITY																																																																																																																																																																																																																																									
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																																																																							
LOW PLASTICITY	0-5	VERY LOW																																																																																																																																																																																																																																							
MED. PLASTICITY	6-15	SLIGHT																																																																																																																																																																																																																																							
HIGH PLASTICITY	16-25	MEDIUM																																																																																																																																																																																																																																							
	26 OR MORE	HIGH																																																																																																																																																																																																																																							
COLOR																																																																																																																																																																																																																																									
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.																																																																																																																																																																																																																																									
<table border="1"> <tr> <th colspan="3">MISCELLANEOUS SYMBOLS</th> </tr> <tr> <td></td> <td>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</td> <td>SPT TEST BORING</td> </tr> <tr> <td></td> <td>SOIL SYMBOL</td> <td>AUGER BORING</td> </tr> <tr> <td></td> <td>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</td> <td>CORE BORING</td> </tr> <tr> <td></td> <td>INFERRED SOIL BOUNDARIES</td> <td>MONITORING WELL</td> </tr> <tr> <td></td> <td>INFERRED ROCK LINE</td> <td>PIEZOMETER INSTALLATION</td> </tr> <tr> <td></td> <td>ALLUVIAL SOIL BOUNDARY</td> <td>SLOPE INDICATOR INSTALLATION</td> </tr> <tr> <td></td> <td>DIP/DIP DIRECTION OF ROCK STRUCTURES</td> <td>SPT N-VALUE</td> </tr> <tr> <td></td> <td>SOUNDING ROD</td> <td>SPT REFUSAL</td> </tr> </table>		MISCELLANEOUS SYMBOLS				ROADWAY EMBANKMENT WITH SOIL DESCRIPTION	SPT TEST BORING		SOIL SYMBOL	AUGER BORING		ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS	CORE BORING		INFERRED SOIL BOUNDARIES	MONITORING WELL		INFERRED ROCK LINE	PIEZOMETER INSTALLATION		ALLUVIAL SOIL BOUNDARY	SLOPE INDICATOR INSTALLATION		DIP/DIP DIRECTION OF ROCK STRUCTURES	SPT N-VALUE		SOUNDING ROD	SPT REFUSAL	<table border="1"> <tr> <th colspan="3">ABBREVIATIONS</th> </tr> <tr> <td>AR - AUGER REFUSAL</td> <td>BT - BORING TERMINATED</td> <td>CL - CLAY</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>CSE - COARSE</td> <td>DMT - DILATOMETER TEST</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>e - VOID RATIO</td> <td>F - FINE</td> </tr> <tr> <td>FOSS - FOSSILIFEROUS</td> <td>FRAC. - FRACTURED</td> <td>FRAGS. - FRAGMENTS</td> </tr> <tr> <td>MED. - MEDIUM</td> <td>PMT - PRESSUREMETER TEST</td> <td>SO. - SAND, SANDY</td> </tr> <tr> <td>SL - SILT, SILTY</td> <td>SLL - SLIGHTLY</td> <td>TR - TRICONE REFUSAL</td> </tr> <tr> <td>U - UNIT WEIGHT</td> <td>W_d - DRY UNIT WEIGHT</td> <td>W - MOISTURE CONTENT</td> </tr> <tr> <td>V - VERY</td> <td>VST - VANE SHEAR TEST</td> <td></td> </tr> </table>		ABBREVIATIONS			AR - AUGER REFUSAL	BT - BORING TERMINATED	CL - CLAY	CPT - CONE PENETRATION TEST	CSE - COARSE	DMT - DILATOMETER TEST	DPT - DYNAMIC PENETRATION TEST	e - VOID RATIO	F - FINE	FOSS - FOSSILIFEROUS	FRAC. - FRACTURED	FRAGS. - FRAGMENTS	MED. - MEDIUM	PMT - PRESSUREMETER TEST	SO. - SAND, SANDY	SL - SILT, SILTY	SLL - SLIGHTLY	TR - TRICONE REFUSAL	U - UNIT WEIGHT	W _d - DRY UNIT WEIGHT	W - MOISTURE CONTENT	V - VERY	VST - VANE SHEAR TEST																																																																																																																																																																																	
MISCELLANEOUS SYMBOLS																																																																																																																																																																																																																																									
	ROADWAY EMBANKMENT WITH SOIL DESCRIPTION	SPT TEST BORING																																																																																																																																																																																																																																							
	SOIL SYMBOL	AUGER BORING																																																																																																																																																																																																																																							
	ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS	CORE BORING																																																																																																																																																																																																																																							
	INFERRED SOIL BOUNDARIES	MONITORING WELL																																																																																																																																																																																																																																							
	INFERRED ROCK LINE	PIEZOMETER INSTALLATION																																																																																																																																																																																																																																							
	ALLUVIAL SOIL BOUNDARY	SLOPE INDICATOR INSTALLATION																																																																																																																																																																																																																																							
	DIP/DIP DIRECTION OF ROCK STRUCTURES	SPT N-VALUE																																																																																																																																																																																																																																							
	SOUNDING ROD	SPT REFUSAL																																																																																																																																																																																																																																							
ABBREVIATIONS																																																																																																																																																																																																																																									
AR - AUGER REFUSAL	BT - BORING TERMINATED	CL - CLAY																																																																																																																																																																																																																																							
CPT - CONE PENETRATION TEST	CSE - COARSE	DMT - DILATOMETER TEST																																																																																																																																																																																																																																							
DPT - DYNAMIC PENETRATION TEST	e - VOID RATIO	F - FINE																																																																																																																																																																																																																																							
FOSS - FOSSILIFEROUS	FRAC. - FRACTURED	FRAGS. - FRAGMENTS																																																																																																																																																																																																																																							
MED. - MEDIUM	PMT - PRESSUREMETER TEST	SO. - SAND, SANDY																																																																																																																																																																																																																																							
SL - SILT, SILTY	SLL - SLIGHTLY	TR - TRICONE REFUSAL																																																																																																																																																																																																																																							
U - UNIT WEIGHT	W _d - DRY UNIT WEIGHT	W - MOISTURE CONTENT																																																																																																																																																																																																																																							
V - VERY	VST - VANE SHEAR TEST																																																																																																																																																																																																																																								
<table border="1"> <tr> <th colspan="3">EQUIPMENT USED ON SUBJECT PROJECT</th> </tr> <tr> <td><input type="checkbox"/> MOBILE B-</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input type="checkbox"/> 152 mm CONTINUOUS FLIGHT AUGER</td> <td><input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-45</td> <td><input checked="" type="checkbox"/> 203 mm HOLLOW AUGERS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input checked="" type="checkbox"/> CASING</td> <td><input checked="" type="checkbox"/> W/ ADVANCER</td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> TRICONE</td> <td><input type="checkbox"/> 3 mm STEEL TEETH</td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> TRICONE</td> <td><input type="checkbox"/> 6 mm TUNG-CARB.</td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> CORE BIT</td> <td></td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> OTHER</td> <td></td> </tr> </table>		EQUIPMENT USED ON SUBJECT PROJECT			<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC	<input type="checkbox"/> BK-51	<input type="checkbox"/> 152 mm CONTINUOUS FLIGHT AUGER	<input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-45	<input checked="" type="checkbox"/> 203 mm HOLLOW AUGERS		<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS		<input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> CASING	<input checked="" type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE	<input type="checkbox"/> 3 mm STEEL TEETH	<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE	<input type="checkbox"/> 6 mm TUNG-CARB.	<input type="checkbox"/> OTHER	<input type="checkbox"/> CORE BIT		<input type="checkbox"/> OTHER	<input type="checkbox"/> OTHER		<table border="1"> <tr> <th colspan="2">FRACTURE SPACING</th> <th colspan="2">BEDDING</th> </tr> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 3 m</td> <td>VERY THICKLY BEDDED</td> <td>> 1 m</td> </tr> <tr> <td>WIDE</td> <td>1 TO 3 m</td> <td>THICKLY BEDDED</td> <td>0.5 - 1 m</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>30 TO 100 cm</td> <td>THINLY BEDDED</td> <td>0.05 - 0.5 m</td> </tr> <tr> <td>CLOSE</td> <td>5 TO 30 cm</td> <td>VERY THINLY BEDDED</td> <td>10 - 50 mm</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 5 cm</td> <td>THICKLY LAMINATED</td> <td>2.5 - 10 mm</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 2.5 mm</td> </tr> </table>		FRACTURE SPACING		BEDDING		TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 3 m	VERY THICKLY BEDDED	> 1 m	WIDE	1 TO 3 m	THICKLY BEDDED	0.5 - 1 m	MODERATELY CLOSE	30 TO 100 cm	THINLY BEDDED	0.05 - 0.5 m	CLOSE	5 TO 30 cm	VERY THINLY BEDDED	10 - 50 mm	VERY CLOSE	LESS THAN 5 cm	THICKLY LAMINATED	2.5 - 10 mm			THINLY LAMINATED	< 2.5 mm																																																																																																																																																																					
EQUIPMENT USED ON SUBJECT PROJECT																																																																																																																																																																																																																																									
<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC																																																																																																																																																																																																																																							
<input type="checkbox"/> BK-51	<input type="checkbox"/> 152 mm CONTINUOUS FLIGHT AUGER	<input type="checkbox"/> MANUAL																																																																																																																																																																																																																																							
<input type="checkbox"/> CME-45	<input checked="" type="checkbox"/> 203 mm HOLLOW AUGERS																																																																																																																																																																																																																																								
<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS																																																																																																																																																																																																																																								
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS																																																																																																																																																																																																																																								
<input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> CASING	<input checked="" type="checkbox"/> W/ ADVANCER																																																																																																																																																																																																																																							
<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE	<input type="checkbox"/> 3 mm STEEL TEETH																																																																																																																																																																																																																																							
<input type="checkbox"/> OTHER	<input type="checkbox"/> TRICONE	<input type="checkbox"/> 6 mm TUNG-CARB.																																																																																																																																																																																																																																							
<input type="checkbox"/> OTHER	<input type="checkbox"/> CORE BIT																																																																																																																																																																																																																																								
<input type="checkbox"/> OTHER	<input type="checkbox"/> OTHER																																																																																																																																																																																																																																								
FRACTURE SPACING		BEDDING																																																																																																																																																																																																																																							
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																																																																																						
VERY WIDE	MORE THAN 3 m	VERY THICKLY BEDDED	> 1 m																																																																																																																																																																																																																																						
WIDE	1 TO 3 m	THICKLY BEDDED	0.5 - 1 m																																																																																																																																																																																																																																						
MODERATELY CLOSE	30 TO 100 cm	THINLY BEDDED	0.05 - 0.5 m																																																																																																																																																																																																																																						
CLOSE	5 TO 30 cm	VERY THINLY BEDDED	10 - 50 mm																																																																																																																																																																																																																																						
VERY CLOSE	LESS THAN 5 cm	THICKLY LAMINATED	2.5 - 10 mm																																																																																																																																																																																																																																						
		THINLY LAMINATED	< 2.5 mm																																																																																																																																																																																																																																						
<table border="1"> <tr> <th colspan="3">INDURATION</th> </tr> <tr> <td>FRIABLE</td> <td colspan="2">RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED</td> <td colspan="2">GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED</td> <td colspan="2">GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td> <td colspan="2">SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>		INDURATION			FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.		MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.		INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.		EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.		<p>NOTES: BENCH MARK: SPIKE IN BASE OF POWER POLE # 140 @ BASELINE STATION 13+87.38, 4.877m LT ELEVATION: 132.627 meters</p>																																																																																																																																																																																																																								
INDURATION																																																																																																																																																																																																																																									
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																																																																																																																																								
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																																																																																								
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																																																																																								
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																																																																								