

END BENT 1

FOUNDATION LAYOUT

DIMENSIONS LOCATING END BENT PILES AND BENT DRILLED PIERS ARE SHOWN TO CENTERLINE OF PILES AND DRILLED PIERS.

FOUNDATION NOTES

THE DRILLED PIERS AT BENT 1 AND 2 HAVE BEEN DESIGNED FOR BOTH SKIN FRICTION AND TIP BEARING. THE REQUIRED TIP BEARING CAPACITY IS 30 TSF.

THE REQUIRED TIP BEARING CAPACITY AT BENTS 1 AND 2 SHALL BE VERIFIED.

DRILLED PIERS FOR BENTS 1 AND 2 HAVE BEEN DESIGNED FOR AN APPLIED LOAD OF 206 TONS EACH AT THE TOP OF THE COLUMN.

PERMANENT STEEL CASING IS REQUIRED FOR DRILLED PIERS AT BENTS 1 AND 2, AND THE CASING SHALL NOT EXTEND BELOW ELEVATION 266.5 FT. WITHOUT THE ENGINEER'S PERMISSION.

FOR PERMANENT STEEL CASING, SEE SPECIAL PROVISION FOR DRILLED PIERS.

DRILLED PIERS AT BENTS 1 AND 2 SHALL EXTEND TO AN ELEVATION NO HIGHER THAN 259 FT. AND SATISFY THE REQUIRED TIP BEARING CAPACITY.

THE SCOUR CRITICAL ELEVATION FOR BENTS 1 AND 2 IS ELEVATION 265 FT. THE SCOUR CRITICAL ELEVATIONS ARE FOR USE BY MAINTENANCE FORCES TO MONITOR POSSIBLE SCOUR PROBLEMS DURING THE LIFE OF THE STRUCTURE.

FOR DRILLED PIERS, SEE SPECIAL PROVISIONS.

SPT TESTING IS NOT REQUIRED TO DETERMINE THE TIP BEARING CAPACITY OF THE DRILLED PIERS AT BENT 1 AND 2.

SLURRY CONSTRUCTION SHALL NOT BE USED FOR THIS PROJECT.

SID INSPECTIONS ARE NOT REQUIRED TO DETERMINE THE BOTTOM CLEANLINESS OF THE DRILLED PIERS AT BENT 1 AND BENT 2.

CSL TUBES ARE REQUIRED AND CSL TESTING MAY BE REQUIRED FOR THE DRILLED PIERS AT BENT 1 AND BENT 2. SEE SPECIAL PROVISION FOR CROSSHOLE SONIC LOGGING.

PILES FOR END BENT 1 AND END BENT 2 SHALL BE DRIVEN TO A MINIMUM BEARING CAPACITY OF 50 TONS EACH.

WHEN DRIVING PILES, THE MAXIMUM BLOW COUNT SHALL NOT BE EXCEEDED.

END BENT 2



PROJECT NO. B-3451

DURHAM COUNTY

STATION: 14+99.30 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION

RALEIGH

GENERAL DRAWING FOR BRIDGE ON SR 1306 OVER MUD CREEK BETWEEN SR 1308 & NC 751

REVISIONS

BY: DATE: NO. BY: DATE:

3 TOTAL SHEETS
27

DRAWN BY: T.A. HARRIS DATE: 6/5/03
CHECKED BY: K. MCCAULEY DATE: 6/11/03