STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH STANDARD DRUMS DRAWING **FOR**

DIAMETER NOT TO EXCEED BASE DIAMETER ORANGE, OR FLUORESCENT RED-ORANGE ULTRA VIOLET STABILIZED IMPACT RESISTANT PLASTIC 6" TO 8" STRIPES TYPICAL CIRCUMFERENTIAL ALTERNATE ORANGE & WHITE RETROREFLECTIVE STRIPES, 36" MINIMUM 2 ORANGE & 2 WHITE MINIMUM 2" MAX. TYPICAL BETWEEN STRIPES 21" MIN. TO 24" MAX. DIAMETER

TOP 18" MIN. TO 24" MAX.

GENERAL NOTES

- -BALLASTING SHALL BE ACHIEVED BY THE SAND BAG OR TIRE-SIDEWALL BALLASTING METHODS. DO NOT PLACE BALLAST ON TOP OF THE DRUM, NOR AS TO PRESENT A HAZARD WHEN STRUCK.
- -IF NECESSARY PLACE THE NAME OF THE AGENCY, CONTRACTOR, OR SUPPLIER ON NON-RETROREFLECTIVE DRUM SURFACES. SHOW THE LETTERS AND NUMBERS USING A NON-RETROREFLECTIVE COLOR AND NOT OVER 2" IN HEIGHT.

SHEET 1 OF 1

1130.01

NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

DEPT

1-02

FOR

STANDARD DRAWING

ENGLISH

DRUMS

SHEET 1 OF 1

1130.01