STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

INDEX OF SHEETS

PROJECT U-4008

INDEX OF SHEETS

1	TITLE SHEET
1A	INDEX OF SHEETS, GENERAL NOTES, AND LIST OF STANDARDS
1B	CONVENTIONAL SYMBOLS
1C	SURVEY CONTROL SHEET
2 thru 2-B	PAVEMENT SCHEDULE, TYPICAL SECTIONS, DETAIL SHOWING METHOD OF WEDGING, AND WEDGING DETAIL FOR RESURFACING
2-C thru 2-F	DETAIL DRAWINGS FOR GUARDRAIL INSTALLATION
2-G thru 2-J	DETAIL DRAWINGS FOR 41" PRECAST REINFORCED CONCRETE BARRIER
2-K	DETAIL DRAWING FOR GUARDRAIL ANCHOR UNIT TYPE B-77
2-L thru 2-M	DETAIL DRAWINGS FOR WHEELCHAIR RAMP
2-N thru 2-O	DETAIL DRAWINGS FOR PILE / PANEL WALL
2-P	DETAIL DRAWING FOR DROP INLET INSTALLATION IN EXPRESSWAY GUTTER
2-Q	DETAIL DRAWING FOR CONVERTING DROP INLET TO OPEN THROAT CATCH BASIN
2-R	DETAIL DRAWING FOR TWO GRATE INLET
2-S	DETAIL DRAWING FOR MEDIAN CONSTRUCTION SHOWING 6" CONCRETE ISLAND COVER
2-T	DETAIL DRAWING FOR BIKE PATH RESTRICTION CONCRETE BOLLARD
2-U	DETAIL DRAWING FOR STAMPED ASPHALT
3	SUMMARY OF QUANTITIES
3-A thru 3-B	SUMMARY OF PIPES 48" AND UNDER AND SUMMARY OF PIPES 54" AND OVER
3-C	SUMMARY OF EARTHWORK, ASPHALT PAVEMENT REMOVAL SUMMARY, AND GUARDRAIL SUMMARY
3-Z	PARCEL INDEX SHEET
4 thru 5	PLAN SHEETS
6 thru 9	PROFILE SHEETS
TCP-1 thru TCP-11	TRAFFIC CONTROL PLANS
PM-1 thru PM-4	PAVEMENT MARKING PLANS
EC-1 thru EC-6	EROSION CONTROL PLANS
SIGN-1 thru SIGN-9	SIGNING PLANS
SIG-1 thru SIG-29	SIGNAL PLANS
UC-1 thru UC-4	UTILITY CONSTRUCTION PLANS
UO-1 thru UO-3	UTILITIES BY OTHERS PLANS
X-0	CROSS SECTION SUMMARY
	CDOCC OF CTIONS

CROSS SECTIONS

X-1 thru X-22

GENERAL NOTES:

2002 SPECIFICATIONS EFFECTIVE: 01-15-02 REVISED: 05-14-03

GRADE LINE:

GRADING AND SURFACING OR RESURFACING AND WIDENING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. WHERE NO GRADE LINES ARE SHOWN, THE PROFILES SHOWN DENOTE THE TOP ELEVATION OF THE EXISTING PAVEMENT ALONG THE CENTER LINE OF SURVEY ON WHICH THE PROPOSED RESURFACING WILL BE PLACED. GRADE LINES MAY BE ADJUSTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH **STD. NO. 225.04** USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

ASHPALT AND EARTH SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01.

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

BERM DITCHES:

BERM DITCHES SHALL BE CONSTRUCTED IN ACCORDANCE WITH **STD. NO. 240:01** AT LOCATIONS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER.

UNDERDRAINS:

UNDERDRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH **STD. NO. 815.03** AT LOCATIONS DIRECTED BY THE ENGINEER.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC WILL BE PAID FOR AS "EXTRA WORK" IN ACCORDANCE WITH SECTION 104-7.

SUBSURFACE PLANS:

NO SUBSURFACE PLANS ARE AVAILABLE ON THIS PROJECT. THE CONTRACTOR SHOULD MAKE HIS OWN INVESTIGATION AS TO THE SUBSURFACE CONDITIONS.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE:

PSNC ENERGY, DUKE POWER, BELLSOUTH, TIME WARNER CABLE, PROGRESS TELECOM

ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS, EXCEPT AS SHOWN ON THE PLANS.

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY OTHERS.

WHEELCHAIR RAMPS:

WHEELCHAIR RAMPS ARE SHOWN ON THE PLANS AT APPROXIMATE LOCATIONS. THE CONSTRUCTION OF ALL WHEELCHAIR RAMPS SHALL BE IN ACCORDANCE WITH DETAILS IN PLANS.

EFF. 01-15-02

ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch - N. C. Department of Transportation - Raleigh, N. C., Dated January 15, 2002 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO. TITLE

DIVISION 2 - EARTHWORK

200.03 Method of Clearing – Method III

225.02 Guide for Grading Subgrade – Secondary and Local

225.04 Method of Obtaining Superelevation- Two Lane Pavement

240.01 Guide for Berm Ditch Construction

DIVISION 3 – PIPE CULVERTS

300.01 Method of Pipe Installation – Method 'A'

560.01 Method of Shoulder Construction- High Side of Superelevated Curve – Method I

DIVISION 5 – SUBGRADE, BASES, AND SHOULDERS

DIVISION 8 – INCIDENTALS

815.03 Pipe Underdrain and Blind Drain

838.01 Concrete Endwall for Single and Double Pipe Culverts – 15" thru 48" Pipe 90° Skew

838.22 Reinforced Concrete Endwall – for Double and Triple 54" Pipes 90° Skew

838.45 Notes for Reinforced Concrete Endwall – Std. Dwg.s 838.21 thru 838.40

838.52 Reinforced Brick Endwall – for Double and Triple 54" Pipes 90° Skew

838.75 Notes for Reinforced Brick Endwall – Std. Dwg.s 838.51 thru 838.70

838.80 Precast Endwalls - 12" thru 72" Pipe 90° Skew

840.00 Concrete Base Pad for Drainage Structures

2

840.01 Brick Catch Basin - 12" thru 54" Pipe

840.02 Concrete Catch Basin - 12" thru 54" Pipe

240.04 Community Catal Davis mid Circle and Malkinda Direct 127 dams 407 Di

840.04 Concrete Catch Basin with Single and Multiple Pipes - 12" thru 48" Pipe

840.05 Brick Catch Basin with Single and Multiple Pipes - 12" thru 48" Pipe

840.03 Frame, Grates and Hood - for Use on Standard Catch Basin

840.17 Concrete Median Drop Inlet Type `A' - 12" thru 72" Pipe

840.18 Concrete Median Drop Inlet Type `B' - 12" thru 36" Pipe

840.18 Concrete Median Drop Inlet Type B - 12 thru 30 P

840.24 Frames and Narrow Slot Sag Grates

840.26 Brick Median Drop Inlet Type `A' - 12" thru 72" Pipe

840.27 Brick Median Drop Inlet Type `B' - 12" thru 36" Pipe

840.29 Frames and Narrow Slot Flat Grates

840.31 Concrete Junction Box - 12" thru 66" Pipe

840.32 Brick Junction Box - 12" thru 66" Pipe

840.35 Traffic Bearing Drop Inlet - for Cast Iron Double Frame and Grates

840.45 Precast Drainage Structure

840.46 Traffic Bearing Precast Drainage Structure

840.51 Brick Manhole - 12" thru 36" Pipe

840.53 Precast Manhole with Masonry Base - 12" thru 42" Pipe

840.54 Manhole Frame and Cover

840.66 Drainage Structure Steps

840.71 Concrete and Brick Pipe Plug

840.72 Pipe Collar

846.01 Concrete Curb, Gutter and Curb & Gutter

850.01 Concrete Paved Ditches

850.10 Guide for Berm Drainage Outlet – 15" and 18" Pipe

852.01 Concrete Islands

852.05 Median Curb for Catch Basin - for Use with 1'-6" Curb and Gutter

862.01 Guardrail Placement

876.02 Guide for Rip Rap at Pipe Outlets

876.04 Drainage Ditches with Class 'B' Rip Rap