STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH STANDARD DRAWING FOR
DRUMS

SHEET 1 OF 1

1130D01

TOP
18" MIN. TO 24" MAX.
DIAMETER

NOT TO EXCEED
BASE DIAMETER

ORANGE, OR FLUORESCENT RED-ORANGE
ULTRA VIOLET STABILIZED
IMPACT RESISTANT PLASTIC

CIRCUMFERENTIAL
ALTERNATE WHITE & ORANGE
RETROREFLECTIVE STRIPES,
3 ORANGE & 2 WHITE MINIMUM
COVERING ENTIRE OUTSIDE

6" TO 8" STRIPES
TYPICAL

36"
MINIMUM

2" MAX. TYPICAL
BETWEEN STRIPES

21" MIN. TO 24" MAX. DIAMETER

GENERAL NOTES

-BALLASTING SHALL BE ACHIEVED BY THE SAND BAG, TIRE-SIDEWALL BALLAST, OR PREFORMED WEIGHTED BASE BALLASTING
METHODS. DO NOT PLACE BALLAST ON TOP OF THE DRUM.

-IF NECESSARY PLACE THE NAME OF THE AGENCY, CONTRACTOR, OR SUPPLIER ON NON-RETROREFLECTIVE DRUM SURFACES.
SHOW THE LETTERS AND NUMBERS USING A NON-RETROREFLECTIVE COLOR AND NOT OVER 2" IN HEIGHT.

02-DEC-2004 16:04
S:\TCUs2Group_MM\Resurfacing\Div08\8cr10771\3etcRichmond\8cr10771\Drums_english\1304.dgn
dseymore
AT TETC206427

APPROVED:	DATE:		REPLACEMENT DETAIL FOR
			RSD 1130.01

SEAL	SCALE:	NONE		REVISIONS
	DATE:	4/02		11/02
	DWG. BY:	MMM		
	DESIGN BY:	MMM		
	REVIEWED BY:	MMM	CADD FILE	