PROJECT REFERENCE NO.	SHEET NO.
R-2552AA	7-S

METRIC

STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

METRIC DETAIL DRAWING FOR
REINFORCED BRIDGE APPROACH FILLS
INSETS AND CHARTS

SHEET 4 OF 4
422D10

Height of Backwall	Number of Fabric Layers
1400-1750	3
1760-2200	4
2210-2650	5
2660-3100	6
3110-3550	7

Note: Cored Slab Structures Require 2 Fabric Layers.

Length of Bridge End Bent Inside Wingwalls
If Bridge Skew is Less Than or Equal to 90°: (Roadway Width + 2140mm) / Sin (Bridge Skew Angle) = Dis. Between Wingwalls
If Bridge Skew is Greater Than 90°: (Roadway Width + 2140mm) / Cos (Bridge Skew Angle - 90°) = Dis. Between Wingwalls

Note:
This drawing is dimensioned in millimeters unless otherwise depicted within the drawing.

STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

METRIC DETAIL DRAWING FOR
REINFORCED BRIDGE APPROACH FILLS
CORED SLAB BRIDGES

SHEET 3 OF 4
422D10

Note:
This drawing is dimensioned in millimeters unless otherwise depicted within the drawing.

PROJECT SERVICES UNIT
STANDARDS AND SPECIAL DESIGN
Office 919-250-4128 FAX 919-250-4119

SEE PLATE FOR TITLE

ORIGINAL BY: 2002 STANDARDS DATE: 01-15-02
MODIFIED BY: E.E. WARD DATE: 11-04-04
CHECKED BY: DATE: 11/2/04
FILE SPEC.: stds/02stdstodetails/metric/422d10.dgn

08-NOV-2004 13:34
W:\Special Details\eriward\stds\02' Stds to Special Details\metric\422l0\0422d10m.dgn
eriward AT DS212260