

**SP 03353**

SIGN NUMBER: SP-03353 TYPE: A QUANTITY: 1	BACKG COLOR: Fluorescent Orange COPY COLOR: Black	DESIGN BY: CLD PROJECT ID: ALL PROJECTS	CHECKED BY: CHECKED DIV: DIV	STD #: W20-1 DATE: Sep 19, 2003
---	--	--	---------------------------------	------------------------------------

  

SYMBOL	X	Y	WID	HT

  

SIGN WIDTH: 1219mm  
HEIGHT: 1219mm  
TOTAL AREA: 1.5 Sq.m

BORDER TYPE: FLUSH  
RECESS: 13mm  
WIDTH: 19mm  
RADII: 35mm

NO. Z BARS: N/A  
LENGTH: N/A

MAT'L:

USE NOTES: 2, 4  
1. Legend and border shall be direct applied Type VII reflective sheeting.  
2. Legend and border shall be direct applied non-reflective sheeting.  
3. Shields shall be Type VII reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
4. Background shall be Type VII reflective sheeting.  
5. Background shall be Type I reflective sheeting.  
6. Center arrow(s) vertically on sign.  
7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

BORDER  
R=35mm  
TH=19mm  
IN=13mm

LETTER POSITIONS

Letter spacings are to start of next letter										Series/Size Text Length
B	E	G	I	N						C180
561	139	122	139	64	100	561				563
R	O	A	D							C180
586	130	136	145	100	586					511
W	O	R	K							C180
567	167	144	139	100	567					550

Spacing Factor is 1 unless specified otherwise

FILENAME: COPY

NORTH CAROLINA D.O.T. SIGN DETAIL

**SP 03350**

SIGN NUMBER: SP-03350 TYPE: D QUANTITY: 1	BACKG COLOR: White COPY COLOR: Black	DESIGN BY: CLD PROJECT ID: ALL PROJECTS	CHECKED BY: DIV	STD #: REGULATORY DATE: Sep 19, 2003
---	---	--	-----------------	---

  

SYMBOL	X	Y	WID	HT

  

SIGN WIDTH: 1219mm  
HEIGHT: 762mm  
TOTAL AREA: 0.9 Sq.m

BORDER TYPE: FLUSH  
RECESS: 6mm  
WIDTH: 10mm  
RADII: 38mm

NO. Z BARS: N/A  
LENGTH: N/A

MAT'L:

USE NOTES: 2, 4  
1. Legend and border shall be direct applied Type III reflective sheeting.  
2. Legend and border shall be direct applied non-reflective sheeting.  
3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.  
4. Background shall be Type III reflective sheeting.  
5. Background shall be Type I reflective sheeting.  
6. Center arrow(s) vertically on sign.  
7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

BORDER  
R=38mm  
W=10mm  
IN=6mm

LETTER POSITIONS

Letter spacings are to start of next letter										Series/Size Text Length
\$	2	5	0							C152
384	133	117	110	89	384					450
S	P	E	E	D	I	N	G			C152
202	118	117	104	104	117	54	117	85	202	816
P	E	N	A	L	T	Y				C152
248	117	104	110	123	86	86	97	248		723

Spacing Factor is 1 unless specified otherwise

FILENAME: ISHAK

NORTH CAROLINA D.O.T. SIGN DETAIL

**GENERAL NOTES FOR THE "BEGIN ROAD WORK" SIGN**

- SIGN SP-03353 "BEGIN ROAD WORK" ONLY APPLIES TO FULL CONTROL AND PARTIAL CONTROL OF ACCESS ROADWAYS
- WHEN USED, INSTALL SIGN SP-03353 "BEGIN ROAD WORK" ACCORDING TO DETAIL A ON SHEET TCP-37.

**GENERAL NOTES FOR THE "\$250 SPEEDING PENALTY" SIGN**

- SIGN SP-03350 "\$250 SPEEDING PENALTY" IS USED ONLY WHEN ORDINANCED BY THE TRAFFIC ENGINEERING AND SAFETY SYSTEMS BRANCH.
- SIGN SP-03350 "\$250 SPEEDING PENALTY" ONLY APPLIES TO FULL CONTROL AND PARTIAL CONTROL OF ACCESS ROADWAYS
- WHEN USED, MOUNT SIGN SP-03350 "\$250 SPEEDING PENALTY" BELOW SIGN R2-1 "SPEED LIMIT 55" (SEE DETAIL B ON SHEET TCP-39) AND SIGN W21-4 "ROAD WORK AHEAD" (SEE DETAIL C ON SHEET TCP-37).

STATE OF NORTH CAROLINA  
 DEPT. OF TRANSPORTATION  
 DIVISION OF HIGHWAYS  
 RALEIGH, N.C.

DETAIL DRAWING FOR  
 WORK ZONE SIGNS  
 \$250 PENALTY SIGN

APPROVED: <i>Michael T. Reppin</i> DATE: 1-31-05	DETAIL DRAWING FOR ADVANCED WORK ZONE WARNING SIGN DESIGNS	
	SCALE: NONE	
	DATE: 0803	
	DWG. BY:	
	DESIGN BY:	
REVIEWED BY:	REVISIONS	
	0404	