


guilford3_typicals_revised.dgn 12/06/2005 07:29:39 AM_

 STATE
 PROJECT NO.
 SHEET NO.
 TOTAL SHEETS

 N.C.
 7CR.10411.11, ETC
 8
 14

7CR.10411.11, 7CR20411.11, 7CR.304106.11, 7CR.304126.11, 7CR.304129.11, 7CR.304134.11


MILLLING DETAIL 1



MILL EXISTING ASPHALT PAVEMENT 0-1.5" AT LOCATIONS AS DIRECTED BY THE ENGINNER

NOTE:
TO BE USED IN CONJUCTION WITH
TS. NO. 3 & 4 ON MAP 5

MILLLING DETAIL 2



MILL EXISTING ASPHALT PAVEMENT 3" IN DEPTH, AT LOCATIONS AS DIRECTED BY THE ENGINEER.

NOTE:
TO BE USED IN CONJUCTION WITH
TS. NO. 1 ON MAP 5

PAVEMENT SCHEDULE

17/4 EMIERT GOTTEBOLE					
C1	PROP. APPROX. 1½" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.	Ε	PROP. APPROX. 8 " ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 912 LBS. PER SQ. YD.		
C2	PROP. APPROX. 1 " ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A, AT AN AVERATE RATE OF 110 LBS. PER SQ. YD.	F	ASPHALT SURFACE TREATMENT, NO. 78M STONE		
СЗ	PROP. APPROX. 114" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERATE RATE OF 140 LBS. PER SQ. YD.	R	EXISTING CONCRETE ISLAND.		
D	PROP. APPROX. 3" ASPHALT INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERATE RATE OF 342 LBS. PER SQ. YD.	U	EXISTING PAVEMENT.	Т	EARTH MATERIAL.