







## PAVEMENT SCHEDULE

Cl	PROP. APPROX. 1.5 "ASPHALT CONC. SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER S0. YD.
(E1)	PROP. APPROX. 5' ASPHALT CONC. BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.
(T1)	SHOULDER RECONSTRUCTION
(T2)	SHOULDER CONSTRUCTION
U	EXISTING PAVEMENT

NOTES: ON MAP \*8 USE TYPICAL \*10 FROM THE END OF THE C&G TO SILVER ORE LN.APPROX.O.16 MILES.

ON MAP\*3 SKIP THE TURN LANES AT STEELE CREEK CORP.CENTER (VIRKLER DR.) APPROX. O.25 MILES.

MECKLENBURG COUNTY RESURFACING

1	
SCALE	-NA-
DATE	
DWG. BY	TWB
DESIGN BY	
+00000000	

A Carry Carry 12	
	ŀ
**************************************	ſ

REVISIONS

	1		Q.		1 1 1
	2'-4' SHLDR.	10'	. 10		2'-4' 4' SHLDR.
	SALUK.			2'	SALUN.
	$(\tau_l)$		(CI)		(T2)
٠				9/20 59/20 0 225/2020	011.
2:1				4	2:1
			U	(EI)	
		TVDICAL	SECTION NO.	$\sim$	•
		IIIICHL	SECTION NO.	10	