WBS Elements: 13CR.10121.3, 13CR.20121.3, 13CR.301219.4 See to the Left

PROJ. REFERENCE NO. SHEET NO. TCP-3

HIGHWAYS

0F

DIVISION

GNS

S

WARNIN

NO

7-98 10/01

10-98 03/04 01/01 11/04

UNDIVIDED

OML

FOR


DRAWING

ETAIL

S Z

RALEIGH






	RECOMMENDED Minimum Sign Spacing
POSTED SPEED LIMIT (M.P.H.)	⊗ -
≤ 50	500′
≥ 55	1000'


NORTH CAROLINA TRANSPORTATION OF. PF STATE DEPT

ROADWAYS INTERSECTING ALONG 2 WAY UNDIVIDED WORK ZONE (Y-LINES)




GENERAL NOTES

- USE FLUORESCENT ORANGE SHEETING (TYPE VII OR HIGHER) ON ALL ADVANCED WORK ZONE SIGNS.
- DO NOT INSTALL ADVANCE WARNING SIGNS MORE THAN 3 DAYS PRIOR TO BEGINNING OF WORK.
- ALL SIGN SPACING DIMENSIONS ARE APPROXIMATE, FIELD ADJUST AS NECESSARY OR AS DIRECTED.
- USE PORTABLE WORK ZONE SIGNS ONLY WITH PORTABLE WORK ZONE SIGN STANDS SPECIFICALLY DESIGNED FOR ONE ANOTHER. PORTABLE WORK ZONE SIGNS MAY BE ROLL UP OR APPROVED COMPOSITE.
- PROVIDE PORTABLE WORK ZONE SIGN STANDS, PORTABLE SIGNS AND SIGN SHEETING WHICH ARE LISTED ON THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION'S APPROVED PRODUCT LIST OR ACCEPTED AS TRAFFIC QUALIFIED BY THE TRAFFIC CONTROL UNIT.
- ** TWO-WAY UNDIVIDED ADVANCE WARNING SIGN CONFIGURATION MAY BE USED ON URBAN MULTI-LANE FACILITIES WHERE CONDITIONS LIMIT THE USE OF DUAL MOUNTED SIGNS AS DETERMINED BY THE ENGINEER.



SHEET 1 OF 1



2I-DEC-2005 12:44 \\DOT\DFSR00T0I\