


TIP PROJECT: B-2146


CONTRACT: C201785

STRUCTURE



VICINITY MAP

OFF-SITE DETOUR —●—●—●—●—●—



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS


IREDELL COUNTY

LOCATION: BRIDGE NO. 86 AND APPROACHES
ON SR 1333 (EUFOLA ROAD)
OVER BUFFALO SHOALS CREEK

TYPE OF WORK: GRADING, PAVING, DRAINAGE, AND STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-2146		
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
32620.1.1	BRZ-1333(5)	P.E.	
32620.3.1	BRZ-1333(5)	UTIL. & RW	
32620.2.3	BRZ-1333(5)	CONST.	

** DESIGN EXCEPTION FOR HORIZONTAL ALIGNMENT AND SAG VERTICAL CURVE REQUIRED.




DESIGN DATA	
ADT 2008 =	730
ADT 2028 =	1,048
DHV =	12 %
D =	60 %
T =	3 % *
** V =	60 MPH
* TTST 1 %	DUAL 2 %

PROJECT LENGTH	
LENGTH ROADWAY TIP PROJECT B-2146	= 0.142 mi
LENGTH STRUCTURE TIP PROJECT B-2146	= 0.024 mi
TOTAL LENGTH OF TIP PROJECT B-2146	= 0.166 mi


Prepared In the Office of: DIVISION OF HIGHWAYS	
2006 STANDARD SPECIFICATIONS	OMAR R. AZIZI, P.E. PROJECT ENGINEER
LETTING DATE: JUNE 17, 2008	EMILY E. MURRAY, P.E. PROJECT DESIGN ENGINEER

STRUCTURE DESIGN UNIT
1000 BIRCH RIDGE DR. RALEIGH, N.C. 27610


DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA	
P.E.	
STATE DESIGN ENGINEER	
DEPARTMENT OF TRANSPORTATION FEDERAL HIGHWAY ADMINISTRATION	
APPROVED DIVISION ADMINISTRATOR	DATE



SECTION ALONG C -L-



SECTION THRU TEMPORARY ACCESS



PLAN
(PILES NOT SHOWN FOR CLARITY)



PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 1 OF 3 REPLACES BRIDGE NO. 86

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


GENERAL DRAWING

BRIDGE OVER
 BUFFALO SHOALS CREEK
 ON SR 1333 BETWEEN US 70
 AND SR 1369





DRAWN BY : PEGGY ADKINS DATE : 12-05
 CHECKED BY : T. AVERETTE DATE : 1-06

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-1
1			3			TOTAL SHEETS 24
2			4			



END BENT #1



END BENT #2


PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING

BRIDGE OVER
 BUFFALO SHOALS CREEK
 ON SR 1333 BETWEEN US 70
 AND SR 1369




FOUNDATION LAYOUT

DIMENSIONS LOCATING PILES ARE SHOWN TO PILE CENTERLINE.
 STEEL BRACE PILES ARE BATTERED 3:12.

DRAWN BY : PEGGY ADKINS DATE : 12-05
 CHECKED BY : T. AVERETTE DATE : 1-06

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-2
1			3			TOTAL SHEETS
2			4			24

B.M. #2: R.R. SPIKE IN 24" PINE 63' RT. OF -BL- STA. 10+75
53.13' RT. OF -L- STA. 17+64.76, ELEV. 783.82', NAVD 88.



LOCATION SKETCH

HYDRAULIC DATA

DESIGN DISCHARGE = 3400 C.F.S.
 FREQUENCY OF DESIGN FLOOD = 25 YR.
 DESIGN HIGH WATER ELEVATION = 774.9'
 DRAINAGE AREA = 22.1 SQ. MI.
 BASIC DISCHARGE (Q100) = 5010 C.F.S.
 BASIC HIGH WATER ELEVATION = 777.0'

OVERTOPPING FLOOD DATA

OVERTOPPING DISCHARGE = 7340+
 FREQUENCY OF OVERTOPPING FLOOD = 500 YR.+
 OVERTOPPING FLOOD ELEVATION = 785.35'

TOTAL BILL OF MATERIAL

	CONSTRUCTION, MAINTENANCE AND REMOVAL OF TEMPORARY ACCESS	REMOVAL OF EXISTING STRUCTURE	FOUNDATION EXCAVATION	UNCLASSIFIED STRUCTURE EXCAVATION	REINFORCED CONCRETE DECK SLAB	GROOVING BRIDGE FLOORS	CLASS A CONCRETE	BRIDGE APPROACH SLABS	REINFORCING STEEL	STRUCTURAL STEEL	HP 12 X 53 STEEL PILES	CONCRETE BARRIER RAIL	FLASH RIP RAP CLASS II (2'-0" THICK)	FILTER FABRIC FOR DRAINAGE	ELASTOMERIC BEARINGS	EVAZOTE JOINT SEALS	
	LUMP SUM	LUMP SUM	LUMP SUM	CU.YDS.	SQ.FT.	SQ.FT.	CU.YDS.	LUMP SUM	LBS.	APPROX.LBS.	NO.	LIN.FT.	LIN.FT.	TON	SQ. YD.	LUMP SUM	LUMP SUM
SUPERSTRUCTURE					4210	4233		LUMP SUM		148,785		245.83			LUMP SUM	LUMP SUM	
END BENT NO.1			LUMP SUM	176			55.4		6168				50	56			
END BENT NO.2				681			23.5		3155		9	540	70	78			
TOTAL	LUMP SUM	LUMP SUM	LUMP SUM	857	4210	4233	78.9	LUMP SUM	9323	148,785	9	540	245.83	120	134	LUMP SUM	LUMP SUM

DRAWN BY : PEGGY ADKINS DATE : 12-05
 CHECKED BY : T. AVERETTE DATE : 1-06

08-MAY-2008 10:28
 G:\Structures\Final Plans\B2146.sd.GD_01.dgn
 emurray

NOTES:

ASSUMED LIVE LOAD = HS20 OR ALTERNATE LOADING, EXCEPT THAT THE GIRDERS HAVE BEEN DESIGNED FOR HS25.

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE AASHTO STANDARD SPECIFICATIONS FOR SEISMIC DESIGN OF HIGHWAY BRIDGES FOR SEISMIC PERFORMANCE CATEGORY A.

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.

FOR EROSION CONTROL MEASURES SEE EROSION CONTROL PLANS.

ALL STRUCTURAL STEEL SHALL BE AASHTO M270 GRADE 50W AND PAINTED IN ACCORDANCE WITH SYSTEM 4 OF ARTICLE 442-7 OF THE STANDARD SPECIFICATIONS UNLESS OTHERWISE NOTED ON THE PLANS.

THE EXISTING STRUCTURE CONSISTING OF TWO SPANS AT 36'-6" WITH TIMBER DECK ON I-BEAMS AND A CLEAR ROADWAY WIDTH OF 19.2' ON ABUTMENTS OF REINFORCED CONCRETE AND A BENT OF REINFORCED CONCRETE POST AND BEAM ON SPREAD FOOTINGS AND LOCATED AT SITE OF PROPOSED STRUCTURE SHALL BE REMOVED. THE EXISTING BRIDGE IS PRESENTLY POSTED BELOW THE LEGAL LOAD LIMIT. SHOULD THE STRUCTURAL INTEGRITY OF THE BRIDGE FURTHER DETERIORATE, THIS LOAD LIMITATION MAY BE REDUCED AS FOUND NECESSARY DURING THE LIFE OF THE PROJECT.

REMOVAL OF THE EXISTING BRIDGE SHALL BE PERFORMED SO AS NOT TO ALLOW DEBRIS TO FALL INTO THE WATER. THE CONTRACTOR SHALL REMOVE THE BRIDGE AND SUBMIT PLANS FOR DEMOLITION IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS.

THE MATERIAL SHOWN IN THE CROSS-HATCHED AREA ON SHEET 1 OF 3 SHALL BE EXCAVATED FOR A DISTANCE OF 27' FT. LEFT AND 24' RIGHT OF CENTERLINE ROADWAY AS DIRECTED BY THE ENGINEER. THIS WORK WILL BE MEASURED AND PAID FOR AT THE CONTRACT UNIT PRICE PER CUBIC YARD FOR UNCLASSIFIED STRUCTURE EXCAVATION.

THE CONTRACTOR SHALL PROVIDE INDEPENDENT ASSURANCE SAMPLES OF REINFORCING STEEL AS FOLLOWS: FOR PROJECTS REQUIRING UP TO 400 TONS OF REINFORCING STEEL, ONE 30 INCH SAMPLE OF EACH SIZE BAR USED, AND FOR PROJECTS REQUIRING OVER 400 TONS OF REINFORCING STEEL, TWO 30 INCH SAMPLES OF EACH SIZE BAR USED. THE BARS FROM WHICH THE SAMPLES ARE TAKEN MUST THEN BE SPLICED WITH REPLACEMENT BARS OF THE SIZE AND LENGTH OF THE SAMPLE, PLUS A MINIMUM LAP SPLICE OF THIRTY BAR DIAMETERS.

AT THE CONTRACTOR'S OPTION, AND UPON REMOVAL OF THE CAUSEWAY, THE CLASS II RIP RAP USED IN THE CAUSEWAY MAY BE PLACED AS RIP RAP SLOPE PROTECTION. SEE SPECIAL PROVISIONS FOR CONSTRUCTION, MAINTENANCE AND REMOVAL OF TEMPORARY ACCESS AT STATION 18+13.50 -L-.

NEEDLE BEAMS WILL NOT BE ALLOWED UNLESS OTHERWISE CALLED FOR ON THE PLANS OR APPROVED BY THE ENGINEER.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

THE REQUIRED BEARING CAPACITY FOR SPREAD FOOTINGS AT END BENT NO. 1 IS 15 TSF. CHECK FIELD CONDITIONS FOR THE REQUIRED BEARING CAPACITY JUST PRIOR TO PLACING CONCRETE. THE REQUIRED BEARING CAPACITY IS EQUAL TO THE ALLOWABLE BEARING CAPACITY WITH A MINIMUM FACTOR OF SAFETY OF THREE. THE ALLOWABLE BEARING CAPACITY FOR SPREAD FOOTINGS AT END BENT NO. 1 IS 5 TSF.

SPREAD FOOTINGS AT END BENT NO. 1 SHALL BE KEYS AT LEAST 12 IN. INTO ROCK WITH MINIMUM THICKNESS SHOWN ON THE PLANS.

DRIVE PILES AT END BENT NO. 2 TO A REQUIRED BEARING CAPACITY OF 120 TONS PER PILE. THE REQUIRED BEARING CAPACITY IS EQUAL TO THE ALLOWABLE BEARING CAPACITY WITH A MINIMUM FACTOR OF SAFETY OF TWO. THE ALLOWABLE BEARING CAPACITY FOR PILES AT END BENT NO. 2 IS 60 TONS PER PILE.

THE CONTRACTOR MAY CHOOSE TO CONSTRUCT END BENT NO. 1 PRIOR TO PLACING FILL. PLACE FILL IN ACCORDANCE WITH ARTICLE 410-8 OF THE STANDARD SPECIFICATIONS.

FOR BLASTING ADJACENT TO HIGHWAY STRUCTURES, SEE ARTICLE 410-11 OF THE STANDARD SPECIFICATIONS.

THIS STRUCTURE HAS BEEN DESIGNED IN ACCORDANCE WITH HEC 18, "EVALUATING SCOUR AT BRIDGES", MAY, 2001.

INASMUCH AS THE PAINT SYSTEM ON THE EXISTING STRUCTURAL STEEL CONTAINS LEAD, THE CONTRACTOR'S ATTENTION IS DIRECTED TO ARTICLE 107-1 OF THE STANDARD SPECIFICATIONS. ANY COSTS RESULTING FROM COMPLIANCE WITH APPLICABLE STATE OR FEDERAL REGULATIONS PERTAINING TO HANDLING OF MATERIALS CONTAINING LEAD BASED PAINT SHALL BE INCLUDED IN THE BID PRICE FOR "REMOVAL OF EXISTING STRUCTURE AT STATION 18+13.50 -L-."

THE CLASS AA CONCRETE IN THE BRIDGE DECK SHALL CONTAIN FLY ASH OR GROUND GRANULATED BLAST FURNACE SLAG AT THE SUBSTITUTION RATE SPECIFIED IN ARTICLE 1024-1 AND IN ACCORDANCE WITH ARTICLES 1024-5 AND 1024-6 OF THE STANDARD SPECIFICATIONS. NO PAYMENT WILL BE MADE FOR THIS SUBSTITUTION AS IT IS CONSIDERED INCIDENTAL TO THE COST OF THE REINFORCED CONCRETE DECK SLAB.

REMOVABLE FORMS MAY BE USED IN LIEU OF METAL STAY-IN-PLACE FORMS IN ACCORDANCE WITH ARTICLE 420-3 OF THE STANDARD SPECIFICATIONS.

THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST INFORMATION AVAILABLE. SINCE THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR, THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

THIS BRIDGE HAS BEEN DESIGNED BY THE STRENGTH DESIGN METHOD AS SPECIFIED IN AASHTO STANDARD SPECIFICATIONS.

FOR SHIPPING STRUCTURAL STEEL MEMBERS, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

PROJECT NO. B-2146
 IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 3 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING

BRIDGE OVER
 BUFFALO SHOALS CREEK
 ON SR 1333 BETWEEN US 70
 AND SR 1369




5-9-08

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-3
1			3			TOTAL SHEETS
2			4			24


NOTES:

PROVIDE 1/4" HIGH BEAM BOLSTERS UPPER AT 4'-0" CTS. ATOP THE METAL STAY-IN-PLACE FORMS TO SUPPORT THE BOTTOM MAT OF 'A' BARS. WHEN USING REMOVABLE FORMS, PROVIDE CONTINUOUS HIGH CHAIRS FOR METAL DECK (C.H.C.M.) @ 4'-0" CTS. WITH A HEIGHT TO SUPPORT THE BOTTOM MAT OF 'A' BARS A CLEAR DISTANCE OF 2 1/2" ABOVE THE TOP OF THE REMOVABLE FORM.


THE CONTRACTOR MAY, WHEN NECESSARY, PROPOSE A SCHEME FOR AVOIDING INTERFERENCE BETWEEN METAL STAY-IN-PLACE FORM SUPPORTS OR FORMS AND BEAM/GIRDER STIFFENERS OR CONNECTOR PLATES. THE PROPOSAL SHALL BE INDICATED, AS APPROPRIATE, ON EITHER THE STEEL WORKING DRAWINGS OR THE METAL STAY-IN-PLACE FORM WORKING DRAWINGS.



TYPICAL SECTION
(SHOWING END BENT DIAPHRAGMS)



DETAIL "A"



TYPICAL SECTION
(SHOWING INTERMEDIATE DIAPHRAGMS)

PROJECT NO. B-2146
IREDELL COUNTY
STATION: 18+13.50 -L-

SHEET 1 OF 2


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE
TYPICAL SECTION




DRAWN BY: M.D.PISO DATE: 06/2007
CHECKED BY: B.N.BARODAWALA DATE: 10/10/07

REVISIONS						SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:	S-4	
1			3			TOTAL SHEETS	24
2			4				





PLAN OF GIRDER @ END BENT

(END BENT #1 SHOWN, END BENT #2 SIMILAR)



SECTION THRU END BENT DIAPHRAGM

(END BENT #1 SHOWN, END BENT #2 SIMILAR)



DRAIN CONNECTOR DETAIL

(3 DRAINS REQUIRED)

COUPLING IN DRAIN PIPE WILL BE PERMITTED AS APPROVED BY THE ENGINEER.

TOP OF FLOOR DRAIN TO BE SET 3/8" BELOW SURFACE OF SLAB.

4 - 1/2" SQUARE LUGS TO BE GLUED TO THE PVC PLASTIC PIPE AT EQUAL SOACES AROUND THE PIPE DRAIN APPROXIMATELY 4" FROM THE TOP OF THE PIPE.

BOLT SIZE TO BE SAME AS DIAPHRAGM AND CROSSFRAME CONNECTIONS. STAINLESS STEEL WORM DRIVE HOSE CLAMP SHALL BE COMMERCIAL QUALITY.

THE 6" Ø PVC PLASTIC PIPE AND FITTINGS SHALL BE SCHEDULE 40 AND CONFORM TO ASTM D1785.


PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 2 OF 2



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUPERSTRUCTURE					
TYPICAL SECTION DETAILS					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					TOTAL SHEETS
					24

DRAWN BY : M.D.PISO DATE : 06/2007
 CHECKED BY : B.M.BARODAWALA DATE : 10/10/07



FRAMING PLAN

PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 FRAMING PLAN



DRAWN BY : M.D. PISO DATE : 10/2006
 CHECKED BY : B.N. BARODAWALA DATE : 10/10/07

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-7
1			3			TOTAL SHEETS
2			4			24






PLATE GIRDER ELEVATION


* 8 ADDITIONAL ROWS OF SHEAR STUDS ARE LOCATED ON THE TOP OF THE BOLTED FIELD SPLICE. SEE "BOLTED FIELD SPLICE" SHEET 3 OF 3 FOR PLACEMENT OF THESE STUDS.



BOTTOM FLANGE DETAIL



TYPICAL FLANGE AND WEB BUTT JOINT



SHEAR STUD DETAILS

(TYP. EA. GIRDER)

PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 1 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 STRUCTURAL STEEL
 DETAILS

REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

S-8
 TOTAL SHEETS
 24

DRAWN BY : M.D.PISO DATE : 12/2006
 CHECKED BY : B.N.BARODAWALA DATE : 10/10/07



NOTES

ALL STRUCTURAL STEEL SHALL BE AASHTO M270 GRADE 50W AND PAINTED IN ACCORDANCE WITH SYSTEM 4 OF ARTICLE 442-7 OF THE STANDARD SPECIFICATIONS UNLESS OTHERWISE NOTED ON THE PLANS.

ALL DIMENSIONS SHOWN ARE HORIZONTAL OR VERTICAL, UNLESS OTHERWISE NOTED.

ALL FIELD CONNECTIONS TO BE 7/8" DIA. HIGH STRENGTH BOLTS UNLESS OTHERWISE NOTED. FOR HIGH STRENGTH BOLTS, SEE SPECIAL PROVISIONS.

BEARING STIFFENERS ARE TO BE PLACED NORMAL TO THE WEB OF THE GIRDER AND SHALL BE PLUMB.

A CHARPY V-NOTCH TEST IS REQUIRED FOR WEB PLATES, BOTTOM FLANGE PLATES, BOTTOM FLANGE SPLICE PLATES AND WEB SPLICE PLATES (IF USED) FOR ALL GIRDERS AND IN ACCORDANCE WITH ARTICLE 1072-9 OF THE STANDARD SPECIFICATIONS.


SHOP SPLICES ARE PERMITTED TO LIMIT THE MAXIMUM REQUIRED FLANGE PIECE LENGTHS TO 60 FEET AND WEB PIECE LENGTHS TO 45 FEET. PERMITTED FLANGE AND WEB SHOP SPLICES SHALL NOT BE LOCATED WITHIN 15 FEET OF MAXIMUM DEAD LOAD DEFLECTION (NOR WITHIN 15 FEET OF INTERMEDIATE BEARINGS OF CONTINUOUS UNITS). KEEP 2 FEET MINIMUM BETWEEN WEB AND FLANGE SHOP SPLICES. KEEP 6" MINIMUM BETWEEN CONNECTOR PLATE OR TRANSVERSE STIFFENER WELDS AND WEB OR FLANGE SHOP SPLICES.

TENSION ON THE AASHTO M164 BOLTS SHALL BE CALIBRATED USING DIRECT TENSION INDICATOR WASHERS IN ACCORDANCE WITH ARTICLE 440-8 OF THE STANDARD SPECIFICATIONS.


STUDS ON GIRDERS MAY BE SHIFTED UP TO 1" IF NECESSARY TO CLEAR FLANGE SPLICE WELD.

END OF GIRDERS SHALL BE PLUMB.

BEARING STIFFENER MAY REQUIRE COPING IF WIDER THAN BOTTOM FLANGE TO AVOID INTERFERENCE WITH THE ANCHOR BOLT.




END BENT DIAPHRAGM




BEARING STIFFENER/
CONNECTOR PLATE


(@ END BENTS)




INTERMEDIATE DIAPHRAGM
CONNECTOR PLATE




INTERMEDIATE DIAPHRAGM



SECTION A-A



SHEAR STUD DETAIL



TYPICAL STIFFENER OR
CONNECTOR PLATE CONNECTIONS

WELD TERMINATION DETAILS

PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 2 OF 3


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUPERSTRUCTURE
 STRUCTURAL STEEL
 DETAILS




REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-9
1			3			TOTAL SHEETS
2			4			24


DRAWN BY : M.D.PISO DATE : 12/2006
 CHECKED BY : B.N. BARODAWALA DATE : 10/10/07




PLAN (TOP OF TOP FLANGE)




PLAN (TOP OF BOTTOM FLANGE)



ELEVATION



SECTION A-A




SHEAR STUD DETAIL FOR TOP FLANGE SPLICE PLATE

* SHEAR STUDS ARE TO BE SHOP WELDED ON TOP OF PLATE BEFORE FIELD ASSEMBLY.

PROJECT NO. B-2146
 IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 3 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 STRUCTURAL STEEL
 OPTIONAL BOLTED
 FIELD SPLICE DETAILS



OPTIONAL BOLTED FIELD SPLICE DETAILS

DRAWN BY: E.E. MURRAY DATE: 4/1/08
 CHECKED BY: T.L. AVERETTE DATE: 4/1/08

08-MAY-2008 16:01
 G:\Structures\Final Plans\B2146.sd.SS.dgn
 emurray

REVISIONS						SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:	S-10	
1			3			TOTAL SHEETS	
2			4			24	

NOTES

AT ALL FIXED POINTS OF SUPPORT, NUTS FOR ANCHOR BOLTS ARE TO BE TIGHTENED FINGER TIGHT AND THEN BACKED OFF 1/2 TURN. THE THREAD OF THE NUT AND BOLT SHALL THEN BE BURRED WITH A SHARP POINTED TOOL.

THE 2" Ø PIPE SLEEVE SHALL BE CUT FROM SCHEDULE 40 PVC PLASTIC PIPE. THE PVC PLASTIC PIPE SHALL MEET THE REQUIREMENTS OF ASTM D1785.


THE PAYMENT FOR THE PIPE SLEEVES SHALL BE INCLUDED IN THE SEVERAL PAY ITEMS.

FOR AASHTO M270 GRADE 50W STRUCTURAL STEEL, SOLE PLATE SHALL BE AASHTO M270 GRADE 50W AND SHALL NOT BE GALVANIZED. ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.


ANCHOR BOLTS SHALL MEET THE REQUIREMENTS OF ASTM A449. NUTS SHALL MEET THE REQUIREMENTS OF AASHTO M291-DH OR AASHTO M292-2H. WASHERS SHALL MEET THE REQUIREMENTS OF AASHTO M293. SHOP DRAWINGS ARE NOT REQUIRED FOR ANCHOR BOLTS, NUTS AND WASHERS. SHOP INSPECTION IS REQUIRED.

WHEN FIELD WELDING THE SOLE PLATE TO THE GIRDER FLANGE, USE TEMPERATURE INDICATING WAX PENS, OR OTHER SUITABLE MEANS, TO ENSURE THAT THE TEMPERATURE OF THE SOLE PLATE DOES NOT EXCEED 300°F. TEMPERATURES ABOVE THIS MAY DAMAGE THE ELASTOMER.

ALL SURFACES OF BEARING PLATES SHALL BE SMOOTH AND STRAIGHT.



FIXED EXPANSION
END VIEW




DETAIL "A"

THE CLOSURE PLATE, GROUT PIPE AND STANDARD PIPE FOR THE EXPANSION ASSEMBLY NEED NOT BE GALVANIZED.


THE CONTRACTOR'S ATTENTION IS CALLED TO THE FOLLOWING PROCEDURES TO ACCOMMODATE GIRDER TRANSLATION AND END ROTATION:

1. ONCE THE DECK HAS CURED, THE GIRDERS SHALL BE JACKED AND THE ANCHOR BOLTS, SOLE PLATE, AND ELASTOMERIC BEARING SLOTS SHALL BE CENTERED AS NEARLY AS PRACTICAL ABOUT THE BEARING STIFFENER. THIS OPERATION SHALL BE PERFORMED AT APPROXIMATELY 60° F.
2. AFTER CENTERING THE SLOTS AND ANCHOR BOLTS, THE SOLE PLATES SHALL BE FIELD WELDED TO THE GIRDER FLANGES AND ANCHOR BOLTS GROUTED.


THE CONTRACTOR MAY PROPOSE ALTERNATE METHODS, PROVIDED DETAILS ARE SUBMITTED TO THE ENGINEER FOR REVIEW AND APPROVAL.



TYPICAL SECTION OF ELASTOMERIC BEARING




SOLE PLATE PLACEMENT DETAIL



E2 (4 REQ'D) E1 (4 REQ'D)
PLAN VIEW OF ELASTOMERIC BEARING

TYPE IV



SOLE PLATE DETAILS ("P")

-LOAD RATINGS-	
	MAX.D.L.+ L.L.
TYPE IV	184 K

PROJECT NO. B-2146
IREDELL COUNTY
STATION: 18+13.50 -L-



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
STANDARD
ELASTOMERIC BEARING
DETAILS
(STEEL SUPERSTRUCTURE)

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-11
1			3			TOTAL SHEETS
2			4			24

ASSEMBLED BY : M.D.PISO	DATE : 04/2007
CHECKED BY : B.N.BARODAWALA	DATE : 10/10/07
DRAWN BY : EEM	10/95
CHECKED BY : PEK	10/95
REV. 10/17/00	RWW/LES
REV. 7/10/01	LES/RDR
REV. 5/1/06	TLA/GM


DEAD LOAD DEFLECTION TABLE FOR EXTERIOR GIRDERS																					
	GIRDER #1 & GIRDER #4																				
@ TWENTIETH POINTS BETWEEN C BEARINGS	0	.05	.10	.15	.20	.25	.30	.35	.40	.45	.50	.55	.60	.65	.70	.75	.80	.85	.90	.95	0
DEFLECTION DUE TO WEIGHT OF GIRDER ↓	0.000	0.020	0.039	0.058	0.075	0.089	0.102	0.112	0.119	0.124	0.125	0.124	0.119	0.112	0.102	0.089	0.075	0.058	0.039	0.020	0.000
DEFLECTION DUE TO WEIGHT OF SLAB * ↓	0.000	0.061	0.140	0.214	0.283	0.343	0.394	0.436	0.465	0.484	0.490	0.484	0.465	0.436	0.394	0.343	0.283	0.214	0.140	0.061	0.000
DEFLECTION DUE TO WEIGHT OF BARRIER RAIL ↓	0.000	0.008	0.015	0.023	0.029	0.035	0.040	0.044	0.043	0.049	0.049	0.049	0.043	0.044	0.040	0.035	0.029	0.023	0.015	0.008	0.000
TOTAL DEAD LOAD DEFLECTION ↓	0.000	0.088	0.194	0.295	0.386	0.467	0.536	0.592	0.627	0.657	0.664	0.657	0.627	0.592	0.536	0.467	0.386	0.295	0.194	0.088	0.000
VERTICAL CURVE ORDINATE ↑	0.000	-0.053	-0.100	-0.142	-0.177	-0.207	-0.232	-0.250	-0.263	-0.270	-0.272	-0.267	-0.257	-0.242	-0.220	-0.193	-0.160	-0.122	-0.081	-0.041	0.000
ORDINATE DUE TO SUPERELEVATION	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
REQUIRED CAMBER ↑	0.000	7/16	1/8	1 13/16	2 1/2	3 1/8	3 5/8	4 1/8	4 3/8	4 5/8	4 11/16	4 11/16	4 7/16	4 3/16	3 13/16	3 5/16	2 11/16	2 1/16	1 3/8	7/16	0.000

* INCLUDES SLAB, BUILDUPS & STAY-IN-PLACE FORMS.
ALL VALUES ARE SHOWN IN FEET (DECIMAL FORM), EXCEPT "REQUIRED CAMBER", WHICH IS GIVEN IN INCHES (FRACTION FORM).

DEAD LOAD DEFLECTION TABLE FOR INTERIOR GIRDERS																					
	GIRDER #2 & GIRDER #3																				
@ TWENTIETH POINTS BETWEEN C BEARINGS	0	.05	.10	.15	.20	.25	.30	.35	.40	.45	.50	.55	.60	.65	.70	.75	.80	.85	.90	.95	0
DEFLECTION DUE TO WEIGHT OF GIRDER ↓	0.000	0.020	0.039	0.058	0.075	0.089	0.102	0.112	0.119	0.124	0.125	0.124	0.119	0.112	0.102	0.089	0.075	0.058	0.039	0.020	0.000
DEFLECTION DUE TO WEIGHT OF SLAB * ↓	0.000	0.062	0.143	0.219	0.288	0.350	0.402	0.444	0.474	0.493	0.499	0.493	0.474	0.444	0.402	0.350	0.288	0.219	0.143	0.062	0.000
DEFLECTION DUE TO WEIGHT OF BARRIER RAIL ↓	0.000	0.008	0.015	0.022	0.028	0.034	0.039	0.043	0.046	0.047	0.048	0.047	0.046	0.043	0.039	0.034	0.028	0.022	0.015	0.008	0.000
TOTAL DEAD LOAD DEFLECTION ↓	0.000	0.090	0.197	0.298	0.391	0.473	0.543	0.599	0.639	0.664	0.672	0.664	0.639	0.599	0.543	0.473	0.391	0.298	0.197	0.090	0.000
VERTICAL CURVE ORDINATE ↑	0.000	-0.053	-0.100	-0.142	-0.177	-0.207	-0.232	-0.250	-0.263	-0.270	-0.272	-0.267	-0.257	-0.242	-0.220	-0.193	-0.160	-0.122	-0.081	-0.041	0.000
ORDINATE DUE TO SUPERELEVATION	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
REQUIRED CAMBER ↑	0.000	7/16	1 3/16	1 7/8	2 5/16	3 3/16	3 3/4	4 3/16	4 1/2	4 3/4	4 13/16	4 3/4	4 9/16	4 5/16	3 7/8	3 3/8	2 3/4	2 1/8	1 3/8	7/16	0.000

* INCLUDES SLAB, BUILDUPS & STAY-IN-PLACE FORMS.
ALL VALUES ARE SHOWN IN FEET (DECIMAL FORM), EXCEPT "REQUIRED CAMBER", WHICH IS GIVEN IN INCHES (FRACTION FORM).

PROJECT NO. B-2146
IREDELL COUNTY
STATION: 18+13.50 -L-




STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
SUPERSTRUCTURE
DEAD LOAD DEFLECTIONS



DRAWN BY : M.D.PISO DATE : 10/2006
CHECKED BY : B.N.BARADAWALA DATE : 10/10/07

08-MAY-2008 17:02
G:\Structures\Final Plans\B2146_sd.DL.dgn
emurray

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-12
1			3			TOTAL SHEETS
2			4			24



PLAN OF BARRIER RAIL



END OF RAIL DETAILS

FOR ADHESIVE ANCHORING AT SAWED JOINTS

NOTES



THE BARRIER RAIL SHALL NOT BE CAST UNTIL ALL SLAB CONCRETE IN THE SPAN HAS BEEN CAST AND HAS REACHED A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI.

WHEN EVAZOTE JOINT SEAL IS REQUIRED, THE JOINT IN THE DECK SHALL BE SAWED PRIOR TO THE CASTING OF BARRIER RAIL.


ALL REINFORCING STEEL IN BARRIER RAILS SHALL BE EPOXY COATED.

THE #5 S3 AND #5 S4 BARS SHALL BE INSTALLED, USING AN ADHESIVE ANCHORING SYSTEM, AFTER SAWING THE JOINT. THE YIELD LOAD FOR THE #5 S3 AND #5 S4 BARS IS 18.6 KIPS. FIELD TESTING FOR THE ADHESIVE BONDING SYSTEM IS NOT REQUIRED.


VERTICAL GROOVED CONTRACTION JOINTS, 1/2" IN DEPTH, SHALL BE TOOLED IN ALL EXPOSED FACES OF THE BARRIER RAIL AND IN ACCORDANCE WITH ARTICLE 825-10(B) OF THE STANDARD SPECIFICATIONS. THE CONTRACTION JOINT SHALL BE LOCATED AT EACH THIRD POINT BETWEEN BARRIER RAIL EXPANSION JOINTS. ONLY ONE CONTRACTION JOINT IS REQUIRED AT MIDPOINT OF BARRIER RAIL SEGMENTS LESS THAN 20 FEET IN LENGTH AND NO CONTRACTION JOINTS ARE REQUIRED FOR THOSE SEGMENTS LESS THAN 10 FEET IN LENGTH.



C 1/2" EXP. JT. MAT'L HELD IN PLACE WITH GALVANIZED NAILS.
(NOTE: OMIT EXP. JT. MAT'L. WHEN SLIP FORM IS USED.)



ELEVATION AT EXPANSION JOINTS
BARRIER RAIL DETAILS



BILL OF MATERIAL
FOR CONCRETE BARRIER RAIL ONLY

BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
* B1	28	#5	STR	23'-7"	689
* B2	42	#5	STR	24'-8"	1,081
* S1	236	#5	1	4'-7"	1,128
* S2	236	#5	2	5'-2"	1,272
* S3	12	#5	3	3'-4"	42
* S4	12	#5	STR	3'-2"	40
* EPOXY COATED REINFORCING STEEL					4,252 LBS.
CLASS AA CONCRETE					24.6 CU. YDS.
CONCRETE BARRIER RAIL					245.83 LIN. FT.

PROJECT NO. B-2146
IREDELL COUNTY
STATION: 18+13.50 -L-

SHEET 1 OF 2





STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

STANDARD CONCRETE BARRIER RAIL

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-13
1			3			TOTAL SHEETS 24
2			4			

EMILY E. MURPHY
5-9-08

ASSEMBLED BY : M.D.PISO DATE : 10/2006
CHECKED BY : B.N.BARODWALA DATE : 10/10/07
DRAWN BY : ARB 5/87 REV. 10/17/00 RWW/LES
CHECKED BY : SJD 9/87 REV. 5/17/03R RWW/JTE
REV. 5/1/06 TLA/GM



LOCATION OF ANCHORS FOR GUARDRAIL
END BENT #1 SHOWN, END BENT #2 SIMILAR.

NOTES

THE GUARDRAIL ANCHOR ASSEMBLY SHALL CONSIST OF A 1/4" HOLD DOWN PLATE AND 4 - 1/8" Ø BOLTS WITH NUTS AND WASHERS, RUBRAIL, AND ADHESIVELY ANCHORED BOLTS.

THE HOLD-DOWN PLATE SHALL CONFORM TO AASHTO M270 GRADE 36. AFTER FABRICATION, THE HOLD-DOWN PLATE SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH AASHTO M11.

BOLTS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307 AND NUTS SHALL CONFORM TO THE REQUIREMENTS OF AASHTO M291. BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED. (AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS, NUTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE 1/8" Ø GALVANIZED BOLTS, NUTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.)


THE GUARDRAIL ANCHOR ASSEMBLY IS REQUIRED AT ALL POINTS WHERE APPROACH GUARDRAIL IS TO BE ATTACHED TO THE END OF BARRIER RAIL. FOR POINTS OF ATTACHMENT, SEE SKETCH.

AFTER INSTALLATION, THE EXPOSED THREAD OF THE BOLT SHALL BE BURRED WITH A SHARP POINTED TOOL.

THE COST OF THE GUARDRAIL ANCHOR ASSEMBLY SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR CONCRETE BARRIER RAIL.

THE 1 1/4" Ø HOLES SHALL BE FORMED OR DRILLED WITH A CORE BIT. IMPACT TOOLS WILL NOT BE PERMITTED. ANY CONCRETE DAMAGED BY THIS WORK SHALL BE REPAIRED TO THE SATISFACTION OF THE ENGINEER.


THE C6 X 8.2 RUBRAIL IS TO BE ADHESIVELY ANCHORED TO THE RAIL USING THREE 3/4" Ø X 6" BOLTS WITH WASHERS. LEVEL ONE FIELD TESTING IS REQUIRED, AND THE YIELD LOAD OF THE 3/4" Ø BOLT IS 12 KIPS. FOR ADHESIVELY ANCHORED ANCHOR BOLTS OR DOWELS, SEE SPECIAL PROVISIONS. SEE ROADWAY STANDARD 862.03 FOR DETAILS AND LOCATION OF THE RUBRAIL.



SKETCH SHOWING POINTS OF ATTACHMENTS

ASSEMBLED BY : M.D.PISO DATE : 08/2007
 CHECKED BY : B.N.BARODAWALA DATE : 10/10/07
 DRAWN BY : TLA 5/06 ADDED 5/1/06
 CHECKED BY : GM 5/06

04-APR-2008 16:31
 r:\structures\final plans\b2146_ed.br.dgn.dgn
 mdpiso



PROJECT NO. B-2146
 IREDELL COUNTY
 STATION: 18+13.50 -L-
 SHEET 2 OF 2

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-14
1			3			TOTAL SHEETS 24
2			4			

STD. NO. GRA2

SUPERSTRUCTURE REINFORCING STEEL LENGTHS ARE BASED ON THE FOLLOWING MINIMUM SPLICE LENGTHS

BAR SIZE	SUPERSTRUCTURE EXCEPT APPROACH SLABS, PARAPET, AND BARRIER RAIL		APPROACH SLABS		PARAPET AND BARRIER RAIL
	EPOXY COATED	UNCOATED	EPOXY COATED	UNCOATED	
#4	2'-0"	1'-9"	2'-0"	1'-9"	2'-9"
#5	2'-6"	2'-2"	2'-6"	2'-2"	3'-5"
#6	3'-0"	2'-7"	3'-10"	2'-7"	4'-4"
#7	5'-3"	3'-6"			
#8	6'-10"	4'-7"			

REINFORCING BAR SCHEDULE

BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
* A1	227	#5	STR	33'-11"	8,030
A2	227	#5	STR	33'-11"	8,030
* B1	120	#4	STR	26'-2"	2,098
B2	123	#5	STR	42'-4"	5,431
* K1	8	#5	1	9'-9"	81
* K2	8	#5	2	12'-11"	108
* S1	48	#4	3	3'-4"	107


REINFORCING STEEL 13,461 LBS.

* EPOXY COATED REINFORCING STEEL 10,424 LBS.

GROOVING BRIDGE FLOORS

APPROACH SLABS	803	SQ.FT.
BRIDGE DECK	3,430	SQ.FT.
TOTAL	4,233	SQ.FT.

BAR TYPES




ALL BAR DIMENSIONS ARE OUT TO OUT

— SUPERSTRUCTURE BILL OF MATERIAL —

	CLASS AA CONCRETE	REINFORCING STEEL	EPOXY COATED REINFORCING STEEL
	(CU.YDS.)	(LBS.)	(LBS.)
	138.0	13,461	10,424
TOTALS**	138.0	13,461	10,424

**QUANTITIES FOR BARRIER RAIL ARE NOT INCLUDED



LAYOUT FOR COMPUTING AREA OF REINFORCED CONCRETE DECK SLAB (SQ. FT. = 4,210)



PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 SUPERSTRUCTURE
 BILL OF MATERIAL

ASSEMBLED BY :	M.D.PISO	DATE :	10/2006
CHECKED BY :	B.N.BARODWALA	DATE :	10/10/07
DRAWN BY :	JMB 5/87	REV. 6/1/94	EEM/GRP
CHECKED BY :	SJD 9/87	REV. 8/16/99	RWW/LES
		REV. 5/1/06	TLA/GM

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-15
1			3			TOTAL SHEETS
2			4			24



NOTES:

STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR ANCHOR BOLTS.

BACKWALL SHALL BE PLACED BEFORE APPLYING THE EPOXY PROTECTIVE COATING

THE TOP SURFACE AREAS OF THE END BENT CAP SHALL BE CURED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS EXCEPT THAT THE MEMBRANE CURING COMPOUND METHOD SHALL NOT BE USED.

THE TOP SURFACE OF THE CAP EXCEPT THE BRIDGE SEAT BUILD-UPS SHALL BE SLOPED TRANSVERSELY FROM THE FILL FACE AT THE RATE OF 2%.


THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE JOINT BETWEEN THE DECK AND THE APPROACH SLAB HAS BEEN SAWED AND THE BARRIER RAIL IS CAST IF SLIP FORMING IS USED.

EPOXY COAT THE END BENT CAP AFTER ADJUSTMENTS ARE MADE TO BEARINGS AND ANCHOR BOLTS ARE GROUTED.

FOR TEMPORARY DRAINAGE DETAIL, SEE END BENT #2, SHEET 3 OF 3.

FOR BLOCKOUT IN WING WALL DETAIL, SEE END BENT #2, SHEET 3 OF 3.

THE CONTRACTOR SHALL PROVIDE FOR INSTALLATION OF THE 4" DIAMETER DRAIN PIPE THROUGH THE WING WALL. REINFORCING STEEL IN THE WING WALL MAY BE SHIFTED AS NECESSARY TO CLEAR THE DRAIN PIPE.



PROJECT NO. B-2146

IREDELL COUNTY

STATION: 18+13.50 -L-

SHEET 1 OF 3


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH


SUBSTRUCTURE
END BENT #1

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-16
1			3			TOTAL SHEETS
2			4			24

DRAWN BY: J.B. WILSON DATE: 6/2007
CHECKED BY: M. PISO DATE: 2/2008


FOR FOOTING DIMENSIONS & REINFORCING STEEL, SEE SHEET 3 OF 3.






PLAN OF WING AND WING FOOTING (W1)

SEE SHEET 3 OF 3 FOR PLAN VIEW OF 'T' BARS IN WING FOOTING




PLAN OF WING AND WING FOOTING (W2)


SEE SHEET 3 OF 3 FOR PLAN VIEW OF 'T' BARS IN WING FOOTING




SECTION Y-Y



ELEVATION OF WING (W1)



SECTION X-X



ELEVATION OF WING (W2)

PROJECT NO. B-2146
 IREDELL COUNTY
 STATION: 18+13.50 -L-


SHEET 2 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUBSTRUCTURE
 END BENT #1




DRAWN BY: J.B. WILSON DATE: 6/2007
 CHECKED BY: M. PISO DATE: 2/2008


REVISIONS						SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:	S-17	
1			3			TOTAL SHEETS 24	
2			4				



PLAN OF FOOTING




SECTION A-A



SECTION B-B

DRAWN BY : J.B. WILSON DATE : 6/2007
 CHECKED BY : M.PISO DATE : 2/2008

08-MAY-2008 16:59
 G:\Structures\Final Plans\B2146.ed.eb*1.dgn
 emurray



ALL BAR DIMENSIONS ARE OUT TO OUT.

BILL OF MATERIAL

FOR END BENT #1

BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	8	#9	1	42'-3"	1149
B2	12	#4	STR	21'-2"	170
B3	4	#4	STR	16'-6"	44
H1	20	#4	4	10'-0"	134
H2	22	#4	4	11'-0"	162
K1	16	#4	STR	21'-2"	226
K2	8	#4	STR	3'-6"	19
M1	40	#8	6	7'-8"	819
M2	40	#4	STR	3'-6"	94
M3	9	#4	STR	6'-10"	41
M4	9	#6	STR	7'-8"	104
M5	10	#4	STR	7'-5"	50
M6	10	#6	STR	8'-3"	124
S1	40	#4	2	9'-5"	252
S2	40	#4	3	3'-2"	85
T1	14	#4	STR	8'-9"	82
T2	14	#4	STR	9'-9"	91
T3	79	#6	STR	5'-8"	672
T4	45	#6	1	6'-10"	462
T5	28	#4	STR	23'-8"	443
U1	33	#4	5	3'-8"	81
U2	11	#4	5	5'-5"	40
V1	36	#5	STR	7'-1"	266
V2	30	#5	STR	7'-5"	232
V3	10	#5	STR	8'-9"	91
V4	10	#5	STR	9'-4"	97
V5	18	#4	STR	5'-5"	65
V6	20	#4	STR	5'-6"	73

REINFORCING STEEL = 6168 LBS

CLASS A CONCRETE BREAKDOWN


POUR #1 FOOTING	C.Y.	27.1
POUR #2 CAP & LOWER PORTION OF WINGS	C.Y.	18.0
POUR #3 BACKWALL & UPPER PORTION OF WINGS	C.Y.	10.3
TOTAL CLASS A CONCRETE	C.Y.	55.4

PROJECT NO. B-2146
 IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 3 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 END BENT #1



REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.

S-18

TOTAL SHEETS 24

NOTES

STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR ANCHOR BOLTS.


BACKWALL SHALL BE PLACED BEFORE APPLYING THE EPOXY PROTECTIVE COATING.

THE TOP SURFACE AREAS OF THE END BENT CAPS SHALL BE CURED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS EXCEPT THE MEMBRANE CURING COMPOUND METHOD SHALL NOT BE USED.

THE TOP SURFACE OF THE CAP EXCEPT THE BRIDGE SEAT BUILDUPS SHALL BE SLOPED TRANSVERSELY FROM THE FILL FACE TO THE BACK FACE AT THE RATE OF 2%.

THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE JOINT BETWEEN THE DECK AND THE APPROACH SLAB HAS BEEN SAWED AND THE BARRIER RAIL IS CAST IF SLIP FORMING IS USED.

THE CONTRACTOR SHALL PROVIDE FOR INSTALLATION OF THE 4" DIAMETER DRAIN PIPE THROUGH THE WING WALL AS REQUIRED FOR REINFORCED BRIDGE APPROACH FILLS. SEE THE ROADWAY PLANS. REINFORCING STEEL IN THE WING WALL MAY BE SHIFTED AS NECESSARY TO CLEAR THE DRAIN PIPE.



DETAIL 'A'
(TYP. EA. GDR.)


PROJECT NO. B-2146
IREDELL COUNTY
STATION: 18+13.50 -L-

SHEET 1 OF 3


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

**SUBSTRUCTURE
END BENT #2**

REVISIONS						SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:	S-19	
1			3			TOTAL SHEETS	
2			4			24	




PLAN




ELEVATION


DRAWN BY: J.B. WILSON DATE: 10/2007
CHECKED BY: M. PISO DATE: 12/2007




PLAN OF WING (W1)



PLAN OF WING (W2)




ELEVATION OF WING (W1)



SECTION X-X

SECTION Y-Y



ELEVATION OF WING (W2)

PROJECT NO. B-2146
 IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 END BENT #2




DRAWN BY: J.B. WILSON DATE: 10/2007
 CHECKED BY: M. PISO DATE: 12/2007


04-APR-2008 16:32
 r:\structures\final plans\b2146_sd.eb#2.dgn
 mdpleo

REVISIONS				SHEET NO.	
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		


TOTAL SHEETS: 24



SECTION A-A




SECTION B-B



ALL BAR DIMENSIONS ARE OUT TO OUT.

BILL OF MATERIAL FOR END BENT #2					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	8	#9		42'-3"	1149
B2	2	#5	STR	39'-11"	83
B3	8	#4	STR	21'-2"	113
B4	10	#4	STR	2'-5"	16
B5	4	#4	STR	16'-6"	44
H1	18	#4		10'-5"	125
H2	20	#4		11'-4"	151
K1	16	#4	STR	21'-2"	226
K2	8	#4	STR	3'-6"	19
S1	42	#4		7'-5"	208
S2	42	#4		3'-2"	89
S3	18	#4		6'-6"	78
V1	36	#5	STR	6'-0"	225
V2	30	#5	STR	6'-4"	198
V3	28	#4	STR	7'-8"	143
V4	30	#4	STR	8'-4"	167
U1	33	#4		3'-8"	81
U2	11	#4		5'-5"	40
REINFORCING STEEL					LBS 3155
CLASS A CONCRETE BREAKDOWN					
POUR #1 CAP & LOWER PORTION OF WINGS					C.Y. 13.3
POUR #2 BACKWALL & UPPER PORTION OF WINGS					C.Y. 10.2
TOTAL CLASS A CONCRETE					C.Y. 23.5
HP 12 X 53 STEEL PILES					
NO. 9					LIN. FT. 540




BAGGED STONE AND PIPE SHALL BE PLACED IMMEDIATELY AFTER COMPLETION OF END BENT EXCAVATION. PIPE MAY BE EITHER CONCRETE, CORRUGATED STEEL, CORRUGATED ALUMINUM ALLOY, OR CORRUGATED PLASTIC. PERFORATED PIPE WILL NOT BE ALLOWED.

BAGGED STONE SHALL REMAIN IN PLACE UNTIL THE ENGINEER DIRECTS THAT IT BE REMOVED. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF SILT ACCUMULATIONS AT BAGGED STONE WHEN SO DIRECTED BY THE ENGINEER. BAGS SHALL BE REMOVED AND REPLACED WHENEVER THE ENGINEER DETERMINES THAT THEY HAVE DETEIORATED AND LOST THEIR EFFECTIVENESS.

NO SEPARATE PAYMENT WILL BE MADE FOR THIS WORK AND THE ENTIRE COST OF THIS WORK SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR THE SEVERAL PAY ITEMS.


TEMPORARY DRAINAGE AT END BENT



PLAN

ELEVATION

BLOCKOUT IN WING WALL



* POSITION OF PILE DURING WELDING.

PILE SPLICE DETAILS

PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-


SHEET 3 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

**SUBSTRUCTURE
 END BENT #2**

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-21
1			3			TOTAL SHEETS 24
2			4			

DRAWN BY: J.B. WILSON DATE: 6/2007
 CHECKED BY: M. PISO DATE: 12/2007




END BENT 1


END BENT 2

PLAN

ESTIMATED QUANTITIES		
BRIDGE @ STA. 18+13.50 -L-	RIP RAP CLASS II	FILTER FABRIC FOR DRAINAGE
	TONS	SQUARE YARDS
END BENT 1	50	56
END BENT 2	70	78




SECTION @ E.B. #1
BERM RIP RAPPED



SECTION @ E.B. #2
BERM RIP RAPPED

PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 RIP RAP DETAILS






ASSEMBLED BY : J.B. WILSON DATE : 3/19/07
 CHECKED BY : T.L. AVERETTE DATE : 4/02/08
 DRAWN BY : FCJ 2/88 REV. 8/16/99 RWW/LES
 CHECKED BY : ARB 8/88 REV. 10/17/00 RWW/LES
 REV. 5/1/06 TLA/GM

REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

S-22
 TOTAL SHEETS 24



DIMENSIONS SHOWN ARE TYPICAL FOR BOTH APPROACH SLABS



NOTES

APPROACH SLAB SHALL NOT BE CONSTRUCTED PRIOR TO COMPLETION OF THE BRIDGE DECK.

SUBDRAIN FINE AGGREGATE FOR APPROACH SLAB AT END BENT #1 IS TO BE CONTINUOUS ALONG FILL FACE OF BACKWALL AND END BENT FROM WINGWALL TO WINGWALL.

FOR REINFORCED BRIDGE APPROACH FILL AT END BENT #2 INCLUDING FABRIC, IMPERMEABLE GEOMEMBRANE, 4" Ø CORRUGATED PERFORATED DRAINAGE PIPE, OR IMPERMEABLE GEOMEMBRANE AT END BENT #1. THIS WORK SHALL BE INCLUDED IN THE PAY ITEM FOR "BRIDGE APPROACH SLABS."

NO SEPARATE PAYMENT SHALL BE MADE FOR THE SUBDRAIN FINE AGGREGATE, #78M STONE, 4" Ø CORRUGATED PERFORATED DRAINAGE PIPE, OR IMPERMEABLE GEOMEMBRANE AT END BENT #1. THIS WORK SHALL BE INCLUDED IN THE PAY ITEM FOR "BRIDGE APPROACH SLABS."

AREA BETWEEN THE WINGWALL AND APPROACH SLAB SHALL BE GRADED TO DRAIN THE WATER AWAY FROM THE FILL FACE OF THE BRIDGE AND SHALL BE PAVED. SEE ROADWAY PLANS.

THE 6" COMP. A.B.C. SHALL BE FLUSH WITH THE ROADWAY END OF THE APPROACH SLAB AND SHALL EXTEND 1'-0" OUTSIDE EACH EDGE OF THE APPROACH SLAB.

THE CONTRACTOR MAY USE 4" TYPE B-25.0B ASPHALT CONCRETE BASE COURSE IN LIEU OF 6" COMP. A.B.C. IF THIS OPTION IS USED, THE BASE COURSE SHALL BE FLUSH WITH THE ROADWAY END OF THE APPROACH SLAB, AND THE WIDTH SHALL BE THE SAME AS THAT OF THE APPROACH SLAB.

THE CONTRACTOR MAY USE 5" CLASS "A" CONCRETE BASE IN LIEU OF 6" COMP. A.B.C. IF THIS OPTION IS USED, THE CONCRETE BASE SHALL BE FLUSH WITH THE ROADWAY END OF THE APPROACH SLAB, AND THE WIDTH SHALL BE THE SAME AS THAT OF THE APPROACH SLAB. THE CONCRETE SHALL BE FINISHED TO A SMOOTH SURFACE AND A LAYER OF 30 LB ROOFING FELT SHALL BE PLACED BETWEEN THE CONCRETE BASE AND THE APPROACH SLAB TO PREVENT BOND. THE APPROACH SLAB SHALL NOT BE CAST UNTIL THE CONCRETE BASE HAS REACHED AN AGE OF THREE CURING DAYS.

THE JOINT SHALL BE SAWS PRIOR TO THE CASTING OF THE BARRIER RAIL.

WITH EVAZOTE JOINT SEAL

FOR EVAZOTE JOINT SEALS, SEE SPECIAL PROVISIONS.

THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE EVAZOTE JOINT SEAL SHALL BE 2 1/2".

FOR ELASTOMERIC CONCRETE, SEE SPECIAL PROVISIONS.

BILL OF MATERIAL					
APPROACH SLAB AT EB #1					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
*A1	30	#4	STR	17'-0"	341
A2	32	#4	STR	16'-11"	362
*B1	65	#5	STR	13'-8"	927
B2	65	#6	STR	14'-8"	1432
REINFORCING STEEL					LBS. 1794
*EPOXY COATED REINFORCING STEEL					LBS. 1268
CLASS AA CONCRETE					C. Y. 18.6
APPROACH SLAB AT EB #2					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
*A1	30	#4	STR	17'-0"	341
A2	32	#4	STR	16'-11"	362
*B1	65	#5	STR	13'-8"	927
B2	65	#6	STR	14'-8"	1432
REINFORCING STEEL					LBS. 1794
*EPOXY COATED REINFORCING STEEL					LBS. 1268
CLASS AA CONCRETE					C. Y. 18.6

SPlice CHART	
BAR	SPlice LENGTH
*4 A1	2'-0"
*4 A2	1'-9"

ASSEMBLED BY : CHRIS MCDUFFEE	DATE : 12/06
CHECKED BY : T.L. AVERETTE	DATE : 12/06
DRAWN BY : EEM 3/95	REV. 7/10/01 LES/RDR
CHECKED BY : VAP 3/95	REV. 5/7/03R RWW/JTE
	REV. 5/1/06R KMM/GM




PROJECT NO. B-2146
 IREDELL COUNTY
 STATION: 18+13.50 -L-


SHEET 1 OF 2

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STANDARD BRIDGE APPROACH SLAB FOR FLEXIBLE PAVEMENT					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		


TOTAL SHEETS 24




SECTION C-C
EVAZOTE JOINT SEAL
(PRE-SAWED ELASTOMERIC
CONCRETE DIMENSIONS)




SECTION C-C
EVAZOTE JOINT SEAL
(EXPANSION)




SECTION C-C
EVAZOTE JOINT SEAL
(FIXED)



SECTION B-B




PLAN



SECTION A-A


JOINT SEAL DETAILS @ END BENT

EVAZOTE JOINT SEAL TO BE CUT, HEAT WELDED AND TURNED UP PARALLEL TO SLOPED FACE OF THE BARRIER RAIL.



PLAN VIEW


NOTE: IMMEDIATELY AFTER THE CONSTRUCTION OF THE APPROACH SLAB, THE CONTRACTOR SHALL PROVIDE TEMPORARY BERM AND SLOPE DRAIN. CONTRACTOR SHALL GRADE TO PIPE INLET AND PROVIDE EROSION RESISTANT MATERIAL AS SHOWN. THE EROSION RESISTANT MATERIAL SHALL BE EITHER 1) ASPHALT PLANT MIX, TYPE 1 OR TYPE 2, MIN. 2\"/>



SECTION S-S

TEMPORARY BERM AND SLOPE DRAIN DETAILS

(TO BE USED WHEN SHOULDER BERM GUTTER IS REQUIRED)




NOTE: IF THE APPROACH SLAB IS NOT CONSTRUCTED IMMEDIATELY AFTER THE BACKFILLING OF THE END BENT EXCAVATION, GRADE TO DRAIN TO THE BOTTOM OF THE SLOPE AND PROVIDE EROSION RESISTANT MATERIAL, SUCH AS FIBERGLASS ROVING OR AS DIRECTED BY THE ENGINEER TO PREVENT SOIL EROSION AND TO PROTECT THE AREA ADJACENT TO THE STRUCTURE. THE CONTRACTOR WILL BE REQUIRED TO REMOVE THESE MATERIALS PRIOR TO CONSTRUCTION OF THE APPROACH SLAB.

TEMPORARY DRAINAGE DETAIL


ELASTOMERIC CONCRETE	
END BENT NO.	ELASTOMERIC CONCRETE * (CU. FT.)
1	5.3
2	5.3
TOTAL	10.6

* BASED ON THE MINIMUM BLOCKOUT SHOWN.



SECTION THRU SLAB AT END BENT #2

ASSEMBLED BY : CHRIS MCDUFFEE	DATE : 12/20/06
CHECKED BY : T. L. AVERETTE	DATE : 12/20/06
DRAWN BY : FCJ 11/88	REV. 10/17/00 RWW/LES
CHECKED BY : ARB 11/88	REV. 5/1/03 RWW/JTE
	REV. 5/1/06R MAA/KMM



PROJECT NO. B-2146
IREDELL COUNTY
 STATION: 18+13.50 -L-

SHEET 2 OF 2

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STANDARD					
BRIDGE APPROACH SLAB DETAILS					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.	S-24
TOTAL SHEETS	24

STD. NO. BAS10

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	-----	A.A.S.H.T.O. (CURRENT)
LIVE LOAD	-----	SEE PLANS
IMPACT ALLOWANCE	-----	SEE A.A.S.H.T.O.
STRESS IN EXTREME FIBER OF		
STRUCTURAL STEEL - AASHTO M270 GRADE 36	-	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	-	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	-	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION		
GRADE 60	--	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	-----	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	-----	SEE A.A.S.H.T.O.
STRUCTURAL TIMBER - TREATED OR		
UNTREATED - EXTREME FIBER STRESS	-----	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	-----	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	-----	30 LBS. PER CU. FT. (MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2002 STANDARD SPECIFICATIONS "FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP; AND CLASS S SHALL BE USED FOR UNDERWATER FOOTING SEALS.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1-1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4" FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.

ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.

IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED WITH THE EXCEPTION OF #2 BARS WHICH MAY BE FABRICATED FROM COLD DRAWN STEEL WIRE. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.

WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8" Ø SHEAR STUDS FOR THE 3/4" Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8" Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4" Ø STUDS BASED ON THE RATIO OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".

EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.

PLACEMENT OF BEAM OR GIRDER MEMBERS ON TRUCKS FOR HAULING SHALL BE DONE IN COMPLIANCE WITH LIMITS SHOWN ON SKETCHES PROVIDED TO THE MATERIALS AND TEST UNIT APPROVED BY THE STRUCTURE DESIGN UNIT DATED MAY 8, 1991. THESE SKETCHES PRIMARILY LIMIT THE UNSUPPORTED CANTILEVER LENGTH OF MEMBERS. WHEN THE CONTRACTOR WISHES TO PLACE MEMBERS ON TRUCKS NOT IN ACCORDANCE WITH THESE LIMITS, TO SHIP BY RAIL, TO ATTACH SHIPPING RESTRAINTS TO THE MEMBERS OR TO INVERT MEMBERS, HE SHALL SUBMIT A SKETCH FOR APPROVAL PRIOR TO SHIPPING. SEE ALSO ARTICLE 1072-11.

WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16 INCH OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.

METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINIS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.

ENGLISH

JANUARY, 1990

STD. NO. SN