

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

**PLAN FOR PROPOSED
TRAFFIC CONTROL, MARKING & DELINEATION
CUMBERLAND COUNTY**

ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS"-PROJECT SERVICES UNIT-N.C. DEPARTMENT OF TRANSPORTATION-RALEIGH, N.C., DATED JULY 2006 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
904.50	SIGN MOUNTING
1101.02	TEMPORARY LANE CLOSURES
1101.04	TEMPORARY SHOULDER CLOSURES
1101.05	WORK ZONE VEHICLE ACCESSES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1110.02	PORTABLE WORK ZONE SIGNS
1115.01	FLASHING ARROW PANELS
1130.01	DRUM
1135.01	CONES
1145.01	BARRICADES
1150.01	FLAGGING DEVICES
1165.01	TRUCK MOUNTED IMPACT ATTENUATOR
1180.01	SKINNY-DRUM
1205.01	PAVEMENT MARKINGS - LINE TYPES & OFFSETS
1205.02	PAVEMENT MARKINGS - 2 LANE & MULTILANE ROADWAYS
1205.04	PAVEMENT MARKINGS - INTERSECTIONS
1205.05	PAVEMENT MARKINGS - TURN LANES
1205.08	PAVEMENT MARKINGS - SYMBOLS & WORD MESSAGES
1250.01	PAVEMENT MARKER SPACING
1253.01	SNOWPLOWABLE RAISED PAVEMENT MARKERS
1261.01	GUARDRAIL & BARRIER DELINEATOR SPACING
1261.02	GUARDRAIL & BARRIER DELINEATOR TYPES
1262.01	GUARDRAIL END DELINEATION

INDEX OF SHEETS

SHEET NO.	TITLE
TCP-1	LIST OF APPLICABLE ROADWAY STANDARD DRAWINGS, LEGEND, TEMPORARY PAVEMENT SCHEDULE AND INDEX OF SHEETS
TCP-2	PROJECT NOTES
TCP-3	PHASING
TCP-4	PLANS PHASE I
TCP-5	PLANS PHASE II
TCP-6	PLANS PHASE III
TCP-7	WORK ZONE ADVANCED WARNING SIGNS
TCP-8	DETAIL DRAWING FOR ADVANCE WORK ZONE WARNING SIGN
PM & SIGN-1 THRU PM & SIGN-8	PAVEMENT MARKING & SIGNING PLANS

TEMP. PAVEMENT MARKING SCHEDULE


DESCRIPTION	INTERMEDIATE PAY ITEM QUANTITY	TOTAL QUANTITY
PAVEMENT MARKINGS		
PAINT (4")		
WHITE EDGELINE	2054 LF	
YELLOW EDGELINE	7160 LF	
2' WHITE MINI SKIP	308 LF	
2' YELLOW MINI SKIP	127 LF	
WHITE SOLID LANE LINE	5630 LF	
TOTAL		15279 LF
PAINT (24")		
WHITE STOP BAR	460 LF	
TOTAL		460 LF
PAINT (SYMBOL)		
LEFT TURN ARROW	21 EA	
TOTAL		21 EA

LEGEND

- GENERAL**
- ← DIRECTION OF TRAFFIC FLOW
 - ↑ NORTH ARROW
 - PROPOSED PVMT. - - - - - EXIST. PVMT.
 - WORK AREA
 - ▨ REMOVAL OF EXISTING PAVEMENT

- TRAFFIC CONTROL DEVICES**
- I TYPE I BARRICADE
 - II TYPE II BARRICADE
 - III TYPE III BARRICADE
 - ▲ CONE
 - DRUM
 - FLASHING ARROW PANEL (TYPE C)
 - ⊥ STATIONARY SIGN
 - ⊥ PORTABLE SIGN
 - ⊕ STATIONARY OR PORTABLE SIGN
 - ⚠ WARNING FLAGS
 - ⋄ CRASH CUSHION
 - Ⓜ CHANGEABLE MESSAGE SIGN
 - Ⓜ TRUCK MOUNTED IMPACT ATTENUATOR (TMIA)
 - Ⓜ POLICE
 - Ⓜ FLAGGER

- PAVEMENT MARKINGS**
- CRYSTAL/CRYSTAL PAVEMENT MARKER
 - ◆ YELLOW/YELLOW PAVEMENT MARKER
 - ▣ CRYSTAL/RED PAVEMENT MARKER
 - ↔ PAVEMENT MARKING SYMBOLS

APPROVED: _____	DATE: _____	TITLE SHEET	
			
SCALE: NONE	REVISIONS		
DATE: _____			
DWG. BY: _____			
DESIGN BY: _____			
REVIEWED BY: _____		<small>SCALE FILE</small>	

\$\$\$ SYSTEMS \$\$\$
\$\$\$ USER NAME \$\$\$

PROJECT NOTES

PROJ. REFERENCE NO. W-5006	SHEET NO. TCP-2
--------------------------------------	---------------------------

GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS, OR RESULT IN DUPLICATE, OR UNDESIRE OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING OR REMOVAL OF DEVICES, AS DIRECTED BY THE ENGINEER.

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

TIME RESTRICTIONS

A) DO NOT CLOSE OR NARROW TRAVEL LANES AS FOLLOWS:

ROAD NAME	DAY AND TIME RESTRICTIONS
NC 87	MONDAY THRU FRIDAY: 7 TO 9 AM AND 4 TO 6 PM

B) DO NOT CLOSE OR NARROW TRAVEL LANES DURING HOLIDAYS AND SPECIAL EVENTS AS FOLLOWS:

ROAD NAME
NC 87

HOLIDAY

1. FOR ANY UNEXPECTED OCCURRENCE THAT CREATES UNUSUALLY HIGH TRAFFIC VOLUMES, AS DIRECTED BY THE ENGINEER.
2. FOR NEW YEAR'S, BETWEEN THE HOURS OF 6:00 P.M. DECEMBER 31st TO 7:00 A.M. JANUARY 2ND. IF NEW YEAR'S DAY IS ON A FRIDAY, SATURDAY, SUNDAY, OR MONDAY THEN UNTIL 7:00 A.M. THE FOLLOWING TUESDAY.
3. FOR EASTER, BETWEEN THE HOURS OF 6:00 P.M. THURSDAY AND 7:00 A.M. MONDAY.
4. FOR MEMORIAL DAY, BETWEEN THE HOURS OF 6:00 P.M. FRIDAY TO 7:00 A.M. TUESDAY.
5. FOR INDEPENDENCE DAY, BETWEEN THE HOURS OF 6:00 P.M. THE DAY BEFORE INDEPENDENCE DAY AND 7:00 A.M. THE DAY AFTER INDEPENDENCE DAY.

IF INDEPENDENCE DAY IS ON A FRIDAY, SATURDAY, SUNDAY OR MONDAY THEN BETWEEN THE HOURS OF 6:00 P.M. THE THURSDAY BEFORE INDEPENDENCE DAY AND 7:00 A.M. THE TUESDAY AFTER INDEPENDENCE DAY.
6. FOR LABOR DAY, BETWEEN THE HOURS OF 6:00 P.M. FRIDAY AND 7:00 A.M. TUESDAY.
7. FOR THANKSGIVING DAY, BETWEEN THE HOURS OF 6:00 P.M. TUESDAY TO 7:00 A.M. MONDAY.
8. FOR CHRISTMAS, BETWEEN THE HOURS OF 6:00 P.M. THE FRIDAY BEFORE THE WEEK OF CHRISTMAS DAY AND 7:00 A.M. THE FOLLOWING TUESDAY AFTER THE WEEK OF CHRISTMAS.

C) DO NOT CONDUCT ANY HAULING OPERATIONS AGAINST THE FLOW OF TRAFFIC OF AN OPEN TRAVELWAY UNLESS THE HAULING OPERATION IS PROTECTED BY BARRIER OR GUARDRAIL OR AS DIRECTED BY THE ENGINEER.

LANE AND SHOULDER CLOSURE REQUIREMENTS

- D) REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED, OR AS DIRECTED BY THE ENGINEER.
- E) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.
- F) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO A DIVIDED FACILITY AND WITHIN 10 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

- G) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN A LANE OF TRAVEL OF AN UNDIVIDED OR DIVIDED FACILITY, CLOSE THE LANE ACCORDING TO THE TRAFFIC CONTROL PLANS, ROADWAY STANDARD DRAWINGS OR AS DIRECTED BY THE ENGINEER. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL LANE.
- H) DO NOT WORK SIMULTANEOUSLY WITHIN 15 FT ON BOTH SIDES OF AN OPEN TRAVELWAY, RAMP OR LOOP WITHIN THE SAME LOCATION UNLESS PROTECTED WITH GUARDRAIL OR BARRIER.
- I) DO NOT INSTALL MORE THAN ONE LANE CLOSURE, IN ANY ONE DIRECTION, ON NC 87.

PAVEMENT EDGE DROP OFF REQUIREMENTS

J) BACKFILL AT A 6:1 SLOPE UP TO THE EDGE AND ELEVATION OF EXISTING PAVEMENT IN AREAS ADJACENT TO AN OPENED TRAVEL LANE THAT HAS AN EDGE OF PAVEMENT DROP-OFF AS FOLLOWS:

BACKFILL DROP-OFFS THAT EXCEED 2 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS OF 45 MPH OR GREATER.

BACKFILL DROP-OFFS THAT EXCEED 3 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS LESS THAN 45 MPH.

BACKFILL WITH SUITABLE COMPACTED MATERIAL, AS APPROVED BY THE ENGINEER, AT NO EXPENSE TO THE DEPARTMENT.

K) DO NOT EXCEED A DIFFERENCE OF 2 INCHES IN ELEVATION BETWEEN OPEN LANES OF TRAFFIC FOR NOMINAL LIFTS OF 1.5 INCHES. INSTALL ADVANCE WARNING "UNEVEN LANES" SIGNS (W8-11) 500 FT IN ADVANCE AND A MINIMUM OF EVERY HALF MILE THROUGHOUT THE UNEVEN AREA.

TRAFFIC PATTERN ALTERATIONS

L) NOTIFY THE ENGINEER TWENTY ONE (21) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

SIGNING

- M) INSTALL ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.
- N) PROVIDE PERMANENT SIGNING.
- O) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.

TRAFFIC CONTROL DEVICES

- P) SPACE CHANNELIZING DEVICES IN WORK AREAS NO GREATER THAN TWICE THE POSTED SPEED LIMIT (MPH), EXCEPT 10 FT ON-CENTER IN RADII, AND 3 FT OFF THE EDGE OF AN OPEN TRAVELWAY, WHEN LANE CLOSURES ARE NOT IN EFFECT. WHEN SKINNY DRUMS ARE ALLOWED, REFER TO SECTION 1180 OF STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES OR AS SHOWN IN THE PLANS.
- Q) PLACE TYPE III BARRICADES, WITH "ROAD CLOSED" SIGN R11-2 ATTACHED, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY.
- R) PLACE ADDITIONAL SETS OF THREE CHANNELIZING DEVICES PERPENDICULAR TO THE EDGE OF TRAVELWAY ON 500 FT CENTERS WHEN UNOPENED LANES ARE CLOSED TO TRAFFIC.

PAVEMENT MARKINGS AND MARKERS

S) INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE AS FOLLOWS:

ROAD NAME	MARKING	MARKER
ALL ROADS	THERMOPLASTIC	SNOWPLOWABLE

T) INSTALL TEMPORARY PAVEMENT MARKINGS AND TEMPORARY PAVEMENT MARKERS ON INTERIM LAYERS OF PAVEMENT AS FOLLOWS:

ROAD NAME	MARKING	MARKER
ALL ROADS	PAINT	NONE

U) PLACE ONE APPLICATION OF PAINT FOR TEMPORARY TRAFFIC PATTERNS. PLACE A SECOND APPLICATION OF PAINT SIX (6) MONTHS AFTER THE INITIAL APPLICATION AND EVERY SIX MONTHS AS DIRECTED BY THE ENGINEER.


V) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.

W) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS BY THE END OF EACH DAY'S OPERATION.

X) TRACE THE EXISTING AND PROPOSED MONOLITHIC ISLAND LOCATIONS WITH PROPER COLOR PAVEMENT MARKINGS PRIOR TO REMOVAL AND INSTALLATION. PLACE DRUMS TO DELINEATE ANY EXISTING AND PROPOSED MONOLITHIC ISLANDS AFTER REMOVAL AND BEFORE INSTALLATION

MISCELLANEOUS

Y) POLICE MAY BE USED TO MAINTAIN TRAFFIC THROUGH THE WORK AREA AND/OR INTERSECTIONS, AS DIRECTED BY THE ENGINEER.

APPROVED: _____ DATE: _____ 	<h3 style="margin: 0;">PROJECT NOTES</h3>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">REVISIONS</th> </tr> </thead> <tbody> <tr> <td style="width: 50%;"> </td> <td style="width: 50%;"> </td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </tbody> </table>	REVISIONS							
REVISIONS										
SCALE: NONE DATE: _____ DWG. BY: _____ DESIGN BY: _____ REVIEWED BY: _____										

PHASING

PHASE 1
(MEDIAN U-TURNS)

STEP 1:
INSTALL WORK ZONE ADVANCE WARNING SIGNS AS SHOWN ON SHEET TCP-7. WHEN NO WORK IS BEING CONDUCTED FOR A PERIOD LONGER THAN ONE WEEK, REMOVE OR COVER ALL ADVANCE WORK ZONE SIGNS, AS DIRECTED BY THE ENGINEER, AT NO COST TO THE DEPARTMENT.

STEP 2:
USING ROADWAY STANDARD DRAWING # 1101.02 (SHEET 3 OF 9), DEMOLISH NC 87 NORTHBOUND AND SOUTHBOUND LEFT-TURN LANES FROM STA. 35+10+/- TO STA. 47+60+/-, INSTALL DRAINAGE AT STA. 53+00+/-, AND CONSTRUCT UP TO THE EDGE AND ELEVATION OF EXISTING PAVEMENT PROPOSED LEFT-TURN LANES, MEDIAN U-TURNS AND BULB-OUTS AT STA. 12+65+/- TO STA. 20+30+/-, AND STA. 45+00+/- TO 58+40+/- . SEE SHEET TCP-4.

NOTE: AT THE END OF EACH WORK DAY, RETURN TRAFFIC TO TWO-WAY, FOUR-LANE TRAFFIC PATTERN. INSTALL DRUMS AND TYPE III BARRICADES TO KEEP WORK AREA CLOSED TO TRAFFIC. KEEP MEDIAN CROSSOVERS CLOSED WHILE CONSTRUCTING BULB-OUTS.

STEP 3:
USING ROADWAY STANDARD DRAWING # 1101.02 (SHEET 3 OF 9), INSTALL PERMANENT SIGNS AND APPLY TEMPORARY PAVEMENT MARKINGS (PAINT) FROM STA. 12+65 TO STA. 20+30 AND FROM STA.35+10 TO STA.58+40 AS SHOWN ON PAVEMENT MARKING PLANS.

STEP 4:
OPEN CROSSOVERS TO TRAFFIC.

PHASE 2
(NC 87/SR 2233 AND NC 87/SR 2261/SR 2235 INTERSECTIONS)

STEP 1:
USING ROADWAY STANDARD DRAWING # 1101.02 (SHEET 3 OF 9), CONSTRUCT UP TO THE EDGE AND ELEVATION OF EXISTING PAVEMENT PROPOSED MEDIAN CROSS-OVERS AND WIDENINGS ON -L- AND -Y- LINES FROM STA. 20+30+/- TO STA. 30+50+/- AND FROM STA. 65+00+/- TO STA. 75+20+/- . SEE SHEET TCP-5.

NOTE: AT THE END OF EACH WORK DAY, RETURN TRAFFIC TO TWO-WAY, FOUR-LANE TRAFFIC PATTERN. INSTALL DRUMS AND TYPE III BARRICADES TO KEEP WORK AREA CLOSED TO TRAFFIC. KEEP MEDIAN CROSSOVERS CLOSED WHILE CONSTRUCTING WIDENINGS.

STEP 2:
USING ROADWAY STANDARD DRAWING # 1101.02 (SHEET 3 OF 9), INSTALL PERMANENT SIGNS AND APPLY TEMPORARY PAVEMENT MARKINGS (PAINT) FROM STA. 20+30 TO STA. 30+50 AND FROM STA.65+00 TO STA.75+20 AS SHOWN ON PAVEMENT MARKING PLANS.

STEP 3: OPEN INTERSECTIONS TO TRAFFIC.

STEP 4:
CONSTRUCT -Y- LINES CONCRETE ISLANDS WHILE MAINTAINING TRAFFIC .

PHASE 3
(NC 87/SR 2245)

STEP 1:
USING ROADWAY STANDARD DRAWING # 1101.02 (SHEET 3 OF 9) DEMOLISH EXISTING SOUTHBOUND LEFT TURN LANE FROM STA. 90+45 TO STA. 96+40 AND CONSTRUCT UP TO THE EDGE AND ELEVATION OF EXISTING PAVEMENT, PROPOSED MEDIAN CROSS-OVER AND WIDENING AT -L- AND -Y- LINES FROM STA. 83+50+/- TO STA. 96+40+/- . SEE SHEET TCP-6.

NOTE: AT THE END OF EACH WORK DAY, RETURN TRAFFIC TO TWO-WAY, FOUR-LANE TRAFFIC PATTERN. INSTALL DRUMS AND TYPE III BARRICADES TO KEEP WORK AREA CLOSED TO TRAFFIC. KEEP MEDIAN CROSSOVER CLOSED WHILE CONSTRUCTING WIDENING.


STEP 2:
USING ROADWAY STANDARD DRAWING # 1101.02 (SHEET 3 OF 9), INSTALL PERMANENT SIGNS AND APPLY TEMPORARY PAVEMENT MARKINGS (PAINT) FROM STA. 83+50 TO STA. 96+40 AS SHOWN ON PAVEMENT MARKING PLANS.

STEP 3: OPEN INTERSECTION TO TRAFFIC.


STEP 4:
CONSTRUCT -Y- LINE CONCRETE ISLAND WHILE MAINTAINING TRAFFIC.

STEP 5:
USING ROADWAY STANDARD DRAWING # 1101.02 (SHEET 3 OF 9) INSTALL FINAL LAYER OF SURFACE COURSE, AND APPLY PERMANENT PAVEMENT MARKINGS AND MARKERS THROUGHOUT THE LENGTH OF THE PROJECT.

STEP 6:
OPEN NC 87 TO FINAL TRAFFIC PATTERN.

APPROVED: _____ DATE: _____ 	<h2 style="margin: 0;">PHASING</h2>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="font-size: small;">SCALE:</td> <td style="text-align: center;">NONE</td> </tr> <tr> <td style="font-size: small;">DATE:</td> <td> </td> </tr> <tr> <td style="font-size: small;">DWG. BY:</td> <td> </td> </tr> <tr> <td style="font-size: small;">DESIGN BY:</td> <td> </td> </tr> <tr> <td style="font-size: small;">REVIEWED BY:</td> <td> </td> </tr> </table>	SCALE:	NONE	DATE:		DWG. BY:		DESIGN BY:		REVIEWED BY:	
SCALE:	NONE											
DATE:												
DWG. BY:												
DESIGN BY:												
REVIEWED BY:												
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left;">REVISIONS</th> </tr> <tr> <td> </td> </tr> <tr> <td> </td> </tr> <tr> <td> </td> </tr> </table>	REVISIONS									
REVISIONS												


5/20/2008 Control\TCPGeneralNotes.dgn
ARCADIS G & M




NOTE: REFER TO RSD 110102 SHEET 3 OF 9 (TEMPORARY LANE CLOSURE) FOR INSTALLATION OF TRAFFIC CONTROL DEVICES

APPROVED: _____ DATE: _____	PHASE I		
	SCALE: NONE		
	DATE: _____		REVISIONS
	DWG. BY: _____		_____
	DESIGN BY: _____		_____
REVIEWED BY: _____	_____	CADD FILE	


5/20/2008 Control\TCP4.dgn
ARCADIS G & M



NOTE: REFER TO RSD 1101.02 SHEET 3 OF 9 (TEMPORARY LANE CLOSURE) FOR INSTALLATION OF TRAFFIC CONTROL DEVICES



APPROVED:	DATE:	PHASE II									
SCALE:	NONE										
DATE:											
DWG. BY:											
DESIGN BY:											
REVIEWED BY:		<table border="1"> <thead> <tr> <th colspan="2">REVISIONS</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </tbody> </table>		REVISIONS							
REVISIONS											



NOTE: REFER TO RSD 1101.02 SHEET 3 OF 9 (TEMPORARY LANE CLOSURE) FOR INSTALLATION OF TRAFFIC CONTROL DEVICES


APPROVED: _____	DATE: _____	PHASE III		
	SCALE: NONE			
	DATE: _____			REVISIONS
	DWG. BY: _____			_____
	DESIGN BY: _____			_____
REVIEWED BY: _____	_____	CADD FILE	_____	

5/20/2008 Control\TCP6.dgn
ARCADIS & M

ADVANCED WORK ZONE WARNING SIGNING FOR FREEWAYS (4 LANES OR GREATER)


PROJ. REFERENCE NO.	SHEET NO.
W-5006	TCP-7

DETAIL A




LEGEND	
	STATIONARY SIGN
▶	DIRECTION OF TRAFFIC FLOW

DETAIL B




NOTE: SIGN NOT REQUIRED IF ADVANCE WARNING SIGNS HAVE BEEN PLACED ALONG -Y- LINE THAT RAMP INTERSECTS. IF CONSTRUCTION LIMITS ARE AT END OF RAMP, PLACE SIGN AT END OF RAMP.

DETAIL C



DETAIL D



GENERAL NOTES

- USE FLUORESCENT ORANGE SHEETING (TYPE VII OR HIGHER) ON ALL ADVANCED WORK ZONE SIGNS.
- DO NOT INSTALL ADVANCE WARNING SIGNS MORE THAN 3 DAYS PRIOR TO BEGINNING OF WORK.
- SIGNS SHOWN ARE REQUIRED FOR WORK ZONES THAT WILL REMAIN IN EFFECT OVERNIGHT. FOR SHORT-TERM DAILY MAINTENANCE TYPE OPERATIONS, THIS SIGNING APPLICATION IS OPTIONAL; MAY USE ONLY APPLICABLE ROADWAY STANDARD DRAWINGS INSTEAD. HOWEVER, IF THIS SIGNING APPLICATION IS USED, SIGNS MAY BE PORTABLE MOUNTED.
- ALL SIGN SPACING DIMENSIONS ARE APPROXIMATE, FIELD ADJUST AS NECESSARY OR AS DIRECTED.
- USE 3LB STEEL U-CHANNEL POST OR 4" X 4" WOOD POST FOR ALL WORK ZONE SIGNS. 3LB STEEL U-CHANNEL POSTS MUST MEET THE REQUIREMENTS OF STANDARD SPECIFICATION SECTION 1094-1(B), MAY BE GALVANIZED STEEL, OR MAY BE PAINTED GREEN BY THE POST MANUFACTURER. SQUARE STEEL TUBING POSTS HAVING EQUIVALENT STRENGTH OF THE 3 LB STEEL U-CHANNEL POST ARE ALSO ACCEPTABLE FOR USE. ERECT SIGNS PER ROADWAY STANDARD DRAWING 1110.01. PAYMENT FOR WOOD POSTS, 3LB STEEL U-CHANNEL AND SQUARE STEEL TUBING POSTS WITH SIGNS WILL BE MADE ACCORDING TO STANDARD SPECIFICATION "WORK ZONE SIGNS" SECTION 1110.
- WHEN NECESSARY, USE SPLICING IN ACCORDANCE WITH ROADWAY STANDARD DRAWING NO. 1110.01. REMOVE ENTIRE POST WHEN REMOVING SIGNS WITH SPLICED POSTS.
- DO NOT BACK BRACE SIGN SUPPORTS.

APPROVED: _____	DATE: _____	ADVANCE WORKZONE SIGNS	
	SCALE: NONE		REVISIONS
	DATE: _____		
	DWG. BY: _____		
	DESIGN BY: _____		
REVIEWED BY: _____		CADD FILE	

5/20/2008 Control\TCPGeneralNotes.dgn
A:\TCF\TC & M
ARCADIS G & M

SP 03353

<p>SIGN NUMBER: SP-03353 TYPE: A QUANTITY: 1 SIGN WIDTH: 4'-0" HEIGHT: 4'-0" TOTAL AREA: 16.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0.59" WIDTH: 0.75" RADII: 1.38" NO. Z BARS: N/A LENGTH: N/A</p>	<p>BACKG COLOR: Fluorescent Orange COPY COLOR: Black</p> <table border="1"> <tr> <th>SYMBOL</th> <th>X</th> <th>Y</th> <th>WID</th> <th>HT</th> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table>	SYMBOL	X	Y	WID	HT																																				<p>DESIGN BY: CL DOWNEY CHECKED BY: CHECKED PROJECT ID: ALL PROJECTS DIV: DIV STD #: W20-1 DATE: Aug 20, 2003</p>
SYMBOL	X	Y	WID	HT																																						

USE NOTES: 2, 4

- Legend and border shall be direct applied Type VII reflective sheeting.
- Legend and border shall be direct applied non-reflective sheeting.
- Shields shall be Type VII reflective sheeting on 0.032" (0.8mm) aluminum and demountable.
- Background shall be Type VII reflective sheeting.
- Background shall be Type I reflective sheeting.
- Center arrow(s) vertically on sign.
- Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

Letter positions											Series/Size
Letter spacings are to start of next letter											Text Length
	B	E	G	I	N						C7
22.4	5.3	4.6	5.4	2.5	3.8	22.4					21.6
	R	O	A	D							C7
23.4	5	5.2	5.6	3.8	23.4						19.6
	W	O	R	K							C7
22.6	6.4	5.6	5.2	4	22.6						21.2

Spacing Factor is 1 unless specified otherwise

GENERAL NOTES FOR THE "BEGIN ROAD WORK" SIGN

-SIGN SP-03353 "BEGIN ROAD WORK" ONLY APPLIES TO FULL CONTROL AND PARTIAL CONTROL OF ACCESS ROADWAYS

-WHEN USED, INSTALL SIGN SP-03353 "BEGIN ROAD WORK" ACCORDING TO DETAIL A ON SHEET TCP-7.

APPROVED: _____	DATE: _____	<p>DETAIL DRAWING FOR ADVANCED WORK ZONE WARNING SIGN DESIGNS</p>	
	SCALE: NONE		
	DATE: _____		
	DWG. BY: _____		
	DESIGN BY: _____		
REVIEWED BY: _____	REVISIONS		