


PROJECT: B-4196

STATE	PROJECT NO.	SHEET NO.
N.C.	B-4196	Sig. 1
F.A. PROJ. NO.		
PROJECT ID. NO.		




VICINITY MAP

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

McDOWELL COUNTY

LOCATION: Bridge No. 238 over Garden Creek on SR 1506, Garden Creek Road in Marion

TYPE OF WORK: TRAFFIC SIGNALS



INDEX OF PLANS

SHEET NO.	SIGNAL INVENTORY NO.	LOCATION /DESCRIPTION
SIG. 1	N/A	Title Sheet
SIG. 2-3	13-0193	US 70 at US 70/221 Bus./NC 226 and US 221 Bus./NC 226
SIG. 4-6	N/A	Inductive Detection Loops Details

LEGEND


##-#### SIGNAL INVENTORY NUMBER

NCDOT CONTACTS:

INTELLIGENT TRANSPORTATION SYSTEMS & SIGNALS UNIT

Timothy J. Williams, PE - S&G Contracts Engineer
George C. Brown, PE - Signal Equipment Design Engineer




Prepared in the Offices of:



750 N. Greenfield Parkway, Garner, NC 27529

EDI MODEL 2010ECL-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



- NOTES:
- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
 - Make sure jumpers SEL2-SEL5 are present on the monitor board.

- ### NOTES
- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
 - Ensure that Red Enable is active at all times during normal operation. To prevent Red Failures on unused monitor channels, tie unused red monitor inputs 1,3,7,8, 10,11,12,13,14,15 & 16 to load switch AC+ per the cabinet manufacturer's instructions.
 - Program phases 2 and 6, on the controller unit, for Start Up In Green.
 - Enable Simultaneous Gap-Out, on the controller unit, for all phases.

BACKUP PROTECTION NOTE

(program controller as shown below)

From Main Menu press '2' (Phase Control), then '1' (Phase Control Functions). Program phase 2 for 'Backup Protect'. Make sure the Red Revert times shown on the Signal Design Plans are programmed in the 'Phase Timing' menu.

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S2P	S3	S4	S4P	S5	S6	S6P	S7	S8	S8P	S9	S10	S11	S12	S13	S14
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	** OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22	NU	NU	41	63	NU	51,52	61,62 63	NU	NU	NU	42,43	NU	NU	NU	NU	NU
RED		128							134									
YELLOW		129							135									
GREEN		130							136									
RED ARROW					101			131					A121					
YELLOW ARROW					102	102		132					A122					
GREEN ARROW					103	103		133					A123					

NU = NOT USED
** Rework OLA to flash on flash unit #2 circuit #2

EQUIPMENT INFORMATION

CONTROLLER.....CONTRACTOR SUPPLIED 2070L
CABINETCONTRACTOR SUPPLIED 332
SOFTWAREECONOLITE OASIS
CABINET MOUNT.....BASE
OUTPUT FILE POSITIONS..18 (12-STD, 6 AUX)
LOAD SWITCHES USED.....S2,S4,S5,S6,S9
PHASES USED.....2,4,5,6
OVERLAP "A".....4+5

OVERLAP PROGRAMMING DETAIL

(program controller as shown below)

FROM MAIN MENU PRESS '8' (OVERLAPS), THEN '1' (VEHICLE OVERLAP SETTINGS).

PAGE 1: VEHICLE OVERLAP 'A' SETTINGS
 PHASE: 12345678910111213141516
 VEH OVL PARENTS: XX
 VEH OVL NOT VEH: :
 VEH OVL NOT PED: :
 VEH OVL GRN EXT: :
 STARTUP COLOR: - RED - YELLOW - GREEN
 FLASH COLORS: - RED - YELLOW - GREEN
 SELECT VEHICLE OVERLAP OPTIONS: (Y/N)
 FLASH YELLOW IN CONTROLLER FLASH?...N
 GREEN EXTENSION (0-255 SEC).....0
 YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0
 RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0
 OUTPUT AS PHASE # (0=NONE, 1-16)....0

OVERLAP PROGRAMMING COMPLETE

INPUT FILE POSITION LAYOUT

(front view)

FILE "I"	1	2	3	4	5	6	7	8	9	10	11	12	13	14
U	FS	2A												FS
L	2B					4A								DC ISOLATOR
U						NOT USED								ST
L														DC ISOLATOR
U	5A	5C	6A	6C										
L	5B	5D	6B	NOT USED										

EX. : 1A, 2A, ETC. = LOOP NO.'S
FS = FLASH SENSE
ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	INPUT ASSIGNMENT NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND	FULL TIME DELAY	STRETCH TIME	DELAY TIME
2A	TB2-5,6	I2U	39	1	2	2	Y	Y		1.9	
2B	TB2-7,8	I2L	43	5	12	2	Y	Y			
4A	TB4-9,10	I6U	41	3	4	4	Y	Y			3
5A	TB3-1,2	J1U	55	17	5	5	Y	Y			
5B	TB3-3,4	J1L	55	17	5	5	Y	Y			
5C	TB3-5,6	J2U	40	2	6	5	Y	Y			10
5D	TB3-7,8	J2L	44	6	16	5	Y	Y			15
6A	TB3-9,10	J3U	64	26	36	6	Y	Y		1.6	
6B	TB3-11,12	J3L	77	39	46	6	Y	Y			
6C	TB5-1,2	J4U	48	10	26	6	Y	Y			

INPUT FILE POSITION LEGEND: J2L
FILE J
SLOT 2
LOWER

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 13-0193
DESIGNED: April 2008
SEALED: 4-28-08
REVISED: N.A.

Signal Upgrade

ELECTRICAL AND PROGRAMMING DETAILS FOR:

Prepared in the Office of:

 NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
 750 N. Greenfield Parkway, Garner, NC 27529

US 70 at 221 Business/NC 226/US 70 and US 221 Business/NC 226

Division 13 McDowell County Marion

PLAN DATE: 4-29-08 REVIEWED BY: D.T. Joyce

PREPARED BY: D.H. Spaulding REVIEWED BY:

REVISIONS

INIT. DATE

Signature: DATE: 4/30/08

SEAL: NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 022013 GEORGE C. BROWN

SIG. INVENTORY NO. 13-0193

13-0193-2008-08107
s:\w\ts\sig\01\sew\work\p\08\sig\g_mon\spauld\img\in-progress\130193_sml_e_2008xxx.dgn
spauld\img

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

5-07

ENGLISH DETAIL DRAWING FOR
INDUCTIVE DETECTION LOOPS




SHEET 1 OF 3
1725D01

CONVENTIONAL 4-SIDED LOOP


SAW CUT OPTIONS

SAW SLOT DEPTH CHART

DEPTH (IN)	NO. OF WIRE TURNS				
	2	3	4	5	6
CONCRETE	2.0	2.0	2.5	2.5	3.0
ASPHALT	2.0	2.5	3.0	3.0	3.0



LOOP WINDING METHOD




STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

5-07

ENGLISH DETAIL DRAWING FOR
INDUCTIVE DETECTION LOOPS

SHEET 1 OF 3
1725D01

LOOP WIRE TWISTING METHOD






NOTES

- OVERLAP SAW CUTS AT CORNERS AND INTERSECTION POINTS TO ENSURE UNIFORM SAW SLOT DEPTH.
- MAINTAIN 12" SPACING BETWEEN LOOP WIRE TAIL SECTIONS.
- WIRE LOOPS CONNECTED TO THE SAME DETECTOR CHANNEL IN SERIES.
- LOCATE LOOPS IN CENTER OF LANES UNLESS OTHERWISE SHOWN ON PLANS OR APPROVED BY ENGINEER.


QUADRUPOLE LOOP

SAW CUT OPTIONS



DEPTH IS 2.5" FOR CONCRETE AND 3.0" FOR ASPHALT

LOOP WINDING METHOD



See Plate for Title

Prepared in the Offices of:

750 N. Greenfield Parkway
Gartner, NC 27529

SEAL

Milton I. Dean 9/5/07
SIGNATURE DATE

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.


5-07

ENGLISH DETAIL DRAWING FOR
INDUCTIVE DETECTION LOOPS
LOOP WIRE DETAILS


SHEET 2 OF 3
1725D01

LOOP WIRE SPLICE POINT DETAILS

LOOP WIRE AT JUNCTION BOX



LOOP WIRE AT POLE




NOTE


SPLICE ALL LOOP WIRE TAIL SECTIONS/LEAD-IN CABLE IN JUNCTION BOXES OR APPROVED CONDULETS.

LOOP WIRE PAVEMENT EDGE DETAILS

LOOP WIRE AT CURB & GUTTER SECTION



LOOP WIRE AT PAVEMENT SECTION



NOTES

1. DO NOT EXCAVATE UNDER CURB AND GUTTER SECTIONS FOR CONDUIT INSTALLATION.
2. TWIST LOOP WIRE TAIL SECTIONS FROM WHERE LOOP WIRE TAIL LEAVES SAW CUT TO JUNCTION BOX, INCLUDING THROUGH CONDUIT.
3. BEFORE SEALING LOOPS, INSTALL DUCT SEAL WHERE LOOP WIRE TAIL SECTION LEAVES SAW CUT IN PAVEMENT AND AT ENTRANCE OF CONDUIT TO JUNCTION BOX.

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

5-07

ENGLISH DETAIL DRAWING FOR
INDUCTIVE DETECTION LOOPS
LOOP WIRE DETAILS

SHEET 2 OF 3
1725D01

See Plate for Title

Prepared in the Offices of:

750 N. Greenfield Parkway
Garner, NC 27529

SEAL

ENGINEER
MILTON I. DEAN

Milton I. Dean 9/5/07
SIGNATURE DATE


STATE OF NORTH CAROLINA
 DEPT. OF TRANSPORTATION
 DIVISION OF HIGHWAYS
 RALEIGH, N.C.

5-07


ENGLISH DETAIL DRAWING FOR
INDUCTION DETECTION LOOPS
 SPLICING FOR LEAD-IN CABLE AND LOOP WIRE

SHEET 3 OF 3
1725D01

STEP 1. STRIP LOOP WIRE AND LEAD-IN CABLE




STEP 2. CONNECT AND SOLDER




BOND SHIELD DRAIN WIRE AT SPLICE SECTIONS (DO NOT GROUND)


LOOP WIRE AND LEAD-IN CABLE CONNECTION DETAILS



STEP 3. INSULATE EACH SOLDER JOINT SEPARATELY



STEP 4. ENVIRONMENTALLY PROTECT SPLICE



STATE OF NORTH CAROLINA
 DEPT. OF TRANSPORTATION
 DIVISION OF HIGHWAYS
 RALEIGH, N.C.

5-07

ENGLISH DETAIL DRAWING FOR
INDUCTIVE DETECTION LOOPS
 SPLICING FOR LEAD-IN CABLE AND LOOP WIRE

SHEET 3 OF 3
1725D01

See Plate for Title

Prepared in the Offices of:

750 N. Greenfield Parkway
 Garner, NC 27529

SEAL

Milton I. Dean 9/5/07
 SIGNATURE DATE