


09/08/99

TIP PROJECT: B-3677

CONTRACT: C201969

See Sheet 1-A For Index of Sheets



VICINITY MAP



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

MECKLENBURG COUNTY

**LOCATION: BRIDGE NO. 36 OVER IRVINS CREEK ON SR 3135
(LEBANON ROAD)**

TYPE OF WORK: GRADING, DRAINAGE, PAVING, & STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-3677	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
33220.1.1	BRSTP-3135(4)	PE	
33220.2.1	BRSTP-3135(4)	R/W, UTILITIES	
33220.3.1	BRSTP-3135(4)	CONST.	



DESIGN DATA

ADT 2009 =	7,525
ADT 2029 =	13,025
DHV =	11 %
D =	55 %
T =	6 % *
V =	40 MPH

* (TTST 1% + DUAL 5%)

FUNCTIONAL CLASSIFICATION = URBAN COLLECTOR

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT B-3677 =	0.171 MI
LENGTH STRUCTURE TIP PROJECT B-3677 =	0.018 MI
TOTAL LENGTH TIP PROJECT B-3677 =	0.189 MI

PLANS PREPARED BY:
TGS ENGINEERS
975 WALNUT STREET
CARY, NC 27511
PH (919) 319-8850

2006 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE:
NOVEMBER 28, 2007

LETTING DATE:
AUGUST 18, 2008

NCDOT CONTACT:

PLANS PREPARED FOR:
DIVISION OF HIGHWAYS
1000 Birch Ridge Dr.
Raleigh, NC 27610

CHARLES L. FLOWE, PE
PROJECT ENGINEER

W. CRAIG PARKER, PE
PROJECT DESIGN ENGINEER

B. DOUG TAYLOR, PE
PROJECT ENGINEER - ROADWAY DESIGN

HYDRAULICS ENGINEER

Charles L. Flowe
SIGNATURE: 6/19/2009


ROADWAY DESIGN ENGINEER

W. Craig Parker
SIGNATURE: 5/20/08

**DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA**

Ant M. Miller P.E.
STATE HIGHWAY DESIGN ENGINEER

\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$DCN\$\$\$\$\$
\$\$\$\$\$USERNAME\$\$\$\$\$

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

INDEX OF SHEETS

SHEET NO.	SHEET
1	Title Sheet
1-A	Index of Sheets, General Notes, and List of Standards
1-B	Conventional Symbols
1-C & 1-D	Survey Control Sheets
2	Pavement Schedule, Typical Sections, Detail of Asphalt Wearing Surface on Cored Slab Bridge & Wedging Detail
2-A	Temporary Pavement Detail
2-B thru 2-M	Temporary Shoring Details
2-N	Bridge Approach Fills - Cored Slab & Box Beam Bridges
2-O	Temporary Steel Plate Cover
3	Summary of Quantities
3-A	Summary of Earthwork, Guardrail, and Asphalt Pavement Removal
3-B	Summary of Drainage
4	Plan Sheet
5	Profile Sheet
TCP-1 thru TCP-9	Traffic Control Plans
PMP-1 thru PMP-2	Pavement Marking Plans
EC-1 thru EC-5	Erosion Control Plans
SIGN-1 thru SIGN-3	Signing Plans
UC-1 thru UC-6	Utility Construction Plans
UO-1 thru UO-2	Utilities By Others Plans
X-SUM	Earthwork Volume Summary
X-1 thru X-10	Cross Sections
S-1 thru S-37	Structure Plans

GENERAL NOTES

2006 SPECIFICATIONS
EFFECTIVE: 07-18-06
REVISED: 07-30-08

GRADING AND SURFACING OR RESURFACING AND WIDENING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. WHERE NO GRADE LINES ARE SHOWN, THE PROFILES SHOWN DENOTE THE TOP ELEVATION OF THE EXISTING PAVEMENT ALONG THE CENTER LINE OF SURVEY ON WHICH THE PROPOSED RESURFACING WILL BE PLACED. GRADE LINES MAY BE ADJUSTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01.

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

UNDERDRAINS:

UNDERDRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 815.03 AT LOCATIONS DIRECTED BY THE ENGINEER.

STREET TURNOUT:

STREET RETURNS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 848.04 USING THE RADII NOTED ON PLANS.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC NOT SHOWN ON THE PLANS WILL BE PAID FOR AT THE CONTRACT PRICE FOR "TEMPORARY SHORING".

END BENTS:

THE ENGINEER SHALL CHECK THE STRUCTURE END BENT PLANS, DETAILS, AND CROSS-SECTION PRIOR TO SETTING OF THE SLOPE STAKES FOR THE EMBANKMENT OR EXCAVATION APPROACHING A BRIDGE.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE CHARLOTTE-MECKLENBURG UTILITIES (WATER & SEWER), DUKE ENERGY, AT&T, PIEDMONT NATURAL GAS, & TIME WARNER.

ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS, EXCEPT AS SHOWN ON THE PLANS.

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY OTHERS.

WHEELCHAIR RAMPS:

WHEELCHAIR RAMPS ARE SHOWN ON THE PLANS AT APPROXIMATE LOCATIONS. THE CONSTRUCTION OF ALL WHEELCHAIR RAMPS SHALL BE IN ACCORDANCE WITH STD. NO. 848.05

STANDARD DRAWINGS

2006 ROADWAY ENGLISH STANDARD DRAWINGS
EFF. 07-18-06
REV. 01-02-07

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch - N. C. Department of Transportation - Raleigh, N. C., Dated July 18, 2006 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO.	TITLE
DIVISION 2 - EARTHWORK	
200.02	Method of Clearing - Method II
225.02	Guide for Grading Subgrade - Secondary and Local
225.04	Method of Obtaining Superelevation - Two Lane Pavement
DIVISION 3 - PIPE CULVERTS	
300.01	Method of Pipe Installation - Method 'A'
310.02	Parallel Pipe End Section - Precast Concrete Section for 15" to 24" Pipe
310.04	Parallel Pipe End Section - Prefabricated Steel Section for 15" to 24" Pipe
310.10	Driveway Pipe Construction
DIVISION 5 - SUBGRADE, BASES AND SHOULDERS	
560.01	Method of Shoulder Construction - High Side of Superelevated Curve - Method I
DIVISION 6 - ASPHALT BASES AND PAVEMENTS	
654.01	Pavement Repairs
DIVISION 8 - INCIDENTALS	
815.03	Pipe Underdrain and Blind Drain
816.04	Markers for Drainage Structure and Concrete Pad
838.01	Concrete Endwall for Single and Double Pipe Culverts - 15" thru 48" Pipe 90 Skew
838.11	Brick Endwall for Single and Double Pipe Culverts - 15" thru 48" Pipe 90 Skew
838.80	Precast Endwalls - 12" thru 72" Pipe 90 Skew
840.00	Concrete Base Pad for Drainage Structures
840.01	Brick Catch Basin - 12" thru 54" Pipe
840.02	Concrete Catch Basin - 12" thru 54" Pipe
840.03	Frame, Grates and Hood - for Use on Standard Catch Basin
840.34	Traffic Bearing Junction Box - for Use with Pipes 42" and Under
840.36	Traffic Bearing Grated Drop Inlet - for Steel (840.37) Double Frame and Grates
840.37	Steel Grate and Frame
840.45	Precast Drainage Structure
840.46	Traffic Bearing Precast Drainage Structure
840.66	Drainage Structure Steps
840.71	Concrete and Brick Pipe Plug
846.01	Concrete Curb, Gutter and Curb & Gutter
848.01	Concrete Sidewalk
848.04	Street Turnout
848.05	Wheelchair Ramp - Curb Cut
862.01	Guardrail Placement
862.02	Guardrail Installation
862.03	Structure Anchor Units
876.01	Rip Rap in Channels
876.02	Guide for Rip Rap at Pipe Outlets
876.04	Drainage Ditches with Class 'B' Rip Rap

Note: Not to Scale

*S.U.E. = Subsurface Utility Engineering

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

CONVENTIONAL PLAN SHEET SYMBOLS

BOUNDARIES AND PROPERTY:

State Line	_____
County Line	_____
Township Line	_____
City Line	_____
Reservation Line	_____
Property Line	_____
Existing Iron Pin	○ EP
Property Corner	_____ X
Property Monument	□ EOM
Parcel/Sequence Number	②③
Existing Fence Line	-X-X-X-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	-WLB-
Proposed Wetland Boundary	-WLB-
Existing Endangered Animal Boundary	-EAB-
Existing Endangered Plant Boundary	-EPB-

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	○ S
Well	○ W
Small Mine	⋈
Foundation	□
Area Outline	□
Cemetery	↑
Building	□
School	□
Church	□
Dam	□

HYDROLOGY:

Stream or Body of Water	_____
Hydro, Pool or Reservoir	□
Jurisdictional Stream	JS
Buffer Zone 1	BZ 1
Buffer Zone 2	BZ 2
Flow Arrow	←
Disappearing Stream	→
Spring	○
Wetland	⋈
Proposed Lateral, Tail, Head Ditch	_____
False Sump	◇

RAILROADS:

Standard Gauge	_____
RR Signal Milepost	○ MILEPOST 35
Switch	□ SWITCH
RR Abandoned	_____
RR Dismantled	_____

RIGHT OF WAY:

Baseline Control Point	◇
Existing Right of Way Marker	△
Existing Right of Way Line	_____
Proposed Right of Way Line	_____ R/W
Proposed Right of Way Line with Iron Pin and Cap Marker	_____ R/W
Proposed Right of Way Line with Concrete or Granite Marker	_____ R/W
Existing Control of Access	○ CA
Proposed Control of Access	○ CA
Existing Easement Line	-E-
Proposed Temporary Construction Easement	-E-
Proposed Temporary Drainage Easement	-TDE-
Proposed Permanent Drainage Easement	-PDE-
Proposed Permanent Utility Easement	-PUE-
Proposed Permanent Easement with Iron Pin and Cap Marker	◇

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	_____
Existing Curb	_____
Proposed Slope Stakes Cut	-C-
Proposed Slope Stakes Fill	-F-
Proposed Wheel Chair Ramp	WCR
Existing Metal Guardrail	_____
Proposed Guardrail	_____
Existing Cable Guiderail	_____
Proposed Cable Guiderail	_____
Equality Symbol	⊕
Pavement Removal	XXXX

VEGETATION:

Single Tree	○
Single Shrub	○
Hedge	_____
Woods Line	_____
Orchard	_____
Vineyard	_____ Vineyard

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	_____ CONC
Bridge Wing Wall, Head Wall and End Wall	_____ CONC WW
MINOR:	
Head and End Wall	_____ CONC HW
Pipe Culvert	_____
Footbridge	_____
Drainage Box: Catch Basin, DI or JB	□ CB
Paved Ditch Gutter	_____
Storm Sewer Manhole	○ S
Storm Sewer	_____ S

UTILITIES:

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊗
Power Transformer	⊗
U/G Power Cable Hand Hole	□ PH
H-Frame Pole	●
Recorded U/G Power Line	_____ P
Designated U/G Power Line (S.U.E.*)	_____ P

TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Booth	□
Telephone Pedestal	□
Telephone Cell Tower	⊗
U/G Telephone Cable Hand Hole	□ PH
Recorded U/G Telephone Cable	_____ T
Designated U/G Telephone Cable (S.U.E.*)	_____ T
Recorded U/G Telephone Conduit	_____ TC
Designated U/G Telephone Conduit (S.U.E.*)	_____ TC
Recorded U/G Fiber Optics Cable	_____ T FO
Designated U/G Fiber Optics Cable (S.U.E.*)	_____ T FO

WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊗
Water Hydrant	⊕
Recorded U/G Water Line	_____
Designated U/G Water Line (S.U.E.*)	_____
Above Ground Water Line	_____ A/G Water

TV:

TV Satellite Dish	⊗
TV Pedestal	□
TV Tower	⊗
U/G TV Cable Hand Hole	□ PH
Recorded U/G TV Cable	_____ TV
Designated U/G TV Cable (S.U.E.*)	_____ TV
Recorded U/G Fiber Optic Cable	_____ TV FO
Designated U/G Fiber Optic Cable (S.U.E.*)	_____ TV FO

GAS:

Gas Valve	◇
Gas Meter	⊕
Recorded U/G Gas Line	_____ G
Designated U/G Gas Line (S.U.E.*)	_____ G
Above Ground Gas Line	_____ A/G Gas



SANITARY SEWER:

Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	_____ SS
Above Ground Sanitary Sewer	_____ A/G Sanitary Sewer
Recorded SS Forced Main Line	_____ FSS
Designated SS Forced Main Line (S.U.E.*)	_____ FSS

MISCELLANEOUS:

Utility Pole	●
Utility Pole with Base	□
Utility Located Object	○
Utility Traffic Signal Box	⊗
Utility Unknown U/G Line	_____ UTIL
U/G Tank; Water, Gas, Oil	□
A/G Tank; Water, Gas, Oil	□
U/G Test Hole (S.U.E.*)	⊕
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.
Temporary Shoring	_____

SURVEY CONTROL SHEET B-3677



NCDOT GPS STATION B3677-1
 LOCALIZED PROJECT COORDINATES
 N= 520365.445
 E= 1494826.102
 ELEV.= 672.57

NCDOT GPS STATION B3677-2
 LOCALIZED PROJECT COORDINATES
 N= 521104.105
 E= 1494767.865
 ELEV.= 694.70

BL POINT	DESC.	NORTH	EAST	ELEVATION	L STATION	OFFSET
8	BL-8	518451.8470	1495550.0060	691.68	OUTSIDE PROJECT LIMITS	
9	BL-9	519074.8860	1495367.6540	676.10	12+41.89	23.02 RT
917	BY1-917	519420.5160	1495233.5620	663.80	16+11.30	26.19 RT
10	BL-10	519729.2700	1495110.9610	656.48	19+42.66	41.28 RT
1	B3677-1	520365.4450	1494826.1020	672.57	26+40.63	23.92 LT
11	BL-11	520589.6940	1494791.8350	680.22	OUTSIDE PROJECT LIMITS	
2	B3677-2	521104.1050	1494767.8650	694.70	OUTSIDE PROJECT LIMITS	

BY1 POINT	DESC.	NORTH	EAST	ELEVATION	L STATION	OFFSET
12	BY1-12	519312.1230	1494914.9590	675.18	16+39.89	309.18 LT
5000	BY1-917	519420.5160	1495233.5620	663.80	16+11.30	26.19 RT

BY2 POINT	DESC.	NORTH	EAST	ELEVATION	L STATION	OFFSET
5001	B3677-1	520365.4450	1494826.1020	672.57	26+40.63	23.92 LT
13	BY2-13	520591.9960	1495264.0490	663.36	OUTSIDE PROJECT LIMITS	

BY3 POINT	DESC.	NORTH	EAST	ELEVATION	L STATION	OFFSET
14	BY3-14	520361.3120	1494460.5450	671.36	26+95.66	385.33 LT
5002	BL-11	520589.6940	1494791.8350	680.22	OUTSIDE PROJECT LIMITS	

DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "B3677-1"
 WITH NAD 83/95 STATE PLANE GRID COORDINATES OF
 NORTHING: 520365.445(ft) EASTING: 1494826.102(ft)
 THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT
 (GROUND TO GRID) IS: 0.99984624
 THE N.C. LAMBERT GRID BEARING AND
 LOCALIZED HORIZONTAL GROUND DISTANCE FROM
 "B3677-1" TO -L- STATION 15+00.00 IS
 S 21°58'00.3" E 1140.691
 ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
 VERTICAL DATUM USED IS NAVD 88

 BM1 ELEVATION = 656.50
 N 519727 E 1495117
 L STATION 19+38 46 RIGHT
 CITY OF CHARLOTTE SURVEY MARK S33-01

 BM2 ELEVATION = 653.31
 N 519684 E 1494813
 L STATION 20+24 248 LEFT
 RR SPIKE IN BASE OF 15' HAWTHORN

NOTES:

1. THE SITE CALIBRATION SHOWN IS BASED UPON A NETWORK TIED TO THE HARN (HIGH ACCURACY REFERENCE NETWORK) NAD 8395 ADJUSTMENT. THIS CALIBRATION WILL ALLOW THE END USER TO WORK WITHIN THE SAME COORDINATE SYSTEM WHEN USING RTK (REAL TIME KINEMATIC) GPS AND A LOCAL BASE STATION. IF ANOTHER SYSTEM SUCH AS VRS (VIRTUAL REFERENCE STATION) IS USED, ADDITIONAL FIELD TIES MAY BE NEEDED TO REDUCE POSSIBLE ERRORS, OR BIASES.
 2. THE CONTROL DATA FOR THIS PROJECT CAN BE FOUND ELECTRONICALLY BY SELECTING PROJECT CONTROL DATA AT:
[HTTP://WWW.NCDOT.ORG/DOH/PRECONSTRUCT/HIGHWAY/LOCATION/PROJECT/](http://www.ncdot.org/doh/preconstruct/highway/location/project/)
 THE FILES TO BE FOUND ARE AS FOLLOWS:
 B3677_LS_GPSCALIB_070920.HTML
 B3677_LS_WGS84_070920.TXT
 B3677_LS_LOCAL_070920.TXT
 B3677_LS_CONTROL_070920.TXT
 THE WGS84 AND LOCAL FILES ARE COMMA DELIMITED AND CAN BE USED TO REPRODUCE THE SITE CALIBRATION FOR THE END USER'S GPS EQUIPMENT. IF FURTHER INFORMATION IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
- ⊙ INDICATES GEODETIC CONTROL MONUMENTS USED OR SET FOR HORIZONTAL PROJECT CONTROL BY THE NCDOT LOCATION AND SURVEYS UNIT.
 PROJECT CONTROL ESTABLISHED USING GLOBAL POSITIONING SYSTEM.
 NETWORK ESTABLISHED FROM EXISTING HARN MONUMENTATION
 SEE GPS CALIBRATION SHEET FOR HORIZONTAL AND VERTICAL COORDINATE VALUES.

9/20/07

PROJECT REFERENCE NO.	SHEET NO.
33220.1.1	1 D
Location and Surveys	

SURVEY CONTROL SHEET B-3677

GPS CALIBRATION SHEET

GPS CALIBRATION REPORT
 PROJECT : 33220.1.1
 TIP NUMBER B-3677
 COORDINATE SYSTEM US STATE PLANE 1983 ZONE NORTH CAROLINA 3200
 HORIZONTAL DATUM NAD 1983 (CONUS)
 VERTICAL DATUM NAVD 88 GEOID MODEL GEOID03 (CONUS) NC SUB GRID
 COORDINATE UNITS US SURVEY FEET
 DISTANCE UNITS US SURVEY FEET
 HEIGHT UNITS US SURVEY FEET

LOCAL SITE INFORMATION
 LOCALIZED AROUND B3677-1
 LATITUDE N/A
 LONGITUDE N/A
 SITE SCALE FACTOR N/A
 HEIGHT N/A

DATUM TRANSFORMATION PARAMETERS
 WARNING: DATUM PARAMETER CALCULATION DID NOT CONVERGE

METHOD THREE PARAMETER
 TRANSLATION ALONG X AXIS 12.232SFT
 TRANSLATION ALONG Y AXIS -80.558SFT
 TRANSLATION ALONG Z AXIS 57.146SFT

UPDATED DEFAULT PROJECTION (TRANSVERSE MERCATOR) DEFINITION
 UPDATED DEFAULT PROJECTION NOT REQUESTED

HORIZONTAL ADJUSTMENT PARAMETERS
 NORTHING COORDINATE OF ROTATION CENTER 519093.435SFT
 EASTING COORDINATE OF ROTATION CENTER 1488753.623SFT
 ROTATION ABOUT THE CENTER POINT 0.00'00"
 TRANSLATION NORTH 0.000SFT
 TRANSLATION EAST 0.000SFT
 SCALE FACTOR 1.00015858

VERTICAL ADJUSTMENT PARAMETERS
 NORTHING COORDINATE OF ORIGIN POINT 520365.445SFT
 EASTING COORDINATE OF ORIGIN POINT 1494826.100SFT
 VERTICAL SEPARATION AT ORIGIN 0.254SFT
 SLOPE NORTH 0.209PPM
 SLOPE EAST 0.210PPM

GEOID MODEL DEFINITION
 GEOID03 (CONUS) NC SUB GRID

RESIDUAL DIFFERENCES BETWEEN GPS (WGS84) AND LOCAL COORDINATES SUMMARY

	MAXIMUM ERROR	ROOT MEAN SQUARE ERROR	POINT
HORIZONTAL	0.004SFT	0.001	M 048 GPS
VERTICAL	0.025SFT	0.004	B3677-1 GPS
THREE-DIMENSIONAL	0.025SFT	0.004	B3677-1 GPS

POINT RESIDUALS

WGS84 COORDINATES	CALCULATED POINT FOR DISPLAY ONLY	LOCAL COORDINATES
POINT B3677-1 GPS LATITUDE 35°10'04.73530"N LONGITUDE 80°41'25.70548"W HEIGHT 573.086SFT	NORTHING 520365.445SFT EASTING 1494826.100SFT ELEVATION 672.545SFT HORZ ERROR 0.002SFT VERT ERROR 0.025SFT 3D ERROR 0.025SFT	POINT B3677-1 NORTHING 520365.446SFT EASTING 1494826.102SFT ELEVATION 672.570SFT UTILIZED HORZ AND VERT QUALITY SURVEY QUALITY
POINT B3677-2 GPS LATITUDE 35°10'12.02990"N LONGITUDE 80°41'26.55828"W HEIGHT 595.242SFT	NORTHING 521104.104SFT EASTING 1494767.867SFT ELEVATION 694.699SFT HORZ ERROR 0.002SFT VERT ERROR 0.001SFT 3D ERROR 0.002SFT	POINT B3677-2 NORTHING 521104.105SFT EASTING 1494767.865SFT ELEVATION 694.700SFT UTILIZED HORZ AND VERT QUALITY SURVEY QUALITY
POINT M 099 GPS LATITUDE 35°05'49.18169"N LONGITUDE 80°41'42.00983"W HEIGHT 671.295SFT	NORTHING 494554.125SFT EASTING 1492981.579SFT ELEVATION 770.861SFT HORZ ERROR 0.002SFT VERT ERROR 0.012SFT 3D ERROR 0.012SFT	POINT M 099 NORTHING 494554.127SFT EASTING 1492981.580SFT ELEVATION 770.849SFT UTILIZED HORZ AND VERT QUALITY SURVEY QUALITY
POINT M 048 GPS LATITUDE 35°14'17.58661"N LONGITUDE 80°40'17.44825"W HEIGHT 645.307SFT	NORTHING 545831.902SFT EASTING 1500922.921SFT ELEVATION 744.837SFT HORZ ERROR 0.004SFT VERT ERROR 0.012SFT 3D ERROR 0.013SFT	POINT M 048 NORTHING 545831.899SFT EASTING 1500922.923SFT ELEVATION 744.825SFT UTILIZED HORZ AND VERT QUALITY SURVEY QUALITY
POINT M 084 GPS LATITUDE 35°08'51.93089"N LONGITUDE 80°48'20.36612"W HEIGHT 578.772SFT	NORTHING 513611.601SFT EASTING 1460269.647SFT ELEVATION 678.371SFT HORZ ERROR 0.004SFT VERT ERROR 0.002SFT 3D ERROR 0.004SFT	POINT M 084 NORTHING 513611.599SFT EASTING 1460269.644SFT ELEVATION 678.369SFT UTILIZED HORZ AND VERT QUALITY SURVEY QUALITY

DATUM DESCRIPTION
 THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "B3677-1"
 WITH NAD 83/95 STATE PLANE GRID COORDINATES OF
 NORTHING: 520365.445(FT) EASTING: 1494826.102(FT)
 THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.99984624
 THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "B3677-1" TO -L- STATION 15+00.00 IS
 S 21°58'00.3" E 1140.691
 ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
 VERTICAL DATUM USED IS NAVD 88

NOTES:

1. THE SITE CALIBRATION SHOWN IS BASED UPON A NETWORK TIED TO THE HARN (HIGH ACCURACY REFERENCE NETWORK) NAD 83/95 ADJUSTMENT. THIS CALIBRATION WILL ALLOW THE END USER TO WORK WITHIN THE SAME COORDINATE SYSTEM WHEN USING RTK (REAL TIME KINEMATIC) GPS AND A LOCAL BASE STATION. IF ANOTHER SYSTEM SUCH AS VRS (VIRTUAL REFERENCE STATION) IS USED, ADDITIONAL FIELD TIES MAY BE NEEDED TO REDUCE POSSIBLE ERRORS, OR BIASES.

2. THE CONTROL DATA FOR THIS PROJECT CAN BE FOUND ELECTRONICALLY BY SELECTING PROJECT CONTROL DATA AT:
[HTTP://WWW.NCDOT.ORG/DOH/PRECONSTRUCT/HIGHWAY/LOCATION/PROJECT/](http://www.ncdot.org/doh/preconstruct/highway/location/project/)

THE FILES TO BE FOUND ARE AS FOLLOWS:
 B3677_LS_GPSCALIB_070920.HTML
 B3677_LS_WGS84_070920.TXT
 B3677_LS_LOCAL_070920.TXT
 B3677_LS_CONTROL_070920.TXT

THE WGS84 AND LOCAL FILES ARE COMMA DELIMITED AND CAN BE USED TO REPRODUCE THE SITE CALIBRATION FOR THE END USER'S GPS EQUIPMENT. IF FURTHER INFORMATION IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.

PROJECT CONTROL ESTABLISHED USING GLOBAL POSITIONING SYSTEM.
 NETWORK ESTABLISHED FROM EXISTING HARN MONUMENTATION



9/20/07

5/14/99

5/14/99
 11:00 AM
 11:05 AM
 11:10 AM
 11:15 AM
 11:20 AM
 11:25 AM
 11:30 AM
 11:35 AM
 11:40 AM
 11:45 AM
 11:50 AM
 11:55 AM
 12:00 PM
 12:05 PM
 12:10 PM
 12:15 PM
 12:20 PM
 12:25 PM
 12:30 PM
 12:35 PM
 12:40 PM
 12:45 PM
 12:50 PM
 12:55 PM
 1:00 PM
 1:05 PM
 1:10 PM
 1:15 PM
 1:20 PM
 1:25 PM
 1:30 PM
 1:35 PM
 1:40 PM
 1:45 PM
 1:50 PM
 1:55 PM
 2:00 PM
 2:05 PM
 2:10 PM
 2:15 PM
 2:20 PM
 2:25 PM
 2:30 PM
 2:35 PM
 2:40 PM
 2:45 PM
 2:50 PM
 2:55 PM
 3:00 PM
 3:05 PM
 3:10 PM
 3:15 PM
 3:20 PM
 3:25 PM
 3:30 PM
 3:35 PM
 3:40 PM
 3:45 PM
 3:50 PM
 3:55 PM
 4:00 PM
 4:05 PM
 4:10 PM
 4:15 PM
 4:20 PM
 4:25 PM
 4:30 PM
 4:35 PM
 4:40 PM
 4:45 PM
 4:50 PM
 4:55 PM
 5:00 PM
 5:05 PM
 5:10 PM
 5:15 PM
 5:20 PM
 5:25 PM
 5:30 PM
 5:35 PM
 5:40 PM
 5:45 PM
 5:50 PM
 5:55 PM
 6:00 PM


PAVEMENT SCHEDULE	
C1	PROP. APPROX. 1½" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.
C2	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
C3	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 1½" IN DEPTH OR GREATER THAN 2" IN DEPTH.
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 2½" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX. 5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5½" IN DEPTH.
R	2'-6" CONCRETE CURB AND GUTTER.
S	4" CONCRETE SIDEWALK
T	EARTH MATERIAL.
U	EXISTING PAVEMENT.
W	WEDGING EXISTING PAVEMENT (SEE DIAGRAMS BELOW).

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.




TYPICAL SECTION NO. 1

USE TYPICAL SECTION NO. 1 AS FOLLOWS:
 -L- STA. 15+50.00 TO 19+25.00 (BEGIN BRIDGE) RT
 -L- STA. 15+94+/- TO 19+25.00 (BEGIN BRIDGE) LT
 -L- STA. 20+20.00 (END BRIDGE) TO 20+80.00
 NOTE: TRANSITION FROM EXISTING TO TYPICAL SECTION NO. 1 FROM -L- STA. 15+00.00 TO 15+50.00 RT



BRIDGE TYPICAL SECTION NO. 2

USE BRIDGE TYPICAL NO. 2 AS FOLLOWS:
 -L- STA. 19+25.00 TO 20+20.00







TYPICAL SECTION NO. 3


USE TYPICAL SECTION NO. 3 AS FOLLOWS:
 -L- STA. 15+50.00 TO 15+94+/- LT
 -L- STA. 20+80.00 TO 24+50.00
 NOTE: TRANSITION FROM TYPICAL SECTION NO. 3 TO EXISTING FROM -L- STA. 15+00.00 TO 15+50.00 LT AND -L- STA. 24+50.00 TO 25+00.00

TEMPORARY PAVEMENT DETAIL


PROJECT REFERENCE NO. B-3677	SHEET NO. 2-A
RW SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	ENGINEER
6/1/2009	6/1/2009
TGS ENGINEERS SUITE 141 975 WALNUT STREET CARY, NC 27511 PH (919) 319-8850 CORP. LICENSE NO. C-0275	



NOTE: DRAINAGE STRUCTURES #21,22,23,24 & 25 ARE TO BE PLACED AS TEMPORARY TB2G WITH TEMP. STEEL PLATE COVERS IN PHASE 1 (SEE TCP-4 & PHASING).
CONVERT TB2G TO CB IN FINAL PATTERNS. (SEE PSH 4)
DRAINAGE STRUCTURE #24A IS TO BE PLACED AS A TEMPORARY TB2G WITH TEMP. STEEL GRATE AND FRAME (WELD GRATE TO FRAME).
DRAINAGE STRUCTURE #24A IS TO BE REMOVED IN FINAL PATTERNS AND THE 15" RCP IS TO BE PLUGGED AT STRUCTURE #24 AND LEFT IN PLACE. (SEE THIS SHEET)
PROPOSED PIPES CONNECTING STRUCTURES #22,23 & 24 ARE OMITTED FOR CLARITY IN THIS DETAIL, BUT ARE TO BE INSTALLED DURING PHASE 1 OF CONSTRUCTION. (SEE SHEET 3-B AND PSH 4 FOR INVERTS AND SIZES)



NOTE: TEMPORARY PAVEMENT USES -L- PAVEMENT DESIGN (SEE SHEET 2)



NOTE: TEMPORARY PAVEMENT USES -L- PAVEMENT DESIGN (SEE SHEET 2)

LEGEND

- TEMPORARY PAVEMENT
- TEMPORARY DRAINAGE STRUCTURE



SEE SHEET TCP-4 FOR TRAFFIC CONTROL PLANS

SEE SHEET 4 FOR -L- PLAN

REVISIONS

8/17/99

C:\PROJECTS\B3677\DWG\TEMP_PAVEMENT.dwg 6/1/2009 12:57:09 PM



NOTES:

FOR STANDARD TEMPORARY SHORING, SEE TEMPORARY SHORING SPECIAL PROVISION.
 WHEN NOTES ON PLANS DO NOT PROHIBIT STANDARD TEMPORARY SHORING OR STANDARD SHORING, STANDARD TEMPORARY SHORING IS OPTIONAL.

SUBMIT "STANDARD TEMPORARY SHORING SELECTION FORM" AT LEAST 14 DAYS BEFORE BEGINNING SHORING CONSTRUCTION. UP TO THREE LOCATIONS MAY BE INCLUDED ON EACH SELECTION FORM.

- STANDARD TEMPORARY SHORING IS BASED ON THE FOLLOWING CONDITIONS:
- 1) MAXIMUM SHORING HEIGHT IS 12'-0" (3.7m).
 - 2) TRAFFIC SURCHARGE IS 240 PSF (11.5 KPA) MAXIMUM OR BACKSLOPE IS 2:1 (H:V) OR FLATTER.
 - 3) BOTTOM OF EXCAVATION OR EXISTING GRADE IN FRONT OF SHORING IS 6:1 (H:V) SLOPE OR FLATTER.
 - 4) H PILE SPACING IS 6'-0" (1.8m).
 - 5) H PILE EMBEDMENT DEPTHS ARE FOR DRIVEN PILES.
 - 6) TIMBER LAGGING IS A MINIMUM OF 3" (75mm) THICK.

STANDARD TEMPORARY SHORING IS BASED ON THE FOLLOWING IN-SITU ASSUMED SOIL PARAMETERS:
 TOTAL UNIT WEIGHT = 120 PCF (18.8 KN/M³)
 FRICTION ANGLE = 30 DEGREES
 COHESION = 0 PSF (0 KPA)
 GROUNDWATER IS ASSUMED TO BE BELOW BOTTOM OF SHORING.

DO NOT USE STANDARD TEMPORARY SHORING WHEN THE ASSUMED SOIL PARAMETERS ARE NOT APPLICABLE OR GROUNDWATER IS ABOVE THE BOTTOM OF SHORING.

DO NOT USE STANDARD TEMPORARY SHORING WHEN VERY LOOSE OR SOFT SOIL OR MUCK IS PRESENT WITHIN THE EMBEDMENT DEPTH.

VERIFY GROUNDWATER ELEVATION BEFORE BEGINNING SHORING CONSTRUCTION.

IF THE CLEAR DISTANCE AVAILABLE IS LESS THAN THE MINIMUM REQUIRED IN ACCORDANCE WITH THE TRAFFIC CONTROL PLANS, SET THE BARRIER AGAINST THE TRAFFIC SIDE OF THE SHORING AND USE THE "SURCHARGE CASE WITH TRAFFIC IMPACT".

AT THE CONTRACTOR'S OPTION, H PILE EMBEDMENT DEPTHS FOR PILES SET IN DRILLED HOLES MAY BE REDUCED BY 25%. FOR PILE EXCAVATION, SEE TEMPORARY SHORING SPECIAL PROVISION.

CONTROL DRAINAGE DURING CONSTRUCTION IN THE VICINITY OF THE SHORING. COLLECT AND DIRECT RUNOFF AWAY FROM SHORING.

CONTACT THE ENGINEER IF MINIMUM REQUIRED EMBEDMENT IS NOT ACHIEVED.

GROUNDWATER CONDITION	SHORING HEIGHT FT (m)	SLOPE OR SURCHARGE CASE WITH NO TRAFFIC IMPACT					SURCHARGE CASE WITH TRAFFIC IMPACT				
		SHEET PILES		H PILES WITH TIMBER LAGGING			SHEET PILES		H PILES WITH TIMBER LAGGING		
		MINIMUM REQUIRED EMBEDMENT FT (m)	MINIMUM REQUIRED SECTION MODULUS IN ³ /FT (cm ³ /m)	MINIMUM REQUIRED EMBEDMENT FT (m)			MINIMUM REQUIRED EMBEDMENT FT (m)	MINIMUM REQUIRED SECTION MODULUS IN ³ /FT (cm ³ /m)	MINIMUM REQUIRED EMBEDMENT FT (m)		
			HP 10x42 (HP 250x62)	HP 12x53 (HP 310x79)	HP 14x73 (HP 360x108)			HP 10x42 (HP 250x62)	HP 12x53 (HP 310x79)	HP 14x73 (HP 360x108)	
GROUNDWATER ELEVATION BELOW TIP OF SHORING	< 6 (1.8)	7.5 (2.3)	3.0 (161)	8.0 (2.4)	8.0 (2.4)	8.0 (2.4)	11.0 (3.4)	10.0 (538)	9.5 (2.9)	9.5 (2.9)	9.5 (2.9)
	7 (2.1)	8.5 (2.6)	4.5 (242)	9.5 (2.9)	9.5 (2.9)	9.5 (2.9)	12.0 (3.7)	12.0 (645)	10.5 (3.2)	10.5 (3.2)	10.5 (3.2)
	8 (2.4)	10.0 (3.0)	6.5 (349)	10.5 (3.2)	10.5 (3.2)	10.5 (3.2)	12.5 (3.8)	14.0 (753)	11.5 (3.5)	11.5 (3.5)	11.5 (3.5)
	9 (2.7)	11.0 (3.4)	9.5 (511)	--	12.0 (3.7)	12.0 (3.7)	13.5 (4.1)	16.5 (887)	--	12.5 (3.8)	12.5 (3.8)
	10 (3.0)	12.5 (3.8)	13.0 (699)	--	--	13.5 (4.1)	14.0 (4.3)	19.5 (1048)	--	13.5 (4.1)	13.5 (4.1)
	11 (3.4)	13.5 (4.1)	17.0 (914)	--	--	14.5 (4.4)	15.0 (4.6)	22.5 (1210)	--	--	14.5 (4.4)
12 (3.7)	15.0 (4.6)	21.5 (1156)	--	--	16.0 (4.9)	16.0 (4.9)	25.5 (1371)	--	--	15.5 (4.7)	
GROUNDWATER ELEVATION BETWEEN BOTTOM OF SHORING AND TIP OF SHORING	< 6 (1.8)	11.5 (3.5)	4.5 (242)	11.5 (3.5)	11.5 (3.5)	11.5 (3.5)	16.0 (4.9)	12.0 (645)	13.0 (4.0)	13.0 (4.0)	13.0 (4.0)
	7 (2.1)	13.0 (4.0)	7.0 (376)	13.0 (4.0)	13.0 (4.0)	13.0 (4.0)	17.0 (5.2)	14.5 (780)	14.5 (4.4)	14.5 (4.4)	14.5 (4.4)
	8 (2.4)	15.0 (4.6)	10.0 (538)	--	15.0 (4.6)	15.0 (4.6)	18.0 (5.5)	17.0 (914)	--	15.5 (4.7)	15.5 (4.7)
	9 (2.7)	17.0 (5.2)	14.0 (753)	--	17.0 (5.2)	17.0 (5.2)	19.0 (5.8)	20.0 (1075)	--	17.0 (5.2)	17.0 (5.2)
	10 (3.0)	18.5 (5.6)	19.5 (1048)	--	--	18.5 (5.6)	20.0 (6.1)	23.5 (1263)	--	--	18.5 (5.6)
	11 (3.4)	20.5 (6.3)	26.0 (1398)	--	--	--	21.0 (6.4)	28.0 (1505)	--	--	20.0 (6.1)
12 (3.7)	22.5 (6.9)	33.0 (1774)	--	--	--	22.0 (6.7)	33.0 (1774)	--	--	21.5 (6.6)	


NOTE: MINIMUM REQUIRED EXTENSION IS 6" (150mm) FOR "SLOPE OR SURCHARGE CASE WITH NO TRAFFIC IMPACT" AND 32" (800 mm) FOR "SURCHARGE CASE WITH TRAFFIC IMPACT".

GEOTECHNICAL ENGINEERING UNIT
 STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

STANDARD DRAWING NO. 1801.01
STANDARD TEMPORARY SHORING
 DATE: 2-20-07

STANDARD TEMPORARY MSE WALL OPTIONS

GEOTECHNICAL ENGINEER



SCOTT A. HADDEN
ENGINEER
022246
NORTH CAROLINA

ENGINEER

SIGNATURE DATE

SIGNATURE DATE

TEMPORARY MSE WALL OPTION	VENDOR	CONTACT INFORMATION	REINFORCEMENT TYPE	SHEETS
TEMPORARY FABRIC WALL	N/A	N/A	POLYESTER OR POLYPROPYLENE FABRIC	3
HILFIKER TEMPORARY WALL	HILFIKER RETAINING WALLS	1902 HILFIKER LANE, EUREKA, CA 95503-5711 707-443-5093 WWW.HILFIKER.COM	WELDED WIRE MAT	4
SIERRASCAPE TEMPORARY WALL	TENSAR EARTH TECHNOLOGIES, INC	5883 GLENRIDGE DRIVE, SUITE 200 ATLANTA, GA 30328-5363 404-250-1290 WWW.TENSARCORP.COM	GEOGRID	5
RETAINED EARTH TEMPORARY WALL	THE REINFORCED EARTH COMPANY	8614 WESTWOOD CENTER DRIVE, SUITE 1100 VIENNA, VA 22182-2233 703-749-4325 WWW.REINFORCEDEARTH.COM	WELDED WIRE MESH	6-8
TERRATREL TEMPORARY WALL	THE REINFORCED EARTH COMPANY	8614 WESTWOOD CENTER DRIVE, SUITE 1100 VIENNA, VA 22182-2233 703-749-4325 WWW.REINFORCEDEARTH.COM	RIBBED STEEL STRIPS	9-11

FOR STANDARD TEMPORARY MSE WALLS, SEE TEMPORARY SHORING SPECIAL PROVISION.

WHEN NOTES ON PLANS DO NOT PROHIBIT TEMPORARY MSE WALLS OR STANDARD SHORING, STANDARD TEMPORARY MSE WALLS ARE OPTIONAL.

WHEN NOTES ON PLANS REQUIRE TEMPORARY MSE WALLS, USE STANDARD TEMPORARY MSE WALLS OR CONTRACTOR DESIGNED TEMPORARY MSE WALLS.

WHEN THE ALIGNMENT OF STANDARD TEMPORARY MSE WALLS RESULTS IN AN INTERIOR ANGLE LESS THAN 90 DEGREES, SUBMIT AN ACUTE CORNER DETAIL FOR THE SPECIFIC SITUATION IN ACCORDANCE WITH THE WALL VENDOR RECOMMENDATIONS. ALSO, SUBMIT A "STANDARD TEMPORARY MSE WALL SELECTION FORM" FOR EACH TEMPORARY MSE WALL LOCATION. SUBMIT THESE ITEMS AT LEAST 14 DAYS BEFORE BEGINNING WALL CONSTRUCTION.

STANDARD TEMPORARY MSE WALLS ARE BASED ON THE FOLLOWING CONDITIONS:

- 1) MAXIMUM WALL HEIGHT IS 28'-0" (8.5m).
- 2) TRAFFIC SURCHARGE IS 240 PSF (11.5 KPA) MAXIMUM OR BACKSLOPE IS 2:1 (H:V) OR FLATTER.
- 3) EXISTING OR FINISHED GRADE IN FRONT OF WALL IS 6:1 (H:V) SLOPE OR FLATTER.
- 4) THE GRADE OF THE TOP OF WALL IS LESS THAN 4% FOR RETAINED EARTH AND TERRATREL TEMPORARY WALLS.
- 5) DESIGN SERVICE LIFE IS 3 YEARS.
- 6) MATERIAL IN REINFORCED ZONE IS SHORING BACKFILL.
- 7) MAXIMUM APPLIED BEARING PRESSURE IS 1 TSF (100 KPA) FOR WALL HEIGHTS UP TO 8'-0" (2.4m), 2 TSF (195 KPA) FOR WALL HEIGHTS BETWEEN 8'-0" AND 18'-0" (2.4m AND 5.5m) AND 3 TSF (290 KPA) FOR WALL HEIGHTS OVER 18'-0" (5.5m).

STANDARD TEMPORARY MSE WALLS ARE BASED ON THE FOLLOWING IN-SITU ASSUMED SOIL PARAMETERS:
 TOTAL UNIT WEIGHT = 120 PCF (18.8 KN/M³)
 FRICTION ANGLE = 30 DEGREES
 COHESION = 0 PSF (0 KPA)
 GROUNDWATER IS ASSUMED TO BE BELOW BOTTOM OF REINFORCED ZONE.

DO NOT USE STANDARD TEMPORARY MSE WALLS WHEN THE ASSUMED SOIL PARAMETERS ARE NOT APPLICABLE OR VERY LOOSE OR SOFT SOIL OR MUCK IS PRESENT BELOW THE BOTTOM OF REINFORCED ZONE.

CONTROL DRAINAGE DURING CONSTRUCTION IN THE VICINITY OF STANDARD TEMPORARY MSE WALLS. COLLECT AND DIRECT RUNOFF AWAY FROM WALLS AND SHORING BACKFILL.

EXCAVATE AS NECESSARY FOR STANDARD TEMPORARY MSE WALLS IN ACCORDANCE WITH THE FOLLOWING FOR THE WALL OPTION CHOSEN:
 1) MINIMUM EMBEDMENT OF 18" (450mm) UNLESS WALL BEARS ON ROCK, CONCRETE OR PAVEMENT AS DETERMINED BY THE ENGINEER
 2) VERTICAL STEPS IN INCREMENTS EQUAL TO THE VERTICAL REINFORCEMENT SPACING
 3) WITH THE EXCEPTION OF EITHER THE FIRST OR LAST SECTION OF WALL, HORIZONTAL SECTION LENGTHS IN INCREMENTS EQUAL TO THE FOLLOWING:

STANDARD TEMPORARY MSE WALL OPTION	INCREMENT
TEMPORARY FABRIC WALL	9'-0" (2.7m) MIN (VARIES)
HILFIKER TEMPORARY WALL	10'-0" (3.0m) MIN (VARIES)
SIERRASCAPE TEMPORARY WALL	18'-7 1/4" (5.7m)
RETAINED EARTH TEMPORARY WALL	24'-0" (7.3m)
TERRATREL TEMPORARY WALL	19'-8" (6.0m)

DO NOT PLACE SHORING BACKFILL OR FIRST REINFORCEMENT LAYER UNTIL OBTAINING APPROVAL OF THE EXCAVATION DEPTH AND FOUNDATION MATERIAL.

IF APPLICABLE, INSTALL FOUNDATIONS LOCATED WITHIN THE REINFORCED ZONE BEFORE BEGINNING WALL CONSTRUCTION UNLESS DIRECTED OTHERWISE BY THE ENGINEER.

ERECT AND MAINTAIN FACINGS AND FORMS AS SHOWN ON THE STANDARD TEMPORARY MSE WALL DETAILS. STAGGER VERTICAL JOINTS OF FACINGS AND FORMS TO CREATE A RUNNING BOND WHEN POSSIBLE UNLESS SHOWN OTHERWISE ON THESE DETAILS.

PLACE FACINGS AND FORMS AS NEAR TO VERTICAL AS POSSIBLE WITH NO NEGATIVE BATTER. CONSTRUCT STANDARD TEMPORARY MSE WALLS WITH A VERTICAL AND HORIZONTAL TOLERANCE OF 3" (75mm) WHEN MEASURED WITH A 10'-0" (3m) STRAIGHT EDGE AND AN OVERALL VERTICAL PLUMBNESS (BATTER) AND HORIZONTAL ALIGNMENT OF LESS THAN 6" (150mm).

PLACE REINFORCEMENT AT LOCATIONS AND ELEVATIONS SHOWN ON THE STANDARD TEMPORARY MSE WALL DETAILS AND IN SLIGHT TENSION FREE OF KINKS, FOLDS, WRINKLES OR CREASES.

DO NOT SPLICE REINFORCEMENT IN THE REINFORCEMENT DIRECTION (RD), i.e., PARALLEL TO THE WALL FACE. SEAMS ARE ALLOWED IN THE CROSS-REINFORCEMENT DIRECTION (CRD).

CONTACT THE ENGINEER WHEN EXISTING OR FUTURE STRUCTURES SUCH AS FOUNDATIONS, PAVEMENTS, PIPES, INLETS OR UTILITIES WILL INTERFERE WITH REINFORCEMENT. TO AVOID STRUCTURES, DEFLECT, SKEW AND MODIFY REINFORCEMENT.


PLACE SHORING BACKFILL IN 8" TO 10" (200mm to 250mm) THICK LIFTS AND COMPACT IN ACCORDANCE WITH SUBARTICLE 235-4(C) OF THE STANDARD SPECIFICATIONS. USE ONLY HAND OPERATED COMPACTION EQUIPMENT WITHIN 3'-0" (1m) OF THE WALL FACE.

DO NOT DAMAGE REINFORCEMENT WHEN PLACING AND COMPACTING SHORING BACKFILL. DO NOT OPERATE HEAVY EQUIPMENT ON REINFORCEMENT UNTIL IT IS COVERED WITH AT LEAST 10" (250mm) OF SHORING BACKFILL. DO NOT USE SHEEPSFOOT, GRID ROLLERS OR OTHER TYPES OF COMPACTION EQUIPMENT WITH FEET.


COVER REINFORCING AND RETENTION FABRIC WITH AT LEAST 3" (75mm) OF SHORING BACKFILL. PLACE TOP REINFORCEMENT LAYER BETWEEN 4" AND 24" (100mm and 600mm) BELOW TOP OF WALL DEPENDING ON WALL OPTION.

BENCH STANDARD TEMPORARY MSE WALLS INTO THE SIDES OF EXCAVATIONS WHERE APPLICABLE.


IF THE TOP OF WALL IS WITHIN 5'-0" (1.5m) OF FINISHED GRADE, REMOVE TOP FORM OR FACING AND INCORPORATE THE TOP REINFORCEMENT LAYER INTO THE FILL WHEN PLACING FILL IN FRONT OF THE WALL. STANDARD TEMPORARY MSE WALLS REMAIN IN PLACE PERMANENTLY UNLESS REQUIRED OTHERWISE.




SLOPE CASE



SURCHARGE CASE



TEMPORARY MSE WALL ON STRUCTURE



GEOTECHNICAL ENGINEERING UNIT
 STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

STANDARD DRAWING NO. 1801.02

STANDARD TEMPORARY MECHANICALLY STABILIZED EARTH (MSE) WALLS

GEOTECHNICAL ENGINEER ENGINEER

SCOTT A. SHIDDEN 3/24/07

HOW TO USE THIS SHEET:

- FOR ALL WALL OPTIONS, DETERMINE MINIMUM REQUIRED REINFORCEMENT LENGTH (B) FROM TABLE AT RIGHT BASED ON WALL HEIGHT (H) AND SLOPE OR SURCHARGE CASE
- FOR STANDARD TEMPORARY FABRIC WALL, SEE SHEET 3 FOR FABRIC STRENGTH REQUIREMENTS BASED ON WALL HEIGHT (H)
- FOR ALL OTHER WALL OPTIONS, DETERMINE REINFORCEMENT TYPE FROM TABLES BELOW FOR EACH HEIGHT TO REINFORCEMENT (Z) BASED ON WALL HEIGHT (H) AND SLOPE OR SURCHARGE CASE

MINIMUM REQUIRED REINFORCEMENT LENGTH B (FT)

(FOR ALL WALL OPTIONS)

WALL HEIGHT H (FT)	<8	8 TO 10	10 TO 12	12 TO 14	14 TO 16	16 TO 18	18 TO 20	20 TO 22	22 TO 24	24 TO 26	26 TO 28
SLOPE CASE	8	11	13	14	16	18	20	22	24	25	27
SURCHARGE CASE	8	9	11	12	14	15	16	18	19	21	22

TERRATREL TEMPORARY WALL (STRIPS PER LEVEL PER PANEL)

H (FT)	<4	4 TO 6	6 TO 8	8 TO 10	10 TO 12	12 TO 14	14 TO 16	16 TO 18	18 TO 20	20 TO 22	22 TO 24	24 TO 26	26 TO 28
SLOPE AND SURCHARGE CASES													

SIERRASCAPE TEMPORARY WALL (GEOGRID TYPE)

11 = UX1100MSE 16 = UX1600MSE
14 = UX1400MSE 17 = UX1700MSE
15 = UX1500MSE

H (FT)	<4	4 TO 6	6 TO 8	8 TO 10	10 TO 12	12 TO 14	14 TO 16	16 TO 18	18 TO 20	20 TO 22	22 TO 24	24 TO 26	26 TO 28
SLOPE CASE													

H (FT)	<4	4 TO 6	6 TO 8	8 TO 10	10 TO 12	12 TO 14	14 TO 16	16 TO 18	18 TO 20	20 TO 22	22 TO 24	24 TO 26	26 TO 28
SURCHARGE CASE													

HILFIKER TEMPORARY WALL (WELDED WIRE MAT TYPE)

4.5 = W4.5 x W3.5
7.0 = W7.0 x W3.5
9.5 = W9.5 x W4.0

H (FT)	<4	4 TO 6	6 TO 8	8 TO 10	10 TO 12	12 TO 14	14 TO 16	16 TO 18	18 TO 20	20 TO 22	22 TO 24	24 TO 26	26 TO 28
SLOPE CASE													

H (FT)	<4	4 TO 6	6 TO 8	8 TO 10	10 TO 12	12 TO 14	14 TO 16	16 TO 18	18 TO 20	20 TO 22	22 TO 24	24 TO 26	26 TO 28
SURCHARGE CASE													

RETAINED EARTH TEMPORARY WALL (WELDED WIRE MESH TYPE)

3X1 = 3W8 x W8 x 1.0'
3X2 = 3W8 x W8 x 2.0'

H (FT)	<4	4 TO 6	6 TO 8	8 TO 10	10 TO 12	12 TO 14	14 TO 16	16 TO 18	18 TO 20	20 TO 22	22 TO 24	24 TO 26	26 TO 28
SLOPE AND SURCHARGE CASES													

NOTES FOR HILFIKER TEMPORARY WALL

- 1) CAP MAT AT TOP OF WALL IS NOT INCLUDED IN TABLES.
- 2) REINFORCEMENT IS NOT REQUIRED AT 1' LEVEL FOR SLOPE CASE UNTIL WALL HEIGHT (H) IS GREATER THAN 24'.
- 3) REINFORCEMENT IS NOT REQUIRED AT 3' LEVEL FOR SLOPE CASE UNTIL WALL HEIGHT (H) IS GREATER THAN 26'.
- 4) REINFORCEMENT IS NOT REQUIRED AT 1' LEVEL FOR SURCHARGE CASE UNTIL WALL HEIGHT (H) IS GREATER THAN 26'.

GEOTECHNICAL ENGINEERING UNIT
STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

STANDARD DRAWING NO. 1801.02



STANDARD TEMPORARY MSE WALL REINFORCEMENT TABLES - ENGLISH UNITS

SHEET 2 OF 11 DATE: 2-20-07


GEOTECHNICAL ENGINEER ENGINEER

SCOTT A. HIDDEN
SEAL 022246
ENGINEER
SCOTT & HIDDEN

Signature: *Scott A. Hidden* DATE: _____



PLAN VIEW OF FABRIC OVERLAP



TYPICAL SECTION

MINIMUM REQUIRED REINFORCING FABRIC STRENGTH FOR RD*
(SLOPE AND SURCHARGE CASES)

WALL HEIGHT H FEET (M)	POLYESTER WIDE WIDTH TENSILE STRENGTH @ ULTIMATE LB/INCH (KN/M)	POLYPROPYLENE WIDE WIDTH TENSILE STRENGTH @ ULTIMATE LB/INCH (KN/M)
4 (1.2)	200 (35)	200 (35)
6 (1.8)	200 (35)	200 (35)
8 (2.4)	200 (35)	200 (35)
10 (3.0)	200 (35)	230 (40)
12 (3.7)	220 (39)	264 (46)
14 (4.3)	248 (43)	297 (52)
16 (4.9)	276 (48)	330 (58)
18 (5.5)	304 (53)	364 (64)
20 (6.1)	332 (58)	397 (70)
22 (6.7)	359 (63)	431 (76)
24 (7.3)	387 (68)	464 (81)
26 (7.9)	415 (73)	497 (87)
28 (8.5)	443 (78)	531 (93)

*RD = REINFORCEMENT DIRECTION

GEOTECHNICAL ENGINEERING UNIT

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH

STANDARD DRAWING NO. 1801.02

TEMPORARY FABRIC WALL

SHEET 3 OF 11 DATE: 12-19-06

GEOTECHNICAL ENGINEER


ENGINEER



Signature: Scott A. Hadden 3/29/07
 DATE: DATE


CENTERLINE OF REINFORCING MAT
 FACE = EDGE OF BACKING MATS

REINFORCING MAT




FOR ASSEMBLY INSTRUCTIONS, SEE WELDED WIRE WALL CONSTRUCTION GUIDE AVAILABLE FROM HILFIKER WEBSITE AT WWW.HILFIKER.COM/WWW

GENERAL ASSEMBLY DETAIL




TYPICAL SECTION


8" X 12" (203mm X 305mm)
 W4.5 X W3.5 (MW29 X MW23)
 CAP MAT
 WELDED WIRE REINFORCEMENT (WWR)



8" X 12" (203mm X 305mm)
 W4.5 X W3.5 (MW29 X MW23) WWR
 TOP REINFORCING MAT (NO PRONGS)




4" X 3" (102mm X 76mm)
 W5 X W2.5 (MW32 X MW16) WWR
 BACKING MAT
 8' (2.4m) WIDE




8" X 21" (203mm X 533mm)
 REINFORCING MAT
 SEE SHEETS 2 AND 3 FOR GAUGE SIZES




WALL COMPONENTS






WALL FACE DETAIL




TYPICAL SECTION




PLACE ALTERNATE LAYERS OF GEOGRID IN STAGGERED PATTERN SUCH THAT THE LAYER ABOVE IS CENTERED OVER SPACE BELOW


TYPICAL GEOGRID COVERAGE



ELEVATION VIEW





SUPPORT STRUT



SIERRASCAPE FORM

WALL COMPONENTS




STANDARD DRAWING NO. 1801.02

SIERRASCAPE TEMPORARY WALL



SHEET 5 OF 11 DATE: 12-19-06

PANEL LAYOUTS


H - WALL HEIGHT
 (FEET-INCHES)
 (METER)



(FEET-INCHES)
 (METER)




TYPE WH20




TYPE WB20

SECTION



TYPE W



TYPE WB40

SECTION

WELDED WIRE FACINGS

WELDED WIRE FORMS


PANEL TYPES (WELDED WIRE FACINGS AND FORMS)

4" X 4" (100mm X 100mm), W8 X W8 (MW52 X MW52) WELDED WIRE REINFORCEMENT (WWR)



GEOTECHNICAL ENGINEERING UNIT
 STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

STANDARD DRAWING NO. 1801.02
 RETAINED EARTH TEMPORARY WALL
 SHEET 6 OF 11 DATE: 12-19-06




REINFORCING MESH PLACEMENT DETAIL (PLAN VIEW)



1/2" (13mm) DIA. BAR

CONNECTOR BAR

LOOPED END OF MESH (SEE REINFORCING MESH LOOP DETAIL)




IF REINFORCEMENT LENGTH IS NOT AN INCREMENT OF 2'-0" (610mm) MAKE CW EQUAL TO 12" (305mm) AT THE END OF THE REINFORCING MESH OPPOSITE THE LOOPED END

3W8 X W8 X 2.0' (3MW52 X MW52 X 610mm)


NO. OF LONGITUDINAL WIRES
 GAUGE OF LONGITUDINAL WIRES
 GAUGE OF CROSS WIRES
 SPACING OF CROSS WIRES IN FT (mm), CW

REINFORCING MESH DESIGNATION








GENERAL ASSEMBLY DETAIL

REINFORCING MESH



REINFORCING MESH LOOP DETAIL

221427 3/29/2007 std no 1801 shidden GE-Oce34bond



GEOTECHNICAL ENGINEERING UNIT


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

STANDARD DRAWING NO. 1801.02

RETAINED EARTH
TEMPORARY WALL

SHEET 8 OF 11 DATE: 12-19-06


GEOTECHNICAL ENGINEER ENGINEER



Scott A. Hadden 3/29/07


PANEL LAYOUTS

H - WALL HEIGHT
(FEET-INCHES)
(METER)




< 28 - 0 < 27 - 8 < 26 - 0 < 24 - 4 < 22 - 8 < 21 - 0 < 19 - 4
< 8.5 < 8.4 < 7.9 < 7.4 < 6.9 < 6.4 < 5.9


(FEET-INCHES)
(METER)




< 17 - 8 < 16 - 0 < 14 - 4 < 12 - 8 < 11 - 0 < 9 - 4 < 7 - 8 < 6 - 0 < 4 - 4
< 5.4 < 4.9 < 4.4 < 3.9 < 3.4 < 2.8 < 2.3 < 1.8 < 1.3




TYPE A



TYPE B



WELDED WIRE FORM




SECTION

WELDED WIRE FACINGS


PANEL TYPES (WELDED WIRE FACINGS AND FORM)

5" X 5" (125mm X 125mm), W5 X W5 (MW32 X MW32) WELDED WIRE REINFORCEMENT (WWR)




GEOTECHNICAL ENGINEERING UNIT
STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

STANDARD DRAWING NO. 1801.02
TERRATREL TEMPORARY WALL
SHEET 9 OF 11 DATE: 12-19-06




KEY: A8
 NUMBER OF REINFORCING STRIPS
 PANEL TYPE


CONNECTOR ROD AND REINFORCING STRIP PLACEMENT DIAGRAMS




REINFORCING STRIP - 2" X 5/32" (50mm X 4mm)




STRIP TO FACING CONNECTION



1/2" (13mm) DIA. ROD
CONNECTOR ROD



1/2" (13mm) BOLT WITH NUT AND WASHER
BOLT SET



HAIRPIN CONNECTOR

WALL COMPONENTS



GEOTECHNICAL ENGINEERING UNIT
 STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH

STANDARD DRAWING NO. 1801.02
 TERRATREL TEMPORARY WALL
 SHEET 10 OF 11 DATE: 12-19-06

GEOTECHNICAL ENGINEER


ENGINEER

SEAL 022246

PROFESSIONAL ENGINEER


W. A. HIDDEN

DATE




OVERLAP FACINGS VERTICALLY ONE FULL 5" (125mm) WIRE SQUARE DISREGARDING HALF SQUARES AT EDGES

VERTICAL OVERLAP DETAIL




PLAN DETAIL 'A' STRIP CONNECTION

PLAN DETAIL 'B' HORIZONTAL OVERLAP DETAIL




PLAN DETAIL 'C' STRIP CONNECTION WITH HORIZONTAL OVERLAP DETAIL




TYPICAL SECTION

PLACE LOWEST REINFORCING STRIP 10" (250mm) FROM BOTTOM OF REINFORCED ZONE



TYPICAL ELEVATION (WIRES NOT SHOWN FOR CLARITY)



TYPICAL PLAN



GEOTECHNICAL ENGINEERING UNIT

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH

STANDARD DRAWING NO. 1801.02

TERRATREL TEMPORARY WALL


SHEET 11 OF 11

DATE: 12-19-06

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH DETAIL DRAWING FOR
BRIDGE APPROACH FILLS
CORED SLAB & BOX BEAM BRIDGES
SUB REGIONAL TIER

SHEET 1 OF 2
422D11



STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.


ENGLISH DETAIL DRAWING FOR
BRIDGE APPROACH FILLS
CORED SLAB & BOX BEAM BRIDGES
SUB REGIONAL TIER

SHEET 1 OF 2
422D11

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH DETAIL DRAWING FOR
BRIDGE APPROACH FILLS
CORED SLAB & BOX BEAM BRIDGES
SUB REGIONAL TIER


SHEET 2 OF 2
422D11



STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH DETAIL DRAWING FOR
BRIDGE APPROACH FILLS
CORED SLAB & BOX BEAM BRIDGES
SUB REGIONAL TIER


SHEET 2 OF 2
422D11



PROJECT SERVICES UNIT
STANDARDS AND SPECIAL DESIGN
Office 919-250-4128 FAX 919-250-4119


BRIDGE APPROACH FILLS
CORED SLAB & BOX BEAM BRIDGES
SUB REGIONAL TIER

ORIGINAL BY: K. A. Kempf DATE: 6-10-08
MODIFIED BY: DATE:
CHECKED BY: DATE: 2/16/09
FILE SPEC.: kempf/english/bridge approach fills.dgn




GENERAL NOTES:

- USE GRADE A36 STEEL
- STEEL COVERS ARE FOR TEMPORARY USE DURING PHASE CONSTRUCTION.
- FILL SHALL BE PLACED DIRECTLY OVER THE STEEL PLATES.
- SEE ROADWAY PLANS AND PROVISIONS FOR LOCATIONS
- QUANTITIES TO BE PAID FOR AT THE UNIT PRICE BID PER EACH.




SECTION VIEW OF STEEL TOP PLATE

PLAN VIEWS



ELEVATION VIEWS



**PROJECT SERVICES UNIT
STANDARDS AND SPECIAL DESIGN**
Office 919-250-4128 FAX 919-250-4119

**DETAIL OF TEMPORARY
1" STEEL COVER
OVER DRAINAGE STRUCTURE**

ORIGINAL BY: _____ DATE: _____
 MODIFIED BY: rbritt DATE: 04-28-04
 CHECKED BY: _____ DATE: _____
 FILE SPEC.: details/nbritt/english/bridge/b3157steelcover.dgn

STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS ROADWAY SUMMARY OF QUANTITIES FOR CONTRACT - C201969

STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS






SUMMARY OF QUANTITIES

Table with columns: ItemNumber, Sec #, Quantity, Unit, Description. Lists items 0000100000-N through 3656000000-E.

Table with columns: ItemNumber, Sec #, Quantity, Unit, Description. Lists items 4072000000-E through 6029000000-E.

Table with columns: ItemNumber, Sec #, Quantity, Unit, Description. Lists items 6030000000-E through 6117000000-N.

Table with columns: ItemNumber, Sec #, Quantity, Unit, Description. Includes schedule notes and items 0366000000-E through 0540000000-E.





FROM -L- STA. 19+02+/- TO STA. 19+55+/- LT
PSRM: EST. 70 SY
DDE: EST. 43 CY

-L- STA. 19+60+/- LT, EST. 10 TONS
-L- STA. 19+70+/- RT, EST. 6 TONS
-L- STA. 19+75+/- LT, EST. 10 TONS
-L- STA. 20+00+/- RT, EST. 6 TONS


FROM -L- STA. 19+80+/- TO STA. 22+25+/- LT
PSRM: EST. 330 SY
DDE: EST. 259 CY

FROM -L- STA. 20+05+/- TO STA. 21+50+/- RT
DDE: EST. 16 CY


FROM -L- STA. 22+25+/- TO STA. 24+50+/- LT
PSRM: 225 EST. SY
DDE: EST. 89 CY



NOTE: RIP RAP STREAM BANK FROM EDGE OF WATER TO TOP OF BANK
EST. CL 'B' RIP RAP = 100 TONS
EST. FILTER FABRIC = 230 SY



PI Sta 11+66.05	PI Sta 15+24.66	PI Sta 23+81.64
$\Delta = 1' 45' 42.3''$ (LT)	$\Delta = 3' 40' 37.3''$ (LT)	$\Delta = 15' 06' 57.6''$ (RT)
$D = 0' 31' 50.0''$	$D = 0' 57' 17.7''$	$D = 4' 46' 28.7''$
$L = 332.07'$	$L = 385.06'$	$L = 316.59'$
$T = 166.05'$	$T = 192.59'$	$T = 159.22'$
$R = 10,799.43'$	$R = 6,000.00'$	$R = 1,200.00'$
$SE = EXISTING$	$SE = NC$	$SE = 0.04$
$Vd = 60$ MPH	$Vd = 45$ MPH	$Vd = 55$ MPH



SEE SHEETS S-1 THRU S-4 FOR STRUCTURE PLANS

SEE SHEET 5 FOR -L- PROFILE

SEE PLANS RT SIDE OF SR4141 (15.7% SLOPE)
CLASS 'B' RIP RAP: EST. 30 TONS
FILTER FABRIC: EST. 43 SY

REVISIONS

8/17/99

5/1/2009 1:00:20 PM


STRUCTURE HYDRAULIC DATA		
DESIGN DISCHARGE	= 2,200	CFS
DESIGN FREQUENCY	= 25	YRS
DESIGN ELEVATION	= 658.3	FT
BASE DISCHARGE	= 3,100	CFS
BASE FREQUENCY	= 100	YRS
BASE ELEVATION	= 659.2	FT
OVERTOPPING DISCHARGE	= 3,600	CFS
OVERTOPPING FREQUENCY	= 100+	YRS
OVERTOPPING ELEVATION	= 658.9	FT

BM# S33-01
 -BL- STA. 18+47.91 OFF 5.22' LT
 ELEV. = 656.500
 CITY OF CHARLOTTE SURVEY MARK.
 (CITY OF CHARLOTTE PUBLISHED ELEV. = 656.08')

BM# 2
 -BL- STA. 19+32.36 OFF 290.09' LT
 ELEV. = 653.306
 RR SPIKE IN THE BASE OF A 15" HAWTHORN.

TGS ENGINEERS
 SUITE 141
 975 WALNUT STREET
 CARY, NC 27511
 PH (919) 319-8850

PROJECT REFERENCE NO. B-3677	SHEET NO. 5
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
5/24/09	5/22/09



SEE SHEET 4 FOR -L- PLAN VIEW