R-2519A

CONTRACT: C202332

CONTENTS:

INVESTIGATION ALONG -L-

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS

GEOTECHNICAL UNIT

SUBSURFACE INVESTIGATION

STATE PROJECT 6.909001T I.D. NO. R-2519A

F.A. PROJECT

COUNTY YANCEY

DESCRIPTION US 19 E FROM SR 1336 (JACKS CREEK ROAD) TO SR 1186 (OLD US 19)

INVENTORY



STA. 345+60 -L- END TIP PROJECT R-2519A

STA. 226+40 -L- BEGIN TIP PROJECT R-2519A

DRAWN BY: J C KUHNE D O CHEEK

NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IT IS CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THE PROJECT.

NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

METRIC

ALL DIMENSIONS IN THESE PLANS ARE IN METERS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-2519A	1	238

STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION
35609.1.1		PE
35609.2.1		RW, UTIL
35609.3.1		CONST

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WAS MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL UNIT @ (919) 250-4088. NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOGS, ROCK CORES, OR SOIL TEST DATA IS PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD.
THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

INVESTIGATED BY J C KUHNE PERSONNEL D P MURPHY

CHECKED BY W D FRYE D O CHEEK

SUBMITTED BY J C KUHNE C COFFEY

DATE 31 Oct 2003

NORTH CAROLINA LICENSED SEAL 1878 GEOLOGIST JODY KUHNE

SEAL

SIGNATURE

ID	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
R-2519A	6.909001T	2	238

METRIC

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION

SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER 30 cm ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:

VERY STIFF, GRAY SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6

SOIL LEGEND AND AASHTO CLASSIFICATION

GENERAL CLASS.	GRANULAR MATERIALS (≤35% PASSING #200)							SILT-CLAY MATERIALS (>35% PASSING #200)				ORGANIC MATERIALS		
GROUP CLASS.	A-1		A-3	A-2				A-4	A-5	A-6	A-7	A-1, A-2 A-3	A-4, A-5 A-6, A-7	
	A-1-a	A-1-b		A-2-4	A-2-5	A-2-6	A-2-7				A-7-5 A-7-6			
SYMBOL														
% PASSING # 10 # 40 # 200	50 MX 30 MX 15 MX		50 MX 25 MX	51 MN 10 MX	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	36 MN	GRANULAR SOILS	SILT-CLAY SOILS	MUCK, PEAT
LIQUID LIMIT PLASTIC INDEX	6 MX		N.P.		40 MX 10 MX	41 MN 10 MX	40 MX 11 MN	41 MN 11 MN	40 MX 10 MX	41 MN 10 MX	40 MX 11 MN	41 MN 11 MN	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS
GROUP INDEX	0		0		0		4 MX		8 MX	12 MX	16 MX	No MX			
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL AND SAND		FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND					SILTY SOILS		CLAYEY SOILS				
GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD								FAIR TO POOR				FAIR TO POOR	POOR	UNSUITABLE

P.I. OF A-7-5 ≤ L.L. - 30 : P.I. OF A-7-6 > L.L. - 30

CONSISTENCY OR DENSENESS

PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTENCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (kN/m^2)
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	<4	N/A
	LOOSE	4 TO 10	
	MEDIUM DENSE	10 TO 30	
	DENSE	30 TO 50	
	VERY DENSE	>50	
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	<2	<25
	SOFT	2 TO 4	25 TO 50
	MEDIUM STIFF	4 TO 8	50 TO 100
	STIFF	8 TO 15	100 TO 200
	VERY STIFF	15 TO 30	200 TO 400
	HARD	>30	>400

TEXTURE OR GRAIN SIZE

U.S. STD. SIEVE SIZE	4	10	40	60	200	270
OPENING (MM)	4.76	2.0	0.42	0.25	0.075	0.053

BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)

GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005
	IN.	12"	3"				

SOIL MOISTURE - CORRELATION OF TERMS

SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION
	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE
LL — LIQUID LIMIT		
PLASTIC RANGE (PI)	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE
PL — PLASTIC LIMIT		
OM — OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE
SL — SHRINKAGE LIMIT		
	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE

PLASTICITY

	PLASTICITY INDEX (PI)	DRY STRENGTH
NONPLASTIC	0-5	VERY LOW
LOW PLASTICITY	6-15	SLIGHT
MED. PLASTICITY	16-25	MEDIUM
HIGH PLASTICITY	26 OR MORE	HIGH

COLOR

DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.

GRADATION

WELL GRADED- INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE
UNIFORM- INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE (ALSO POORLY GRADED).
GAP-GRADED- INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.

ANGULARITY OF GRAINS

THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.

MINERALOGICAL COMPOSITION

MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.

COMPRESSIBILITY

SLIGHTLY COMPRESSIBLE	LIQUID LIMIT LESS THAN 30
MODERATELY COMPRESSIBLE	LIQUID LIMIT 31-50
HIGHLY COMPRESSIBLE	LIQUID LIMIT GREATER THAN 50

PERCENTAGE OF MATERIAL

ORGANIC MATERIAL	GRANULAR SOILS	SILT- CLAY SOILS
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%
MODERATELY ORGANIC	5 - 10%	12 - 20%
HIGHLY ORGANIC	>10%	>20%

OTHER MATERIAL	
TRACE	1 - 10%
LITTLE	10 - 20%
SOME	20 - 35%
HIGHLY	35% AND ABOVE

GROUND WATER

- WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING.
- STATIC WATER LEVEL AFTER 24 HOURS.
- PW — PERCHED WATER, SATURATED ZONE OR WATER BEARING STRATA
- SPRING OR SEEPAGE

MISCELLANEOUS SYMBOLS

- ROADWAY EMBANKMENT WITH SOIL DESCRIPTION
- SOIL SYMBOL
- ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS
- INFERRED SOIL BOUNDARIES
- INFERRED ROCK LINE
- ALLUVIAL SOIL BOUNDARY
- 25/025 — DIP/DIP DIRECTION OF ROCK STRUCTURES
- SOUNDING ROD
- SPT CPT DPT DMT VST PMT — TEST BORING
- AUGER BORING
- CORE BORING
- MW — MONITORING WELL
- PIEZOMETER INSTALLATION
- SLOPE INDICATOR INSTALLATION
- SPT N-VALUE
- REF — SPT REFUSAL

SAMPLE DESIGNATIONS
S- BULK SAMPLE
SS- SPLIT SPOON SAMPLE
ST- SHELBY TUBE SAMPLE
RS- ROCK SAMPLE
RT- RECOMPACTED TRIAXIAL SAMPLE
CBR - CBR SAMPLE

ABBREVIATIONS

AR - AUGER REFUSAL
BT - BORING TERMINATED
CL. - CLAY
CPT - CONE PENETRATION TEST
CSE. - COARSE
DMT - DILATOMETER TEST
DPT - DYNAMIC PENETRATION TEST
e - VOID RATIO
F. - FINE
FOSS. - FOSSILIFEROUS
FRAC. - FRACTURED
FRAGS. - FRAGMENTS
MED. - MEDIUM
PMT - PRESSUREMETER TEST
SD. - SAND, SANDY
SL. - SILT, SILTY
SLI. - SLIGHTLY
TCR - TRICONE REFUSAL
γ - UNIT WEIGHT
γ_d - DRY UNIT WEIGHT
W - MOISTURE CONTENT
V. - VERY
VST - VANE SHEAR TEST

EQUIPMENT USED ON SUBJECT PROJECT

DRILL UNITS:
- [ ] MOBILE B-___
- [ ] BK-51
- [X] CME-45
- [X] CME-550
- [ ] PORTABLE HOIST
- [ ] OTHER _____
- [ ] OTHER _____

ADVANCING TOOLS:
- [ ] CLAY BITS
- [ ] 152 mm CONTINUOUS FLIGHT AUGER
- [X] 203 mm HOLLOW AUGERS
- [ ] HARD FACED FINGER BITS
- [ ] TUNG.-CARBIDE INSERTS
- [ ] CASING [ ] W/ ADVANCER
- [ ] TRICONE _____ mm STEEL TEETH
- [ ] TRICONE _____ mm TUNG.-CARB.
- [ ] CORE BIT
- [ ] OTHER _____

HAMMER TYPE:
- [X] AUTOMATIC [ ] MANUAL

CORE SIZE:
- [ ] -B_____
- [ ] -N_____
- [ ] -H_____

HAND TOOLS:
- [ ] POST HOLE DIGGER
- [ ] HAND AUGER
- [X] SOUNDING ROD
- [ ] VANE SHEAR TEST
- [ ] OTHER _____

ROCK DESCRIPTION

HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 2.5 cm PER 50 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK.
ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLOWS:

WEATHERED ROCK (WR)	NON-COASTAL PLAIN MATERIAL THAT YIELDS SPT N VALUES > 100 BLOWS PER 30 cm.
CRYSTALLINE ROCK (CR)	FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.
NON-CRYSTALLINE ROCK (NCR)	FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.
COASTAL PLAIN SEDIMENTARY ROCK (CP)	COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.

WEATHERING

FRESH	ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.
VERY SLIGHT (V. SLI.)	ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.
SLIGHT (SLI.)	ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 2.5 cm. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.
MODERATE (MOD.)	SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.
MODERATELY SEVERE (MOD. SEV.)	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES 'CLUNK' SOUND WHEN STRUCK. *IF TESTED, WOULD YIELD SPT REFUSAL*
SEVERE (SEV.)	ALL ROCKS EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. *IF TESTED, YIELDS SPT N VALUES > 100 BLOWS PER 30 cm.*
VERY SEVERE (V. SEV.)	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. *IF TESTED, YIELDS SPT N VALUES < 100 BLOWS PER 30 cm,*
COMPLETE	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.

ROCK HARDNESS

VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGISTS PICK.
HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.
MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 6 mm DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGISTS PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.
MEDIUM HARD	CAN BE GROOVED OR GOUGED 1 mm DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 25 mm MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGISTS PICK.
SOFT	CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL CENTIMETERS IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.
VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 25 mm OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.

FRACTURE SPACING

TERM	SPACING
VERY WIDE	MORE THAN 3 m
WIDE	1 TO 3 m
MODERATELY CLOSE	30 TO 100 cm
CLOSE	5 TO 30 cm
VERY CLOSE	LESS THAN 5 cm

BEDDING

TERM	THICKNESS
VERY THICKLY BEDDED	> 1 m
THICKLY BEDDED	0.5 - 1 m
THINLY BEDDED	0.05 - 0.5 m
VERY THINLY BEDDED	10 - 50 mm
THICKLY LAMINATED	2.5 - 10 mm
THINLY LAMINATED	< 2.5 mm

INDURATION

FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.

FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.

TERMS AND DEFINITIONS

ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER.

AQUIFER - A WATER BEARING FORMATION OR STRATA.

ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.

ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC.

ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.

CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.

COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.

CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.

DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.

DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.

DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.

FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.

FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.

FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL

FLOOD PLAIN (F.P.) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.

FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.

JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.

LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.

LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.

MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.

PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.

RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.

ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.

SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.

SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.

SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.

STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N) OF A 63.5 kg HAMMER FALLING 0.76 METERS REQUIRED TO PRODUCE A PENETRATION OF 30 cm INTO SOIL WITH A 5 cm OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS LESS THAN 2.5 cm PENETRATION WITH 50 BLOWS.

STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.

STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.

TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.

BENCH MARK:

ELEVATION:

NOTES:

REVISED 09/15/00

R-2519A

PROJECT: 6.909001T

See Sheet 1-A For Index of Sheets
See Sheet 1-B For Conventional Symbols



VICINITY MAP

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

YANCEY COUNTY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-2519A	2A	238

STATE PROJ. NO.	F. A. PROJ. NO.	DESCRIPTION
6.909001T		PE

METRIC
ALL DIMENSIONS IN THESE PLANS ARE IN METERS

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION
INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

LOCATION: US 19 E FROM SR 1336 (JACKS CREEK ROAD) TO SR 1186 (OLD US 19)

TYPE OF WORK: GRADING, DRAINAGE, WIDENING, RESURFACING CURB & GUTTER, SIGNALS, GUARDRAIL, AND STRUCTURES

Proposed Median Crossover
Proposed Additional Median Crossover

NAD83



STA. 345 + 60.000 –L– END STATE PROJECT 6.909001T

STA. 226 + 40 –L– BEGIN STATE PROJECT 6.909001T

PART OF THIS PROJECT IS WITHIN THE MUNICIPAL BOUNDARIES OF BURNSVILLE

THIS IS A PARTIAL CONTROLLED-ACCESS PROJECT WITH ACCESS BEING LIMITED TO POINTS AS SHOWN ON THE PLANS.

** DESIGN EXCEPTION REQUIRED FOR DESIGN SPEED FROM 100kph (60mph) TO 80kph (50mph) (–L– STA. 306 + 50.000 TO –L– STA. 345 + 60.000)

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD _____.

5 0 10
PLANS
5 0 10
PROFILE (HORIZONTAL)
1 0 2
PROFILE (VERTICAL)

DESIGN DATA

ADT 2006 = 25539
ADT 2026 = 37182
DHV = 8 %
D = 63 %
T = 8 % *
(C&G sect.)V = 80 km/h
(Shld. sect.) V = 100 km/h**
* TTST 4 % DUAL 4 %

PROJECT LENGTH

LENGTH OF ROADWAY PROJECT 6.909001T = 11.899 Km

LENGTH OF STRUCTURE PROJECT 6.909001T = 0.021 Km

TOTAL LENGTH OF ROADWAY PROJECT 6.909001T = 11.920 Km

Prepared in the Office of:
DIVISION OF HIGHWAYS
1000 BIRCH RIDGE DR., RALEIGH NC 27610

2002 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: MAY 21, 2004

LETTING DATE: MAY 16, 2006

BRENDA MOORE, PE
PROJECT ENGINEER

RON McCOLLUM, PE
PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER
SIGNATURE: P.E.

ROADWAY DESIGN ENGINEER
SIGNATURE: P.E.

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA
STATE DESIGN ENGINEER P.E.

DEPARTMENT OF TRANSPORTATION
FEDERAL HIGHWAY ADMINISTRATION
APPROVED
DIVISION ADMINISTRATOR DATE

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

Michael F. Easley
GOVERNOR

P.O. BOX 25201, RALEIGH, N.C. 27611-5201

Lyndo Tippett
SECRETARY

23 October, 2003

STATE PROJECT: 6.909001 T, R-2519A

COUNTY: Yancey

DESCRIPTION: US 19 E from SR 1336 (Jack's Creek Road) to SR 1186 (Old US 19)

SUBJECT: Geotechnical Report – Inventory

PROJECT DESCRIPTION

The project consists of 11.92 km of roadway widening from 2 and 3 lane existing to 4 and 5 lanes. Widening is exclusively along existing with no realignment. Structures to be added or lengthened are eight 2-barrel culverts, two 3-barrel culverts, ten retaining walls and no bridge work.

A geotechnical investigation was performed from April through June of 2003 utilizing a CME 550 ATV mounted drill and CME 45C Track mounted drill. Standard Penetration Tests were performed at selected locations along the alignment for embankments, cut slopes and retaining walls. Representative soil samples were obtained for visual classification in the field and for laboratory analysis by the Material and Tests Unit.

The following survey line was investigated:

Line	Stations
- L -	226+40 – 345+60

AREAS OF SPECIAL GEOTECHNICAL INTEREST

STRUCTURES

There are ten retaining walls on the project. These are covered in separate Structure reports included in this document. No bridge structures are included and it is assumed that existing culverts will be lengthened. Borings and dynamic penetrometer tests were done at these existing culvert locations:

Sta. 257+20
Sta. 279+40, on –Y 17 –
Sta. 285+00
Sta. 289+70
Sta. 300+60 and 301+30, for culverts on –L- and – Y 24 –
Sta. 312+60
Sta. 316+60

POTENTIALLY UNSUITABLE SUBSURFACE CONDITIONS

Highly plastic clays, PI>35, exist in residual soils around Stations 252-253+00. These were encountered while drilling, but no other evidence such a pavement cracking or settlement are associated.

UNSUITABLE FILL

Areas of artificial fill exist at Stas. 300-303+00 and 318+00. Drilling revealed waste materials (wood, metal, etc.) in these locations. Reinforcing fabric will be recommended in a quantity sufficient to allow undercutting under –Y 24 -, but the quality and strength of the overall material is good enough to not require undercutting. The fill at 318+00 will not be a factor once culvert and retaining wall construction have been completed.

GROUNDWATER

High groundwater exists in cuts at:

238+40 rt
308+80 lt
323+60 lt

The fill will toe in a private pond at 310+60, 30m right.

PHYSIOGRAPHY AND GEOLOGY

The project lies in moderately rolling terrain with the steepest grade from the start of the project near the Cane River at Sta. 226+40, el. 775m, to Sta. 239+00, el. 825m. It then enters a relatively broad valley and reaches a maximum elevation of 850m at Sta. 269+00. From Sta. 269+00 the grade enters the headwaters of Little Crabtree Creek and drops to 805m by Sta. 281. The project roughly follows Little Crabtree Creek valley to an elevation of 770m at Sta. 346+60.

Burnsville is the most populated town in Yancey County and many residences, business developments, schools, etc., lie along the project corridor.

The project lies entirely within Ashe Formation rocks. These are categorized as muscovite-biotite geisses, poorly to moderately foliated.

Cemeteries affected by the proposed slope and ROW boundaries exist at Sta. 232+60, 309+60 and access at 246+00.

SOIL PROPERTIES

High mica content in the parent gneisses generates mostly silty material in all residual and saprolite soils in the project corridor.

Residual soils in the wide valleys, Sta. 252+00 – 265+00, 278+00 – 290+00 and 298+00 – 305+00 tend to be silts, clayey silts and clayey sands. Alluvium in these areas are predominately non-plastic clays, silts and lenses of gravel and sandy gravel. Alluvium in the tighter stream valleys, Sta.290+00 – 293+00, 314+00 – 342+00 are predominately coarse sands, silty sands and gravel. The only highly plastic, PI>35, soils on the project were encountered in the vicinity of Stations 252+00 - 253+00.

Cut areas consist of mostly silts, silty sands and clayey sands. Weathered rock horizons generally range from 1-3m. **Manganese oxide, MnO, filled joints are visible in cut areas from Sta. 267+00 – 275+00 and were encountered in soils throughout the project.**

All areas denoted on cross sections as "saprolite and weathered rock", or "weathered rock" may contain very weathered to slightly weathered rock that requires select ripping or blasting to excavate.

Two Shelby tube samples were taken at 228+60, 21 m rt, for CU triaxial tests in plastic clays with PI 30 and 33.

ROCK PROPERTIES

Rock exposed in cuts shows moderate foliation, weathering to some degree and is highly jointed. The rock is generally moderately to slightly weathered and not found in appreciable amounts except for stations 281+00-282+50, 318+00-322+00, 327+00, 336+00, 338+00 and 343-344+00. Foliations generally dip 35-90^0 ESE with some dipslope for the left hand cuts on the project.
The volume of rock, the orientation of foliation, weathering and the degree of jointing as mapped in outcrop do not lend to efficient rock slope design so no coring was done, nor are rock slopes steeper than 1 ½:1 recommended for any cut area.

GROUNDWATER

Rainfall amounts were higher than average during the investigation of this project. Due to the highly jointed nature of the rock and the free draining soils in cut areas, groundwater was rarely encountered. It was encountered in cuts at 238+40 rt, 308+80 lt, and 323+60 lt. The stream valleys and alluvial floodplains invariably have groundwater levels between 1 and 3m. No springs or known private wells were encountered. The areas where groundwater can uniformly be expected between 1 and 3m are:

Sta. 226+40 – 233+50 rt
Sta. 251+00 – 266+00 lt
Sta. 269+40 – 271+00 lt
Sta. 277+00 – 290+40 lt and rt
Sta. 290+40 – 298+00 rt
Sta. 298+00 – 302+60 lt and rt
Sta. 302+60 – 306+00 lt
Sta. 313+00 – 318+60 lt and rt
Sta. 318+60 – 342+40 rt

GEOTECHNICAL DESCRIPTIVE ANALYSIS

Stations 226+40 – 248+00

This section involves widening existing with sliver cuts and fills. 226+40 to 231+00 has 1 ½:1 existing cuts in saprolite and some weathered rock on the left. The fills will toe in 1 – 2m of loose alluvium (AASHTO A-2-4) or loose residual soils and saprolite consisting of sandy clays (A-7-6) or silty sands (A-2-4). Auger refusal was consistent through this section on the right at 1 –2m. From 231+00 to 237+60 fills on either side will toe in 1 – 2m of residual silty clay overlying dense saprolite and weathered rock. 237+60 to 248+00 has predominately two sided cuts consisting mostly of loose to dense saprolite and 1 – 5m of weathered rock and rock in the deepest part of the cuts.

Stations 248+00 – 266+60

This section involves mostly adding 1-2m of fill to widen over loose alluvial silty clays and sands (A-7, A-7-5) and loose residual silts and sands (A-2-4, A-4). Highly plastic clays exist from 252+00 – 253+00 and there is a small retaining wall to keep the fill out of the stream from 256+60 to 257+20.

Stations 266+60 – 269+20

Moderate sized cut on right in med. dense to dense saprolite (A-4, A-2-5) with some very dense layering, 0.5 – 1m thick. MnO on existing joints is prevalent in this cut.

Stations 269+20 – 279+60

Section typified by cuts on the right and sliver fills with retaining walls on the left. The largest cut from 272+60 to 275+40 is dry and consists mostly of loose to dense saprolite (A-5) with auger refusal at 11 – 15m in holes drilled 30 – 40m rt. The three wall sections, 269+40 – 270+80, 277+60 – 278+00 and 278+70 – 279+20 will be founded through loose embankment and loose residual soil and saprolite to dense saprolite and/or weathered rock 5 – 10m deep. The fills will toe on loose alluvium (A-7-5, A-2-5) and

residual soils (A-5).

Stations 279+60 – 290+60

Proposed widening and fill 1-2m, will occur mostly on loose alluvium with small cuts predominately in slightly weathered to fresh rock on the right at 280+80 – 282+60 and in saprolite to end at 283+60.

Stations 290+60 – 304+20

The largest cut in this section, 290+60 – 292+20 lt, has mostly rock overlain by 1-2m of weathered rock and saprolite. The rest of the section consists of low cuts in loose to med. dense saprolite on the left with low fills over loose alluvium and dense saprolite on the right. A low retaining wall keeps fill out of the stream at 300+00 to 300+60 rt and is founded on loose fill, alluvium and saprolite to depths of 5+ m. A retaining wall above grade supports the parking lot from 303+00 – 303+60 rt and is founded in loose saprolite to depths of 5+ m. –Y 24- intersects at 301+25 and is a new alignment with low fill over loose alluvium and artificial fill.

Stations 304+20 – 313+20

This section has two moderate cuts from 304+20 – 306+60 rt and 308+00 – 312+40 lt typified by up to 6m of loose to dense saprolite (A-2-4, A-4) over 6 -7m of weathered rock. Rock is showing at 311+60 lt and can be expected in the bottom 1-2m of each of these cuts and the ditchline excavations. The culvert at 312+60 is founded in 1 - 1.5m of alluvium with thin weathered rock and rock below. –Y 27- intersects at 312+65 and shows mostly rock in the cut associated with the tie in.

Stations 313+20 – 318+40

This section consists of low cuts in artificial fill or saprolite and fills over loose alluvial sands and gravel. A small retaining wall supports 0.1 – 1.3m of embankment along –Y 28- at 315+50 – 315+70, 39 – 15 m rt, and is founded in loose to dense saprolite. The culvert at 316+60 is founded in 3 m of alluvium over dense saprolite and weathered rock. The culvert at 318+20 is founded in 2 m of alluvium over weathered rock and rock.

No proposal in the plans addresses fill overriding the creek from 314+20 – 315+60.

Stations 318+40 – 328+00

This section contains the largest cuts on the project with rock exposed in existing cuts at the intersection of –Y 30-, 318+60 – 318+80, 319+20 – 319+60, 320+60, 321+00, 322+00 and 326+70 lt. Rock is overlain by 1-5m of weathered rock which is capped by loose to med. dense saprolite. Loose to med. dense saprolite (A-2-5, A-2-4) makes up the majority of the remaining cut excavation with weathered rock possible at the ditchline excavations. Fills are low on the right and will toe in loose alluvial sands, gravel and cobbles. The retaining wall along –Y 30- is founded in 2-4m of embankment and .5 – 1.5m of alluvium over thin weathered rock and rock.

Stations 328+00 – 335+20

This section consists of several low cuts on the left in loose to med. dense saprolite with low fills on the left and right that rest on loose alluvium and residual soils.

Stations 335+20 – 345+60

Three moderate to large cuts are on the left side of this section with rock exposed in existing cuts at 335+90, 338+00 and 343+80. The remaining cut material consists of loose to dense saprolite overlying 1-2 m of weathered rock. Perched colluvium exists in the cut from 342+80 to 343+60, but will be undercut and removed with any slope design of 1 ½:1 or flatter. Two retaining walls at 339+35 – 339+45 and 341+20 – 341+80 will be founded in 2 – 3 m of alluvium (A-2-4 w/ gravel layers) over weathered rock.

Respectfully Submitted,

Jody C. Kuhne

EARTHWORK BALANCE SHEET

RDTOSIC

LOCATION	EXCAVATION					EMBANKMENT					WASTE			
	TOTAL UNCLASS.	ROCK	UNDERCUT	UNSUIT. UNCLASS.	SUITABLE UNCLASS.	TOTAL	ROCK	EARTH	EMBANK. (+) 15%	BORROW	ROCK	SUITABLE	UNSUIT.	TOTAL
-L- 226+40 TO 235+40 LT	15086	9780			5306	388	323		323		9457	5306		14763
SUBTOTAL	15086	9780			5306	388	323		323		9457	5306		14763
-L- 235+40 TO 244+40 LT	22102	1477			20625	1001	834		834		643	20625		21268
-Y3- 10+47.000 TO 11+70.994	1400				1400	691		691	795			605		605
-Y5- 10+17.709 TO 10+95.923	304				304	89		89	102			202		202
SUBTOTAL	23806	1477			22329	1781	834	780	1731		643	21432		22075
-L- 244+40 TO 253+40 LT	22433	1363			21070	1691	1363	55	1427			21006		21006
-Y6- 10+50.340 TO 11+30.114	196				196	260		260	299	103				
-Y8- 10+32.155 TO 10+60.264	174				174							174		174
SUBTOTAL	22803	1363			21440	1951	1363	315	1726	103		21180		21180
-L- 253+40 TO 262+40 LT	764				764	5936		5936	6826	6062				
-Y9- 11+24.000 TO 11+68.066	1				1	139		139	160	159				
-Y10- 10+06.458 TO 10+59.121	11				11	337		337	388	377				
SUBTOTAL	776				776	6412		6412	7374	6598				
-L- 262+40 TO 271+40 LT	2011				2011	8351		8351	9604	7593				
-Y11- 10+26.868 TO 10+58.037	22				22	27		27	31	9				
-Y12- 10+19.000 TO 10+55.694	1				1	35		35	40	39				
-Y14- 10+31.355 TO 10+48.791	64				64	42		42	48			16		16
SUBTOTAL	2098				2098	8455		8455	9723	7641		16		16
-L- 271+40 TO 280+40 LT	1436				1436	18681		18681	21483	20047				
-Y17- 10+25.000 TO 11+47.744	261				261	777		777	894	633				
SUBTOTAL	1697				1697	19458		19458	22377	20680				
-L- 280+40 TO 289+40 LT	3153				3153	2091		2091	2405			748		748
-Y19- 10+25.000 TO 12+19.754	787				787	247		247	284			503		503
SUBTOTAL	3940				3940	2338		2338	2689			1251		1251
-L- 289+40 TO 298+40 LT	29693	8434			21259	2004	1670		1670		6764	21259		28023
-Y21- 10+67.500 TO 12+33.932	402				402	346		346	398			4		4
-Y22- 10+03.955 TO 10+66.203	149				149	169		169	194	45				
-Y23- 10+37.000 TO 10+77.414	76				76	14		14	16			60		60
-Y24A- 11+55.566 TO 11+83.566	319				319	50		50	58			262		262
-Y24- 10+30.144 TO 11+52.962	195				195	2122		2122	2440	2245				
SUBTOTAL	30834	8434			22400	4705	1670	2701	4776	2291	6764	21585		28349
-L- 298+40 TO 307+40 LT	4625				4625	4985		4985	5733	1108				
-Y26- 10+26.848 TO 11+17.687	5				5	1390		1390	1599	1594				
SUBTOTAL	4630				4630	6375		6375	7331	2701				
-L- 307+40 TO 316+40 LT	28333	1974			26359	4901	1974	2532	4886			23447		23447
SUBTOTAL	28333	1974			26359	4901	1974	2532	4886			23447		23447
-L- 316+40 TO 324+80 LT	234619	140525			94094	1984	1653		1653		138872	94094		232966
-Y29- 11+00.000 TO 11+31.399	7				7	190		190	219	212				
-Y30- 10+28.278 TO 11+07.189	13024				13024	570		570	656			12369		12369
-D11- 10+15.00 TO 10+73.07	4895	4508			387						4508	387		4895
-D12- 10+06.30 TO 10+60.02	5913				5913							5913		5913
-D13REV- 10+21.21 TO 11+71.21	21327				21327	2		2	2			21325		21325
SUBTOTAL	279785	145033			134752	2746	1653	762	2530	212	143380	134087		277467
-L- 324+80 TO 333+80 LT	164575	57244			107331	3255	2713		2713		54532	107331		161863
-D14REV- 10+28.00 TO 12+05.83	44745	4089			40656	1	1		1		4088	40656		44744
-Y32- 10+00.000 TO 10+59.314	2318				2318	618		618	711			1607		1607
-Y33- 10+15.00 TO 10+70.08	118				118	677		677	779	661				
SUBTOTAL	211756	61333			150423	4551	2713	1295	4203	661	58620	149594		208214
-L- 333+80 TO 342+80 LT	182266	86351			95915	4504	3753		3753		82598	95915		178513
-Y35- 10+64.255 TO 11+15.981	1313				1313	63		63	73			1240		1240
SUBTOTAL	183579	86351			97228	4567	3753	63	3826		82598	97155		179753
-L- 342+80 TO 345+60 LT	95656	21160			74496	116	97		97		21063	74496		95559
-D15REV- 10+02.00 TO 10+67.24	12098				12098	50		50	58			12041		12041
SUBTOTAL	107754	21160			86594	166	97	50	154		21063	86537		107600
TOTAL LEFT	916877	336905			579972	68794	14381	51537	73649	40885	322524	561590		884114
-L- 226+40 TO 235+40 RT	4439				4439	35479		35479	40801	36362				
-D1- 10+11.165 TO 10+56.000	7				7	2116		2116	2433	2426				
-Y2- 10+09.935 TO 10+83.900	478				478	311		311	358			120		120
-D22- 10+04.420 TO 10+71.14	23				23	6		6	8			15		15
SUBTOTAL	4947				4947	37912		37912	43600	38788		135		135
-L- 235+40 TO 244+40 RT	46252	3440			42812	7139	3440	3011	6903			39349		39349
-D2- 10+10.00 TO 11+56.167	951				951	10		10	12			940		940
-Y4- 10+10.177 TO 11+34.000	952				952	1736		1736	1996	1044				
-Y5- 11+15.907 TO 11+93.760	399				399	230		230	265			135		135
SUBTOTAL	48554	3440			45114	9115	3440	4987	9175	1044		40423		40423
-L- 244+40 TO 253+40 RT	39653	4216			35437	4102	3418		3418		798	35437		36235
-D23- 10+11.025 TO 10+54.95						965		965	1110	1110				
-Y7- 10+09.883 TO 10+40.720	35				35	251		251	289	254				
SUBTOTAL	39688	4216			35472	5318	3418	1216	4817	1363	798	35437		36235
-L- 253+40 TO 262+40 RT	1349				1349	4135		4135	4755	3406				
-D3- 10+14.63 TO 10+42.00	53				53	104		104	120	67				
-D4REV- 10+13.350 TO 10+35.000	17				17	81		81	93	76				
-Y10- 10+81.191 TO 11+40.912	174				174	233		233	268	94				
SUBTOTAL	1593				1593	4553		4553	5236	3643				
-L- 262+40 TO 271+40 RT	3579	166			3413	2019	166	1820	2259			1320		1320
-Y11- 10+80.125 TO 11+38.355	155				155	12		12	14			141		141
-Y12- 10+78.902 TO 11+15.000	178				178	22		22	25			153		153
-Y13- 10+11.026 TO 10+30.377	2				2	41		41	47	45				
SUBTOTAL	3914	166			3748	2094	166	1895	2345	45		1614		1614
-L- 271+40 TO 280+40 RT	49818	3787			46031	630	525		525		3262	46031		49293
-Y16- 10+11.414 TO 10+90.198	8463				8463	29		29	33			8430		8430
-Y17- 11+69.832 TO 13+40.000	240				240	473		473	544	304				
SUBTOTAL	58521	3787			54734	1132	525	502	1102	304	3262	54461		57723
-L- 280+40 TO 289+40 RT	22671	15549			7122	3276	2730		2730		12819	7122		19941
-Y18- 10+11.034 TO 10+31.000	45				45	131		131	151	106				
-Y20- 10+11.029 TO 10+72.980	55				55	553		553	636	581				
SUBTOTAL	22771	15549			7222	3960	2730	684	3517	687	12819	7122		19941
-L- 289+40 TO 298+40 RT	1655				1655	11805		11805	13576	11921				
-D5- 10+14.63 TO 10+57.28	11				11	126		126	145	134				
SUBTOTAL	1666				1666	11931		11931	13721	12055				
-L- 298+40 TO 307+40 RT	54037				54037	3412		3412	3924			50113		50113
-Y25- 10+09.87 TO 10+69.02	136				136	22		22	25			111		111
-D6- 10+11.03 TO 10+42.00	232				232							232		232
-Y26- 11+38.531 TO 12+63.347	768				768	208		208	239			529		529
SUBTOTAL	55173				55173	3642		3642	4188			50985		50985
-L- 307+40 TO 316+40 RT	12989	628			12361	14607	628	13853	16559	3570				
-D18- 10+10.13 TO 10+24.14	9				9							9		9
-Y27- 10+09.917 TO 10+95.550	1183				1183	1230		1230	1415	232				
-D8- 10+48.83 TO 10+58.00	48				48							48		48
-D9- 10+11.03 TO 10+45.00	355				355	25		25	29			326		326
-D16- 10+09.83 TO 10+45.00						133		133	153	153				
-D10- 10+10.00 TO 10+42.52	220				220	1		1	1			219		219
SUBTOTAL	14804	628			14176	15996	628	15242	18157	3955		602		602
-L- 316+40 TO 324+80 RT	1254	56			1198	483	56	416	534			720		720
SUBTOTAL	1254	56			1198	483	56	416	534			720		720
-L- 324+80 TO 333+80 RT	1940				1940	1188		1188	1366			574		574
-Y31- 10+09.841 TO 10+58.994	5				5	173		173	199	194				
SUBTOTAL	1945				1945	1361		1361	1565	194		574		574
-L- 333+80 TO 342+80 RT	1987				1987	118		118	136			1851		1851
-Y34- 10+10.082 TO 10+89.563	118				118	484		484	557	439				
-Y36- 10+09.829 TO 11+39.000	5062				5062	1487		1487	1710			3352		3352
SUBTOTAL	7167				7167	2089		2089	2402	439		5203		5203
-L- 342+80 TO 345+60 RT	7073	1529			5544	1749	1458		1458		72	5544		5616
SUBTOTAL	7073	1529			5544	1749	1458		1458		72	5544		5616
TOTAL RIGHT	269070	29371			239699	101335	12421	86430	111817	62517	16951	202820		219770
SHEET TOTAL:	1185947	366276			819671	170129	26802	137967	185465	103402	339475	764409		1103884
TOTAL:	1185947	366276			819671	170129	26802	137967	185465	103402	339475	764409		1103884
Loss Due to Clearing & Grub	-10000				-10000							-10000		-10000
Rock to Repl. Borrow							74929			-74929	-74929			-74929
Adjustment to Rock Borrow									-28473	-28473				
GRAND TOTAL:	1175947	366276			809671	170129	101731	137967	156992		264545	754409		1018955
SAY:	1176000													

EST. SHALLOW UNDERCUT: 2000 CM
EST. CLASS IV SUBGRADE STABILIZATION: 4300 METRIC TONS
SHOULDER BORROW: 27090 CM

Earthwork quantities are calculated by the Roadway Design Unit. These earthwork quantities are based in part on subsurface data provided by the Geotechnical Engineering Unit.

RDTOSIC

PROJECT REFERENCE NO. | SHEET NO. 36 of 238

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	4 of 238
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER | HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____

R/W REV. _____

5 0 10

NAD 83

GARY ADKINS
DB 209 PG 755

CHRISTOPHER WARREN COOPER
DB 288 PG 695

DENNIS WOODY
DB 135 PG 360

ARNOLD MCINTOSH
DB 207 PG 806

GEORGE W. ROBERTS
DB 139 PG 607

MACK WHITSON
DB 220 PG 239

RIVERSIDE BAPTIST CHURCH
DB 164 PG 71

JOHN A. COOPER
DB 137 PG 463

NORMAN J. RABEK
DB 297 PG 205

ESTEL HIGGINS
DB 139 PG 553

BOYD WHEELER
DB 202 PG 672

TANKS
2SBKD
2SF&BK BUS
MTL CANOPY
EXISTING R/W
R/W MON
EIP
DK
225
226
227
POT Sta. 224+30.000
BAPT CHURCH
1SBK
1800mm CONC
900mm CONC
1200mm WD RAIL
REBAR
1SBKD
2SFAPT
WALL
1300mm WD & WW
1300mm WD RAIL
1300mm WW
1S ELEC
MTL GATE
SFD ABAND
CONC
SILO
BST
B
N 81°00'16.0" E -L-
STA. 226+40 -L- BEGIN STATE PROJ. R-2519A
TS Sta. 226+85.636
SC Sta. 227+05.636
MATCHLINE -L- STA. 227+20 SEE SHEET NO. 5

-L-

PIs Sta. 226+85.636	PI Sta. 227+14.312	PIs Sta. 227+42.988
θs = 0° 51' 34.0"	Δ = 0° 29' 49.5" (RT)	θs = 0° 51' 34.0"
Ls = 60.000	L = 17.352	Ls = 60.000
LT = 40.000	T = 8.676	LT = 40.000
ST = 20.000	R = 2,000.000	ST = 20.000
	SE = 03	

FOR -L- PROFILE SEE SHEET 44

METRIC

5 0 10

NAD 83

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	5 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION



-L-

PIs Sta 226+85.636	PI Sta 227+14.312	PIs Sta 227+42.988
θs = 0°51' 34.0"	Δ = 0°29' 49.5" (RT)	θs = 0°51' 34.0"
Ls = 60.000	L = 17.352	Ls = 60.000
LT = 40.000	T = 8.676	LT = 40.000
ST = 20.000	R = 2,000.000	ST = 20.000
	SE = 03	

FOR -L- PROFILE SEE SHEET 44

METRIC

5 0 10

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	60 OF 238
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____

R/W REV. _____

NAD 83

-L-

PIs Sta. 231+35.483
Θs = 1° 46' 19.3"
Ls = 60.000
LT = 40.002
ST = 20.002

PI Sta. 232+53.744
Δ = 11° 34' 07.8" (RT)
L = 195.857
T = 98.263
R = 970.000
SE = 04

PIs Sta. 233+71.340
Θs = 1° 46' 19.3"
Ls = 60.000
LT = 40.002
ST = 20.002

POT -L- Sta. 233+69.591
POT -Y2- Sta. 10+00.000

231 232 233 234

1½SFD
200mm WD RAIL
WALL
HTR
S
ISFD
800mm WD RAIL
800mm WD WALL
GATE
ISBKO
C
10

MATCHLINE -L- STA. 230+60 SEE SHEET NO. 5

MATCHLINE -L- STA. 234+00 SEE SHEET NO. 7

230+80
29 m rt

233+20
15 m rt

POSSTIES

TSSta. 230+95.481

SCSta. 231+55.481

1200mm CML

† CEM

CSSta. 233+51.338

PCSta. 10+15.711

BEARING BACK = S 1° 02' 00.0" E

HTR

DK

45BM

-Y2-

PI Sta. 10+41.186
Δ = 75° 20' 00.0" (LT)
L = 43.389
T = 25.475
R = 33.000
SE = SEE PLANS

FOR -L- PROFILE SEE SHEET 45
FOR -Y2- PROFILE SEE SHEET 62

METRIC

5 0 10

NAD 83

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	7 of 236
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

234 235 236 237

-L-

PIs Sta. 231+35.483
Θs = 1° 46' 19.3"
Ls = 60.000
LT = 40.002
ST = 20.002

PI Sta. 232+53.744
Δ = 11° 34' 07.8" (RT)
L = 195.857
T = 98.263
R = 970.000
SE = 04

PIs Sta. 233+71.340
Θs = 1° 46' 19.3"
Ls = 60.000
LT = 40.002
ST = 20.002

-Y3-

PI Sta. 11+05.865
Δ = 32° 48' 03.1" (LT)
L = 114.497
T = 58.865
R = 200.000
SE = SEE PLANS

PT Sta. 11+61.497
BEARING AH = S 23° 48' 26.9" W

MATCHLINE -Y3- STA. 11+40 SEE SHEET NO. 40

POT -L- Sta. 237+14.259
POT -Y3- Sta. 11+81.89
POT -Y4- Sta. 10+00.000

MATCHLINE -L- STA. 234+00 SEE SHEET NO. 6

MATCHLINE -L- 237+40 SEE SHEET NO. 8

-L- S 81° 40' 00.0" E

ST Sta. 234+11.338

-Y2- S 76° 22' 00.0" E

POT/-L- Sta. 236+63.500
POT -D2- Sta. 10+00.000
BEARING AH = S 8° 19' 59.9" W

PC Sta. 10+15.261

PT Sta. 10+33.03

PC Sta. 10+41.07

S 12° 06' 46.8" E -D2-

PC Sta. 10+58.167
BEARING BACK = S 23° 26' 58.4" W

PT Sta. 10+73.025
BEARING AH = S 3° 07' 37.1" W

PC Sta. 10+93.976

PT Sta. 11+21.493
BEARING AH = S 49° 07' 00.9" E

PT Sta. 11+13.352
BEARING AH = S 33° 52' 42.7" E

PC Sta. 11+16.874

PT Sta. 11+31.624
BEARING AH = S 5° 42' 26.4" E

POT -D2- Sta. 11+33.89

-Y4-

END CONST.
POT -Y4- Sta. 11+34.000

POT Sta. 11+38.561

END CONST.
POT -Y2- Sta. 10+83.900

PT Sta. 10+59.00

-Y2-
PI Sta. 10+41.86
Δ = 75° 20' 00.0" (LT)
L = 43.389
T = 25.475
R = 33.000
SE = SEE PLANS

POT Sta. 12+02.780 -Y2-

-D2-

PI Sta. 10+24.278	PI Sta. 10+57.161	PI Sta. 11+04.015	PI Sta. 11+24.401
Δ = 20° 26' 46.7" (LT)	Δ = 15° 14' 23.9" (RT)	Δ = 37° 00' 19.8" (LT)	Δ = 28° 10' 16.3" (RT)
L = 17.843	L = 31.919	L = 19.376	L = 14.750
T = 9.017	T = 16.054	T = 10.039	T = 7.527
R = 50.000	R = 120.000	R = 30.000	R = 30.000
SE = SEE PLANS	SE = SEE PLANS	SE = SEE PLANS	SE = SEE PLANS

-Y4-
PI Sta. 10+94.873
Δ = 72° 33' 59.4" (LT)
L = 63.326
T = 36.706
R = 50.000
SE = SEE PLANS

FOR -L- PROFILE SEE SHEET 45
FOR -Y3- & -Y4- PROFILE SEE SHEET 62

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	8 of 238
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

5 0 10

CONST.REV. _____

R/W REV. _____

NAD 83

MATCHLINE -L- STA. 237+40 SEE SHEET NO. 7

MATCHLINE -L- STA. 240+80 SEE SHEET NO. 9

238 BST

239

240

TS Sta. 238+63.36

SC Sta. 238+63.36

CHURCH

1200mm CONC

1000mm WD RAIL

S 81° 40' 00.1" E

-L-

1600mm WW

238+40
20 m rt

239+20
28 m rt

POC -L- Sta. 239+77.400
POC -D3- Sta. 10+00.000

POT -D3- Sta. 10+46.768

S 20° 50' 34.3" E

ISBLK BUS

BST

GR

2000mm CHL

375mm CMP

EOP
EOT 12 BST
US 19E 7.3 BST
EOT 09 BST
EOP

1800mm CHL

LOADING RAMP

GATE

1200mm WD RAIL

CONC

ISF

ISF& CONC STND

MTL LT

BASEBALL FIELD

BLEACHERS

ISFD

CROSSTIES

W/LT

-L-

PIs Sta 238+43.362	PI Sta 240+68.553	PIs Sta 242+91.981
θs = 0° 57' 17.7"	Δ = 13° 00' 24.4" (LT)	θs = 0° 57' 17.7"
Ls = 60.000	L = 408.620	Ls = 60.000
LT = 40.001	T = 205.192	LT = 40.001
ST = 20.001	R = 1,800.000	ST = 20.001
	SE = 03	

FOR -L- PROFILE SEE SHEET 46

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	9 of 238
R/W SHEET NO.	

5 0 10

CONST.REV. _____

R/W REV. _____

NAD 83

POT Sta.10+00.000

BEGIN CONST.
POT -Y5- Sta.10+17.709

-Y5-
S 11°17'00.0" E

POC -L- Sta.241+20.206
POT -Y5- Sta.11+05.916

ROCK

CSSta.242+71.981

ST Sta.243+31.981

N 83°25'00.0" E

241 242 243 244

SR 1186 W BURNSVILLE CHURCH CREEK RD 5.9 BST

US 19E 7.3 BST

MATCHLINE -L- STA. 240+80 SEE SHEET NO. 8

MATCHLINE -L- STA. 244+20 SEE SHEET NO. 10

PCSta.11+46.648

END CONST.
POC -Y5- Sta.11+93.760
PTSta.12+13.808

-Y5-
PI Sta 11+80.449
Δ = 16°02'00.0" (LT)
L = 67.160
T = 33.801
R = 240.000
SE = SEE PLANS

-L-

PIs Sta 238+43.362	PI Sta 240+68.553	PIs Sta 242+91.981
Θs = 0°57'17.7"	Δ = 13°00'24.4" (LT)	Θs = 0°57'17.7"
Ls = 60.000	L = 408.620	Ls = 60.000
LT = 40.001	T = 205.192	LT = 40.001
ST = 20.001	R = 1,800.000	ST = 20.001
	SE = 03	

FOR -L- PROFILE SEE SHEET 46
FOR -Y5- PROFILE SEE SHEET 63

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	10 OF 23
R/W SHEET NO.	

5 0 10

CONST.REV. _____

R/W REV. _____

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

NAD 83

SR 1438 CHARLIE BROWN RD 5.8 BST

475mm CMP

750mm

4SBW

245

246

247

B

SILO

WD RAIL

1800mm CROSSTIES WALL

1200mm CML

1200mm WD RAIL

3SBW

W/LT

I/4SFD

ISFD

RK AND WEATHERED RK

ROCK

MTL

EOP

EOT 1.5 BST

EOT 0.9 BST

US 19E 7.0 BST

450mm CMP

MATCHLINE -L- STA. 244+20 SEE SHEET NO. 9

MATCHLINE -L- STA. 247+60 SEE SHEET NO. 11

TSSta. 244+28.375

SCSta. 244+88.375

CSSta. 247+45.133

246+00
25 m rt

247+00
33 m rt

IS ELEC

GR

3.4 BST

t_{CEM}

MTL GATES

TWR

ISBKO

CONC

S

-L-

PIs Sta 244+68.377	PI Sta 246+17.246	PIs Sta 247+65.134
θs = 1° 25' 56.6"	Δ = 12° 15' 33.4" (RT)	θs = 1° 25' 56.6"
Ls = 60.000	L = 256.758	Ls = 60.000
LT = 40.001	T = 128.871	LT = 40.001
ST = 20.001	R = 1,200.000	ST = 20.001
	SE = 04	

FOR -L- PROFILE SEE SHEET 47

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	11 OF 238
R/W SHEET NO.	

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

NAD 83

POT Sta.10+00.000

SR 1439 CHARLIE BROWN RD 6.2 BST

-Y6-

BEGIN CONST.
POT -Y6- Sta.10+50.340

S 16° 56' 00.0" E

248

249

250

251

TREE FARM

ISBKD

ISFD

750mm CONC

450mm CMP

POT -L- Sta.248+51.546
POT -Y6- Sta.11+40.997

TS Sta.249+68.230

SC Sta.250+28.230

MTL

US 19E

BST

S 81° 27' 33.3" E

-L-

GR

MATCHLINE -L- STA. 247+60 SEE SHEET NO. 10

MATCHLINE -L- STA. 251+00 SEE SHEET NO. 12

450mm CMP

3SBW

St Sta.248+05.33

HTR

HTRBUS

W/LT

750mm CMP

1100mm BLK WALL

FUEL TANKS

CONC

ISFD

600mm CONC

ISBLKBUS

SR 1139 PINE SWAMP RD

N 87° 12' 00.0" W

SR 1196 W BURNSVILLE CHURCH CREEK RD 7.0 BST

2.8 BST

POT Sta.11+80.420 -Y7-

PIs Sta 244+68.377	PI Sta 246+17.246	PIs Sta 247+65.134	PIs Sta 250+08.231	PI Sta 250+89.963	PIs Sta 251+71.604
θs = 1° 25' 56.6"	Δ = 12° 15' 33.4" (RT)	θs = 1° 25' 56.6"	θs = 1° 19' 20.0"	Δ = 5° 26' 15.0" (LT)	θs = 1° 19' 20.0"
Ls = 60.000	L = 256.758	Ls = 60.000	Ls = 60.000	L = 123.373	Ls = 60.000
LT = 40.001	T = 128.871	LT = 40.001	LT = 40.001	T = 61.733	LT = 40.001
ST = 20.001	R = 1,200.000	ST = 20.001	ST = 20.001	R = 1,300.000	ST = 20.001
	SE = 04			SE = 04	

FOR -L- PROFILE SEE SHEET 47
FOR -Y6- PROFILE SEE SHEET 63

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	12 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83



-Y7-

PI Sta 10+34.741
Δ = 98°01'00.0" (RT)
L = 51.321
T = 34.521
R = 30.000
SE = SEE PLANS

-L-

PIs Sta 250+08.231	PI Sta 250+89.963	PIs Sta 251+71.604
θs = 1°19'20.0"	Δ = 5°26'15.0" (LT)	θs = 1°19'20.0"
Ls = 60.000	L = 123.373	Ls = 60.000
LT = 40.001	T = 61.733	LT = 40.001
ST = 20.001	R = 1,300.000	ST = 20.001
	SE = 04	

FOR -L- PROFILE SEE SHEET 48
FOR -Y7- PROFILE SEE SHEET 63
FOR -Y8- PROFILE SEE SHEET 64

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	13 of 238
R/W SHEET NO.	

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

NAD 83

-Y9-
PI Sta 11+03.917
Δ = 63° 20' 48.5" (LT)
L = 149.257
T = 83.291
R = 135.000
SE = SEE PLANS

PCSta.10+20.626

POTSta.10+00.000

S 86° 15' 06.9" W

BURNSVILLE CITY LIMITS

POTSta.10+00.000
BEARING AH = S 11° 10' 00.0" E

BEGIN CONST.
POT -Y10- Sta.10+06.458

255

256

257

2SFBUS

1SFBUS

R=35

R=15

DI

BST

SR 1428

70
450mm CMP TAPER
LT & RT EP TAPER

GATE

1800mm CHL & 3SBW

BEGIN CONST.
POC -Y9- Sta.10+47.000

CONC WHEEL GUARDS

PTSta.11+69.883

PCSta.255+23.530

POT -L- Sta.254+43.469
POT -Y9- Sta.11+80.000

PROP.200X450 mm CONCRETE CURB

1200mm BLK WALL

FUEL TANK

CONC

W/LT

TRUCK SCALES

POC -L- Sta.257+52.804
POT -Y10- Sta.10+70.161

LT & RT EP TAPER

1800mm CHL & 3SBW

CHERRY LN

-Y10-

MATCHLINE -L- STA. 254+40 SEE SHEET NO.12

MATCHLINE -L- STA. 257+80 SEE SHEET NO. 14

S 22° 54' 18.4" W

S 89° 32' 28.5" E

-L-

CONC ISL

US 19 E

107 BST 12 BST EOT EOP

12 BST EOT EOP

MTL

PROP.200X450 mm CONCRETE CURB

1000mm BLK WALL

MTL TANKS 2 - 6883 L

ISF&BLKBUS

2SLOGSBUS

CONC

HTR

WD DK

7.2 DR

GR

450mm WD RAIL

POC -L- Sta.256+22.620
POT -D5- Sta.10+00.000

S 28° 25' 56" E

1500mm CMP

900mm CMP

800mm WD RAIL

HTR

CONC

END GRADE
-D5- 10+45

POT -D- Sta.10+45.090

1200mm CHL

256+60
26 m rt

PROPOSED RETAINING WALL

257+00
19 m rt

PCSta.10+71.330

450mm CMP

SR 1439

64 BST

PTSta.11+35.617
BEARING AH = S 39° 30' 00.0" E

END CONST.
POT -Y10- Sta.11+40.912

PCSta.11+44.243

PTSta.11+71.793

-L-
PI Sta 256+63.645
Δ = 17° 41' 52.6" (LT)
L = 277.999
T = 140.115
R = 900.000
SE = 03

-Y10-

PI Sta 11+04.145	PI Sta 11+58.050
Δ = 28° 20' 00.0" (LT)	Δ = 9° 34' 00.0" (LT)
L = 64.286	L = 27.550
T = 32.815	T = 13.807
R = 130.000	R = 165.000
SE = SEE PLANS	SE = SEE PLANS

FOR -L- PROFILE SEE SHEET 48
FOR -Y9- & -Y10- PROFILE SEE SHEET 64

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	14 of 138
R/W SHEET NO.	

5 0 10

CONST.REV. _____

R/W REV. _____

NAD 83

MATCHLINE -L- STA. 257+80 SEE SHEET NO. 13

MATCHLINE -L- STA. 261+20 SEE SHEET NO. 15

258 259 260 261

PT Sta.258+01.428

ISF

ISBLK&FBUS

S

GR

ISF BUS

BST

CONC

ISBK&BLK BUS

ISBK BUS

CONC

ISMTL BUS

POT -D8- Sta.10+00.000
BEARING AH = S 17° 14' 20.6" E

ISBLK&MTLBUS

POT -D9- Sta.10+00.000
BEARING AH = S 20° 29' 12.9" E

D1 1200mm CMP

POT -D7- Sta.10+00.000
BEARING AH = S 25° 46' 35.5" E

POT -L- Sta.260+16.370
POT -D8- Sta.10+36.000

POT -L- Sta.258+93.950
POT -D7- Sta.10+27.609

POT -L- Sta.260+87.607
POT -D9- Sta.10+37.309

POT

POT

-D7-

-80-

-80-1

1200mm CMP

1200mm CML

600mm CMP

-L-

N 72° 45' 39" E

US 19 E 107 BST

450mm CMP

250mm CMP

10 BST

C F

CURB

200mm BST CURB

200mm CONC CURB

-90-

POT -L- Sta.260+07.000
POT -D6- Sta.10+00.000
BEARING AH = S 11° 16' 59.5" E

POT -D6- Sta.10+33.754

W/LT

LT

ISMTLBUS

ISBLKBUS

CONC

POT Sta.11+95.659

S 49° 04' 00.0" E

-L-
PI Sta 256+63.645
Δ = 17° 41' 52.6" (LT)
L = 277.999
T = 140.115
R = 900.000
SE = 03

FOR -L- PROFILE SEE SHEET 49

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	15 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

262

263

264

BEGIN CONST.
POT -Y11- Sta.10+26.868

POT Sta.10+00.000

POT -D10- Sta.10+00.000

POT -D11- Sta.10+00.000

POT -L- Sta.261+89.441
POT -D11- Sta.10+36.000

POT -L- Sta.262+64.905
POT -Y11- Sta.10+69.081

-L- Sta.261+61.733
-D10- Sta.10+36.000

N 72° 45' 39" E -L-

S 17° 14' 21" E -D10-

S 17° 14' 19" E -D11-

S 13° 54' 00" E -Y11-

POT -L- Sta.263+00.368
POT -D12- Sta.10+00.000
BEARING AH = S 9° 58' 10.4" E

POT -D12- Sta.10+20.477

PC Sta.263+20.277

POT Sta.11+44.400

END CONST.
POT -Y11- Sta.11+38.355

MATCHLINE -L- STA. 261+20 SEE SHEET NO. 14

MATCHLINE -L- STA. 264+60 SEE SHEET NO. 16

-L-
PI Sta 263+94.812
Δ = 4° 16' 06.9" (RT)
L = 149.002
T = 74.535
R = 2,000.000
SE = 02

FOR -L- PROFILE SEE SHEET 49
FOR -Y11- PROFILE SEE SHEET 65

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	16 OF 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

METRIC

5 0 10

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____

R/W REV. _____

NAD 83

POT Sta.10+00.000

BEGIN CONST.
POT -Y12- Sta.10+19.000

BST PCSta.10+33.489
BEARING BACK = S 6° 17' 00.0" E

PTSta.10+53.019

POT -L- Sta.264+80.870

POT -Y12- Sta.10+67.295

-Y12- S 37° 09' 00.0" E

N 77° 01' 46.0" E

-L-

PCSta.10+89.686

POT -L- Sta.266+16.325

POT -DI3- Sta.10+00.000
BEARING AH = S 12° 44' 43.2" E

POT -DI3- Sta.10+19.268

END CONST.
POT -Y12- Sta.11+15.000

PTSta.11+22.527

PCSta.264+69.279

PCSta.267+47.318

267+55
31 m RT

267+20
38 m rt

268+00
25 m rt

MATCHLINE -L- STA. 264+60 SEE SHEET NO. 15

MATCHLINE -L- STA. 268+00 SEE SHEET NO. 17

E.WEST BLVD

-Y12-	
PI Sta 10+43.410	PI Sta 11+06.115
Δ = 24° 52' 00.0" (LT)	Δ = 7° 32' 00.0" (RT)
L = 19.530	L = 32.870
T = 9.921	T = 16.459
R = 45.000	R = 250.000
SE = SEE PLANS	SE = SEE PLANS

-L-	
PI Sta 263+94.812	PI Sta 268+55.992
Δ = 4° 16' 06.9" (RT)	Δ = 20° 52' 23.1" (RT)
L = 149.002	L = 214.939
T = 74.535	T = 108.674
R = 2,000.000	R = 590.000
SE = 02	SE = 03

FOR -L- PROFILE SEE SHEET 50
FOR -Y12- PROFILE SEE SHEET 65

$$$$$$SYSTIME$$$$$
$$$$$$USERNAME$$$$$
$$$$$$

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	17 OF 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____

R/W REV. _____

NAD 83

5 0 10

268

269

270

271

BEGIN CONST.
POT -Y14- Sta.10+31.355

POT Sta.10+00.000

PC Sta.10+12.576

PT Sta.10+25.866

BEARING AH = S 2° 02' 52.7" E

S 5° 34' 00.2" W

-Y14-

269+62

270+17
20m LT

270+84
15m LT

S 82° 05' 50.9" E

-L-

-Y13-

S 5° 59' 40.0" W

POC -L- Sta.268+83.253
POT -Y13- Sta.10+00.000
POT -Y14- Sta.10+59.825

END CONST.
POT -Y13- Sta.10+30.377

POT Sta.10+65.176

PT Sta.269+62.257

MATCHLINE -L- STA. 268+00 SEE SHEET NO. 16

MATCHLINE -L- STA. 271+40 SEE SHEET NO. 18

2SFBUS
3SFBUS
2SFD
2SBKBUS
1SFBUS
1SBK&BLKBUS
2SBK&BLKBUS
ISM&FBUS
UNDER CONSTRUCTION

S. MAIN ST
E. WEST BLVD
PROPOSED RETAINING
PROP. 200x450 mm CONCRETE CURB
200mm BST CURB
1200mm CONC
600mm CONC C&G
450mm CONC C&G
1500mm STEEL
600mm CMP
1500mm CMP
1200mm WD RAIL
1000mm WD RAIL
800mm WD RAIL
300mm CONC WALL & MTL RAIL
200mm CONC CURB
2300mm WD
300mm CMP
BST
CONC
GR
MTL
W/LT
W/SIG LT
EOP W/SIG LT
EOT
EP TAPER
RT EP TAPER
LT P TAPER
DR
CB
CONC HW
BOW DITCH
ST

-Y14-

PI Sta. 10+19.231
Δ = 7° 36' 52.7" (LT)
L = 13.290
T = 6.655
R = 100.000
SE = SEE PLANS

-L-

PI Sta. 268+55.992
Δ = 20° 52' 23.1" (RT)
L = 214.939
T = 108.674
R = 590.000
SE = 03

FOR -L- PROFILE SEE SHEET 50
FOR -Y13- & -Y14- PROFILE SEE SHEET 65

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

NAD 83

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	18 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION



FOR -L- PROFILE SEE SHEET 51

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	19 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

MATCHLINE -L- STA. 274+80 SEE SHEET NO. 18

MATCHLINE -L- STA. 278+20 SEE SHEET NO. 20

275 276 277 278

POT -L- Sta. 275+15.421

POT -Y16- Sta. 10+00.000

PCSta. 278+08.028

276+20 22m LT

277+60 21m LT

278+00 21m LT

PROPOSED RET. WALL

S 82° 05' 50.9" E

-L-

S 14° 14' 31.5" E

-Y16-

PCSta. 10+06.300

BEARING BACK
S 2° 05' 52.3" E

PTSta. 10+19.017

PCSta. 10+59.704

PTSta. 10+85.953

END CONST.
POC -Y16- Sta. 10+85.953

ISBKBUS

ISROCKBUS

ISFD

ISBLKD

ISBLK

ISBLKBU

DK

ISFD

CONC

CONC WALL

REPEATER

200mm BST CURB

375mm CMP

376mm CMP

200 mm

2000mm CONC

100mm CONC

100mm CONC CURB

2700mm CONC WALL

1200mm BLK WALL

2200mm BLK WALL

BST

GR

F

S

LT

W/LT

EOT

EOP

MTL

US 19E

107 BST

12 BST

06 BST

37 BST

44 BST

42 BST

-Y16-

PI Sta 10+12.683
Δ = 12° 08' 39.2" (LT)
L = 12.717
T = 6.383
R = 60.000
SE = SEE PLANS

PI Sta 10+74.184
Δ = 60° 09' 31.5" (RT)
L = 26.249
T = 14.480
R = 25.000
SE = SEE PLANS

-L-

PI Sta 279+24.981
Δ = 18° 42' 28.0" (LT)
L = 231.824
T = 116.953
R = 710.000
SE = 03

FOR -L- PROFILE SEE SHEET 51
FOR -Y16- PROFILE SEE SHEET 65

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	20 of 23
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

-Y17-

PI Sta 10+54.183
Δ = 15° 50' 00.0" (RT)
L = 45.597
T = 22.945
R = 165.000
SE = SEE PLANS

PI Sta 11+31.039
Δ = 24° 06' 00.0" (RT)
L = 60.991
T = 30.953
R = 145.000
SE = SEE PLANS

PI Sta 12+03.510
Δ = 2° 22' 00.0" (RT)
L = 41.306
T = 20.656
R = 1,000.000
SE = SEE PLANS

BEGIN CONST.
POT -Y17- Sta.*******

POT Sta.10+00.000

PC Sta.10+31.839

POC -L- Sta.279+42.984
POT -Y17- Sta.10+88.788

279+30
39m LT

PT Sta.10+76.835

PC Sta.11+00.086

279+60
23m LT

PT Sta.280+39.852

S 0° 23' 00.0" W

N 79° 11' 41.1" E

-L-

PROP. RET. WALL

PROP. RET. WALL

MATCHLINE -L- STA. 278+20 SEE SHEET NO. 19

MATCHLINE -L- STA. 281+60 SEE SHEET NO. 21

MATCHLINE -Y17- STA. 11+60 SEE SHEET NO. 41

ROCK

279

280

281

BUS

JS

BST

ISD

1950mm STONE

BENS CRK RD SR 1402

5.5 BST

W/L

US 19E

107 BST

EOT

0.9 BST

0.6 BST

7.3 BST

600mm CMP

375mm CMP

150mm CONC CURB

ISBKBUS

1400mm CONC

CONC

MTL CANOPY

GAS

1324.9

ISBL.KBUS

1200mm CMP

CONC. HW

6.1 BST

ISFBUS

1800mm CHL

HTR

HTRBUS

W/LT

W/SIGLT

2-3.8 W LB RCBC

GR

4SBW

ISBL.K&FBUS

2SBL.K&FBUS

1500mm CMP

450mm CMP

-L-
PI Sta 279+24.981
Δ = 18° 42' 28.0" (LT)
L = 231.824
T = 116.953
R = 710.000
SE = 03

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	21 of 238
R/W SHEET NO.	

5 0 10

CONST.REV. _____

R/W REV. _____

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

-Y19-
PI Sta. 11+16.931
Δ = 73° 41' 00.0" (RT)
L = 51.441
T = 29.969
R = 40.000
SE = SEE PLANS

NAD 83

282 283 284 285

POT Sta. 10+00.000

BEGIN CONST.
POT -Y19- STA. **********

-Y19-
S 86° 48' 00.0" E

PCSta. 10+86.962

MATCHLINE -L- STA. 281+60 SEE SHEET NO. 20

MATCHLINE -L- STA. 285+00 SEE SHEET NO. 22

284+85
15m LT

284+96
5m RT

F

C

10

N 79° 11' 41.3" E

-L-

10

POT -L- Sta. 282+12.100
POT -D15- Sta. 10+00.000
BEARING AH = S 10° 48' 18.9" E

POT -L- Sta. 283+38.350
POT -D16- Sta. 10+00.000
BEARING AH = S 10° 48' 19.0" E

-D15-

PCSta. 10+18.604

PTSta. 10+28.540
BEARING AH = S 33° 34' 31.2" E

POT -D15- Sta. 10+44.504

ROCK

PCSta. 10+15.014

S 76° 39' 13.0" E

PTSta. 10+38.000

POT -D16- Sta. 10+59.077

-D15-	-D16-
PI Sta. 10+23.638	PI Sta. 10+27.965
Δ = 22° 46' 18.3" (LT)	Δ = 65° 50' 54.0" (LT)
L = 9.936	L = 22.985
T = 5.034	T = 12.951
R = 25.000	R = 20.000

FOR -L- PROFILE SEE SHEET 52
FOR -Y19- PROFILE SEE SHEET 66

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	22 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

FOR -L- PROFILE SEE SHEET 53
FOR -Y18- & -Y19- PROFILE SEE SHEET 66
FOR -Y20- PROFILE SEE SHEET 67

-Y19-
PI Sta 11+16.931
Δ = 73° 41' 00.0" (RT)
L = 51.441
T = 29.969
R = 40.000
SE = SEE PLANS

-D16-
PI Sta 10+32.324
Δ = 74° 46' 34.7" (RT)
L = 26.102
T = 15.285
R = 20.000

PT Sta. 11+38.402

PC Sta. 10+17.040

POT -D17- Sta. 10+00.000

PC Sta. 285+86.257

PT Sta. 10+43.142

POT -D17- Sta. 10+61.585

POC -L- Sta. 285+87.180

BEARING BACK = S 10° 47' 53.7" E

S 85° 34' 28.4" E

-D17-

S 13° 07' 00.0" E

N 79° 11' 41.1" E

MATCHLINE -L- STA. 285+00 SEE SHEET NO. 21

MATCHLINE -L- STA. 288+40 SEE SHEET NO. 23

NAD 83

285

286

287

288

BURNSVILLE CITY LIMITS

2SMTLBUS

HTRBUS

ISMTL& RKBUS

MTL STOR TANK

CANOPY

GATE

ROCK BORDER

CONC STEPS

BUS

US 19E

US 19 E BUS

SR 1140

SR 1201

2100mm CHL & 3SBW

1750mm CHL & 3SBW

1350mm CONC

1200mm CMP

300mm CMP

750mm WD RAIL

600mm BLKWALL

1.2 BK HW

1.6 ROCK HW

200mm AST CURB

POT -L- Sta. 285+23.067
POT -Y18- Sta. 10+00.000
POT -Y19- Sta. *****

END CONST.
POT -Y18- Sta. 10+46.064
BEARING BACK = S 13° 07' 00.0" E

POT Sta. 10+54.069

-L-
PI Sta 286+87.870
Δ = 18° 55' 06.6" (LT)
L = 201.416
T = 101.633
R = 610.000
SE = 0.3

POC -L- Sta. 287+35.854
POT -Y20- Sta. 10+00.000

PT Sta. 287+87.653

S 26° 20' 00.0" E

END CONST.
POT -Y20- Sta. 10+72.980

POT Sta. 10+75.992

METRIC

5 0 10

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	230 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____

R/W REV. _____

MATCHLINE -Y21- STA. ##+##.000 SEE SHEET NO. 42

NAD 83

POT Sta.10+00.000

289

290

291

S 16° 50' 00.0" E

-Y21-

-L-

POC -L- Sta.290+24.562
POT -Y21-Sta.

ISMTL&BKBUS

N 60° 16' 34.5" E

289+70
15m RT

POT Sta.289+10.393

POWER SUB STATION

GRAU-350

36-12-36
1.5 OS

36-12-36
0.6 OS

4.0 CONC HW

3.0 CONC WW

1.0 4.6 CONC WW

W/SIGLT

W/LT

BST

GR

EOP

EOT

BLK HW

12 BST

09 BST

45 EP TAPER

90 TAPER

TAPER

MATCHLINE -L- STA. 288+40 SEE SHEET NO. 22

MATCHLINE -L- STA. 291+80 SEE SHEET NO. 24

SR 1329

-L-
PI Sta 292+26.933
Δ = 63° 09' 11.2" (RT)
L = 567.648
T = 316.540
R = 515.000
SE = 0.03

FOR -L- PROFILE SEE SHEET 53
FOR -Y21- PROFILE SEE SHEET 67

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	24 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

292

293

294

295

MATCHLINE -L- STA. 291+80 SEE SHEET NO. 23

MATCHLINE -L- STA. 295+20 SEE SHEET NO. 25

POT Sta.10+00.000
BEARING AH = S 7° 15' 00.0" W

BEGIN CONST.
POT -Y22- Sta.10+03.955

POC -L- Sta.293+34.800
POT -D18- Sta.10+00.000
BEARING AH = S 11° 29' 35.8" W

POC -L- Sta.294+54.665
POT -Y22- Sta.10+77.238

POC -L- Sta.294+63.040
POT -D20- Sta.10+00.000
BEARING AH = S 31° 45' 37.2" W

POC Sta.10+09.157

PT Sta.10+29.410
BEARING AH = S 11° 31' 01.1" E

PC Sta.10+33.946

PT Sta.10+43.161

POT -D18- Sta.10+59.796

POC -L- Sta 293+89.760
POT -D19- Sta.10+00.000
BEARING AH = S 23° 36' 27.5" W

POT -D19- Sta.10+30.000

POT -D20- Sta.10+30.000

PT Sta 294+78.042

S 56° 34' 14.3" E

S 01° 52' 25.1" E

-L-
PI Sta 292+26.933
Δ = 63° 09' 11.2" (RT)
L = 567.648
T = 316.540
R = 515.000
SE = 0.03

-D18-

PI Sta 10+19.505	PI Sta 10+38.567
Δ = 29° 00' 36.9" (LT)	Δ = 10° 33' 36.0" (RT)
L = 20.253	L = 9.215
T = 10.349	T = 4.621
R = 40.000	R = 50.000

FOR -L- PROFILE SEE SHEET 54
FOR -Y22- PROFILE SEE SHEET 67

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	25 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

-Y23-
PI Sta. 10+21.672
Δ = 2° 26' 30.5" (LT)
L = 17.047
T = 8.525
R = 400.000
SE = SEE PLANS

MATCHLINE -L- STA. 295+20 SEE SHEET NO. 24

MATCHLINE -L- STA. 298+60 SEE SHEET NO. 26

POT Sta.10+00.000
BRG AH = S 16° 04' 30.5" W

PC Sta.10+13.147

PT Sta.10+30.194
BRG AH = S 13° 38' 00.0" W

BEGIN CONST
POC -Y23- Sta.10+37.000

POT -L- Sta.296+25.000
POT -D23- Sta.10+00.000
BEARING AH = S 33° 25' 46.1" W

POT -L- Sta.296+16.540
POT -D22- Sta.10+00.000
BEARING AH = S 33° 25' 45.7" W

POT -L- Sta.295+60.000
POT -D21- Sta.10+00.000
BEARING AH
= S 33° 25' 52.5" W

POT -L- Sta.296+43.300
POT -D24- Sta.10+00.000
BEARING AH = S 32° 45' 18.1" W

POC -L- Sta.297+71.045
POT -Y23- Sta.10+88.792

POC -L- Sta.296+72.
POT -D25- Sta.10+00.000
BEARING AH = S 31° 39' 09.3" W

POC -L- Sta.297+75.300
POT -D26- Sta.10+00.000
BEARING AH = S 27° 42' 46.9" W

POT Sta.10+35.000

PC Sta.10+13.680

PT Sta.10+30.277

POT -D21- Sta.10+52.777

POT -D22- Sta.10+28.368

PC Sta.10+19.493

PT -D23- Sta.10+30.531

PC Sta.10+21.499

PT -D24- Sta.10+29.382

POT -D25- Sta.10+26.397

S 14° 06' 52.8" E

S 56° 34' 14.3" E

-D21-
PI Sta. 10+22.490
Δ = 47° 32' 45.3" (LT)
L = 16.597
T = 8.810
R = 20.000

-D23-
PI Sta. 10+26.536
Δ = 90° 21' 03.5" (LT)
L = 11.038
T = 7.043
R = 7.000

-D24-
PI Sta. 10+26.528
Δ = 90° 19' 25.8" (RT)
L = 7.882
T = 5.028
R = 5.000

-L-
PI Sta. 297+71.472
Δ = 11° 06' 19.7" (LT)
L = 290.740
T = 145.827
R = 1,500.000
SE = 0.02

FOR -L- PROFILE SEE SHEET 54
FOR -Y23- PROFILE SEE SHEET 67



FOR -L- PROFILE SEE SHEET 55
FOR -Y24A-, -Y24-, & -Y25- PROFILE SEE SHEET 68

METRIC
5 0 10

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	26 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION
INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____
R/W REV. _____

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	27 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

303

304

305

MATCHLINE -L- STA. 302+00 SEE SHEET NO. 26

MATCHLINE -L- STA. 305+40 SEE SHEET NO. 28

ISFBUS

ISFBUS

W/LT

POT -L- Sta.302+63.590
POT -D27- Sta.10+00.000
BEARING AH = S 22° 19' 26.5" W

2SFBUS

POT -L- Sta.302+68.890
POT -D28- Sta.10+00.000
BEARING AH = S 22° 19' 25.4" W

ISMTLBUS

ISFBUS

ISBKBUS

POT -L- Sta.305+24.700
POT -D30- Sta.10+00.000
BEARING AH = S 16° 21' 39.7" W

POT -D30- Sta.10+36.371

W/LT

BST

GR

GR

GR

C

F

POSTS

EOP

EOP 12' BST

US 19 E 7.6 BST

S 67° 40' 34.0" E -L-

EOP

EOP 12' BST

375mm CMP

CONC HW

300mm CONC

300mm CONC

PCSta.10+11.298

PT Sta.10+17.129

S 64° 04' 52.8" W

-D27-

S 22° 19' 25.7" E

-D28-

POT Sta.10+10.760 PROPOSED RET. WALL

303+00
23m RT

303+60
23m RT

POT =-D28- Sta.10+43.625

ISBKBUS

PT Sta.10+17.969

POT Sta.10+43.888

ISBKD

CONC POOL

27 BST

WD RAIL

W/LT

W/LT

W/LT

W/LT

SIGNAL BOX

BST

-D29-

POT -L- Sta.304+00.000
POT -D29- Sta.10+00.000
BEARING AH = S 12° 19' 46.9" W

POT -D29- Sta.10+38.498

305+20
38m RT

C

-D27-	-D28-
PI Sta. 10+14.350	PI Sta. 10+14.630
Δ = 41° 45' 26.3" (RT)	Δ = 51° 37' 51.1" (LT)
L = 5.830	L = 7.209
T = 3.051	T = 3.870
R = 8.000	R = 8.000

FOR -L- PROFILE SEE SHEET 55

-Y26-

PI Sta 10+99.760
Δ = 9° 45' 32.9" (RT)
L = 119.230
T = 59.760
R = 700.000
SE = SEE PLANS

PI Sta 12+14.021
Δ = 17° 47' 39.1" (LT)
L = 108.699
T = 54.790
R = 350.000
SE = SEE PLANS

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	28 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____

R/W REV. _____

POT Sta.10+00.000

BEGIN CONST.
POT -Y26- Sta.10+26.848

S 4° 22' 00.0" E

306

307

308

PESta.10+40.000

-L- POT Sta.306+89.841
-Y26- POC Sta.11+28.136

TSSta.307+63.144

SCSta.308+53.144

308+70
15m LT

NAD 83

SEE SHEET NO. 27
MATCHLINE -L- STA. 305+40

SEE SHEET NO. 29
MATCHLINE -L- STA. 308+80

PRCSta.11+59.230

S 67° 40' 34.0" E

-L-

-Y26-

END CONST.
POC -Y26- Sta.12+63.347

PTSta.12+67.929

-L-		
PIs Sta 308+23.184	PI Sta 310+51.778	PIs Sta 312+51.910
θs = 6° 26' 44.8"	Δ = 52° 48' 59.8" (LT)	θs = 6° 26' 44.8"
Ls = 90.000	L = 368.730	Ls = 90.000
LT = 60.040	T = 198.634	LT = 60.040
ST = 30.036	R = 400.000	ST = 30.036
	SE = 0.06	
	**V = 96 kph	

** DESIGN EXCEPTION REQUIRED FOR DESIGN SPEED FROM 100kph (60mph) TO 80kph (50MPH)

** DESIGN EXCEPTION REQUIRED FOR DESIGN SPEED FROM 100 kph (60mph) TO 80 kph (50 mph)

-L-

PIs Sta 308+23.184	PI Sta 310+51.778	PIs Sta 312+51.910
Θs = 6° 26' 44.8"	Δ = 52° 48' 59.8" (LT)	Θs = 6° 26' 44.8"
Ls = 90.000	L = 368.730	Ls = 90.000
LT = 60.040	T = 198.634	LT = 60.040
ST = 30.036	R = 400.000	ST = 30.036
	SE = 0.06	
	**V = 96 kph	

-Y27-

PI Sta 10+16.706	PI Sta 10+52.266
Δ = 57° 53' 38.7" (RT)	Δ = 14° 28' 23.7" (RT)
L = 25.261	L = 47.995
T = 13.828	T = 24.126
R = 25.000	R = 190.000
SE = SEE PLANS	SE = SEE PLANS

NAD 83

METRIC

5 0 10

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	29 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____

R/W REV. _____

FOR -L- PROFILE SEE SHEET 56
FOR -Y27- PROFILE SEE SHEET 69

309 310 311 312

MATCHLINE -L- STA. 308+80 SEE SHEET NO. 28

MATCHLINE -L- STA. 312+20 SEE SHEET NO. 30

300mm MD RAILS

55BW

1300mm MW

CEMETERY

5 SBW

375mm CMP

US 158 110 BST

EOP

EOT 08 BST

MTL

1700mm CHL&3SBW

1200mm CHL

GATE

5.5 BST

PRODUCE STAND

GR

310+80
21m RT

POND

W/LT

BST

CONC

MTL CANOPY

ISFBUS

LANDSCAPE TIMBERS

HTRBUS

END CONST.
POT -Y27- Sta.10+95.550

S 31° 00' 000" W
-Y27-

PT Sta.10+76.135

POT Sta.11+21.982

311+60
30m LT

ROCK

48 BST

SR 1149

4SBW

375mm CONC

1050mm WC

600mm CONC

ISFD

GAZEBO

CONC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	30 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

METRIC 5 0 10

CONST.REV. _____

R/W REV. _____

NAD 83

313

314

315

-L-

PIs Sta. 308+23.184
Θs = 6° 26' 44.8"
Ls = 90.000
LT = 60.040
ST = 30.036

PI Sta 310+51.778
Δ = 52° 48' 59.8" (LT)
L = 368.730
T = 198.634
R = 400.000
SE = 0.06
xxV = 96 kph

PIs Sta. 312+51.910
Θs = 6° 26' 44.8"
Ls = 90.000
LT = 60.040
ST = 30.036

PIs Sta. 314+01.908
Θs = 4° 28' 06.5"
Ls = 90.000
LT = 60.019
ST = 30.017

PI Sta 316+01.330
Δ = 32° 43' 50.7" (LT)
L = 329.617
T = 169.442
R = 577.000
SE = 0.06

PIs Sta. 317+91.523
Θs = 4° 28' 06.5"
Ls = 90.000
LT = 60.019
ST = 30.017

-Y27-

PI Sta 10+16.706
Δ = 57° 53' 38.7" (RT)
L = 25.261
T = 13.828
R = 25.000
SE = SEE PLANS

PI Sta 10+52.266
Δ = 14° 28' 23.7" (RT)
L = 47.995
T = 24.126
R = 190.000
SE = SEE PLANS

-Y28-

PI Sta 10+12.569
Δ = 43° 00' 00.0" (RT)
L = 18.762
T = 9.848
R = 25.000
SE = SEE PLANS

PI Sta 10+69.835
Δ = 23° 26' 00.0" (LT)
L = 53.169
T = 26.961
R = 130.000
SE = SEE PLANS

-D31-

PI Sta 10+26.115
Δ = 46° 33' 12.8" (RT)
L = 12.188
T = 6.453
R = 15.000

PI Sta 10+45.515
Δ = 49° 30' 17.7" (LT)
L = 12.960
T = 6.916
R = 15.000

-D32-

PI Sta 10+36.059
Δ = 10° 35' 38.7" (LT)
L = 9.245
T = 4.636
R = 50.000

POC -L- Sta. 312+61.529
POT -Y27- Sta. 10+00.000

PCSta. 10+02.879
BEARING BACK = S 41° 22' 02.4" E

CSSta. 312+21.874

STSta. 313+11.874

TSSta. 313+41.889

312+80
27.57m LT
&
23m LT

POC -L- Sta. 312+02.930
POT -D31- Sta. 10+00.000
BEARING AH
S 43° 17' 55.4" E

N 46° 36' 56.6" E

312+60
10m RT

POT -L- Sta. 313+12.000
POT -D32- Sta. 10+00.000
BEARING AH = S 43° 23' 03.4" E

PCSta. 10+38.599

PCCSta. 10+28.140

PT Sta. 10+51.559
BEARING AH =
S 46° 15' 00.3" E

POT -D31- Sta. 10+60.107

PCSta. 10+19.662

PT Sta. 10+31.850
BEARING AH = S 3° 15' 17.4" W

PCSta. 10+31.423

PT Sta. 10+40.668
BEARING AH = S 53° 58' 42.1" E

POT -D32- Sta. 10+52.722

SCSta. 314+31.889

END CONST.
POC -Y28- Sta. 10+67.662

PROP. RET AM

S 16° 58' 00.0" W

PT Sta. 10+96.043

POT Sta. 11+07.061

MATCHLINE -L- STA. 312+20 SEE SHEET NO. 29

MATCHLINE -L- STA. 315+60 SEE SHEET NO. 31

ISBKD
ISFD
HTR
2SFD
ISBK CHURCH
BST
WD. RAIL
1300mm WDRAIL&WW
600mm WDRAIL&WW
3.4 CONC
3.5GR&WW
150mm PVC
MTL
GR
CONC
EOP
EOT

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

NAD 83

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	310F 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

POT Sta.10+00.000

S 15° 10' 00.0" E

SR 1427 55 BST

49 CONC

316

317

318

319

CONC

PC Sta.10+45.457

PT Sta.10+82.018

BEARING AH = S 57° 16' 00.0" E

BST

ISBK

ISBLK

ISF

ISFD

ISBKD

1500mm - 2000mm CONC WALL

-Y29-

PI Sta 10+64.697
Δ = 44° 06' 00.0" (LT)
L = 36.560
T = 19.239
R = 47.500
SE = SEE PLANS

-L-

PIs Sta 314+01.908
Θs = 4° 28' 06.5"
Ls = 90.000
LT = 60.019
ST = 30.017

PI Sta 316+01.330
Δ = 32° 43' 50.7" (LT)
L = 329.617
T = 169.442
R = 577.000
SE = SEE PLANS

PIs Sta 317+91.523
Θs = 4° 28' 06.5"
Ls = 90.000
LT = 60.019
ST = 30.017

POC -L- Sta.316+89.132
POT -Y29- Sta.11+44.929

HTR

W/LT

ISFBUS

ISF&BLKBUS

10+28
6m RT -Y-30

BEGIN CONST.
POT -Y30- Sta.10+28.278

ROCK

10+68
7m RT -Y-

PROP. RETAINING WALL

-Y30-

S 4° 42' 00.0" E

BEGIN CONST.
POT -Y29- Sta.11+00.000

316+38
10m LT

316+85
12m RT

POC -L- Sta.316+07.953
POT -Y28- Sta.10+00.000

-Y28-

PC Sta.10+02.721

BEARING BACK = S 2° 36' 00.0" E

PT Sta.10+21.483

BEARING AH = S 40° 24' 00.0" W

PC Sta.10+42.874

SOIL

30 BST

PI Sta 10+12.569
Δ = 43° 00' 00.0" (RT)
L = 18.762
T = 9.845
R = 25.000
SE = SEE PLANS

PI Sta 10+69.835
Δ = 23° 26' 00.0" (LT)
L = 53.169
T = 26.961
R = 130.000
SE = SEE PLANS

MATCHLINE -L- STA. 315+60 SEE SHEET NO. 30

MATCHLINE -L- STA. 319+00 SEE SHEET NO. 32

ROCK

POC -L- Sta.318+38.908
POT -Y30- Sta.11+17.027

318+25
6m LT

318+06
15m RT

N. 88° 17' 00.4" E.

CONC ISL

375mm CMP

375mm CONC

CSS Sta.317+61.505

STS Sta.318+91.505

2SBL

B

G

FOR -L- PROFILE SEE SHEET 57
FOR -Y28- PROFILE SEE SHEET 69
FOR -Y29- & -Y30- PROFILE SEE SHEET 70

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	32 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

POT -D34- Sta.10+00.000
BEARING AH = S 11° 07' 20.8" W

PCSta.10+46.379

PTSta.10+61.432
BEARING AH = S 6° 07' 37.3" E

POC -L- Sta.320+13.930
POT -D34- Sta.10+84.657

-D34-
PI Sta 10+53.962
Δ = 17° 14' 58.1" (LT)
L = 15.053
T = 7.584
R = 50.000

-D35-
PI Sta 10+15.193
Δ = 33° 25' 27.0" (RT)
L = 11.667
T = 6.005
R = 20.000

-D35-
PI Sta 10+43.593
Δ = 40° 56' 02.0" (LT)
L = 21.433
T = 11.197
R = 30.000

321+00
40m LT

POT -D35- Sta.10+00.000
BEARING AH = S 32° 29' 37.2" W

PCSta.10+09.189

PTSta.10+20.856
BEARING AH = S 65° 55' 04.2" W

PCSta.10+32.396

PTSta.10+53.829
BEARING AH = S 24° 59' 02.2" W

POC -L- Sta.322+04.000
POT -D35- Sta.10+67.591

TSSta.321+54.622

ROCK

ROCK

SEAMY RK AND WEATHERED RK

S 62° 35' 30.4" E

MATCHLINE -L- STA. 319+00 SEE SHEET NO. 31

MATCHLINE -L- STA. 322+40 SEE SHEET NO. 33

SCSta.319+99.235

TSSta.319+09.235

CSSta.320+61.732

STSta.321+51.732

-L-

PIs Sta 319+69.306	PI Sta 320+30.597	PIs Sta 320+91.797	PIs Sta 322+14.685	PI Sta 322+73.821	PIs Sta 323+32.915
Es = 8° 35' 39.7"	Δ = 11° 56' 09.8" (RT)	Es = 8° 35' 39.7"	Es = 8° 03' 26.0"	Δ = 10° 25' 37.7" (LT)	Es = 8° 03' 26.0"
Ls = 90.000	L = 62.497	Ls = 90.000	Ls = 90.000	L = 58.236	Ls = 90.000
LT = 60.071	T = 31.362	LT = 60.071	LT = 60.062	T = 29.199	LT = 60.062
ST = 30.064	R = 300.000	ST = 30.064	ST = 30.057	R = 320.000	ST = 30.057
	SE = SEE PLANS			SE = 0.06	
	xxV = 85 kph			xxV = 88 kph	

FOR -L- PROFILE SEE SHEET 58

375mm CMP

150mm BST CURB

CONC

C

S

S&FBUS

SOIL

US 19E 7.3 BST

EOT 06 BST

MTL

BST

C

ABAND

LITTLE CRABTREE CREEK

GR

3.5 RR TIES

HW

900mm MTL

WD

HTR

CHRISTMAS TREES

27 BST

D35

319

320

321

322

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	33 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

323

324

325

MATCHLINE -L- STA. 322+40 SEE SHEET NO. 32

MATCHLINE -L- STA. 325+80 SEE SHEET NO. 34

SCSta 322+44.622

CSSta 323+02.858

STSta 323+92.858

323+68
36m LT

S 89°08'00" E

ISFD

ISFD

ISFD

ISFD

ISFBUS

2SRK&FD

DECK

WD. RAIL

B

C

F

G

HTR

HTR

ABAND

ABAND

EOP

EOT 0.6 BST
US 19E
EOT 0.9 BST
7.3 BST

MTL

MTL

GR

W/LT

W/LT

W/LT

DI

LITTLE CRABTREE CREEK

-L-

PIs Sta 322+14.685	PI Sta 322+73.821	PIs Sta 323+32.915
θs = 8°03'26.0"	Δ = 10°25'37.7" (LT)	θs = 8°03'26.0"
Ls = 90.000	L = 58.236	Ls = 90.000
LT = 60.062	T = 29.199	LT = 60.062
ST = 30.057	R = 320.000	ST = 30.057
	SE = SEE PLANS	
	**V = 88 kph	

FOR -L- PROFILE SEE SHEET 58

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	34 of 238
R/W SHEET NO.	

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

326+60
84m LT

325+90
62m LT

-Y33-
PI Sta 10+06.847
Δ = 7° 50' 00.0" (LT)
L = 13.672
T = 6.847
R = 100.000
SE = SEE PLANS

PI Sta 10+28.921
Δ = 34° 03' 11.1" (LT)
L = 23.774
T = 12.249
R = 40.000
SE = SEE PLANS

PI Sta 10+53.630
Δ = 36° 29' 11.1" (RT)
L = 25.472
T = 13.185
R = 40.000
SE = SEE PLANS

-Y32-
PI Sta 10+56.071
Δ = 46° 32' 00.0" (LT)
L = 24.365
T = 12.899
R = 30.000
SE = SEE PLANS

POC -L- Sta.326+22.085
POT -Y31- Sta.10+00.000

PCSta.10+15.998

SCSta.326+75.327

PTSta.10+42.911

END CONST.
POT -Y31- Sta.10+58.994

POTSta.11+04.518

TSSta.325+85.327

MATCHLINE -L- STA. 325+80 SEE SHEET NO.33

POT -Y32- YSta.10+40.600
POT -Y33- Sta.10+74.680

RTSta.10+65.918

BEARING AH=S 20° 54' 00.0" E

BEGIN CONST.
POT -Y33- Sta.10+15.000

BEGIN CONST.
POT -Y32- Sta.10+00.000

PCSta.10+00.000

PTSta.10+13.672

PCSta.10+16.672

PRCSta.10+40.445

S 25° 20' 00.0" E

-Y33-

-Y32- S 69° 06' 00.0" W

SR 1512 PLUM BRIDGE RD

PCSta.10+43.171

PTSta.10+67.536

POC -L- Sta.328+07.257
POT -Y32- Sta.10+69.223

S 22° 36' 00.0" W

-L-

S 5° 32' 00.0" W

ROCK

-Y31-
PI Sta 10+29.556
Δ = 17° 08' 00.0" (RT)
L = 26.913
T = 13.558
R = 90.000
SE = SEE PLANS

-L-

PIs Sta 326+45.398	PI Sta 327+91.925	PIs Sta 329+27.806
θs = 8° 35' 39.7"	Δ = 42° 28' 40.7" (RT)	θs = 8° 35' 39.7"
Ls = 90.000	L = 222.414	Ls = 90.000
LT = 60.071	T = 116.597	LT = 60.071
ST = 30.064	R = 300.000	ST = 30.064
	SE = 0.06	
	**V = 85 kph	

CSSta.328+97.241

MATCHLINE -L- STA. 329+20 SEE SHEET NO. 35

LITTLE CRABTREE CREEK

NAD 83

327

328

326

329

US 19E BST

SR 1442 BEAR WALLOW RD

SR 1144 BEAR WALLOW RD

SR 1512

64 BST

58 BST

50 BST

ISFD

ISBK&FD

ISFBUS

ISRK&FD

W/LT

HTR

MTL

SOIL

GR

1050mm CMP

375mm CMP

-L-

PIs Sta 326+45.398	PI Sta 327+91.925	PIs Sta 329+27.806
Θs = 8° 35' 39.7"	Δ = 42° 28' 40.7" (RT)	Θs = 8° 35' 39.7"
Ls = 90.000	L = 222.414	Ls = 90.000
LT = 60.071	T = 116.597	LT = 60.071
ST = 30.064	R = 300.000	ST = 30.064
	SE = 0.06	
	xxV = 85 kph	
PIs Sta 330+67.086	PI Sta 331+55.524	PIs Sta 332+42.647
Θs = 8° 35' 39.7"	Δ = 22° 04' 18.3" (LT)	Θs = 8° 35' 39.7"
Ls = 90.000	L = 115.567	Ls = 90.000
LT = 60.071	T = 58.509	LT = 60.071
ST = 30.064	R = 300.000	ST = 30.064
	SE = SEE PLANS	
	xxV = 85 kph	

NAD 83

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO. R-2519A

SHEET NO. 35 of 238

R/W SHEET NO.

ROADWAY DESIGN ENGINEER

HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

FOR -L- PROFILE SEE SHEET 59

MATCHLINE -L- STA 329+20 SEE SHEET NO. 34

MATCHLINE -L- STA. 332+60 SEE SHEET NO. 36

ISBKD

ISFD

HTR

330

331

332

TS Sta. 330+07.015

SC Sta. 330+97.015

CS Sta. 332+12.582

POT -d36- Sta. 10+00.000

POC -L- Sta. 330+22.900

POT -D36- Sta. 10+39.896

S 31° 34' 19.4" W

S 29° 28' 00.0" E

ST Sta. 329+87.24

331+68

36m LT

US 19E 7.3 BST

EOP

EOT 0.6 BST

EOT 0.9 BST

375mm CMP

EOT

-L-

INV. ELEV. 164.38

INV. ELEV. 163.45

INV. ELEV. 164.18

INV. ELEV. 163.45

MTL

C

W10

LITTLE CRABTREE CREEK

CHRISTMAS TREES

30 BST

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	360 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

METRIC

5 0 10

NAD 83

CONST.REV. _____

R/W REV. _____

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

-L-

PIs Sta. 330+67.086
Es = 8° 35' 39.7"
Ls = 90.000
LT = 60.071
ST = 30.064

PI Sta 331+55.524
Δ = 22° 04' 18.3" (LT)
L = 115.567
T = 58.509
R = 300.000
SE = SEE PLANS
xxV = 85 kph

PIs Sta. 332+42.647
Es = 8° 35' 39.7"
Ls = 90.000
LT = 60.071
ST = 30.064

PIs Sta. 334+41.527
Es = 1° 13' 40.0"
Ls = 60.000
LT = 40.001
ST = 20.001

PI Sta. 337+35.985
Δ = 22° 11' 00.2" (LT)
L = 542.042
T = 274.458
R = 1,400.000
SE = SEE PLANS

PIs Sta. 340+23.570
Es = 1° 13' 40.0"
Ls = 60.000
LT = 40.001
ST = 20.001

-Y34-

PI Sta. 10+75.879
Δ = 9° 54' 00.0" (RT)
L = 207.35
T = 103.93
R = 1200.000
SE = SEE PLANS

333 334 335 336

ST Sta. 333+02.982

TS Sta. 334+01.526

SC Sta. 334+61.526

POC -L- Sta. 335+77.506
POT -Y34- Sta. 10+00.000

POT Sta. 11+01.88 W/LT

PC Sta. 10+65.485

PT Sta. 10+86.220

END CONST.
POT -Y34- Sta. 10+89.563

MATCHLINE -L- STA. 332+60 SEE SHEET NO. 35

MATCHLINE -L- STA. 336+00 SEE SHEET NO. 37

S 68° 43' 37.1" E

S 28° 18' 00.0" W

S 38° 12' 00.0" W

US 19E BST

EXISTING R/W

MTL CARPORT

2SBKD

2SBKBUS

ISMTLG

GAS PUMPS
2 FUEL- 30283L
1 FUEL- 15142L

ROCK

ABAND

HTR

SFD

MTL

BST

GR

ISBK

CONC

RR (ABANDONED)

SR 1146 (OLD BRIDGE RD)

EXISTING R/W 3.288 BST

250mm CONC CURB

250mm BST CURB

200mm CONC CURB

2-1850mm CMP

1050mm CMP

750mm CMP

375mm CMP

4.0 CONC WW'S

7.0 ROCK HW

L3 CONC HW

L2 CONC

5.240 (180')

22.860 (75')

27.887

3.048

3.454

-L-

Pls Sta 334+41.527
Es = 1 13' 40.0"
Ls = 60.000
LT = 40.001
ST = 20.001

Pl Sta 337+35.985
Δ = 22 11' 00.2" (LT)
L = 542.042
T = 274.458
R = 1,400.000
SE = 0.03

Pls Sta 340+23.570
Es = 1 13' 40.0"
Ls = 60.000
LT = 40.001
ST = 20.001

NAD 83

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	37 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

336
337
338
339

B
ISFD
450mm CMP
CHRISTMAS TREES
SOIL
ABAND
HTR
2SBLK & FBUS
3.4 GR
1050mm CONC
2SFD
336+28
45m LT
338+15
42m LT
ROCK
MATCHLINE -L- STA. 336+00 SEE SHEET NO. 36
MATCHLINE -L- STA. 339+40 SEE SHEET NO. 38
EOP
EOT
US 19E
7.3 BST
0.8 BST
MTL
339+35
6m RT
PROPOSED RET.WALL
BLK WALL
LITTLE CRABTREE CREEK
4 SBW
SEED BED
3.0 BST
2.7 BST
BST
1200mm CML
RR (ABANDONED)
GR
2.4 GR
S
ISFD
G
1500mm BLK WALL
1200mm CML
W/LT
B
HTR

FOR -L- PROFILE SEE SHEET 60

METRIC

5 0 10

CONST.REV. _____

R/W REV. _____

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	38 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

NAD 83

-L-

PIs Sta 334+41.527
Θs = 1° 13' 40.0"
Ls = 60.000
LT = 40.001
ST = 20.001

PI Sta 337+35.985
Δ = 22° 11' 00.2" (LT)
L = 542.042
T = 274.458
R = 1,400.000
SE = 0.03

PIs Sta 340+23.570
Θs = 1° 13' 40.0"
Ls = 60.000
LT = 40.001
ST = 20.001

PIs Sta 342+86.635
Θs = 8° 35' 39.7"
Ls = 90.000
LT = 60.071
ST = 30.064

PI Sta 343+89.679
Δ = 27° 23' 38.4" (RT)
L = 143.435
T = 73.115
R = 300.000
SE = SEE PLANS
xxV = 85 kph

PIs Sta 344+90.063
Θs = 8° 35' 39.7"
Ls = 90.000
LT = 60.071
ST = 30.064

-Y35-

PI Sta 10+55.129
Δ = 38° 14' 00.0" (RT)
L = 33.365
T = 17.330
R = 50.000
SE = SEE PLANS

PI Sta 11+08.820
Δ = 23° 50' 00.0" (LT)
L = 24.958
T = 12.662
R = 60.000
SE = SEE PLANS

POT Sta. 10+00.000

PCSta. 10+37.798

PCSta. 10+96.158

PTSta. 11+21.116
BRG AH = S 10° 27' 00.0" W

CSSta. 340+03.569

BEGIN CONST.
POC -Y35- Sta. 10+64.255

PTSta. 10+71.163
BRG AH = S 34° 17' 00.0" W

TSSta. 342+26.564

POC -L- Sta. 342+75.338
POT -Y36- Sta. 10+00.000

342+00
38m LT

342+80
26m LT

339+45
6m RT

341+20
7m RT

341+80
8m RT

N 86°38' 02.2" E

POC -L- Sta. 340+40.112
POT -Y35- Sta. 11+26.151

ST Sta. 340+63.569

PCSta. 10+12.480
BRG BK = S 1° 28' 00.0" E

-Y36-

PI Sta 10+28.891
Δ = 66° 34' 00.0" (LT)
L = 29.045
T = 16.412
R = 25.000
SE = SEE PLANS

MATCHLINE -L- STA. 339+40 SEE SHEET NO. 37

MATCHLINE -L- STA. 342+80 SEE SHEET NO. 39

PROPOSED RETAINING WALL

PROPOSED RETAINING WALL

1500mm WD RAIL

LITTLE CRABTREE CREEK

US 19E BST

SR 1380 52 BST

SR 1186 BST

450mm CMP

4 SBW

MTL

WD

SOIL

CONC

ISFD

2SFD

GR

340

341

342

METRIC

5 0 10

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	39 of 238
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

CONST.REV. _____

R/W REV. _____

NAD 83

-D37-
PI Sta 10+22.059
Δ = 28° 59' 29.0" (LT)
L = 20.240
T = 10.341
R = 40.000

POT -D37- Sta.10+00.000
BEARING AH = S 53° 17' 37.6" W

PC Sta.10+11.717

PT Sta.10+31.957
BEARING AH = S 24° 18' 08.6" W

POC -L- Sta.344+16.440
POT -D37- Sta.10+45.781

SCSta.343+16.564

343+60
35m' LT

THIN VENEER COLLUVIUM

ROCK

450 mm CMP

POT Sta.10+45.781

MATCHLINE -L- STA 342+80 SEE SHEET NO. 38

US 19E 7.3 BST EOP EOT 0.6 BST EOP EOT

S 48° 47' 00.0" E

CSSta.344+59.998

2 FUEL-22.712L
FUEL-11.356L

FUEL PUMPS U/MTL CANOPY

ISBKBUS

ISMTLBUS

ISFD

ISBKD

HTR

W/LT

900mm CONC WALL

1050mm RCP/WALL

2.1 BST

3.0 CONC

900mm CONC

1 1/2 SFD

SR 1308 DIRT

POT Sta. 346+17.171

346

345

344

343

END CONST.
POC -Y36- Sta.11+39.000

-Y36-

SR 1186 BST

S 68° 02' 00.0" E

PC Sta.10+95.473

PT Sta.10+41.525

PT Sta.11+85.924

POT Sta.11+96.960

S 5° 56' 00.0" E

CEMETERY

STA. 345+60 -L- END STATE PROJ. R-2519A

ST Sta.345+49.998

-L-

PIs Sta 342+86.635	PI Sta 343+89.679	PIs Sta 344+90.063
θs = 8° 35' 39.7"	Δ = 27° 23' 38.4" (RT)	θs = 8° 35' 39.7"
Ls = 90.000	L = 143.435	Ls = 90.000
LT = 60.071	T = 73.115	LT = 60.071
ST = 30.064	R = 300.000	ST = 30.064
	SE = SEE PLANS	
	××V = 85 kph	

-Y36-

PI Sta 10+28.891	PI Sta 11+34.607
Δ = 66° 34' 00.0" (LT)	Δ = 62° 06' 00.0" (RT)
L = 29.045	L = 70.450
T = 16.412	T = 39.133
R = 25.000	R = 65.000
SE = SEE PLANS	SE = SEE PLANS

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

790
785
780
775

6:1 1V:2H EXIST

782621

782290

782538

782464

227+80
29.5 RT

RES. SOILS AND SAPROLITE
MED. DENSE TO DENSE

ALLUVIUM:
BROWN SILTY SAND W/ GRAVEL AND RK FRAGS

9
100+
4/22/03

WEATHERED ROCK:

227+80.000

790
785
780
775

6:1

789673

781613

782585

782727

227+60.000

ALLUVIUM

RES. SOILS AND SAPROLITE
MED. DENSE TO DENSE

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

228+40.000

228+20.000

228+00.000

785.107
784.707
784.450
4.5%
2:1
783.563
783.363
783.764
6:1
782.920
782.826
782.436
783.044
782.713
1V:2H (EXIST.)
EMBANKMENT
SILTY SAND, LOOSE
RES. SOILS AND SAPROLITE
LOOSE TO MED. DENSE
EMBANKMENT
SILTY SAND, LOOSE

50 40 30 20 10 0 10 20 30 40 50

785 790 785 790 785 790 785 790 775

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

795
790
785
780

6:1
2:1
786.454
785.111
785.111

229+00.000

785.818
785.040
785.818
786.454
2:1

228+80.000

EMBANKMENT
LOOSE
785.176
784.342
785.176
785.176

228+60
21 RT. OF -L-

RESIDUAL:
ORANGE SILTY CLAY
11
13
35
5/22/03
SAPROLITE:
GREEN TO GREY SILTY SAND

228+60.000

-L-

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

800 795 790 785 780

SAPROLITE
W/ WEATHERED RK
ORANGE/BRN/GRAY SILTY SAND

IVR EXIST.

787132

787226 787226

787986

EMBANKMENT
BROWN SILTY SAND, LOOSE

229+40
19.5 M RT

229+40.000

C
9
100+
100+

SAPROLITE ORANGE/BRN/GRAY SILTY SAND
WEATHERED RK

SAPROLITE
W/ WEATHERED RK
ORANGE/BRN/GRAY SILTY SAND

786435

787259 787259

787240

229+20.000

50 40 30 20 10 0 10 20 30 40 50

800 795 790 785 780


805
800
795
790
785
SAPROLITE
W/ WEATHERED RK
ORANGE/BRN/GRAY SILTY SAND
IV/2 (EST.)
787.829
788.559
788.580
229+60.000

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	45 of 238

50 40 30 20 10 0 10 20 30 40 50

805 800 795 790 785

3:1

6:1

788.527

789.329

789207

789621

3:1

3:1

229+80.000

50 40 30 20 10 0 10 20 30 40 50

805 800 795 790 785

$$$$USERNAME$$$$ $$$$DATE$$$$ $$$$TIME$$$$ $$$$FILENAME$$$$

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	46 OF 238



2.5 0 2.5 5

METRIC



2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

795 790 785

792.060 792.695 792.963 793.045

6:1 6:1 4.0% 4.0% 6:1

STA. 230+80
29 M RT

ALLUVIUM
GRAY/BRN SILTY SAND W/ GRAVEL

(100+) 4/25/03

230+80.000

791.510 792.093 792.309 792.384

2:1 4:1 4.0% 4.0% 4:1 3:1

230+60.000

10/26/98
DGN FILE NAME


50 40 30 20 10 0 10 20 30 40 50
795
790
785
3.96:1
794.753
794.971
794.829
2:1
231+40.000
6:1
793.521
794.095
794.326
794.238
231+20.000
4.38:1
793.380
793.570
794.656
231+00.000

2.5	0	2.5	5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	50 OF 238



2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	51 of 238

50 40 30 20 10 0 10 20 30 40 50

800 805 800 795

800.150

800.397 800.500

2.5:1 3.26:1

233+00.000

795.361

799.620 799.699

2.15:1 6:1 7:1

798.305

232+80.000

798.779

798.975 798.996

2.44:1 6:1 9:1

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND, LOOSE TO MED DENSE

797.594

232+60.000

798.048

798.818 800.222

2.44:1 6:1 12:1

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND, LOOSE TO MED DENSE

796.899

232+40.000

50 40 30 20 10 0 10 20 30 40 50

$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

805 805 805 800 805 800 805 800 805 800

Ditch Depth
6:1
805.311
805.988
805.559
805.336
6:1
805.252
Ditch Depth

234+20.000

6:1
6:1
804.353
804.895
805.269
805.245
6:1
6:1
804.162

234+00.000

3.76:1
803.871

233+80.000

3.01:1
802.966
3.13:1

233+60.000

2.58:1
802.053
802.322
802.271
2.74:1

233+40.000

2.84:1
801.125
801.421
801.379
1.75:1

233+20.000

233+20
15m RT OF -L-

4/24/03

ROADWAY FILL:
REDDISH BROWN SILTY SAND
WEATHERED ROCK:
BROWN & GREY FINE TO MED GRAINED SAND
SAPROLITE:
GREY TO BROWN SANDY CLAY

6
100+
100+

-L-

50 40 30 20 10 0 10 20 30 40 50

10/25/05
$$$$$$SYSTIME$$$$$$
$$$$$$DGN$$$$$$

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	53 of 238

50 40 30 20 10 0 10 20 30 40 50

810
805

6:1 6:1 3:1
810.376
810.450 810.450
810.077
235+20.000

4:1 3.38:1
810.077
810.450 810.450
235+00.000

Ditch Depth
6:1
808.392
808.467 808.467
808.915
234+80.000

5:1 4.06:1
808.095
808.442 808.442
234+60.000

3.54:1 5.76:1
806.972
807.496 807.496
234+40.000

50 40 30 20 10 0 10 20 30 40 50

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	54 OF 238

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

815
810

236+00.000

814.960
814.296
814.396
3.0%
6:1
2:1

815
810

235+80.000

813.999
814.328
814.396
4.0%
6:1
2:1

815
810

235+60.000

812.968
812.295
813.088
813.168
3.4%
6:1
2:1

815
810

235+40.000

812.003
811.337
812.111
812.181
2.85%
6:1
2.94%

815
810

50 40 30 20 10 0 10 20 30 40 50

-L-

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

820 815 810

236+80.000

819.059 819.087 818.680 6:1 6:1 6:1 3:1 Ditch Depth 816.928

236+60.000

817.502 817.244 816.806 2.20:1 6:1 6:1 816.902

236+40.000

816.249 816.255 815.878 2.20:1 2.21:1

236+20.000

50 40 30 20 10 0 10 20 30 40 50


50 40 30 20 10 0 10 20 30 40 50
825
820
822077
822053
6:1
5.22:1
820.242
820.314
2.26:1
821.128
821.192
821.064
237+40.000
5.62:1
820.455
819.597
7.99:1
237+20.000
4.26:1
819.584
819.747
237+00.000



10/26/98
ENGINEERING SERVICES
PROJECT NAME

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	58 OF 238

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

835 830 825

2:1

SAPROLITE

MED. DENSE TO DENSE

WEATHERED ROCK

6:1

824.535

824.814

824.573

824.822

238+80.000

SAPROLITE

MED. DENSE TO DENSE

WEATHERED ROCK

824.114

238+60.000

824.038

824.538

824.212

823.241

823.808

238+40.000

20m RT OF -L-

824.751

824.440

823.874

822.983

RESIDUAL:
RED TO BROWN MICACEOUS SANDY SILT

8
4
7
17
10
13
11
88

SAPROLITE:
4/29/03 ORANGE,BROWN,BLACK AND WHITE CLAYEY SANDY SILT & SILTY SAND

-L-

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

840 835 830 825

FOLD LINE

2:1

SAPROLITE

WEATHERED ROCK

6:1

823.908

824.920

824.765

239+20.000

239+00.000

239+20
28m RT. OF -L-

10
12
13
8
13
15
89
100/1"
100/1"

SAPROLITE:
REDDISH BROWN & WHITE
MICACEOUS SILTY SAND

ORANGE & WHITE SILTY SAND
WITH QUARTS FRAG.

WEATHERED ROCK:

824.510

SAPROLITE
MED. DENSE TO DENSE

WEATHERED ROCK

823.741

824.342

-L-

10-26-99

USENAME=$$$


50 40 30 20 10 0 10 20 30 40 50
840
835
830
825
FOLD LINE
2:1
RES. SOILS AND SAPROLITE
LOOSE TO DENSE
WEATHERED ROCK
6:1
825.220
825.564
825.084
824.060
824.661
239+60.000
SAPROLITE
MED. DENSE TO DENSE
825.075
825.149
825.051
824.014
824.616
239+40.000

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	61 OF 238

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

825 830 835

240+40.000

6:1 6:1 6:1 5:1

824.674

823.630 824.232

825.406 824.887

240+20.000

2:1 6:1 6:1 6:1

824.853

823.829 824.431

826.689 825.528

240+00.000

2:1 6:1 6:1 5.39:1

824.978

823.967 824.569

825.947 825.271

239+80.000

RES. SOILS AND SAPROLITE
LOOSE TO DENSE

2:1 6:1 6:1 2:1

825.079

824.044 824.645

825.304 825.148

RES. SOILS AND SAPROLITE
LOOSE TO DENSE

50 40 30 20 10 0 10 20 30 40 50

825 830 835

$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

830

825

2.36%

6:1

821909

823.881

823.886

823.222

6:1

6:1

822510

24

241+40.000

825

5.67%

6:1

822256

823.282

241+20.000

Ditch Depth

822857

825

823.514

823.395

6:1

6:1

6:1

822667

823.650

241+00.000

Ditch Depth

823268

825

824.296

824.238

6:1

6:1

6:1

6:1

823.049

824.066

240+80.000

823650

825

824.530

824.512

6:1

6:1

6:1

5.99%

823.370

824.395

240+60.000

823.971

50 40 30 20 10 0 10 20 30 40 50

10/26/98
SHEET1.DGN
USERNAME(S)

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	63 OF 238

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

835 830 825 820

24"

Ditch Depth

821.352

6:1

822.348

822.548

822.586

242+00.000

RES. SOILS AND SAPROLITE
ORANGE/BRN SILTY SAND
LOOSE TO MED. DENSE

822.553

241+80.000

821.457

822.407

822.719

822.761

822.053

241+60.000

821.642

822.559

822.920

822.956

822.244

USER NAME = $$$$$$$$ DESIGNED = $$$$$$$$ DRAWN = $$$$$$$$ CHECKED = $$$$$$$$

50 40 30 20 10 0 10 20 30 40 50

830 825 820 835 830 825 820

6:1 6:1 4%

822.447 822.383 822.327

242+60.000

6:1 6:1 2%

821.365 822.339 822.395 822.669

242+40.000

RES. SOILS AND SAPROLITE
ORANGE/BRN SILTY SAND
LOOSE TO MED. DENSE

821.986

6:1 6:1 2%

821.528 822.237 822.264 822.632

242+20.000

RES. SOILS AND SAPROLITE
ORANGE/BRN SILTY SAND
LOOSE TO MED. DENSE

821.929

50 40 30 20 10 0 10 20 30 40 50

SYSTIME = 01/26/98 10:
USERNAME = ssmith

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

835
830
825

RES. SOILS AND SAPROLITE
ORANGE/BRN SILTY SAND
LOOSE TO DENSE

826.732
826.704
827.010
826.732
825.701
4:1
6:1
15'
6:1

244+80.000

825.724
826.633
826.736
825.539
6:1
6:1
25'

244+60.000

825.359
826.291
825.923
825.211
6:1
6:1
3.22'

244+40.000

825.559
825.998
825.551
824.845
Ditch Depth
3.24'
6:1
6:1

244+20.000

-L-

50 40 30 20 10 0 10 20 30 40 50

$SYSTIME$ DWG

10/25/99

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO. R-2519A

SHEET NO. 66 OF 238

50 40 30 20 10 0 10 20 30 40 50

835

830

825

4.3%

6:1

827.310

827.679

827.559

827.744

827.408

245+40.000

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND
LOOSE TO DENSE

826.500

6:1

827.067

827.496

827.642

827.408

245+20.000

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND
LOOSE TO DENSE

826.257

827.092

827.599

827.804

245+00.000

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND
LOOSE TO DENSE

825.060

SYSTINF

2.5 0 2.5 5

METRIC

246+00
25m RT OF -L-

RESIDUAL:
ORANGE CLAYEY SILT SLI.MICACEOUS

SAPROLITE:
ORANGE CLAYEY SILT SLI.MICACEOUS

ORANGE & BLACK SLI.MICACEOUS SILTY SAND

BROWN SLI.MICACEOUS SANDY SILT

4
7
6
16
9
8
12
10
18

2:1 6:1 1.5:1

821.761 826.891

246+00.000

RES.SOILS AND SAPROLITE
ORANGE/BRN SILTY SAND
LOOSE TO DENSE

827.627 828.020 826.817

245+80.000

RES.SOILS AND SAPROLITE
ORANGE/BRN SILTY SAND
LOOSE TO DENSE

827.496 827.872 826.686

245+60.000

-L-

840 835 830

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	68 OF 238

50 40 30 20 10 0 10 20 30 40 50

845
840
835
830

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND
LOOSE TO DENSE

45°

827.740

828.073

828.005

828.145

826.870

246+40.000

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND
LOOSE TO DENSE

827.719

828.117

828.054

828.143

826.909

246+20.000

50 40 30 20 10 0 10 20 30 40 50

$$$$$$ USER NAME = $$$$$$ DESIGNED
$$$$$$ DRAWN
$$$$$$ CHECKED
$$$$$$ DATE = $$$$$$
$$$$$$ PROJECT ENGINEER

10/26/98

2.5	0	2.5	5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	69 OF 238

50 40 30 20 10 0 10 20 30 40 50

845
840
835
830

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND
LOOSE TO DENSE

3:1

6:1

827.435

827.826

825.574

827.470

825.574

827.826

6:1

15:1

825.625

246+80.000

845
840
835
830

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND
LOOSE TO DENSE

3:1

6:1

827.645

827.220

827.220

827.986

827.986

6:1

15:1

826.776

246+60.000

50 40 30 20 10 0 10 20 30 40 50

SYSTEM 8888888888

2.5 0 2.5 5

50 40 30 20 10 0 10 20 30 40 50

835
830
825
840

RES. SOILS AND SAPROLITE

ORANGE/BRN SILTY SAND
LOOSE TO DENSE

826.706
827.059
827.276
827.000
826.836
827.025
827.364
827.580
826.155
827.228
827.617
827.833
826.418

6:1

247+40.000
247+20.000
247+00.000

33m RT OF -L-

RESIDUAL:
BROWN SILTY SAND W/ WEATHERED ROCK FRAGS

9
5
6
64
34

SAPROLITE:
BROWN & WHITE MICACEOUS SANDY SILT

BROWN MICACEOUS SILTY SAND

-L-

DGN: 0025AB
DATE/TIME: 9/25/2013 8:25:49 AM
USER NAME: $$$$

2.5 0 2.5 5

METRIC

248+40.000

248+20.000

248+00.000

247+80.000

247+60.000

RES. SOILS AND SAPROLITE

ORANGE BRN SILTY SAND
LOOSE TO DENSE

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	72 of 238

2.5 0 2.5 5

50 40 30 20 10 0 10 20 30 40 50

820
815

252+40.000

818.341
868.503
868.739
868.716
868.515
4:1
2:1

252+20.000

818.378
868.885
868.735
868.739
868.553
4:1
2:1

252+00.000

252+00
17m RT OF -L-

818.446
868.425
868.691
868.700
868.741
3:1
6:1
4/29/03
RESIDUAL: BROWN SILTY CLAY W/ ROCK FRAGS
ORANGE CLAYEY SILT
SAPROLITE: ORANGE,GREY & BLACK SILTY CLAY W/ SOME ROCK FRAGS
6
3
11
2
818.525
817.505
817.840
2:1

251+80.000

818.596
868.596
868.633
868.641
868.644
4:1
2:1

251+60.000

-L-

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	73 OF 238

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

825 820 815

818.037 818.312 818.336 818.903 818.905

253+20.000

818.116 818.255 818.414 818.497 818.635

253+00.000

253+00
13m RT -L-

RESIDUAL:
SILTY CLAY W/ FR. FRAGS.
4/23/03
SAPROLITE:
BRN. MIC. SILTY SAND

8
5
16

818.189 818.193 818.607 818.651 818.193

252+80.000

818.272 818.472 818.678 818.715 818.472

252+60.000

-L-

50 40 30 20 10 0 10 20 30 40 50

825 820 815

DGN: SYSTEM\standard_dgn\
USER NAME: ######

257+20.000

257+00.000

256+80.000

256+60.000

256+40.000

PROPOSED RETAINING WALL

257+00
19m RT -L-

04/31/03

ALLUVIUM:
ORANGE COARSE SAND

SAPROLITE:
ORANGE MICASILTY FINE SAND

256+60
26m RT -L-

ALLUVIUM:
BROWN SLI.MICACEOUS ORGANIC SILTY SAND

SAPROLITE:
ORANGE, BROWN AND WHITE CLAYEY SILT & SILTY SAND

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	75 of 238

2.5 0 2.5 5 METRIC

50 40 30 20 10 0 10 20 30 40 50

860 855 850 845



266+80.000

SAPROLITE:
BROWN SU.MIC.SILTY SAND
& SANDY SILT W/ MnO
MED.DENSE TO DENSE



266+60.000

SAPROLITE:
BROWN SU.MIC.SILTY SAND
& SANDY SILT W/ MnO
MED.DENSE TO DENSE



266+40.000

50 40 30 20 10 0 10 20 30 40 50

10/26/99
USER NAME = $$USER_NAME$$
PLOT SCALE = $$PLOT_SCALE$$
PLOT DATE = $$PLOT_DATE$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

860 855 850

4:1

848,763
267+40.000

SAPROLITE:
BROWN SU.MIC.SILTY SAND
& SANDY SILT W/ MnO
MED.DENSE TO DENSE

267+20
38m LT -L- FILL:
BROWN SU.MIC.SILTY SAND

17 25 22 21 25 32 43 19 19

847,931
267+20.000

SAPROLITE:
BROWN SU.MIC.SILTY SAND
& SANDY SILT W/ MnO
MED.DENSE TO DENSE

847,047
267+00.000

-L-

DGN: 0625488
USER NAME = $$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

855 850 860 855 850 860 855 850 860 855 850

850.730 850.682 850.617 850.554 850.434

268+20.000

850.326 850.264 850.065 849.954

268+00.000

850.793 850.651 850.482 850.095

267+80.000

850.618 850.269 849.957

849.636

267+60.000

268+00
25m RT -L-

FILL:
RED SLI.MIC.SILTY SAND

SAPROLITE:
WHITE MIC.SILTY SAND W/ MnO
MAY CONTAIN SEAMY
WEATHERED ROCK

WEATHERED ROCK:
W/ BROWN MIC SILTY SAND SEAMS

SAPROLITE:
WHITE MIC.SILTY SAND W/ MnO

SAPROLITE:
MAY CONTAIN SEAMY
WEATHERED ROCK

SAPROLITE W/ SEAMY WEATHERED RK
ORANGE/BLK SILTY SAND
MED.DENSE TO VERY DENSE

267+55
31 m RT -L-

SAPROLITE:
LT.BRN/TAN MIC.SILTY SAND

26 44 45 50 100/1" 100/1" 44 42

7 21 21 33 27 33 6 28 12 11 14

11/10/03

$SYSTIME$$$$
$SYSDATE$$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

PROPOSED RETAINING WALL

EMBANKMENT
SILTY SAND W/ RK FRAGS

SAPROLITE: RED SLI MIC TO MIC. SILY SAND
RED, BLACK & ORANGE SANDY CLAY
LOOSE

851556 850088 850058 850791 850766
269+40.000

851326 851457 851421 851120 851146
269+20.000

852066 851597 851561 851361 851363
269+00.000

852070 851472 851466
268+80.000

852052 851863 851434
268+60.000

852006 851717 851340
268+40.000

855 850

4:1 3:1 2:1

B

$$$$$$$$SYSTEM$$$$$$$$
$$$$$$$$DATE$$$$$$$$
$$$$$$$$FILENAME$$$$$$$$
$$$$$$$$USER$$$$$$$$
$$$$$$$$SCALE$$$$$$$$
$$$$$$$$DESIGN$$$$$$$$
$$$$$$$$DRAWN$$$$$$$$
$$$$$$$$CHECKED$$$$$$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

850 845

ROADWAY FILL:
ABC W/ SILTY SAND
RESIDUAL:
RED WHITE & ORANGE CLAYEY SANDY SILT W/ RK FRAGS
05/09/03
SAPROLITE:
RED MIC TO SLI MIC SILTY SAND
270+17
20m LT -L-
PROPOSED RETAINING WALL
EMBANKMENT
848.852
848.953
848.352
270+20.000

850 845

PROPOSED RETAINING WALL
EMBANKMENT
849.596
270+00.000

850 845

ROADWAY FILL:
ABC W/ SILTY SAND
RESIDUAL:
RED SLI MIC CLAY
05/02/03
269+62
22m LT -L-
PROPOSED RETAINING WALL
EMBANKMENT
850.241
269+80.000

850

SAPROLITE:
RED SLI MIC TO MIC. SILY SAND
RED BLACK & ORANGE SANDY CLAY
269+60.000

50 40 30 20 10 0 10 20 30 40 50

PROPOSED RETAINING WALL

270+84
15m LT -L-

846.158 846.351 846.388 846.158 846.155

0.0154 m/m

846.252

05/09/03

3 3 2 4 10 18 29 23

EMBANKMENT
BRN.GREY YELLOW AND ORANGE MIC SILTY SAND W/ RK.FRAGS.

13 4 7

SAPROLITE 270+80.000
BRN.& WHITE SILTY SAND W/ SOME QUARTZ FRAGS.

846.875 847.074 847.074 846.875

44

846.965

PROPOSED RETAINING WALL

EMBANKMENT
MIC.SILTY SAND W RK FRAGS LOOSE

SAPROLITE
BRN.& WHITE SILTY SAND W/ SOME QUARTZ FRAGS. MED.DENSE

270+60.000

847.592 847.592 847.592 847.592

44

PROPOSED RETAINING WALL

847.705

EMBANKMENT
MIC.SILTY SAND W RK FRAGS LOOSE

SAPROLITE
BRN.& WHITE SILTY SAND W/ SOME QUARTZ FRAGS. MED.DENSE

270+40.000

-L-

50 40 30 20 10 0 10 20 30 40 50

845 840 835 850 845 840 835 850 845 840

SYSTIME

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	81 OF 238

850 845 840 835

50 40 30 20 10 0 10 20 30 40 50

843.965 844.274 844.238 844.105 846.444 846.082

EMBANKMENT 844.065

2:1

SAPROLITE
ORANGE/WHT SILTY SAND
LOOSE TO MED.DENSE

271+40.000

844.723 844.551 844.535 844.723

844.754

EMBANKMENT
SILTY SAND W/ RK FRAGS
LOOSE

2:1

SAPROLITE
ORANGE/WHT SILTY SAND
LOOSE TO MED.DENSE

271+20.000

845.140 845.290 845.673 845.140 846.696

0.0254 m/m

845.510

EMBANKMENT
SILTY SAND W/ RK FRAGS
LOOSE

2:1

SAPROLITE
ORANGE/WHT SILTY SAND
LOOSE TO MED.DENSE

271+00.000

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC



2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

845
840
835

839.774 839.590 839.590 839.701

0.000 0.000

2H

EMBANKMENT
SILTY SAND W/ RK FRAGS, LOOSE 839.803

SAPROLITE
ORANGE/WHT SILTY SAND
LOOSE TO MED. DENSE

272+60.000

840.119 840.650 840.648 840.119

0.000 0.000 0.000

2H 2:1

EMBANKMENT
SILTY SAND W/ RK FRAGS, LOOSE 840.499

SAPROLITE
ORANGE/WHT SILTY SAND
LOOSE TO MED. DENSE

272+40.000

841.136 841.368 841.344 841.136

0.000 0.000 0.000

2H 2:1

EMBANKMENT
SILTY SAND W/ RK FRAGS, LOOSE 841.221

SAPROLITE
ORANGE/WHT SILTY SAND
LOOSE TO MED. DENSE

272+20.000

50 40 30 20 10 0 10 20 30 40 50

SYSTIME$$$


50 40 30 20 10 0 10 20 30 40 50
850
845
840
835
SAPROLITE:
ORANGE MIC. SILTY SAND
LOOSE TO MED. DENSE
ORANGE & BLACK SLI. MIC.
FINE SANDY SILT W/ RK. FRAGS
MAY CONTAIN WEATHERED RK
838.266
838.969
838.466
838.266
838.370
273+00.000
SAPROLITE:
ORANGE MIC. SILTY SAND
LOOSE TO MED. DENSE
838.964
839.063
839.063
838.864
839.097
272+80.000

2.5 0 2.5 5

METRIC



10:26:48
USER NAME = USER
PLOT SCALE = 50.000 '/ IN.
PLOT DATE = 5/15/2008

2.5 0 2.5 5

METRIC

273+80
36m RT -L-

SAPROLITE:
RED SLI.MIC.CLAYEY SANDY SILT

SAPROLITE:
ORANGE SLI.MIC.FINE SANDY SILT

ORANGE SILTY SAND W/
WEATHERED ROCK SEAMS

WEATHERED ROCK:

3
10
7
37
13
30
100/4"
100/4"

835.197
835.597
835.597
835.197
835.480

273+80.000

SAPROLITE:
ORANGE SLI.MIC.FINE SANDY SILT

ORANGE SILTY SAND W/
WEATHERED ROCK SEAMS

WEATHERED ROCK:

836.114
836.314
836.314
836.114
836.187

273+60.000
-L-

50 40 30 20 10 0 10 20 30 40 50

850 845 840 835

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	87 of 238

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

850 845 840 835 830

SAPROLITE:
ORANGE SLI.MIC.FINE SANDY SILT
LOOSE TO MED.DENSE

WEATHERED ROCK:

833.962 833.962 834.462 834.050

274+20.000

SAPROLITE:
ORANGE SLI.MIC.FINE SANDY SILT
LOOSE TO MED.DENSE

WEATHERED ROCK:

834.680 834.870 834.870 834.680

834.758

274+00.000

50 40 30 20 10 0 10 20 30 40 50

850 845 840 835 830

01/26/98

$$$$USERNAME$$$$ $$$$DATE$$$$ $$$$TIME$$$$ $$$$DGNFILE$$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

845
840
835

SAPROLITE:
ORANGE MIC. FINE
SANDY SILT

WEATHERED ROCK

852.502
0.0130 m/m
835.528
835.127
832.356
835.528
832.591
274+60.000

274+00
39m RT -L-

850
845
840
835

SAPROLITE:
RED SLI. MIC. CLAYEY
SANDY SILT

SAPROLITE:
ORANGE MIC. FINE
SANDY SILT

TAN MIC. SILTY
FINE SAND

WEATHERED ROCK

2
6
7
10
7
10
5
30
100+
100+

24"

835.245
835.444
833.680
835.245
833.332
274+40.000

-L-

50 40 30 20 10 0 10 20 30 40 50

DGN: (USER NAME) (SETTINGS)
DATE/TIME: (DATE/TIME)
USERNAME: (USERNAME)

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

840 835 830 845 840 835

SAPROLITE:
RED SLI.MIC.CLAYEY
SANDY SILT
LOOSE TO MED.DENSE

2:1

830.413 830.420 830.575

275+20.000

SAPROLITE:
RED SLI.MIC.CLAYEY
SANDY SILT
LOOSE TO MED.DENSE

2:1

831.059 831.539 831.925 831.085 831.456

275+00.000

SAPROLITE:
RED SLI.MIC.CLAYEY
SANDY SILT
LOOSE TO MED.DENSE

WEATHERED ROCK

2:1

831.830 0.0042 m/m 831.810 832.017 832.043 831.810 831.866

274+80.000

50 40 30 20 10 0 10 20 30 40 50

EMBANKMENT
SILTY SAND W/ RK FRAGS
LOOSE

827.316 827.540 827.538 827.316

827.322

SAPROLITE:
WHITE CLAYEY SAND MIC.
W/ QUARTZ FRAGS
LOOSE

276+00.000

EMBANKMENT
SILTY SAND W/ RK FRAGS
LOOSE

828.122 828.558 828.534 828.122

828.134

SAPROLITE:
WHITE CLAYEY SAND MIC.
W/ QUARTZ FRAGS
LOOSE

275+80.000

828.302 829.134 829.140 828.302

828.312

275+60.000

829.652 829.288 829.660 829.652

SAPROLITE:
RED SU.MIC.CLAYEY
SANDY SILT
LOOSE TO MED.DENSE

829.677

275+10.000

50 40 30 20 10 0 10 20 30 40 50

830 825 820 835

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

EMBANKMENT
SILTY SAND W/ RK FRAGS

824.179 824.329 824.354 824.169 824.571

0.0280 m/m

824.817

825 820 815

2:1

SAPROLITE:
WHITE CLAYEY SAND MIC.
W/ QUARTZ FRAGS

276+60.000

EMBANKMENT
SILTY SAND W/ RK FRAGS

825.513 825.622 825.845 825.653

0.0000 0.0000 0.0000 0.0000 0.0000

825.693

4:1

825 820 830

276+40.000

SAPROLITE:
WHITE CLAYEY SAND MIC.
W/ QUARTZ FRAGS

826.478 826.692 826.716 826.478 826.669

0.0000 0.0000 0.0000 0.0000 0.0000

826.496

0.0130 m/m

825 820

2:1

276+20
22m LT -L-

ALLUVIUM:
BRN SAND

RESIDUAL
RED MIC SILTY SAND

EMBANKMENT
SILTY SAND W/ RK FRAGS

276+20.000

8 3 9 11

SAPROLITE:
WHITE CLAYEY SAND MIC.
W/ QUARTZ FRAGS
LOOSE

-L-

50 40 30 20 10 0 10 20 30 40 50

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	920P236

50 40 30 20 10 0 10 20 30 40 50

825 820 815

EMBANKMENT

LOOSE SILTY SAND W/ RK FRAGS

RES. SOILS AND SAPROLITE

ORANGE/TAN SILTY SAND AND SANDY SILT

LOOSE TO MED. DENSE

4:1

822.792 821.948 822.264 822.475

0.0403 m/m

277+20.000

EMBANKMENT

LOOSE SILTY SAND W/ RK FRAGS

RES. SOILS AND SAPROLITE

ORANGE/TAN SILTY SAND AND SANDY SILT

LOOSE TO MED. DENSE

4:1

822.844 822.959 822.944 823.130

0.0250 m/m

277+00.000

EMBANKMENT

LOOSE SILTY SAND W/ RK FRAGS

RES. SOILS AND SAPROLITE

ORANGE/TAN SILTY SAND AND SANDY SILT

LOOSE TO MED. DENSE

2:1

823.396 824.028 823.396 823.753

0.0160 m/m

823.919

276+80.000

50 40 30 20 10 0 10 20 30 40 50

$$$$SYSTEM$$$$
$$$$DRAWING NAME$$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

820
815
810
825

EMBANKMENT
SILTY SAND W/ RK FRAGS

819.592 819.250 819.240 819.066

2:1

PROPOSED RETAINING WALL

ALLUVIUM:
RED FINE SANDY CLAY

SAPROLITE
TAN CLAYEY SAND

SAPROLITE:
ORANGE CLAYEY SILT

277+80.000

820.911 820.753 820.619 820.004 820.747

0.0806 m/m

277+60
21m LT -L-

819.991

PROPOSED RETAINING WALL

ALLUVIUM:
RED FINE SANDY CLAY

SAPROLITE:
TAN CLAYEY SAND W/ RK FRAGS

05/14/03

SAPROLITE:
ORANGE CLAYEY SILT

BROWN GREY & WITE
MIC. SILTY SAND

3 11 9 4 5 3 7 22 18 17

277+60.000

820.470 820.798

820.938

EMBANKMENT
LOOSE SILTY SAND W/ RK FRAGS

RES. SOILS AND SAPROLITE
ORANGE/TAN SILTY SAND AND SANDY SILT
LOOSE TO MED. DENSE

277+40.000
-L-

10/25/05
$$$$SYSTIME$$$$
$$$$USERNAME$$$$

2.5 0 2.5 5

METRIC

820 815 810

50 40 30 20 10 0 10 20 30 40 50

278+60.000

SAPROLITE:

2:1

0.0334 m/m

815.346

815.076 815.179 815.342 815.520

0.0200 0.0200 0.0200 0.0200 0.0200 0.0200

816.178 816.914

278+40.000

816.142 816.486 816.824 816.838

0.0200 0.0200 0.0200 0.0200 0.0200

0.0015 m/m

816.308

278+20.000

EMBANKMENT

SILTY SAND W/ RK FRAGS

817.094 817.460 817.493 817.714

0.0200 0.0200 0.0200 0.0200 0.0200

0.0337 m/m

817.240

817.579

PROPOSED RETAINING WALL

ALLUVIUM:
RED FINE SANDY CLAY

SAPROLITE:
MIC. SANDY SILT

278+00
21m LT -L-

EMBANKMENT

SILTY SAND W/ RK FRAGS

818.088 818.151 818.425

0.0200 0.0200 0.0200 0.0200 0.0200

4:1

PROPOSED RETAINING WALL

ALLUVIUM:
RED FINE SANDY CLAY
TAN CLAYEY SAND
W/ RK FRAGS

05/15/03

SAPROLITE:
MIC. SANDY SILT

5 5 4 5 2 3 8 4 3 9

278+00.000

-L-

2.5 0 2.5 5

METRIC

279+40.000

811.868 811.839 811.837 4:1 4:1

279+30
39m LT -L-

ALLUVIUM:
GREY MIC.TO SLI.MIC.
SILTY FINE SAND

FILL:
RED MIC.SILTY SAND

05/21/03

100+

100+

EMBANKMENT
LOOSE SILTY SAND
W/ RK FRAGS

PROPOSED
RETAINING WALL

812.705 812.705 812.442 812.347 812.341

0.063 m/m

279+20.000

SAPROLITE:

WEATHERED ROCK:

EMBANKMENT

PROPOSED
RETAINING WALL

813.125 813.125 813.461 813.336 813.330

SAPROLITE

279+00.000

FILL: RED MIC.SILTY SAND

ALLUVIUM:
GREY MIC.TO SLI.MIC.
SILTY FINE SAND

WEATHERED ROCK:

EMBANKMENT

814.169 814.170 814.136 814.351 814.345 4:1

PROPOSED
RETAINING WALL

SAPROLITE:

278+80.000

WEATHERED ROCK:

-L-

50 40 30 20 10 0 10 20 30 40 50

815 810

10:26:48

50 40 30 20 10 0 10 20 30 40 50

810
805

808.#5
808.873
809.645
810.460

0.0392 ft/ft

808.745
808.748

280+20.000
280+00.000
279+80.000
279+60.000

4:1
3:1
2:1

807.977
808.200
808.283
808.545
808.845
808.988
809.024
809.236
809.258
809.779
809.881
810.047
810.066
810.671
810.924

ALLUVIUM:
SILTY SAND W/ GRAVEL

FILL: RED SLI.MIC.SILTY SAND

SAPROLITE: GREY MIC.TO SLI.MIC BRN.SILTY SAND

WEATHERED ROCK:

ALLUVIUM:
SILTY SAND W/ FEW GRAVELES

279+60
23m LT

2
7
26
100+

▼05/21/03

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

820 815 810 805

RES. SOILS AND SAPROLITE
ORANGE/TAN MICASIETY SAND
MED. DENSE

806.762
0.0068 m/m
806.587
806.501
806.492
806.291
806.511
280+80.000

807.067
0.0043 m/m
806.924
807.124
807.482
807.251
806.939
280+60.000

807.321
0.0108 m/m
807.180
807.330
807.675
807.444
0.0254 m/m
806.001
807.443
280+40.000

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

825 820 815 810 805

RES. SOILS AND SAPROLITE
ORANGE/TAN MIC. SILTY SAND
MED. DENSE

806.027 805.963 806.063 806.69 805.965

0.0016 m/m

805.838

281+20.000

RES. SOILS AND SAPROLITE
ORANGE/TAN MIC. SILTY SAND
MED. DENSE

806.694 806.275 806.475 806.275

0.0057 m/m

806.154

281+00.000

-L-

50 40 30 20 10 0 10 20 30 40 50

825 820 815 810 805

USERNAME = USERNAME
DGN = DGN
DATE = DATE
TIME = TIME

50 40 30 20 10 0 10 20 30 40 50

820 815 810 805 825 820 815 810 805

805.139 805.598 805.572 805.539 805.337

281+60.000

RES. SOILS AND SAPROLITE

ORANGE/TAN MIC. SILTY SAND
MED. DENSE

805.651 805.630 805.887 805.651 805.508

281+40.000

50 40 30 20 10 0 10 20 30 40 50

\\SYSTIMES\\$\$\$

2,5 0 2,5 5

METRIC

282+40.000

804.094 804.324 804.500 804.684

803.996

282+20.000

804.450 804.636 804.692 804.843

804.301

SAPROLITE AND WEATHERED RK
TAN MIC. SILTY SAND
MED. DENSE TO VERY DENSE

282+00.000

805.079 804.859

804.555

SAPROLITE AND WEATHERED RK
TAN MIC. SILTY SAND
MED. DENSE TO VERY DENSE

281+80.000

805.460 805.636 805.680 805.807

804.906

DOCUMENT: DOT4700001

10/25/99

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	101 of 236

50 40 30 20 10 0 10 20 30 40 50

815 810 805

SAPROLITE AND WEATHERED RK

TAN MIC. SILTY SAND
MED. DENSE TO VERY DENSE

4:1 2:1

803.055 803.367 803.355 803.055

803.028

283+00.000

815 810 805

4:1 2:1

803.467 803.711 803.567 803.467

803.377

282+80.000

SAPROLITE AND WEATHERED RK

TAN MIC. SILTY SAND
MED. DENSE TO VERY DENSE

815 810 805

4:1 2:1

803.779 804.012 803.988 803.779

803.762

282+60.000

50 40 30 20 10 0 10 20 30 40 50

$$\#\#\#

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

805 810 815

902.705
0.0271 m/m
802.248
802.241
802.081
283+80.000

902.657
0.0024 m/m
802.599
802.586
802.546
802.599
802.399
283+40.000

SAPROLITE AND WEATHERED RK
TAN MIC. SILTY SAND
MED. DENSE TO VERY DENSE

903.266
0.0253 m/m
802.843
802.843
802.843
802.693
283+20.000

SAPROLITE AND WEATHERED RK
TAN MIC. SILTY SAND
MED. DENSE TO VERY DENSE

-L-

10.25.48
USER NAME = USER
PLOT SCALE = 50.000 '/ IN
PLOT DATE = 10/26/2010

50 40 30 20 10 0 10 20 30 40 50

805 800

284+96
5m RT -L-

EMBANKMENT ORANGE BRN.BLACK CLAYEY SAND
02/20/03
285+00.000
FILL: MIC.SILTY SAND
ALLUVIUM: GREY MIC.TO SLI.MIC SILTY SAND
SAPROLITE: BRN.& WHITE SLI.MIC. CLAYEY SAND

284+85
15m RT -L-

FILL: BRN.SILTY SAND W/ ABC RED SANDY CLAY
05/20/03
284+80.000
ALLUVIUM: GREY SLI.MIC.FINE SANDY SILT
GREY WHITE & BRN.SILTY FINE SAND W/ RK.FRAGS
SAPROLITE: BROWN & WHITE SLI.MIC. SILTY FINE SAND

801791 801772

284+60.000

0.0079 m/m

284+40.000

0.0595 m/m

284+20.000

284+00.000

0.0348 m/m

801253

SYSTEM FILE NAME: USER NAME:

50 40 30 20 10 0 10 20 30 40 50

800 800 800 800 800 800

797.393
289+00.000
ALLUVIUM:
BROWN & GREY SILTY SAND W/ GRAVEL & COBBLES
20 30

797.800
288+80.000

798.231
288+60.000
ALLUVIUM:
BROWN & GREY SILTY SAND W/ GRAVEL & COBBLES
20 30

798.653
288+40.000

799.030
288+20.000
ALLUVIUM:
BROWN & GREY SILTY SAND W/ GRAVEL & COBBLES
20 30

799.410
288+00.000
ALLUVIUM:
BROWN & GREY SILTY SAND W/ GRAVEL & COBBLES
20 30

799.738
287+80.000

50 40 30 20 10 0 10 20 30 40 50

10/25/98
$$$$USERNAME$$$$

2.5 0 2.5 5 METRIC

50 40 30 20 10 0 10 20 30 40 50

795

795.772

290+20.000

EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

ALLUVIUM: BROWN & GREY SLI.MIC. SILTY SAND W/ GRAVEL & COBBLES LOOSE

SAPROLITE: BROWN & GREY MIC. SILTY FINE SAND LOOSE

796.296 796.680 796.936 796.683

290+00.000

EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

ALLUVIUM: BROWN & GREY SLI.MIC. SILTY SAND W/ GRAVEL & COBBLES LOOSE

SAPROLITE: BROWN & GREY MIC. SILTY FINE SAND LOOSE

796.547 796.186 795.994

FILL

289+80.000

ALLUVIUM: BROWN & GREY SLI.MIC. SILTY SAND W/ GRAVEL & COBBLES LOOSE

SAPROLITE: BROWN & GREY MIC. SILTY FINE SAND

796.300 796.084 796.488 796.344

289+60.000

289+00
15m RT. -L-

05/20/03 2 3 2

ALLUVIUM: BROWN & GREY SLI.MIC. SILTY SAND W/ GRAVEL & COBBLES

SAPROLITE: BROWN & GREY MIC. SILTY FINE SAND

797.243 797.662 796.762 796.699

289+40.000

ALLUVIUM: BROWN & GREY SLI.MIC. SILTY SAND W/ GRAVEL & COBBLES

797.581 797.146 797.054 797.100

289+20.000
-L-

ALLUVIUM: BROWN & GREY SLI.MIC. SILTY SAND W/ GRAVEL & COBBLES

800

795

50 40 30 20 10 0 10 20 30 40 50

$$$$USERNAME$$$$

50 40 30 20 10 0 10 20 30 40 50

800

795

SAPROLITE
MIC. SILTY SAND DENSE

795.817
795.682
795.564

EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

ALLUVIUM:
BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES

291+00.000

SAPROLITE:
BROWN & GREY MIC. SILTY FINE SAND

EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

795.720

ALLUVIUM:
BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES

290+80.000

SAPROLITE:
BROWN & GREY MIC. SILTY FINE SAND

EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

795.633

ALLUVIUM: BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES LOOSE

290+60.000

SAPROLITE:
BROWN & GREY MIC. SILTY FINE SAND LOOSE

EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

795.702
795.656
795.632

ALLUVIUM: BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES LOOSE

290+40.000

SAPROLITE:
BROWN & GREY MIC. SILTY FINE SAND LOOSE

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

815
810
805
800
795

FOLD LINE

SAP. AND RES. SOILS
MIC. SILTY SAND
MED. DENSE TO DENSE

SAP. AND WEATHERED RK
MIC. SILTY SAND
DENSE TO VERY DENSE

196.742
196.470
196.228

EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

196.016

291+40.000

ALLUVIUM: BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES

SAPROLITE:
BROWN & GREY MIC. SILTY FINE SAND

SAP. AND RES. SOILS
MIC. SILTY SAND
MED. DENSE TO DENSE

SAP. AND WEATHERED RK
MIC. SILTY SAND
DENSE TO VERY DENSE

196.699
196.266
196.026

EMBANKMENT

196.005

MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

291+20.000

ALLUVIUM: BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES

SAPROLITE:
BROWN & GREY MIC. SILTY FINE SAND

10/26/98
SYSTEM\USERNAME\DGN


50
40
30
20
10
0
10
20
30
40
50
815
810
805
800
795
SAP. AND RES. SOILS
MIC. SILTY SAND
MED. DENSE TO DENSE
SAP. AND WEATHERED RK
MIC. SILTY SAND
DENSE TO VERY DENSE
EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE
796.80
796.50
796.158
796.158
29I+60.000
-L-
ALLUVIUM: BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES
SAPROLITE: BROWN & GREY MIC. SILTY FINE SAND

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

810 805 800 795

2V

SAP. AND RES. SOILS
MIC. SILTY SAND
MED. DENSE TO DENSE

796,709
796,741
796,564
796,458

292+00.000

ALLUVIUM: BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES

SAPROLITE:
BROWN & GREY MIC. SILTY FINE SAND

820 815 810 805 800 795

FOLD LINE

2V

SAP. AND RES. SOILS
MIC. SILTY SAND
MED. DENSE TO DENSE

796,452
796,690
796,483

EMBANKMENT
MIC. SILTY SAND W/ VARIED RK AND ROCK FRAGS LOOSE

796,466

291+80.000

ALLUVIUM: BROWN & GREY SLI. MIC. SILTY SAND W/ GRAVEL & COBBLES

SAPROLITE:
BROWN & GREY MIC. SILTY FINE SAND

50 40 30 20 10 0 10 20 30 40 50

10/26/95
$$$$USERNAME$$$$

50 40 30 20 10 0 10 20 30 40 50

800

795

805

810

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

796.994 796.755 796.595 796.297 796.232

292+60.000

ALLUVIUM: BROWN & GREY SU. MIC. SILTY SAND W/ GRAVEL & COBBLES

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

797.026 796.785 796.529 796.304

292+40.000

EMBANKMENT
MIC. SILTY SAND W/ RK FRAGS
LOOSE

ALLUVIUM: BROWN & GREY SU. MIC. SILTY SAND W/ GRAVEL & COBBLES

797.032 796.771 796.511 796.320 796.160

292+20.000

EMBANKMENT
MIC. SILTY SAND W/ RK FRAGS
LOOSE

ALLUVIUM: BROWN & GREY SU. MIC. SILTY SAND W/ GRAVEL & COBBLES

50 40 30 20 10 0 10 20 30 40 50

50 40 30 20 10 0 10 20 30 40 50

800 795

797.204
0.0318 ft/ft
796.408
795.730
795.615
795.225
EMBANKMENT
MIC. SILTY SAND W/ RK FRAGS
LOOSE
RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE
293+60.000

796.550
795.820
795.651
EMBANKMENT
MIC. SILTY SAND W/ RK FRAGS
LOOSE
RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE
293+40.000

796.696
796.743
796.807
795.916
795.999
RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE
293+20.000

796.289
796.576
796.540
796.065
796.132
RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE
293+00.000

796.329
796.687
796.596
796.198
EMBANKMENT
MIC. SILTY SAND W/ RK FRAGS
LOOSE
RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE
292+80.000

50 40 30 20 10 0 10 20 30 40 50

294+60.000

FILL MIC. SILTY SAND W/ RK FRAGS LOOSE TO MED. DENSE

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

294+40.000

FILL
MIC. SILTY SAND W/ RK. FRAGS
LOOSE TO MED. DENSE

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

294+20.000

FILL
MIC. SILTY SAND W/ RK. FRAGS
LOOSE TO MED. DENSE

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

294+00.000

FILL
MIC. SILTY SAND W/ RK. FRAGS
LOOSE TO MED. DENSE

293+80.000

2.5 0 2.5 5

METRIC

10/26/98

$$$$$$SYSTIME$$$$$$
$$$$$$USERNAME$$$$$$
$$$$$$DGNFILE$$$$$$

805 800 795

50 40 30 20 10 0 10 20 30 40 50

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

795.722 795.571 795.572 795.457

RES. SOILS AND SAPROLITE 295+60.000

2:1 4:1

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

795.540 795.739 795.736 795.540 795.615

RES. SOILS AND SAPROLITE 295+40.000

ALLUVIUM
MIC. SILTY SAND W/ GRAVEL
LOOSE

2:1 4:1

795.800 795.809 795.660 795.660 795.719

RES. SOILS AND SAPROLITE 295+20.000

4.393:1 794.401

ALLUVIUM
MIC. SILTY SAND W/ GRAVEL
LOOSE

0.0050 0.0000

796.088 795.994 795.933 796.733 795.782

RES. SOILS AND SAPROLITE 295+00.000

4.576:1 794.056

ALLUVIUM
MIC. SILTY SAND W/ GRAVEL
LOOSE

FILL MIC. SILTY SAND W/ RK. FRAGS
LOOSE TO MED. DENSE

796.809 796.702 795.959 795.759 795.804

294+80.000

4.004:1 793.820

ALLUVIUM
MIC. SILTY SAND W/ GRAVEL
LOOSE

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

805

800

795

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

2:1

3:1

794.427 794.496 794.926 794.939

794.810

296+20.000

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

2:1

3:1

794.909 795.103 795.542 795.935

795.081

296+00.000

RES. SOILS AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

2:1

3:1

795.457 795.536 795.963 795.979

795.272

295+80.000

50 40 30 20 10 0 10 20 30 40 50

USER NAME = SYSTIMEssssss

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

795

793.111 793.520 793.544 793.576

0.0200 0.0200 0.0200 0.0200

793.264

297+20.000

795

793.569 793.578 793.585 793.864

0.0200 0.0200 0.0200 0.0200

793.660

297+00.000

800

795

793.859 794.139 794.128 794.324

0.0200 0.0200 0.0200

793.988

296+80.000

RES. SOILS AND SAPROLITE

ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

805

800

795

794.135 794.339 794.450 794.600

794.277

296+60.000

RES. SOILS AND SAPROLITE

ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

805

800

795

794.191 794.390 794.696 794.856

794.556

296+40.000

RES. SOILS AND SAPROLITE

ORANGE MIC. SILTY SAND
MED. DENSE TO DENSE

50 40 30 20 10 0 10 20 30 40 50

$$$$SYSTIMES$$$$
$$$$USERNAME$$$$
$$$$DGNNAME$$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

800 795 790

789963 789853 789759 789328

4:1 3:1

RDY FILL: BRN.SILTY SAND W/ RK FRAGS

ALLUVIUM: GREY SLI.MIC.COARSE SAND W/ GRAVEL

298+80.000

SAPROLITE: BRN.MIC.SILTY FINE SAND

800 795 790

789725 789540 790003 790055

789890

RDY FILL: BRN.SILTY SAND W/ RK FRAGS

ALLUVIUM: GREY SLI.MIC.COARSE SAND W/ GRAVEL

298+60.000

SAPROLITE: BRN.MIC.SILTY FINE SAND

795 790

790069 790143 790161 790534

790201

298+40.000

-L-

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

299+80.000

790
785
787.618
5.33%
6%
4:1
2%
RDY. FILL: BRN. SILTY SAND W/ RK FRAGS
ALLUVIUM: GREY SLI.MIC. COARSE SAND W/ GRAVEL
SAPROLITE: BRN. MIC. SILTY FINE SAND

299+60.000

790
785
4:1
2%
RDY. FILL: BRN. SILTY SAND W/ RK FRAGS
ALLUVIUM: GREY SLI.MIC. COARSE SAND W/ GRAVEL
SAPROLITE: BRN. MIC. SILTY FINE SAND

299+40.000

790
785
4:1
2%
RDY. FILL: BRN. SILTY SAND W/ RK FRAGS
ALLUVIUM: GREY SLI.MIC. COARSE SAND W/ GRAVEL
SAPROLITE: BRN. MIC. SILTY FINE SAND

299+20.000

790
785
4:1
2%
RDY. FILL: BRN. SILTY SAND W/ RK FRAGS
ALLUVIUM: GREY SLI.MIC. COARSE SAND W/ GRAVEL
SAPROLITE: BRN. MIC. SILTY FINE SAND

299+00.000

800
795
790
4:1
2%
RDY. FILL: BRN. SILTY SAND W/ RK FRAGS
ALLUVIUM: GREY SLI.MIC. COARSE SAND W/ GRAVEL
SAPROLITE: BRN. MIC. SILTY FINE SAND

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

790 785

RDY FILL: SILTY SAND W/RK FRAGS
787.593 787.556 787.413 786.462
301+00.000

RDY FILL: SILTY SAND W/RK FRAGS
787.781 787.739 787.657 786.654
300+80.000

300+60
11.5m RT -L-
RDY FILL: SILTY SAND W/RK FRAGS
PROPOSED RETAINING WALL
787.959 787.921 787.838 786.847
300+60.000
05/16/03
100+ 5 7 7 10
4 6 12
ALLUVIUM: GREY BROWN SLI.MIC. SILTY SAND W/ RK FRAGS
DARK GREY SLI.MIC CLAYEY SILT
SAPROLITE: ORANGE SLI.MIC. SILTY SAND W/ RK FRAGS

300+40
37m LT -L-
ABC
RESIDUAL: RED MIC. SILTY FINE SAND
5 3 5 17 31 29 100+
SAPROLITE: TAN SLI.MIC. FINE SANDY SILT
WEATHERED ROCK
788.039 787.039
300+40.000
PROPOSED RETAINING WALL

300+20
11m RT. -L-
788.306 788.177 787.306 787.232
RDY FILL: BRN. SILTY SAND W/ RK FRAGS
10 13 9
05/16/03
15 3 5 8 8
ALLUVIUM: GREY SLI.MIC. COARSE SAND W/ GRAVEL
SAPROLITE: BRN. MIC. SILTY FINE SAND
300+20.000
PROPOSED RETAINING WALL

788.499 787.459 787.425
RDY FILL: BRN. SILTY SAND W/ RK FRAGS
300+00.000
ALLUVIUM: GREY SLI.MIC. COARSE SAND W/ GRAVEL
-L-
SAPROLITE: BRN. MIC. SILTY FINE SAND
PROPOSED RETAINING WALL

50 40 30 20 10 0 10 20 30 40 50

SSTIMPSON
DESIGNATION

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

795 790 785

5.5%
6:1
785.851
786.668
786.772
786.725
6:1
2:1
RES. SOILS
785.651 ORANGE MIC. SILTY SAND
LOOSE TO MED. DENSE

302+00.000

5.7%
6:1
785.704
786.762
786.892
786.668
6:1
2:1
RES. SOILS
785.784 ORANGE MIC. SILTY SAND
LOOSE TO MED. DENSE

301+80.000

6:1
6:1
785.864
786.869
787.051
786.827
6:1
2.9%
RES. SOILS
785.944
ORANGE MIC. SILTY SAND
LOOSE TO MED. DENSE

301+60.000

2%
787.069
787.215
786.968
6:1

301+40.000

301+30
42m LT -L-

ABC:
FILL:
(33) GREY SILTY SAND W/ RK. FRAG.
ALLUVIUM:
(26) GREY COARSE SAND, GRAVELS & RK. FRAGS.
SAPROLITE:
(3) ORANGE BROWN MIC. SILTY SAND
(6)

4.52%
6:1
6:1
787.261
786.279

301+20.000
-L-

50 40 30 20 10 0 10 20 30 40 50

795 790 785

6:1 6:1 6:1 6:1

785.472 786.421 785.472

FILL:
RED MIC. SILTY SAND
W/ FK. FRAGS.

RES. SOILS
ORANGE MIC. SILTY SAND
LOOSE TO MED. DENSE

302+60.000

785.495 786.413 785.495

RES. SOILS
ORANGE MIC. SILTY SAND
LOOSE TO MED. DENSE

302+40.000

785.555 786.525 785.555

RES. SOILS
ORANGE MIC. SILTY SAND
LOOSE TO MED. DENSE

302+20.000

50 40 30 20 10 0 10 20 30 40 50

01/26/98
SYSTIMES.DGN
USER NAME =

50 40 30 20 10 0 10 20 30 40 50

790
785

FILL:
RED MIC. SILTY SAND
W/ FK. FRAGS.

PROPOSED
RETAINING WALL

SAPROLITE:
RED/BRN MIC. CLAYEY SILT
AND SILTY SAND

6:1 6:1 2:1

786.719
785.141
785.521
786.122

303+40.000

FILL:
RED MIC. SILTY SAND
W/ FK. FRAGS.

PROPOSED
RETAINING WALL

SAPROLITE:
RED/BRN MIC. CLAYEY SILT
AND SILTY SAND

6:1 6:1 2:1

786.615
785.623
786.097
786.697

303+20.000

303+00
23m RT -L-

PROPOSED
RETAINING WALL

FILL:
RED MIC. SILTY SAND
W/ FK. FRAGS.

SAPROLITE:
RED/BRN MIC. CLAYEY SILT
AND SILTY SAND

SAPROLITE:
BROWN MIC. SILTY SAND
W/ RK. FRAGS

6:1 6:1 2:1

7 5 17 22 2 8 10 7 7

786.531
785.536
786.050
786.650

303+00.000

FILL: RED MIC. SILTY SAND
W/ FK. FRAGS.

SAPROLITE:
BROWN MIC. SILTY SAND
W/ RK. FRAGS
LOOSE TO MED. DENSE

6:1 6:1 6:1 2:1

786.464
785.486
786.300
786.560

302+80.000

-L-

$$$$$$$$$$USERNAME$$$$$$$$$$

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	122 of 238

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

795 790 785

5.2%

6:1

786.506

787.580 787.540 787.458

RES. SOILS AND SAPROLITE
BRN MIC. SANDY SILT
LOOSE

2:1

786.506

304+40.000

4.6%

6:1

786.372

787.446 787.346

RES. SOILS AND SAPROLITE
BRN MIC. SANDY SILT
LOOSE

2:1

786.372

304+20.000

6:1 6:1

786.228

787.304 787.247

6:1

786.228

304+00.000

4.5%

6:1

786.072

787.146 787.071

6:1

786.072

303+80.000

3.2%

6:1

785.906

785.960 786.889

6:1

785.906

303+60.000

303+60

PROPOSED
RETAINING WALL

FILL:
RED & BROWN SLI. MIC
SILTY CLAY

RES. SOILS AND SAPROLITE
GREY MIC SILTY CLAY
W/ MnO

05/20/03

11 2 6 7 10 5 9 4 3

50 40 30 20 10 0 10 20 30 40 50

01/26/89

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO. R-2519A

SHEET NO. 1230 of 2356

50 40 30 20 10 0 10 20 30 40 50

800 795 790 785

5.80%

787.703

787.566

787.555

6.1%

786.628

2:1

RES. SOILS AND SAPROLITE
BRN MIC. SANDY SILT
LOOSE

304+60.000
-L-

50 40 30 20 10 0 10 20 30 40 50

800 795 790 785

SYSTIME=Fri Jan 27 08:00:00 1989

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	124 of 235

90 80 70 60 50 40 30 20 10 0

790
785

787.956
3.30%
RES. SOILS
RED/BRN MIC. SILTS
LOOSE TO MED. DENSE
305+20.000

790
785

787.828
3.75%
RES. SOILS
RED/BRN MIC. SILTS
LOOSE TO MED. DENSE
305+00.000

790
785

787.736
3.70%
RES. SOILS
RED/BRN MIC. SILTS
LOOSE TO MED. DENSE
304+80.000

90 80 70 60 50 40 30 20 10 0

$$$

90 80 70 60 50 40 30 20 10 0

790
785

EMBANKMENT
MIC. SILTY SAND W/ RK & FRAGS
LOOSE
788.29ℓ
2:1
RES. SOILS
RED/BRN MIC. SILTS
LOOSE TO MED. DENSE
305+80.000

EMBANKMENT
MIC. SILTY SAND W/ RK & FRAGS
LOOSE
788.17ℓ
2:1
RES. SOILS
RED/BRN MIC. SILTS
LOOSE TO MED. DENSE
305+60.000

EMBANKMENT
MIC. SILTY SAND W/ RK FRAGS
LOOSE
788.09ℓ
2:1
RES. SOILS
RED/BRN. MIC. SILTS
LOOSE TO MED. DENSE
305+40.000

90 80 70 60 50 40 30 20 10 0
-L-

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

800 795 790 785

EMBANKMENT
BRN.MIC.SILTY SAND
LOOSE

0.020 0.020 0.020 0.020

788.594 787.245 788.639

2:1 2:1 6:1

RES.SOILS AND SAPROLITE
MIC.SILTY SAND
LOOSE TO MED.DENSE

787.566

RES.SOILS
LOOSE TO MED.DENSE

306+20.000

800 795 790 785

EMBANKMENT
BRN.MIC.SILTY SAND
LOOSE

0.020 0.020 0.020 0.020

788.522 788.541 788.465

2:1 2:1 6:1

RES.SOILS AND SAPROLITE
MIC.SILTY SAND
LOOSE TO MED.DENSE

787.426

RES.SOILS
LOOSE TO MED.DENSE

306+00.000

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

790
785

EMBANKMENT
BRN.MIC.SILTY SAND
LOOSE

Ditch Depth

6:1

788.260

789.323

6:1

Ditch Depth

788.268

RES.SOILS
LOOSE TO MED.DENSE

306+80.000

790
785

EMBANKMENT
BRN.MIC.SILTY SAND
LOOSE

789.176
789.190

789.039

6:1

5.65:1

787.961

2:1

RES.SOILS
LOOSE TO MED.DENSE

306+60.000

795
790
785

EMBANKMENT
BRN.MIC.SILTY SAND
LOOSE

788.300
788.325

788.813

2:1

5:1

RES.SOILS AND SAPROLITE
MIC.SILTY SAND
LOOSE TO MED.DENSE

RES.SOILS
LOOSE TO MED.DENSE

306+40.000

50 40 30 20 10 0 10 20 30 40 50

307+60.000

RES. SOILS
LOOSE TO MED. DENSE

EMBANKMENT
BRN. MIC. SILTY SAND
LOOSE

Ditch Depth

6:1

791.252

791.243

791.662

790.802

3.61

789924

790.995

789941

3.39

307+40.000

RES. SOILS
LOOSE TO MED. DENSE

EMBANKMENT
BRN. MIC. SILTY SAND
LOOSE

Ditch Depth

6:1

790.379

790.455

790.340

789200

789272

4.30

307+20.000

RES. SOILS
LOOSE TO MED. DENSE

EMBANKMENT
BRN. MIC. SILTY SAND
LOOSE

2:1

6:1

789.694

788753

307+00.000

50 40 30 20 10 0 10 20 30 40 50

795 790 785

SYSTINE\$\$\$

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	129 of 238

50 40 30 20 10 0 10 20 30 40 50

800

795

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

6:1

794783

308+40.000

794738

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

6:1

794038

308+20.000

793773

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

6:1

793245

308+00.000

792299

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

6:1

792464

307+80.000

791769

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

6:1

50 40 30 20 10 0 10 20 30 40 50

50 40 30 20 10 0 10 20 30 40 50

800

795

SAPROLITE:
ORANGE FINE SANDY CLAY
GREY & ORANGE LOOSE TO MED.DENSE
SILTY SAND

6:1

795.123

796.535 796.430 796.408

309+00.000

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

796.454

308+70
15m LT -L-

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

05/28/03

5
14
23
100+

794.693

796.076 796.400

795.922

GREY & ORANGE
SILTY SAND

308+80.000

WEATHERED ROCK:

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

796.927

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

794.156

795.588 795.463

795.407

308+60.000

SAPROLITE:
ORANGE FINE SANDY CLAY
LOOSE TO MED.DENSE

795.487

-L-

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

800
795

SAPROLITE:
ORANGE FINE SANDY CLAY
GREY & ORANGE SILTY SAND LOOSE TO MED.DENSE

797.183
797.109
795.178
795.995
795.951

309+80.000

797.183
797.105
795.174
795.995
795.930

309+60.000

796.982
796.995
795.664
795.995
795.877

309+40.000

796.773
796.771
795.446
795.995
795.764

309+20.000

50 40 30 20 10 0 10 20 30 40 50

10/25/93

800
795
790

50 40 30 20 10 0 10 20 30 40 50

EMBANKMENT
ORANGE CLAYEY SANDY SILT

6:1
2:1
794.735
796.047
796.442
796.448
796.459
796.524
796.987
797.044
797.279
797.101
797.165
796.718
796.927
795.467
795.676

310+60.000

SAPROLITE AND WEATHERED RK
MED. DENSE TO VERY DENSE

310+40.000

SAPROLITE AND WEATHERED RK
MED. DENSE TO VERY DENSE

310+20.000

SAPROLITE
ORANGE FINE SANDY CLAY
LOOSE

310+00.000

-L-

10:26:08

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	133 of 238

50 40 30 20 10 0 10 20 30 40 50

805

800

795

790

SAPROLITE:
ORANGE & WHITE TO BRN.
MIC.TO SLMIC CLAYEY TO
SILTY SAND W/ FEW RK.FRAGS
MED.DENSE TO DENSE

WEATHERED ROCK
VERY DENSE

792.912

794.229

794.169

794.429

6:1

6:1

490.4

794.243

311+20.000

SAPROLITE
MIC.SILTY SAND
MED.TO DENSE

WEATHERED ROCK
VERY DENSE

793.615

795.128

795.062

794.946

311+00.000

SAPROLITE
MIC.SILTY SAND
MED.TO DENSE

WEATHERED ROCK
VERY DENSE

794.223

795.535

795.587

310+80.000

310+80
21m RT -L- EMBANKMENT
ORANGE CLAYEY
SANDY SILT

05/28/03

SAPROLITE:
GREY & WHITE
SILTY SAND

0
24
100+
100+

WEATHERED ROCK:

-L-

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

311+60
30m LT -L-

FOLD LINE

SARROLITE:
ORANGE & WHITE TO BRN.
MIC.TO SLI.MIC CLAYEY TO
SILTY SAND W/ FEW RK.FRAGS

8
36
19
11
6
32
18
20
42
35
36
30

3:1

6:1

WEATHERED ROCK
VERY DENSE

791218

792658

792539

792788

DITCH LINE

7925.49

311+60.000

SARROLITE:
ORANGE & WHITE TO BRN.
MIC.TO SLI.MIC CLAYEY TO
SILTY SAND W/ FEW RK.FRAGS
MED.DENSE TO DENSE

WEATHERED ROCK
VERY DENSE

792.13

793525

794482

793.562

793.444

311+40.000

50 40 30 20 10 0 10 20 30 40 50

805 800 795 790

DESIGN NAME
PROJECT ENGINEER
PROJECT MANAGER

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

805
800
795
790
785

FOLD LINE

SAPROLITE:
ORANGE & WHITE TO BRN.
MIC.TO SLI.MIC CLAYEY TO
SILTY SAND W/ FEW RK.FRAGS
MED.DENSE TO DENSE

WEATHERED ROCK

6:1

6:1

Ditch Depth

791.541
791.839
791.623
791.479
790.228

311+80.000

50 40 30 20 10 0 10 20 30 40 50

805
800
795
790
785

DESIGN ENGINEER'S SEAL AND SIGNATURE

SAPROLITE:
ORANGE & WHITE TO BRN.
MIC.TO SLI.MIC CLAYEY TO
SILTY SAND W/ FEW RK.FRAGS

787.961

789.389
789.196
789.324

EMBANKMENT
ORANGE & BROWN
SLI.MIC.SILTY SAND
W/ ROCK FRAGS

SEE C-127
STA 10+60.000
782.854

312+20.000

SAPROLITE:
ORANGE & WHITE TO BRN.
SILTY SAND W/ FEW RK.FRAGS

WEATHERED ROCK

789.142

790.033
790.057
790.492

EMBANKMENT
ORANGE & BROWN
SLI.MIC.SILTY SAND
W/ ROCK FRAGS

312+00.000

50 40 30 20 10 0 10 20 30 40 50
800 795 790 785 780

312+60
10m RT -L-

786.597

ALLUVIUM:
RED MIC.TO SLI.MIC
SILTY SAND W/ RK FRAGS

EMBANKMENT
ORANGE & BROWN
SLI.MIC.SILTY SAND
W/ ROCK FRAGS

312+60.000

SAPROLITE
MED.DENSE

S.S. 788.365

786.177

788.094

SEE -Y21-
STA 10+40.000

312+40.000

ALLUVIUM:
RED MIC.TO SLI.MIC
SILTY SAND W/ RK FRAGS

-L-

10/26/98
USERNAME=
DGN=

50 40 30 20 10 0 10 20 30 40 50

785 780 790 785 780 795 790 785 780

313+20.000

EMBANKMENT
ORANGE & BROWN
SLI.MIC.SILTY SAND
W/ ROCK FRAGS

ALLUVIUM:
RED MIC.TO SLI.MIC
SILTY SAND W/ RK FRAGS

SAPROLITE
BRN MIC.SILTY SAND
MED.DENSE TO DENSE

Ditch Depth

782.809
783.064
783.457

2:1 6:1

313+00.000

EMBANKMENT
ORANGE & BROWN
SLI.MIC.SILTY SAND
W/ ROCK FRAGS

ALLUVIUM:
RED MIC.TO SLI.MIC
SILTY SAND W/ RK FRAGS

SAPROLITE
MED.DENSE

SAPROLITE
BRN MIC.SILTY SAND
MED.DENSE TO DENSE

784.017
784.459
784.464
783.588

2:1 6:1

312+80.000

EMBANKMENT
ORANGE & BROWN
SLI.MIC.SILTY SAND
W/ ROCK FRAGS

ALLUVIUM:
RED MIC.TO SLI.MIC
SILTY SAND W/ RK FRAGS

SAPROLITE
MED.DENSE

SAPROLITE W/
WEATHERED RK
BRN/WHT MIC.SILTY SAND
MED.TO VERY DENSE

785.387
785.745
785.771
784.994

2:1 6:1

ROCK VERIFIED BY PENETROMETER

50 40 30 20 10 0 10 20 30 40 50


780
775
785
790
50
40
30
20
10
0
10
20
30
40
50
EMBANKMENT
ORANGE & BROWN
SLI.MIC. SILTY SAND
W/ ROCK FRAGS
ALLUVIUM:
RED MIC. TO SLI. MIC
SILTY SAND W/ RK FRAGS
SAPROLITE
BRN MIC. SILTY SAND
MED. DENSE TO DENSE
314+20.000
314+00.000
313+80.000
313+60.000
313+40.000
776.685
777.752
778.996
780.327
781.593
4.32H
2.99H
2.57H
2.38H
2V
2H
1V
1H

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

780
775

772.978
772.245
772.260
771.538
2:1
6:1
SAPROLITE
315+00.000

780
775

EMBANKMENT
773.985
774.688
773.947
772.276
ALLUVIUM
314+80.000

780
775

774.533
774.246
774.564
773.141
EMBANKMENT
ALLUVIUM:
RED MIC.TO SLI.MIC
SILTY SAND W/ RK FRAGS
314+60.000

780
775

775.605
775.242
775.547
ALLUVIUM:
RED MIC.TO SLI.MIC
SILTY SAND W/ RK FRAGS
314+40.000

50 40 30 20 10 0 10 20 30 40 50

01/25/95
BLUEPRINT WORKING

2.5 0 2.5 5	METRIC	PROJECT REFERENCE NO. R-2519A	SHEET NO. 141 OF 236

315+80.000

EMBANKMENT

-Y28-
10+37.442

0.0657 0.0471

6:1 2:1 4.32:1

SAPROLITE

2:1

772.367

771.573 771.278 771.105

315+60.000

EMBANKMENT

-Y28-
10+58.808

0.0441 0.0319

2:1 2.79:1 3.83:1

PROPOSED RETAINING WALL

SAPROLITE
MED. DENSE TO DENSE

FOLD LINE

775.487

2:1 6:1

770.092

771.789 771.604 771.390

315+40.000

2:1 6:1

SAPROLITE

770.446

772.255 771.858 771.779

315+20.000

2:1 6:1

SAPROLITE

770.928

772.595 772.140 772.291

50 40 30 20 10 0 10 20 30 40 50

780 775 770

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	142 of 236

50 40 30 20 10 0 10 20 30 40 50

780 775 770

Ditch Depth

6:1

770.836

771.242

770.906

6:1

6:1

769.505

316+60.000

316+38
10m RT -L-

EMBANKMENT
BRN.SLI.MIC SILTY SAND

771.242

770.878

6:1

5.37:1

769.645

05/29/03

6

18

16

ALLUVIUM:
BRN.SLI.MIC SILTY SAND
W/ RK.FRAGS

SAPROLITE:
BRN.SLI. SILTY SAND
W/ RK.FRAGS

220'

780 775 770

Ditch Depth

6:1

770.956

771.142

770.962

6:1

6:1

769.705

4.24:1

316+20.000

780 775 770

-Y28-
10+15.396

6:1

770.991

771.142

770.104

0.0067

1.79:1

2.39:1

S.S. 780.066

SAPROLITE

316+00.000
-L-

50 40 30 20 10 0 10 20 30 40 50

$$$$SYSTIME$$$$
$$$$SYSDATE$$$$
$$$$DGNFILE$$$$
$$$$MODEL$$$$
$$$$USERNAME$$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

770

5.32:1

EMBANKMENT:
BRN.MIC.SILTY SAND

770.723

770.978

770.722

Ditch Depth

6:1

6:1

769.191

ALLUVIUM:
BRN.SILTY SAND
LOOSE

317+40.000

SAP.AND WEATHERED RK
MIC.SILTY SAND
MED.DENSE TO VERY DENSE

770

5.45:1

EMBANKMENT:
BRN.MIC.SILTY SAND

771.01

770.842

6:1

6:1

769.320

ALLUVIUM: BRN.SILTY SAND
LOOSE

317+20.000

SAP.AND WEATHERED RK
MIC.SILTY SAND
MED.DENSE TO VERY DENSE

775

770

780

775

770

EMBANKMENT:
BRN.MIC.SILTY SAND

4.45:1

771.12

770.877

770.950

6:1

6:1

769.385

ALLUVIUM: BRN.SILTY SAND
LOOSE

317+00.000

SAP.AND WEATHERED RK
MIC.SILTY SAND
MED.DENSE TO VERY DENSE

775

780

775

770

Ditch Depth

6:1

771.212

770.837

770.856

770.922

316+85
12m RT -L-

EMBANKMENT:
BROWN MIC.SILTY SAND
W/ BOULDERS & RK FRAGS

ALLUVIUM:
BRN.SAND,GRAVEL & COBBLES

5:1

05/29/03

9
5
100+
100+

316+80.000

-L-

WEATHERED ROCK

770

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

NOTE:
ENCOUNTERED OLD STUMP OR LOGS

318+25
6m LT -L-

769.758
769.795
769.280

EMBANKMENT:
BRN.SILTY SAND & GRAVELS

ALLUVIUM:
BRN.SILTY SAND

EMBANKMENT:
BRN.SILTY SAND & GRAVELS

10
26
05/29/03
57

WEATHERED ROCK:

770
775

318+06
15m RT -L-

770.029
770.036
769.800

EMBANKMENT:
BRN.MIC.SILTY SAND

ALLUVIUM:
DARK GREY SLI.MIC
SILTY SAND

SAPROLITE AND WEATHERED RK
MIC.SILTY SAND
DENSE TO VERY DENSE
769.448

2
2
05/29/03
100+

318+00.000

WEATHERED ROCK:

FILL
ABC W/ SANDY GRAVEL

770.253
770.267
770.264

EMBANKMENT:
BRN.MIC.SILTY SAND

SAPROLITE AND WEATHERED RK
MIC.SILTY SAND
DENSE TO VERY DENSE
769.935

317+80.000

FILL
ABC W/ SANDY GRAVEL

770.259
770.288
770.392
770.348

EMBANKMENT:
BRN.MIC.SILTY SAND

Ditch Depth

SAPROLITE AND WEATHERED RK
MIC.SILTY SAND
DENSE TO VERY DENSE
769.931

317+60.000

50 40 30 20 10 0 10 20 30 40 50

10/25/95

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	145 of 338



2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	146 of 238

90 80 70 60 50 40 30 20 10 0

795

790

785

780

775

770

24"

SAPROLITE AND WEATHERED RK

MED. TO VERY DENSE

6.1

768.859

768.145

760.625

318+80.000

$$$$$$$$$$FILENAME$$$$$$$$$$
$$$$USERNAME$$$$

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

800
795
790
785
780
775
770

SAPROLITE AND WEATHERED ROCK
MED. TO VERY DENSE

24"

168688
168542

767.977

319+00.000

90 80 70 60 50 40 30 20 10 0

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	148 OF 236

90 80 70 60 50 40 30 20 10 0

800 795 790 785 780 775 770

SAPROLITE AND WEATHERED RK
MED. TO VERY DENSE

24

6:1

767.894

768.318

319+20.000

$$$


90
80
70
60
50
40
30
20
10
0
805
800
795
790
785
780
775
770
2:1
SAPROLITE AND WEATHERED RK
MED. TO VERY DENSE
6:1
767.901
768.249
319+40.000

90 80 70 60 50 40 30 20 10 0

800 795 790 785 780 775 770

SAPROLITE AND WEATHERED RK
MED. TO VERY DENSE

768.119

319+60.000

90 80 70 60 50 40 30 20 10 0

10/25/93

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	151 of 238

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

795 790 785 780 775 770

3:1

SAPROLITE AND WEATHERED RK
MED.TO VERY DENSE

6:1

768.492

168.540

319+80.000

USER NAME = $USERNAME$
DESIGN SYMBOLS

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770

2:1

6:1

768.912

768.915

320+20.000

SAPROLITE
MED. DENSE TO DENSE

2:1

6:1

768.800

768.790

320+00.000

790 785 780 775 770

90 80 70 60 50 40 30 20 10 0

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	153 of 238

90 80 70 60 50 40 30 20 10 0

795

790

785

780

775

770

SAP AND WEATHERED RK
MED. TO VERY DENSE

768.983

768.828

320+40.000

SSSS

90 80 70 60 50 40 30 20 10 0

805
800
795
790
785
780
775
770

SAP. AND WEATHERED IRK
MED. TO VERY DENSE

769013

768889

320+60.000

DGN: TIMMS
USER NAME: DOT

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

805
800
795
790
785
780
775
770

RES. SOILS AND SAPROLITE
MIC. SILTY SAND, MAO & FeO
LOOSE TO DENSE

SAPROLITE AND WEATHERED ROCK
BRN-WHT MIC. SILTY SAND
DENSE TO VERY DENSE

768.954

769.012

320+80.000

90 80 70 60 50 40 30 20 10 0

90 80 70 60 50 40 30 20 10 0

805
800
795
790
785
780
775
770

321+00
40m LT -L-

15
11
17
9
21
18
100/7"
41
100/7"

06/05/03

SAPROLITE:
RED BROWN & WHITE
SLI.MIC TO MIC.SILTY SAND

WEATHERED ROCK AND SAPROLITE
BRN/WHT MIC.SILTY SAND

768/763

769.09'

321+00.000

-L-

01/25/03
SSTIMESAVER

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	157 of 236

90 80 70 60 50 40 30 20 10 0

805 800 795 790 785 780 775 770

24

SAP. AND WEATHERED RK
MED. TO VERY DENSE

WEATHERED RK

768.601

6.1

768.966

768.570

321+20.000

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

90 80 70 60 50 40 30 20 10 0

800

795

790

785

780

775

770

24"

SAP. AND WEATHERED RK

MED. TO VERY DENSE

6:1

768.390

765.015

321+40.000

01/25/96
SSSSSSSYSTIMESSSSSSS

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

800
795
790
785
780
775
770

2:1

SAP. AND WEATHERED RK
MED. TO VERY DENSE

6:1

768.206
768.129
768.861

321+60.000

-L-

90 80 70 60 50 40 30 20 10 0

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

785 780 775 770

SAP. AND WEATHERED RK
MED. TO VERY DENSE

2:1

6:1

768.435

767.468

322+00.000

795 790 785 780 775 770

2:1

SAP. AND WEATHERED RK
MED. TO VERY DENSE

6:1

768.720

767.819

321+80.000

90 80 70 60 50 40 30 20 10 0


50 40 30 20 10 0 10 20 30 40 50
780
775
770
765
SAPROLITE:
BROWN & RED SLI.
MIC. TO MIC SILTY SAND
MED. DENSE TO DENSE
6:1
766.572
767.259
767.954
2:1
322+40.000
SAPROLITE: MED. DENSE
2:1
6:1
767.041
768.139
768.391
2:1
322+20.000

50 40 30 20 10 0 10 20 30 40 50

775
770
765

SAPROLITE:
BROWN & RED SU.
MIC.TO MIC SILTY SAND
MED.DENSE TO DENSE

2:1
6:1
2:1
2T
4T
767.387
765.950
767.358
767.429

322+80.000

780
775
770
765

SAPROLITE:
BROWN & RED SU.
MIC.TO MIC SILTY SAND
MED.DENSE TO DENSE

2:1
6:1
2:1
2T
4T
767.639
767.369
767.429
766.200

322+60.000

50 40 30 20 10 0 10 20 30 40 50

$$$$SS_TYPE$$$$
$$$$USERNAME$$$$

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

780 775 770 765

SAPROLITE:
BROWN & RED SL.
MIC. TO MIC SILTY SAND
MED. DENSE TO DENSE

2:1

6:1

765665

765805

767.29

756.86

4:1

323+20.000

SAPROLITE:
BROWN & RED SL.
MIC. TO MIC SILTY SAND
MED. DENSE TO DENSE

2:1

6:1

765722

767.55

767.45

757.06

2.50%

323+00.000

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5	METRIC	PROJECT REFERENCE NO. R-2519A	SHEET NO. 164 OF 238

50 40 30 20 10 0 10 20 30 40 50

785 780 775 770 765

323+68
36m LT -L-

FOLD LINE

2:1

22
16
38
29
28
27
24
66
15

06/06/03

SAPROLITE:
BROWN & RED SL.
MIC.TO MIC SILTY SAND

6:1

4:1

765.126

766.516

782.117

766.932

323+60.000

FOLD LINE

2:1

SAPROLITE:
BROWN & RED SL.
MIC.TO MIC SILTY SAND
MED.DENSE TO DENSE

6:1

4:1

765.673

766.712

765.978

767.048

323+40.000

-L-

50 40 30 20 10 0 10 20 30 40 50

785 780 775 770 765

10/25/99

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	165 of 238

2.5 0 2.5 5

METRIC

785 780 775 770 765

50 40 30 20 10 0 10 20 30 40 50

FOLD LINE

2:1

SAPROLITE:
BROWN & RED SLI.
MIC.TO MIC SILTY SAND
MED.DENSE TO DENSE

6:1

765.891

766.369

766.755

766.450

4:1

324+00.000

FOLD LINE

2:1

SAPROLITE:
BROWN & RED SLI.
MIC.TO MIC SILTY SAND
MED.DENSE TO DENSE

6:1

765.691

766.456

766.771

766.467

4:1

323+80.000

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

770
765

4.99%
6:1
765.940
766.667
767.275
764.045
Ditch Depth
6:1
765.940

324+60.000

770
765

2:1
SAPROLITE:
MED. DENSE
6:1
765.815
766.289
766.008
766.531
3:1

324+40.000

780
775
770
765

2:1
SAPROLITE:
BROWN & RED SU.
MIC. TO MIC SILTY SAND
MED. DENSE TO DENSE
6:1
765.030
766.054
766.457
766.389
4:1

324+20.000

50 40 30 20 10 0 10 20 30 40 50

50 40 30 20 10 0 10 20 30 40 50

775

770

765

SAPROLITE: MED DENSE

WEATHERED ROCK

2:1

6:1

766.112

766.868

766.756

767.186

324+80.000

50 40 30 20 10 0 10 20 30 40 50

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765

SAPROLITE
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED ROCK
DENSE TO VERY DENSE

24

766.325

766.904

325+00.000

90 80 70 60 50 40 30 20 10 0

90 80 70 60 50 40 30 20 10 0

795 790 785 780 775 770

SAPROLITE
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
DENSE TO VERY DENSE

W.T.

767.210

766.522

325+20.000

90 80 70 60 50 40 30 20 10 0

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

800 795 790 785 780 775 770

SAPROLITE
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
DENSE TO VERY DENSE

767.89

767.334

766674

325+40.000

90 80 70 60 50 40 30 20 10 0

10:26:08
DGN: 0519A_PROFILE.DGN
USER NAME = jmcdonald

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	171 of 238

90 80 70 60 50 40 30 20 10 0

800 795 790 785 780 775 770

SAPROLITE
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
DENSE TO VERY DENSE

766.812

767.496

325+60.000

90 80 70 60 50 40 30 20 10 0

$USERNAME$$$

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	172 of 238

90 80 70 60 50 40 30 20 10 0

800

795

790

785

780

775

770

SAPROLITE
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
DENSE TO VERY DENSE

767.006

767.608

325+80.000

10/25/95

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	173 of 238

90 80 70 60 50 40 30 20 10 0

800

795

790

785

780

775

770

325+90
62m LT -L

10
6
8
17
100+

SAPROLITE:
RED & BRN. MIC.
SILTY SAND

WEATHERED ROCK:

6:1

768008

767155

767585

326400.000

-L-

90 80 70 60 50 40 30 20 10 0

800

795

790

785

780

775

770

DGN: 9525RW
DATE: 10/25/95
DGNNAME: 9525RW

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

805
800
795
790
785
780
775
770

SAPROLITE (SA) MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK DENSE TO VERY DENSE

6:1

767.259

767.678

326+20.000

90 80 70 60 50 40 30 20 10 0

2.5 0 2.5 5

90 80 70 60 50 40 30 20 10 0

805 800 795 790 785 780 775 770

SAPROLITE
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
DENSE TO VERY DENSE

767.318

767.176

326+40.000

-L-

326+60
84m LT -L-

9
10
13
14
23
48
19
35
30
100+
100+
100+
62
100+

SAPROLITE:
BRN.TO LIGHT BRN.& GREY
SLI.MIC.TO MIC.SILTY
FINE SAND TO SILTY SAND

WEATHERED ROCK:

SAPROLITE:
BRN/GRAY MIC.SILTY SAND

2:1

6:1

767.414

767.606

326+60.000

-L-

805 800 795 790 785 780 775 770

90 80 70 60 50 40 30 20 10 0

10/25/95

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	177 of 238

90 80 70 60 50 40 30 20 10 0

795

790

785

780

775

770

SAPROLITE
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
DENSE TO VERY DENSE

767.376

767.439

767.752

326+80.000

90 80 70 60 50 40 30 20 10 0

USER NAME = USER
PLOT STYLE TABLE = STANDARD.STB

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770

SAPROLITE
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
DENSE TO VERY DENSE

WEATHERED ROCK

2:1

6:1

767+69

767+35

767+98

327+00.000

01/26/98
USER NAME = $$USER
PLOT SCALE = 50.000 '/ IN
PLOT DATE = $$DATE


50 40 30 20 10 0 10 20 30 40 50
770
765
6:1
766.345
766.396
766.559
766.750
5.7:1
327+60.000
770
765
6:1
766.629
766.576
766.788
767.255
5.0:1
327+40.000
780
775
770
765
8:1
6:1
766.918
766.846
767.289
767.754
6:1
327+20.000

$$$


50 40 30 20 10 0 10 20 30 40 50
775
770
765
2%
RES. SOIL AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE
6:1
766.158
766.050
766.137
766.255
3.04%
328+40.000
2.54%
RES. SOIL AND SAPROLITE
ORANGE MIC. SILTY SAND
MED. DENSE
766.052
766.022
766.169
EMBANKMENT
3.46%
328+20.000
ALLUVIUM
EMBANKMENT
766.071
3.85%
328+00.000
ALLUVIUM
Ditch Depth
766.145
766.253
766.469
EMBANKMENT
766.046
5.27%
327+80.000
ALLUVIUM

2.5 0 2.5 5


50 40 30 20 10 0 10 20 30 40 50
780
775
770
765
760
2:1
SAPROLITE
WEATHERED RK
6:1
765.081
765.011
763.668
331+00.000
770
765
2:1
6:1
765.030
765.842
765.292
764.293
330+80.000
2:1
6:1
765.905
766.574
765.853
764.938
330+60.000

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	182 of 238

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765

SAPROLITE

WEATHERED RK

2"

763.19'

764.08

764.08

764.08

331+20.000

$$$

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765

COLLUVIUM:
BRN; GREY & WHITE
W/ SILT RK FRAGS BOULDERS & SAND

SAPROLITE

WEATHERED RK

763.896

331+40.000

10-26-98
SURVEYING DIVISION
ROADWAY DESIGN

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	184 of 238

90 80 70 60 50 40 30 20 10 0

795 790 785 780 775 770 765

331+68
36m LT -L-

NOTE:
LARGE WEATHERED BOULDER
FROM 2.30-3.80m

2:1

06/11/03

9 (100+)
94
21
58
(100+)
400+

SAPROLITE

COLLUVIUM:
BRN.GREY & WHITE
W/ SILT RK FRAGS BOULDERS
& SAND

GREY & WHITE SILTY SAND
W/ SMALL RED CLAY SEAMS
& ROCK FRAGS

WEATHERED RK

6:1

763.4

763.480

762.301

331+60.000

-L-

90 80 70 60 50 40 30 20 10 0

CROSS SECTIONS ON THIS SHEET

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

795
790
785
780
775
770
765

COLLUVIUM:
BRN.GREY & WHITE
W/ SILT RK FRAGS BOULDERS
& SAND

SAPROLITE

WEATHERED RK

763.202

6:1

763.086

761.859

33L+80.000

DGN: SYSTIME: USERNAME:

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765

SAPROLITE

WEATHERED RK

763.205

761.499

332+00.000

90 80 70 60 50 40 30 20 10 0

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765 760

(G)

SAPROLITE

WEATHERED RK

761186

762335

332+20.000

11-26-98

$$$$$$SYSTIMES$$$$$$
$$$$$$USERNAME$$$$$$

50 40 30 20 10 0 10 20 30 40 50

765
760

761.305
762.873
762.730
6:1
EMBANKMENT
RES. SOILS
332+80.000

765
760

761.624
762.955
762.082
5.89:1
6:1
EMBANKMENT
RES. SOILS
332+60.000

770
765
760

EMBANKMENT
SAPROLITE
760.986
762.034
762.245
762.149
6:1
EMBANKMENT
332+40.000

50 40 30 20 10 0 10 20 30 40 50

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

760

Ditch Depth

759.607

6:1

760.526

760.601

760.727

EMBANKMENT

2:1

ALLUVIUM

333+60.000

760.038

760.162

760.675

EMBANKMENT

RES. SOILS

333+40.000

760.133

760.288

5.28:1

760.675

EMBANKMENT

RES. SOILS

333+20.000

760.392

760.488

760.968

EMBANKMENT

RES. SOILS

333+00.000

10/26/98
DESIGN UNITS ENGLISH
DRAWN BY: SMITH
DGN FILENAME: 2519A-X-SHEET

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

770
765
760

SAPROLITE
MED.DENSE TO DENSE
6:1
2:1
759.093
759.938
EMBANKMENT
2:1
2:1
334+20.000

SAPROLITE
MED.DENSE TO DENSE
6:1
2:1
759.243
760.091
EMBANKMENT
2:1
2:1
334+00.000

SAPROLITE
MED.DENSE TO DENSE
6:1
2:1
759.414
760.261
EMBANKMENT
2:1
2:1
333+80.000

10/25/95
SSHEET1.DGN
USER:kmeadows
DESIGN:
DRAWN:
CHECK:

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	19 of 238

90 80 70 60 50 40 30 20 10 0

780 775 770 765 760

2:1

SAPROLITE
MED. DENSE TO DENSE

6:1

759.779

759.966

334140.000

USER NAME = SMANGUM
DESIGNED
DRAWN
CHECKED
SUBMITTED

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	192 OF 238

90 80 70 60 50 40 30 20 10 0

785

780

775

770

765

760

SAPROLITE

MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK.

DENSE TO VERY DENSE

759.757

334+60.000

90 80 70 60 50 40 30 20 10 0

DESIGN ENGINEER
DRAWN BY
CHECKED BY
DATE
PROJECT ENGINEER

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	193 of 238

90 80 70 60 50 40 30 20 10 0

785 780 775 770 765 760

SAPROLITE
MED.DENSE TO DENSE

SAPROLITE AND WEATHERED RK
DENSE TO VERY DENSE

759.84

759.84

759.84

758.634

334+80.000

SYSTEMS\$\$\$

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.
R-2519A

SHEET NO.
1940 238

90 80 70 60 50 40 30 20 10 0

790
785
780
775
770
765
760

24

SAPROLITE

759.569

758.521

335+00.000

USER NAME = $$$$

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	195 of 238

90 80 70 60 50 40 30 20 10 0

780 775 770 765 760

SAPROLITE

FILL

759.595

759.561

759.433

758.414

335+20.000

90 80 70 60 50 40 30 20 10 0

780 775 770 765 760

$$$$USER NAME = $$$$

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	196 of 238

90 80 70 60 50 40 30 20 10 0

780 775 770 765 760

2:1

SAPROLITE

FILL

759.479

759.150

759.247

6:1

758.304

335+40.000

90 80 70 60 50 40 30 20 10 0

USERNAME = DOT\$CELL
DGN = ...\...\...dgn

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765 760

SAPROLITE AND WEATHERED RK
MED.TO VERY DENSE

759.363
759.299
759.153
758.123

335+60.000

-L-

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	198 OF 238

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765 760

SAPROLITE AND WEATHERED RK
MED. TO VERY DENSE

758.027

758.984

335+80.000

90 80 70 60 50 40 30 20 10 0

$$$$$SYSTEM$$$$$
$$$$$USERNAME$$$$$

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	199 of 238

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765 760

SAPROLITE

WEATHERED RK

6:1

759.251

758.863

757.974

336+00.000

$$$$$SYSTEM$$$$$
$$$$$USERNAME$$$$$

10/25/99

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	200 of 238

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765 760

336+28
45m LT L

6
8
100+
100+

SAPROLITE:
RED FINE SANDY CLAY
RED & BRN. MIC.
SILTY FINE SAND

WEATHERED RK

759.41

6.1

768.684

757.863

336+20.000

$$$$USERNAME$$$$

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	201 of 238

90 80 70 60 50 40 30 20 10 0

780 775 770 765 760

SAPROLITE AND WEATHERED RK
MED. TO VERY DENSE

2V

6:1

758.323

758.454

757.613

336+60.000

-L-

90 80 70 60 50 40 30 20 10 0

USER NAME = \\ PLOT SCALE = 10.0000 '/ in PLOT DATE = 10/26/98

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	202 of 238

50 40 30 20 10 0 10 20 30 40 50

760
755

758.097
759.511
758.458
6:1
2.5%
-L- 27.9%

337+20.000

760
755

757.317
758.278
760.417
759.629
6:1
2.5%
-L- 23.7%

337+00.000

765
760
755

SAPROLITE
WEATHERED RK
757.471
758.381
759.633
759.275
6:1
2.5%
-L- 20.1%

336+80.000

50 40 30 20 10 0 10 20 30 40 50

-L-

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	203 of 238

50 40 30 20 10 0 10 20 30 40 50

770

765

760

755

SAPROLITE

WEATHERED RK

2

757.949

756.008

757.725

756.784

2334

337+60.000

765

760

755

757.930

756.278

757.915

2734

337+40.000

50 40 30 20 10 0 10 20 30 40 50

10/25/95

2.5	0	2.5	5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	204 of 238

50 40 30 20 10 0 10 20 30 40 50

775 770 765 760 755

FOLD LINE

SAPROLITE
LOOSE TO MED. DENSE

WEATHERED RK

3:1

6:1

756.384

757.275

757.698

757.954

338+00.000

SAPROLITE
LOOSE TO MED DENSE

WEATHERED RK

2:1

6:1

756.585

757.496

757.888

757.749

337+80.000

50 40 30 20 10 0 10 20 30 40 50

775 770 765 760 755

$$$

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	205 OF 238

50 40 30 20 10 0 10 20 30 40 50

775 770 765 760 755

FOLD LINE

SAPROLITE:
WEATHERED RK

756.891
755.092

338+40.000

338+15
42m LT -L-

FOLD LINE

7
8
16
100+

SAPROLITE:
RED FINE SANDY CLAY
GREY SILTY SAND

WEATHERED RK

757.344
752.469
757.025
752.183

338+20.000

-L-

50 40 30 20 10 0 10 20 30 40 50

50 40 30 20 10 0 10 20 30 40 50

775 770 765 760 755

FOLD LINE

2:1

6:1

759.581

756.478

756.855

756.453

Ditch Depth

756.103

338+80.000

FOLD LINE

2:1

SAPROLITE:

WEATHERED RK

6:1

755.782

756.972

757.086

756.732

Ditch Depth

756.303

338+60.000

50 40 30 20 10 0 10 20 30 40 50

775 770 765 760 755

USER NAME = SSTEVENS
PLOT SCALE = 1.0000 '/ IN
PLOT DATE = 10/26/2021

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

770 765 760 755

339+35
6m RT -L- EMBANKMENT:
BRN.SLI.MIC.
SILTY SAND

PROPOSED
RETAINING WALL

ALLUVIUM:
GREY & BRN.SLI.MIC.
SILTY SAND & COBBLES & RK FRAGS.

2:1
6:1
2:1

755.380
756.390
756.664
756.397
08/20/03
16
3
13
7
6
100+

339+20.000

339+00.000

EMBANKMENT:
BRN.SLI.MIC.
SILTY SAND

ALLUVIUM:

Ditch Depth
755.902

-L-

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

760
755

2.89%
6:1
754.584
755.715
755.654
746.889
2.54%

339+80.000

765
760
755

2.89%
6:1
754.778
755.559
756.083
755.750
2.54%

339+60.000

765
760
755

2.89%
6:1
754.979
756.039
756.282
755.949
06/20/03
339+45
6m RT -L-

EMBANKMENT:
BRN.SLI.MIC.
SILTY SAND W./ RK.FRAGS.

ALLUVIUM:
GREY SILTY SAND
& COBBLES & RK.FRAGS

SAPROLITE:
ORANGE CLAYEY SAND

WEATHERED ROCK:

9 7 13 100/1
7 12 7

339+10.000

50 40 30 20 10 0 10 20 30 40 50

50 40 30 20 10 0 10 20 30 40 50

765 760 755

Ditch Depth

6:1

755.949

755.824

755.505

754.774

3.41:1

340+40.000

765 760 755

2.9:1

6:1

755.895

755.767

755.500

754.603

3.12:1

340+20.000

760 755

2.70:1

6:1

755.597

755.791

755.440

754.486

2.33:1

340+00.000

50 40 30 20 10 0 10 20 30 40 50

DESIGN SYSTEMS
MICROSTATION
FILENAME

2.5 0 2.5 5

METRIC

341+20
7.3m RT -L-

EMBANKMENT:
BRN.SILTY SAND
W/ RK.FRAGS

757.281
757.281
757.281

341+20.000

06/20/03

ALLUVIUM:
GREY & BRN.SLI.MIC.
SILTY SAND COBBLES & RK.FRAGS

SAPROLITE:
BRN.SLI.MIC. SILTY SAND
W/ RK.FRAGS

3.89:1

757.068
757.068
757.068

756.640

341+00.000

5.69:1

756.525
756.525
756.525

756.153

2.03:1

340+80.000

6:1

6:1

755.049

755.124
755.124
755.124

755.851

2.24:1

340+60.000

-L-

760
755
50 40 30 20 10 0 10 20 30 40 50

341+60.000

758.293
758.947
759.353
759.762
2:1
6:1
EMBANKMENT:
BRN. SILTY SAND
W/ RK. FRAGS
PROPOSED RETAINING WALL
ALLUVIUM:
GREY & BRN. SLI. MIC.
SILTY SAND COBBLES & RK. FRAGS
SAPROLITE:
BRN. SLI. MIC. SILTY SAND
W/ RK. FRAGS

341+40.000

758.055
759.170
759.462
3:1
2:1
EMBANKMENT:
BRN. SILTY SAND
W/ RK. FRAGS
PROPOSED RETAINING WALL
ALLUVIUM: GREY & BRN. SLI. MIC.
SILTY SAND COBBLES & RK. FRAGS
SAPROLITE:
BRN. SLI. MIC. SILTY SAND
W/ RK. FRAGS

50 40 30 20 10 0 10 20 30 40 50
770 765 760 755



10/26/98
USERNAME
DGN
FILE NAME

0 10 20 30 40 50 60 70 80 90

765 760 755

762.232 762.258 0.026 0.000 0.000 2H 2V
762.023

342+20.000

762.275 762.313 0.000 0.000 2H 2V
760.916

EMBANKMENT:
BRN.TO REDDISH BRN.
SLI.MIC.SILTY SAND
W/ RK.FRAGS.

342+00.000

341+80
8m RT -L-

760.259 760.310 0.000 0.000
759.878

12 8 15 9 18
17 13 32 13

EMBANKMENT:
BRN.TO REDDISH BRN.
SLI.MIC.SILTY SAND
W/ RK.FRAGS.

PROPOSED
RETAINING WALL

06/20/03

ALLUVIUM:
GREY MIC.SILTY SAND W/
FEW RK.FRAGS

SAPPOLITE:
BRN.MIC.SILTY SAND

341+80.000

-L-

0 10 20 30 40 50 60 70 80 90

765 760 755

10/26/05
$$$$USERNAME$$$$
$$$$DATE$$$$
$$$$TIME$$$$
$$$$DESIGNFILE$$$$

90 80 70 60 50 40 30 20 10 0

785 780 775 770 765 760

COLLUVIUM
BRN.MIC.SILTY SAND
W/ ROCK FRAGS.

342+00
32.5m LT =L=

SAPROLITE:
BRN.MIC.SILTY SAND

WEATHERED ROCK:

26
24
36
31
60+
20

6:1

764.25
763.15
760.916
760.218

342+00.000

-L-

USER NAME = $$$$

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

790 785 780 775 770 765 760

COLLUVIUM
BRN. MIC. SILTY SAND
W/ ROCK FRAGS.

2:1

SAP. AND WEATHERED RK
MIC. SILTY SAND
MED. DENSE TO DENSE

2:1

761.325

762.25
762.29
762.34
762.38

7621023

342+20.000

90 80 70 60 50 40 30 20 10 0

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	216 of 238

90 80 70 60 50 40 30 20 10 0

790

785

780

775

770

765

COLLUVIUM
BRN. MIC. SILTY SAND
W/ ROCK FRAGS.

SAP. AND WEATHERED RK

MIC. SILTY SAND
MED. DENSE TO DENSE

6:1

762.480

763.059

763.598

761.337

342+40.000

90 80 70 60 50 40 30 20 10 0

USER NAME = USER
DESIGN FILE = C:\PROJECTS\2519A\DGN\2519A_PROFILE.DGN

2.5 0 2.5 5

METRIC

342+80.000

342+60.000

342+40.000

765.274
764.179
764.623
764.950
764.117
763.179
763.387
763.538
763.059
762.044

6:1

Ditch Depth

0 10 20 30 40 50 60 70 80 90

765 760 755

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

790
785
780
775
770
765

COLLUVIUM
BRN. MIC. SILTY SAND W/ ROCK FRAGS.

SAPROLITE AND RES. SOILS
MIC. SILTY SAND
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
MIC. SILTY SAND
DENSE TO VERY DENSE

764.950
764.425
764.117
6.1
763.748

342+60.000

90 80 70 60 50 40 30 20 10 0

01/26/98
$$$$USER$NAME$$$$
$$$$DESIGN$FILENAME$$$$

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	219 OF 238

90 80 70 60 50 40 30 20 10 0

795 790 785 780 775 770 765

342+80
24m LT -L-

COLLUVIUM:
REDDISH BRN. TO DARK BRN.
SLI.MIC. SILTY SAND W/
RK. FRAGS. & SMALL BOULDERS

SAPROLITE:
REDDISH BRN. BLACK & WHITE
SLI.MIC. SANDY SILTY W/
WEATHERED & HARD RK. LEDGES

WEATHERED ROCK:

5	
17	
33	
4	
80	
28	
100/1"	

764.916

765.274

342+80.000

-L-

90 80 70 60 50 40 30 20 10 0

90 80 70 60 50 40 30 20 10 0

810 805 800 795 790 785 780 775 770 765

FOLD LINE

COLLUVIUM:
REDDISH BRN.TO DARK BRN.
SLI.MIC.SILTY SAND W/
RK.FRAGS.& SMALL BOULDERS

SAPROLITE:
REDDISH BRN.BLACK & WHITE
SLI.MIC.SANDY SILTY W/
WEATHERED & HARD RK.LEDGES

WEATHERED RK

766.32

766.17

766.34

343+00.000

01/26/99
USER NAME = STEVE BOOR
DESIGN FILE = C:\PROJECTS\2519A\DGN\2519A_PROFILE.DGN


0
10
20
30
40
50
60
70
80
90
770
765
760
755
767.316
766.237
765.865
6:1
2:1
4:1
159.728
-Y36-
10+67.624
0.0465
0.0465
EMBANKMENT
ALLUVIUM
S.S. 752.840
343+20.000
766.344
766.412
766.434
4:1
2:1
4:1
761.818
-Y36-
10+49.235
0.0511
0.0518
EMBANKMENT
2:1
S.S. 753.293
ALLUVIUM
343+00.000
-L-

90 80 70 60 50 40 30 20 10 0

815 810 805 800 795 790 785 780 775 770

FOLD LINE

COLLUVIUM:
REDDISH BRN. TO DARK BRN. SU.MIC. SILTY SAND W/ RK. FRAGS. & SMALL BOULDERS

SAPROLITE:
REDDISH BRN. BLACK & WHITE SU.MIC. SANDY SILTY W/ WEATHERED & HARD RK. LEDGES

WEATHERED RK

767.42
767.36
767.58

343+20.000

10/26/95
SSTIVES
SMARKS
SCONTRACT

2.5 0 2.5 5

METRIC

90 80 70 60 50 40 30 20 10 0

815 810 805 800 795 790 785 780 775 770

FOLD LINE

COLLUVIUM:
RED & GREY SILTY SAND

SAPROLITE:
ORANGE GREY & BRN. SLI. MIC. TO MIC. SILTY SAND W/ WEATHERED RK. & HARD ROCK LEDGES

WEATHERED ROCK

767.966

343+40.000

-L-

2.5 0 2.5 5

METRIC



FOLD LINE

343+60
31m LT -L-

COLLUVIUM:
RED & GREY SILTY SAND

SAPROLITE:
ORANGE GREY & BRN. SU.MIC. TO MIC. SILTY SAND W/ WEATHERED PK. & HARD ROCK LEDGES

WEATHERED ROCK

NOTE
DRILL WOULD NOT TURN AUGERS

4
5
12
14
13
9
10
12
10
41
100/1"

768673
768806
768805

343+60.000
-L-

90 80 70 60 50 40 30 20 10 0

820 815 810 805 800 795 790 785 780 775 770

90 80 70 60 50 40 30 20 10 0

815 810 805 800 795 790 785 780 775 770

FOLD LINE

SAP. AND RES. SOILS
MIC. SILTY SAND
MED. DENSE TO DENSE

2:1

SAP. AND WEATHERED RK
MIC. SILTY SAND
DENSE TO VERY DENSE

6:1

769257

769280

769379

343+80.000

0.25.45
USER NAME = USER
PLOT SCALE = 1.0000 '/ IN.
PLOT DATE = 7/19/2006

0 10 20 30 40 50 60 70 80 90

770 765 760 755

344+00.000

769.830

S.S. 769.151

6:1

768.482

-Y36-
11+38.549

6:1

755.419

0.0625 0.0611

Ditch Depth

S.S. 755.023

4:1 6:1

754.830

343+80.000

769.379

6:1

767.940

SAP. AND RES. SOILS
MIC. SILTY SAND
MED. DENSE TO DENSE

SAPROLITE AND WEATHERED RK
ORANGE/TAN MIC. SILTY SAND
DENSE TO VERY DENSE

-Y36-
11+19.703

766.191

0.0725 0.0733

4:1

S.S. 753.709

0 10 20 30 40 50 60 70 80 90

770 765 760 755

10/26/98

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	228 of 238

90 80 70 60 50 40 30 20 10 0

795 790 785 780 775 770

SAP. AND RES. SOILS

SM MIC. SILTY SAND
MED. DENSE TO DENSE

SAP. AND WEATHERED RK

MIC. SILTY SAND
DENSE TO VERY DENSE

769787

769830

344+00.000

-L-

90 80 70 60 50 40 30 20 10 0

795 790 785 780 775 770

INFORMATION SHOWN ON THIS SHEET IS FOR ENGINEERING PURPOSES ONLY


50
40
30
20
10
0
10
20
30
40
50
780
775
770
765
760
2:1
6:1
770.423
770.493
EMBANKMENT
SAP AND WEATHERED RK
344+40.000
770.133
770.162
EMBANKMENT
SAP. AND WEATHERED RK
344+20.000
-L-

2.5 0 2.5 5

METRIC

50 40 30 20 10 0 10 20 30 40 50

780
775
770

SAP. AND WEATHERED RK

2:1
6:1
Ditch Depth

770.545
770.782
769.820

344+80.000

780
775
770

2:1
6:1

770.612
770.631

344+60.000

765

50 40 30 20 10 0 10 20 30 40 50

10-26-98


50
40
30
20
10
0
10
20
30
40
50
775
770
780
2.5%
6:1
0.00%
770.664
769.863
345+40.000
769.681
5.17%
770.52
770.811
769.856
345+20.000
770.392
770.867
769.931
345+00.000

2.5 0 2.5 5

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2519A	232 of 238

50 40 30 20 10 0 10 20 30 40 50

785 780 775 770

4.27%

6%

6%

2.67%

770.420

769.539

345+60.000

769.423

50 40 30 20 10 0 10 20 30 40 50

785 780 775 770

SYSTEM: USER: DATE: TIME:

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	4-22-03	DATE RECEIVED:	5-2-03	DATE REPORTED:	5-14-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-9	SS-10	SS-11	SS-12	SS-13	SS-14	SS-15	SS-16
Lab Sample No. A	141296	141297	141298	141299	141300	141301	141302	141303
HiCAMS Sample #	--	--	--	--	--	--	--	--
Retained #4 Sieve %	--	--	--	--	--	--	--	--
Passing #10 Sieve %	95	79	97	96	97	99	78	87
Passing #40 Sieve %	70	60	84	71	86	91	60	69
Passing #200 Sieve %	27	34	24	28	63	28	30	40

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	42	34	31	39	20	28	35	32
Fine Sand - Ret. #270	36	29	52	41	25	51	33	28
Silt 0.05-0.005 mm %	12	23	9	12	19	11	24	26
Clay < 0.005 mm %	10	14	8	8	36	10	8	14
Passing # 40 Sieve %	--	--	--	--	--	--	--	--
Passing # 200 Sieve %	--	--	--	--	--	--	--	--

Liquid Limit	50	48	41	34	58	62	45	48
Plastic Index	NP	NP	NP	NP	23	NP	NP	NP
AASHTO Classification	A-2-5 (0)	A-2-5 (0)	A-2-5 (0)	A-2-4 (0)	A-7-5 (14)	A-2-5 (0)	A-2-5 (0)	A-5 (1)
Quantity								
Texture								
Station	239+20 RT	239+20 RT	239+20 RT	239+20 RT	238+40 RT	238+40 RT	238+40 RT	238+40 RT
Hole No.								
Depth (ft) From:	1.12	5.68	7.20	10.24	1.00	4.04	5.56	--
To:	1.57	6.13	7.65	10.69	1.45	4.49	4.49	--

Remarks:

A-141288 – A-141314

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

M&T 503E

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	4-22-03	DATE RECEIVED:	5-2-03	DATE REPORTED:	5-14-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-1	SS-2	SS-3	SS-4	SS-5	SS-6	SS-7	SS-8
Lab Sample No. A	141288	141289	141290	141291	141292	141293	141294	141295
HiCAMS Sample #	--	--	--	--	--	--	--	--
Retained #4 Sieve %	--	--	--	--	--	--	--	--
Passing #10 Sieve %	82	68	70	81	89	80	100	89
Passing #40 Sieve %	69	66	64	58	79	73	70	72
Passing #200 Sieve %	23	51	32	17	44	45	17	49

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	36	7	18	43	23	19	45	28
Fine Sand - Ret. #270	41	23	48	38	38	33	39	18
Silt 0.05-0.005 mm %	13	32	18	15	23	26	10	26
Clay < 0.005 mm %	10	38	16	4	16	22	6	28
Passing # 40 Sieve %	--	--	--	--	--	--	--	--
Passing # 200 Sieve %	--	--	--	--	--	--	--	--

Liquid Limit	23	51	33	28	26	38	26	29
Plastic Index	NP	25	NP	NP	6	16	NP	10
AASHTO Classification	A-2-4 (0)	A-7-6 (10)	A-2-4 (0)	A-2-4 (0)	A-4 (2)	A-6 (4)	A-2-4 (0)	A-4 (3)
Quantity								
Texture								
Station	227+80 RT	228+60 RT	228+60 RT	228+60 RT	229+40 RT	229+40 RT	229+40 RT	233+20 RT
Hole No.								
Depth (ft) From:	1.09	.96	2.48	4.00	1.00	2.52	4.04	1.10
To:	1.54	1.41	2.93	4.45	1.45	2.97	4.49	1.55

Remarks:

A-141288 – A-141314

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--		
DATE SAMPLED:	4-22-03	DATE RECEIVED:	5-2-03	DATE REPORTED:	5-14-03		
SAMPLED FROM:	Roadway	SAMPLED BY:	D. Murphy				
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION				
LABORATORY:	Asheville						

TEST RESULTS

Project Sample No.	SS-27	SS-28	SS-29					
Lab Sample No. A	141312	141313	141314					
HiCAMS Sample #	--	--	--					
Retained #4 Sieve %	--	--	--					
Passing #10 Sieve %	99	91	88					
Passing #40 Sieve %	86	61	62					
Passing #200 Sieve %	22	22	16					

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	33	49	51					
Fine Sand - Ret. #270	52	33	37					
Silt 0.05-0.005 mm %	11	14	8					
Clay < 0.005 mm %	4	4	4					
Passing # 40 Sieve %	--	--	--					
Passing # 200 Sieve %	--	--	--					

Liquid Limit	37	36	46					
Plastic Index	NP	NP	NP					
AASHTO Classification	A-2-4 (0)	A-4 (0)	A-2-5 (0)					
Quantity								
Texture								
Station	267+20 RT	267+20 RT	268+00 RT					
Hole No.								
Depth (ft) From:	2.53	10.13	10.12					
To:	2.98	10.58	10.57					

Remarks:

A-141288 – A-141314

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

M&T 503E

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--		
DATE SAMPLED:	4-22-03	DATE RECEIVED:	5-2-03	DATE REPORTED:	5-14-03		
SAMPLED FROM:	Roadway	SAMPLED BY:	D. Murphy				
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION				
LABORATORY:	Asheville						

TEST RESULTS

Project Sample No.	SS-17	SS-18	SS-19	SS-20	SS-21	SS-22	SS-23	SS-24
Lab Sample No. A	141304	141305	141306	141307	141308	141309	141310	141311
HiCAMS Sample #	--	--	--	--	--	--	--	--
Retained #4 Sieve %	--	--	--	--	--	--	--	--
Passing #10 Sieve %	99	62	90	97	74	99	100	98
Passing #40 Sieve %	91	53	80	76	67	87	82	84
Passing #200 Sieve %	40	38	44	43	50	53	44	22

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	21	22	22	33	18	23	30	34
Fine Sand - Ret. #270	49	20	39	32	17	51	33	52
Silt 0.05-0.005 mm %	22	26	31	27	12	14	21	12
Clay < 0.005 mm %	8	32	8	8	53	12	16	2
Passing # 40 Sieve %	--	--	--	--	--	--	--	--
Passing # 200 Sieve %	--	--	--	--	--	--	--	--

Liquid Limit	46	77	53	56	70	51	45	41
Plastic Index	NP	43	NP	16	38	16	14	NP
AASHTO Classification	A-5 (1)	A-7-5 (6)	A-5 (3)	A-7-5 (4)	A-7-5 (12)	A-7-5 (8)	A-7-5 (3)	A-2-5 (0)
Quantity								
Texture								
Station	238+40 RT	252+00 RT	252+00 RT	252+00 RT	253+00 RT	246+00 RT	246+00 RT	247+00 RT
Hole No.								
Depth (ft) From:	10.12	1.09	2.61	5.65	.95	1.00	4.04	5.55
To:	10.57	1.54	3.06	6.10	1.40	1.45	4.49	6.00

Remarks:

A-141288 – A-141314

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

G:/Everyone. . . /M&T Forms/Regional Lab Statesville/Soils Test Report M&T 503E 8-19-2000

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	5-8-03	DATE RECEIVED:	5-16-03	DATE REPORTED:	6-17-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. P. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-33	SS-34	SS-35	SS-36	SS-37	SS-38	SS-45	SS-46
Lab Sample No. A	141483	141484	141485	141486	141487	141488	141489	141490
HiCAMS Sample #	--	--	--	--	--	--	--	--
Retained #4 Sieve %	--	--	--	--	--	--	--	--
Passing #10 Sieve %	81	100	99	88	98	99	84	94
Passing #40 Sieve %	61	84	89	64	83	81	76	83
Passing #200 Sieve %	41	27	33	27	52	39	45	42

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	32	38	25	42	26	31	20	19
Fine Sand - Ret. #270	24	42	46	33	26	37	32	44
Silt 0.05-0.005 mm %	20	12	21	17	22	24	30	25
Clay < 0.005 mm %	24	8	8	8	26	8	18	12
Passing # 40 Sieve %	--	--	--	--	--	--	--	--
Passing # 200 Sieve %	--	--	--	--	--	--	--	--

Liquid Limit	45	62	59	54	43	51	35	42
Plastic Index	7	NP	NP	NP	5	NP	3	NP
AASHTO Classification	A-5 (4)	A-2-5 (0)	A-2-5 (0)	A-2-5 (0)	A-5 (3)	A-5 (1)	A-4 (2)	A-5 (1)
Quantity								
Texture								
Station	270+17 LT	270+17 LT	270+17 LT	270+84 LT	274+40 RT	274+40 RT	300+60 RT	300+60 RT
Hole No.								
Depth (ft) From:	1.21	3.49	8.81	3.63	1.14	4.18	1.76	2.72
To:	1.51	3.79	9.11	3.93	1.44	4.48	2.06	3.02

Remarks:

A-141483 – A-141491

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	4-30-03	DATE RECEIVED:	5-7-03	DATE REPORTED:	5-15-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-25	SS-26	SS-30	SS-31	SS-32			
Lab Sample No. A	141401	141402	141403	141404	141405			
HiCAMS Sample #	--	--	--	--	--			
Retained #4 Sieve %	--	--	--	--	--			
Passing #10 Sieve %	100	96	100	69	98			
Passing #40 Sieve %	96	74	96	60	88			
Passing #200 Sieve %	68	34	75	30	38			

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	10	36	8	25	24			
Fine Sand - Ret. #270	35	35	23	40	48			
Silt 0.05-0.005 mm %	39	23	22	16	18			
Clay < 0.005 mm %	16	6	47	19	10			
Passing # 40 Sieve %	--	--	--	--	--			
Passing # 200 Sieve %	--	--	--	--	--			

Liquid Limit	68	55	64	53	62			
Plastic Index	20	NP	27	11	NP			
AASHTO Classification	A-7-5 (14)	A-2-5 (0)	A-7-5 (19)	A-2-7 (0)	A-5 (1)			
Quantity								
Texture								
Station	256+60 RT	256+60 RT	269+62 LT	269+62 LT	269+62 LT			
Hole No.								
Depth (ft) From:	1.60	2.36	CL	CL	CL			
To:	2.05	2.81	--	--	--			

Remarks:

A-141401 – A-141405

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

G:/Everyone. . . /M&T Forms/Regional Lab Statesville/Soils Test Report M&T 503E 8-19-2000

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	5-8-03	DATE RECEIVED:	5-16-03	DATE REPORTED:	6-17-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. P. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-47							
Lab Sample No. A	141491							
HiCAMS Sample #	--							
Retained #4 Sieve %	--							
Passing #10 Sieve %	96							
Passing #40 Sieve %	65							
Passing #200 Sieve %	23							

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	50							
Fine Sand - Ret. #270	31							
Silt 0.05-0.005 mm %	11							
Clay < 0.005 mm %	8							
Passing # 40 Sieve %	--							
Passing # 200 Sieve %	--							

Liquid Limit	45							
Plastic Index	NP							
AASHTO Classification	A-2-5 (0)							
Quantity								
Texture								
Station	300+60 RT							
Hole No.								
Depth (ft) From:	5.00							
To:	5.30							

Remarks:

A-141483 – A-141491

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	5-13-03	DATE RECEIVED:	5-16-03	DATE REPORTED:	6-17-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. P. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-39	SS-40	SS-41	SS-42	SS-43	SS-44	SS-48	SS-49
Lab Sample No. A	141586	141587	141588	141589	141590	141591	141592	141593
HiCAMS Sample #	--	--	--	--	--	--	--	--
Retained #4 Sieve %	--	--	--	--	--	--	--	--
Passing #10 Sieve %	100	70	76	59	97	98	85	90
Passing #40 Sieve %	82	55	67	48	89	90	74	78
Passing #200 Sieve %	29	29	50	31	62	44	55	61

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	35	33	19	29	15	20	19	20
Fine Sand - Ret. #270	44	33	19	23	33	48	22	15
Silt 0.05-0.005 mm %	15	24	23	18	40	20	19	16
Clay < 0.005 mm %	6	10	39	30	12	12	40	49
Passing # 40 Sieve %	--	--	--	--	--	--	--	--
Passing # 200 Sieve %	--	--	--	--	--	--	--	--

Liquid Limit	24	48	47	46	54	47	53	62
Plastic Index	NP	NP	11	21	NP	NP	18	33
AASHTO Classification	A-2-4 (0)	A-2-5 (0)	A-7-5 (4)	A-2-7 (2)	A-5 (7)	A-5 (2)	A-7-5 (9)	A-7-6 (16)
Quantity								
Texture								
Station	274+40 RT	276+20 LT	277+60 LT	277+60 LT	277+60 LT	300+40 LT	303+60 RT	303+60 RT
Hole No.								
Depth (ft) From:	11.63	2.82	1.0	1.76	3.28	2.62	1.72	2.48
To:	12.08	3.12	1.3	2.06	3.58	2.92	2.02	2.78

Remarks:

A-141586 – A-141599

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	5-19-03	DATE RECEIVED:	6-9-03	DATE REPORTED:	6-17-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. P. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-55	SS-56	SS-57	SS-58	SS-59	SS-60	SS-61	SS-62
Lab Sample No. A	141764	141765	141766	141767	141768	141769	141770	141771
HiCAMS Sample #	--	--	--	--	--	--	--	--
Retained #4 Sieve %	--	--	--	--	--	--	--	--
Passing #10 Sieve %	87	100	88	72	94	95	89	88
Passing #40 Sieve %	62	98	74	54	63	75	66	65
Passing #200 Sieve %	23	61	43	32	18	33	20	21

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	43	12	28	36	52	36	46	44
Fine Sand - Ret. #270	37	37	29	27	36	40	41	41
Silt 0.05-0.005 mm %	12	25	21	21	8	14	7	9
Clay < 0.005 mm %	8	26	22	16	4	10	6	6
Passing # 40 Sieve %	--	--	--	--	--	--	--	--
Passing # 200 Sieve %	--	--	--	--	--	--	--	--

Liquid Limit	31	42	29	42	37	39	41	42
Plastic Index	NP	12	10	NP	NP	NP	NP	NP
AASHTO Classification	A-2-4 (0)	A-7-5 (6)	A-4 (2)	A-2-5 (0)	A-2-4 (0)	A-2-4 (0)	A-2-5 (0)	A-2-5 (0)
Quantity								
Texture								
Station	284+85 LT	308+70 LT	310+80 RT	311+60 LT	318+25 LT	321+00 LT	325+90 LT	323+68 LT
Hole No.								
Depth (ft) From:	6.93	1.15	.97	6.98	4.01	.95	2.63	7.19
To:	7.38	1.60	1.42	7.43	4.46	1.40	3.08	7.64

Remarks:

A-141764 – A-141773

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

M&T 503E

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	5-13-03	DATE RECEIVED:	5-16-03	DATE REPORTED:	6-17-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. P. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-50	SS-51	SS-52	SS-53	SS-54	SS-55		
Lab Sample No. A	141594	141595	141596	141597	141598	141599		
HiCAMS Sample #	--	--	--	--	--	--		
Retained #4 Sieve %	--	--	--	--	--	--		
Passing #10 Sieve %	93	97	88	93	90	96		
Passing #40 Sieve %	80	85	71	59	82	77		
Passing #200 Sieve %	51	53	41	18	39	34		

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	24	22	30	57	22	33		
Fine Sand - Ret. #270	28	32	30	29	41	41		
Silt 0.05-0.005 mm %	14	14	20	8	19	18		
Clay < 0.005 mm %	34	32	20	6	18	8		
Passing # 40 Sieve %	--	--	--	--	--	--		
Passing # 200 Sieve %	--	--	--	--	--	--		

Liquid Limit	54	45	49	38	29	47		
Plastic Index	15	19	17	NP	NP	NP		
AASHTO Classification	A-7-5 (6)	A-7-6 (7)	A-7-5 (3)	A-2-4 (0)	A-4 (1)	A-2-5 (0)		
Quantity								
Texture								
Station	303+60 RT	303+60 RT	303+60 RT	303+00 RT	284+85 LT	284+85 LT		
Hole No.								
Depth (ft) From:	3.24	5.52	7.04	7.00	2.37	6.93		
To:	3.54	5.82	7.49	7.45	2.82	7.38		

Remarks:

A-141586 – A-141599

CC:

W. D. Frye	
J. J. Lail	
File	

SOILS ENGINEER:	

G:/Everyone. . . /M&T Forms/Regional Lab Statesville/Soils Test Report M&T 503E 8-19-2000

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	6-10-03	DATE RECEIVED:	6-18-03	DATE REPORTED:	6-23-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. P. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-65	SS-66	SS-67	SS-68	SS-69	SS-70		
Lab Sample No. A	141921	141922	141923	141924	141925	141926		
HiCAMS Sample #	--	--	--	--	--	--		
Retained #4 Sieve %	--	--	--	--	--	--		
Passing #10 Sieve %	28	28	100	88	96	95		
Passing #40 Sieve %	21	22	98	80	82	78		
Passing #200 Sieve %	9	12	75	28	52	38		

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	41	35	6	25	23	30		
Fine Sand - Ret. #270	33	28	28	56	30	38		
Silt 0.05-0.005 mm %	14	14	31	13	20	22		
Clay < 0.005 mm %	12	23	35	6	27	10		
Passing # 40 Sieve %	--	--	--	--	--	--		
Passing # 200 Sieve %	--	--	--	--	--	--		

Liquid Limit	19	32	56	51	60	47		
Plastic Index	NP	9	28	NP	22	NP		
AASHTO Classification	A-1-a (0)	A-2-4 (0)	A-7-6 (19)	A-2-5 (0)	A-7-5 (9)	A-4 (1)		
Quantity								
Texture								
Station	331+68 LT	331+68 LT	336+28 LT	336+28 LT	338+15 LT	343+60 LT		
Hole No.								
Depth (ft) From:	5.44	6.96	.90	2.42	1.00	5.60		
To:	5.89	7.41	1.35	2.87	1.45	6.05		

Remarks:

A-141921 – A-141926

CC:

W. D. Frye
J. J. Lail
File

SOILS ENGINEER:	

M&T 503E

JJL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS-MATERIALS AND TESTS UNIT
SOILS TEST REPORT-SOILS LABORATORY

T.I.P. ID #:	--

REPORT ON SAMPLES OF:	Soils for Classification

PROJECT:	6.909001	COUNTY:	Yancey	Owner:	--
DATE SAMPLED:	5-19-03	DATE RECEIVED:	6-9-03	DATE REPORTED:	6-17-03
SAMPLED FROM:	Roadway	SAMPLED BY:	D. P. Murphy		
SUBMITTED BY:	W. D. Frye	2002	STANDARD SPECIFICATION		
LABORATORY:	Asheville				

TEST RESULTS

Project Sample No.	SS-63	SS-64						
Lab Sample No. A	141772	141773						
HiCAMS Sample #	--	--						
Retained #4 Sieve %	--	--						
Passing #10 Sieve %	98	99						
Passing #40 Sieve %	77	86						
Passing #200 Sieve %	34	35						

MINUS #10 FRACTION

Soil Mortar - 100%								
Coarse Sand -Ret. #60	37	28						
Fine Sand - Ret. #270	37	50						
Silt 0.05-0.005 mm %	16	14						
Clay < 0.005 mm %	10	8						
Passing # 40 Sieve %	--	--						
Passing # 200 Sieve %	--	--						

Liquid Limit	30	41						
Plastic Index	NP	NP						
AASHTO Classification	A-2-4 (0)	A-2-5 (0)						
Quantity								
Texture								
Station	323+68 LT	326+60 LT						
Hole No.								
Depth (ft) From:	13.27	5.66						
To:	13.72	6.11						

Remarks:

A-141764 – A-141773

CC:

W. D. Frye
J. J. Lail
File

SOILS ENGINEER:	

G:/Everyone. . . /M&T Forms/Regional Lab Statesville/Soils Test Report M&T 503E 8-19-2000