[.I.P.: B-4499

C202438

NIRACI: C

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

TIP NO.		SHEET NO.
B-4499		PMP-1
APPROVED: _	W/15/11	7
SEAL	THE CAROL	William Control of the Control of th

PAVEMENT MARKING PLAN DAVIDSON COUNTY

LOCATION: BRIDGE No. 158 OVER US29/70/I-85 BUSINESS ON SR 1792 (MARTIN LUTHER KING JR. DR.)

PAVEMENT MARKING SCHEDULE

SYMBOL DESCRIPTION

THERMOPLASTIC LINES (4")

YELLOW DOUBLE CENTER

TA WHITE EDGELINE

COLD APPLIED PLASTIC (4") TYPE II

CI YELLOW DOUBLE CENTER
CA WHITE EDGELINE

MARKERS

PERMANENT RAISED PAVEMENT MARKERS

MA YELLOW and YELLOW


ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JULY 2006 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1205.01 1205.02	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS PAVEMENT MARKINGS - 2 LANE AND MULTILANE ROADWAYS
1205.12	PAVEMENT MARKINGS - BRIDGES
1250.01 1251.01	PAVEMENT MARKER SPACING RAISED PAVEMENT MARKERS - TEMPORARY AND PERMANENT
1261.01 1261.02	GUARDRAIL AND BARRIER DELINEATOR SPACING GUARDRAIL AND BARRIER DELINEATOR TYPES
1262.01	GUARDRAIL END DELINEATION

PLAN PREPARED BY: N.C.D.O.T. SIGNING AND DELINEATION UNIT

SUSAN B. KUNZ SIGNING & DELINEATION REGIONAL ENGINEER
GEORGE TERLIZZI SIGNING & DELINEATION DESIGN ENGINEER



GENERAL NOTES

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

A) INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE AS FOLLOWS:

ROAD NAME

MARKING

MARKER

SR 1791

BRIDGE

THERMOPLASTIC
COLD APPLIED TYPE II

RAISED RAISED

- B) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.
- C) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS.
- D) PASSING ZONES WILL BE DETERMINED IN THE FIELD AND MUST BE APPROVED BY THE ENGINEER.
- E) STOPBAR LOCATION AT NON-SIGNALIZED INTERSECTIONS MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER.
- F) REMOVE ALL RESIDUE AND SURFACE LAITANCE BY ACCEPTABLE METHODS ON THE BRIDGE DECK PRIOR TO PLACING COLD APPLIED TYPE II PAVEMENT MARKING.

INDEX

SHEET NO.

DESCRIPTION

PMP-1

PMP-2

PAVEMENT MARKING PLAN TITLE SHEET

PAVEMENT MARKING DETAIL

