

TIP PROJECT: B-4588

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

PLAN FOR PROPOSED
HIGHWAY EROSION CONTROL


NASH COUNTY

LOCATION: BRIDGE NO.1 OVER STONEY CREEK ON SR 1670
TYPE OF WORK: GRADING, DRAINAGE, PAVING, & STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-4588	EC-1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	

EROSION AND SEDIMENT CONTROL MEASURES

Std. #	Description	Symbol
1630.03	Temporary Silt Ditch	--- TSD ---
1630.05	Temporary Diversion	--- TD ---
1605.01	Temporary Silt Fence	
1606.01	Special Sediment Control Fence	--- Z ---
1622.01	Temporary Berms and Slope Drains	--- B ---
1630.02	Silt Basin Type B	--- SB ---
1633.01	Temporary Rock Silt Check Type-A	--- RSC ---
	Temporary Rock Silt Check Type-A with Matting and Polyacrylamide (PAM)	--- RSC/PAM ---
1633.02	Temporary Rock Silt Check Type-B	--- RSC ---
	Wattle / Coir Fiber Wattle	--- W ---
	Wattle / Coir Fiber Wattle with Polyacrylamide (PAM)	--- W/PAM ---
1634.01	Temporary Rock Sediment Dam Type-A	--- RSD ---
1634.02	Temporary Rock Sediment Dam Type-B	--- RSD ---
1635.01	Rock Pipe Inlet Sediment Trap Type-A	--- RPIST ---
1635.02	Rock Pipe Inlet Sediment Trap Type-B	--- RPIST ---
1630.04	Stilling Basin	--- SB ---
1630.06	Special Stilling Basin	--- SSB ---
	Rock Inlet Sediment Trap:	
1632.01	Type A	--- A ---
1632.02	Type B	--- B ---
1632.03	Type C	--- C ---
	Skimmer Basin	--- SB ---
	Tiered Skimmer Basin	--- TSB ---
	Infiltration Basin	--- IB ---



**THIS PROJECT CONTAINS
EROSION CONTROL PLANS
FOR CLEARING AND
GRUBBING PHASE OF
CONSTRUCTION.**

**THIS PROJECT HAS
BEEN DESIGNED TO
SENSITIVE WATERSHED
STANDARDS.**

**ENVIRONMENTALLY
SENSITIVE AREA(S) EXIST
ON THIS PROJECT**
*Refer To E. C. Special Provisions
for Special Considerations.*

GRAPHIC SCALE

0
[Scale Bar]

PLANS

0
[Scale Bar]

PROFILE (HORIZONTAL)

0
[Scale Bar]

PROFILE (VERTICAL)

ROADSIDE ENVIRONMENTAL UNIT
DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

THESE EROSION AND SEDIMENT CONTROL PLANS COMPLY
WITH THE REGULATIONS SET FORTH BY THE
NCG-010000 GENERAL CONSTRUCTION PERMIT EFFECTIVE AUGUST 3, 2011
ISSUED BY THE NORTH CAROLINA DEPARTMENT OF ENVIRONMENT AND
NATURAL RESOURCES DIVISION OF WATER QUALITY.

Prepared In the Office of:
ROADSIDE ENVIRONMENTAL UNIT
1 South Wilmington St.
Raleigh, NC 27611
2012 STANDARD SPECIFICATIONS

Roadway Standard Drawings





The following roadway english standards as appear in "Roadway Standard Drawings"-- Roadway Design Unit - N. C. Department of Transportation - Raleigh, N. C., dated January 2012 and the latest revision thereto are applicable to this project and by reference hereby are considered a part of these plans.

1604.01 Railroad Erosion Control Detail	1632.01 Rock Inlet Sediment Trap Type A
1605.01 Temporary Silt Fence	1632.02 Rock Inlet Sediment Trap Type B
1606.01 Special Sediment Control Fence	1632.03 Rock Inlet Sediment Trap Type C
1607.01 Gravel Construction Entrance	1633.01 Temporary Rock Silt Check Type A
1622.01 Temporary Berms and Slope Drains	1633.02 Temporary Rock Silt Check Type B
1630.01 Riser Basin	1634.01 Temporary Rock Sediment Dam Type A
1630.02 Silt Basin Type B	1634.02 Temporary Rock Sediment Dam Type B
1630.03 Temporary Silt Ditch	1635.01 Rock Pipe Inlet Sediment Trap Type A
1630.04 Stilling Basin	1635.02 Rock Pipe Inlet Sediment Trap Type B
1630.05 Temporary Diversion	1640.01 Coir Fiber Baffle
1630.06 Special Stilling Basin	1645.01 Temporary Stream Crossing
1631.01 Matting Installation	

27-SEP-2010 08:35
R:\ENVI\GIS\SUMMER\2010\B-4588\1a\1b-4588-ec-1.dwg, tsh.dgn

PROJECT REFERENCE NO. B-4588	SHEET NO. EC-2
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

SKIMMER BASIN WITH BAFFLES DETAIL



COIR FIBER MAT ANCHOR OPTIONS




NOTES

1. SEED AND PLACE MATTING FOR EROSION CONTROL ON INTERIOR AND EXTERIOR SIDESLOPES.
2. LIMIT EARTH DIKE HEIGHT TO 5 FT.
3. FOR BASIN DEPTH OF 3 FT., THE MINIMUM BASIN WIDTH SHALL BE 9 FT.
4. DETERMINE EMERGENCY SPILLWAY LENGTH (FT.) USING $Q/0.8$, WHERE Q IS FLOW RATE (CFS) INTO BASIN.
5. PLASTIC SLOPE DRAIN PIPE AT INLET OF BASIN MAY BE REPLACED BY FILTRATION GEOTEXTILE AS DIRECTED.
6. SOIL STABILIZATION GEOTEXTILE FOR EMERGENCY SPILLWAY SHALL BE ONE CONTINUOUS PIECE OF MATERIAL OR OVERLAPPED 18 IN. (MIN.)

NOT TO SCALE



PROJECT REFERENCE NO. B-4588	SHEET NO. EC-2A
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

WATTLE WITH POLYACRYLAMIDE (PAM) DETAIL



NOTES:

- USE MINIMUM 12 IN. DIAMETER EXCELSIOR WATTLE.
- USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.
- ONLY INSTALL WATTLE(S) TO A HEIGHT IN DITCH SO FLOW WILL NOT WASH AROUND WATTLE AND SCOUR DITCH SLOPES AND AS DIRECTED.
- INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO BOTTOM OF DITCH.
- PROVIDE STAPLES MADE OF 0.125 IN. DIAMETER STEEL WIRE FORMED INTO A U SHAPE NOT LESS THAN 12" IN LENGTH.
- INSTALL STAPLES APPROXIMATELY EVERY 1 LINEAR FOOT ON BOTH SIDES OF WATTLE AND AT EACH END TO SECURE IT TO THE SOIL.
- INSTALL MATTING IN ACCORDANCE WITH SECTION 1631 OF THE STANDARD SPECIFICATIONS.
- PRIOR TO POLYACRYLAMIDE (PAM) APPLICATION, OBTAIN A SOIL SAMPLE FROM PROJECT LOCATION, AND FROM OFFSITE MATERIAL, AND ANALYZE FOR APPROPRIATE PAM FLOCCULANT TO BE APPLIED TO EACH WATTLE.
- INITIALLY APPLY 2 OUNCES OF ANIONIC OR NEUTRALLY CHARGED PAM OVER WATTLE WHERE WATER WILL FLOW AND 1 OUNCE OF PAM ON MATTING ON EACH SIDE OF WATTLE. REAPPLY PAM AFTER EVERY RAINFALL EVENT THAT IS EQUAL TO OR EXCEEDS 0.50 IN.



DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

PROJECT REFERENCE NO. <i>B-4588</i>	SHEET NO. <i>EC-3</i>
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER


SOIL STABILIZATION TIMEFRAMES

<i>SITE DESCRIPTION</i>	<i>STABILIZATION TIME</i>	<i>TIMEFRAME EXCEPTIONS</i>
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HQW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 OR FLATTER	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH.
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	NONE, EXCEPT FOR PERIMETERS AND HQW ZONES.

CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 4

NOTE:
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT
DRAINAGE OUTLETS.


NOTE:
UTILIZE SPECIAL STILLING BASIN
AS STILLING BASIN WHERE APPLICABLE.



ENVIRONMENTALLY SENSITIVE AREA
SEE PROJECT SPECIAL PROVISIONS

-L- CURVE DATA
 PI Sta 15+99.18 PI Sta 20+29.90
 $\Delta = 38^{\circ} 33' 33.1''$ (LT) $\Delta = 13^{\circ} 10' 02.1''$ (LT)
 $D = 5^{\circ} 47' 14.8''$ $D = 6^{\circ} 19' 02.7''$
 $L = 666.26'$ $L = 208.43'$
 $T = 346.30'$ $T = 104.67'$
 $R = 990.00'$ $R = 906.95'$
 SE = SEE PLAN SE = SEE PLAN

PROJECT REFERENCE NO. B-4588	SHEET NO. EC-4/CONST.4
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER



BEGIN PROJECT B-4588
-L- POT STA. 11+00.00

END PROJECT B-4588
-L- POC STA. 19+50.00

27 x 9 x 3
1.5 inch Skimmer
with 0.25 inch
Orifice Diameter
4 ft. weir
ID 4.1C

18 x 9 x 3
1.5 inch Skimmer
with 0.125 inch
Orifice Diameter
4 ft. weir
ID 4.3C

20 x 9 x 3
1.5 inch Skimmer
with 0.25 inch
Orifice Diameter
4 ft. weir
ID 4.2C

NOTES: (1) SEE SHEET 5 FOR -L- & -Y- PROFILES
(2) SEE SHEETS S-1 TO S-31 FOR STRUCTURE DETAILS



12-00T-2011h00
 At: Enviro-Point
 12/26/2010
 12:26:58 PM
 B:\4588\EC-ps-h.dgn

PROJECT REFERENCE NO.	SHEET NO.
B-4588	EC-5/CONST.4
RW SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	

-L- CURVE DATA

PI Sta 15+99.18	PI Sta 20+29.90
$\Delta = 38^{\circ} 33' 33.1''$ (LT)	$\Delta = 13^{\circ} 10' 02.1''$ (LT)
D = 5' 47' 14.8"	D = 6' 19' 02.7"
L = 666.26'	L = 208.43'
T = 346.30'	T = 104.67'
R = 990.00'	R = 906.95'
SE = SEE PLAN	SE = SEE PLAN

NOTE: UTILIZE SPECIAL STILLING BASIN AS STILLING BASIN WHERE APPLICABLE.



BEGIN PROJECT B-4588
-L- POT STA. 11 + 00.00

END PROJECT B-4588
-L- POC STA. 19 + 50.00

Place Matting for Erosion Control on Slope as Work Allows.

27 x 9 x 3
1.5 inch Skimmer
with 0.25 inch
Orifice Diameter
4 ft. weir
ID 4.1C

18 x 9 x 3
1.5 inch Skimmer
with 0.125 inch
Orifice Diameter
4 ft. weir
ID 4.3C

Place Matting for Erosion Control on Slope as Work Allows.

NOTES: (1) SEE SHEET 5 FOR -L- & -Y- PROFILES
(2) SEE SHEETS S-1 TO S-31 FOR STRUCTURE DETAILS

12-OCT-2011 10:01 AM
 C:\enviro\p04\p04\B4588\EC-psht.dgn
 B4588-EC-5-CONST.4