NOTE: SEE SHEET 1A FOR PLAN SHEET LAYOUT AT TIME OF INVESTIGATION **CONTENTS** PLAN PROFILE XSECT STATION 10+69.59 TO 24+75 SOIL SAMPLE RESULTS 3

DRAWN BY: LITTLE

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

ROADWAY SUBSURFACE INVESTIGATION

PROJ. REFERENCE NO. 33048.1.1 F.A. PROJ. BRSTP-1002(7) COUNTY CABARRUS

PROJECT DESCRIPTION BRIDGE NO. 266 ON SR 1002 (CABARRUS AVE.)

OVER SOUTHERN RAILWAY

INVENTORY

-L- STA. 24+75.00END TIP PROJECT B-3421


STATS B-3421 N.C. 8 1 STATE PROLNC 33048.1.1 BRSTP-1002(7) P.E. 33048.2.2 BRSTP-1002(29) RW /UTIL. 33048.3.1 BRSTP-1002(27) CONST.

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PUMPOSE OF STUDY, PLANNING, AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PUMPOSES. THE VARBOUS FELD BORNING LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENDINEERING UNIT AT (19) 250-4088. NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOGS, ROCK CORES, OR SOIL TEST DATA ARE PART OF THE CONTRACT,

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABLITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOSITURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION, AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT, FOR BIDDING AND CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISTY HIMSELF AS TO CONDITIONS TO BE DENCOUNTERED. THE BIDDER OR CONTRACTOR TO SATISTY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT, THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY BEASON MESULTING FORM THE ACTUAL CONDITIONS TO MENOLUTIFEED. AT THE SITE DEFERMS FORM ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.



PERSONNEL **ESTEP**

MOORE

INVESTIGATED BY_MURRAY

LITTLE

SUBMITTED BY_ LITTLE

AUGUST 2008

NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IT IS CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THE PROJECT.

NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE

See Sheet 1-A For Index of Sheets BEGIN PROJECT 4 1007

GRAPHIC SCALES

PROFILE (HORIZONTAL)

PROFILE (VERTICAL)

DESIGN DATA

ADT 2010 = 21,723 ADT 2030 = 23,800 DHV = 10 % D = 50 % T = 5 % * V = 40 MPH * (TTST 2% + DUAL 3%)

FUNC. CLASS = URBAN

DESIGN EXCEPTION REQ'D FOR VERTICAL ALIGNMENT & VERTICAL SSD

MINOR ARTERIAL

ADT 2010 = 21,723

STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

CABARRUS COUNTY


LOCATION: BRIDGE NO. 266 ON SR 1002 (CABARRUS AVE.) OVER SOUTHERN RAILWAY

TYPE OF WORK: GRADING, PAVING, DRAINAGE, CURB & GUTTER AND STRUCTURE

STATE	STAT	SHEET NO.	TOTAL SHEBTS		
N.C.		B-3421		1 A	8
STAT	B PROJ.NO.	F. A. PROJ. NO.	T	DESCRIPT	ION
33	048.1.1	BRSTP-1002(7)		P.E./U	ΓIL,
			<u> </u>		
			<u> </u>		
			↓		
			-		
		1	1		

INCOMPLETE PLANS
DO NOT USE FOR BAY ACQUISITION PRELIMINARY PLANS

DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA



= 0.216 MILES

= 0.050 MILES

= 0.266 MILES

PROJECT LENGTH

TOTAL LENGTH ROADWAY TIP PROJECT

TOTAL LENGTH STRUCTURE TIP PROJECT

TOTAL LENGTH TIP PROJECT B-3421

PLANS PREPARED BY:

2006 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: **DECEMBER 19, 2008**

LETTING DATE:

DECEMBER 21, 2010

NCDOT CONTACT:

TGS ENGINEERS
SUITE 141
975 WALNUT STREET
CARY, NC 27511
PH (919) 319-8850

PLANS PREPARED FOR:

1000 Birch Ridge Dr. Raleigh, NC 27610

DIVISION OF HIGHWAYS

CHARLES L. FLOWE, PE

W. CRAIG PARKER, PE

DOUG TAYLOR, PE

HYDRAULICS ENGINEER

ROADWAY DESIGN **ENGINEER**

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS

GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

	SOIL AND ROCK LEGEND, TERM	S, SYMBOLS, AND ABBREVIATIONS	
SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION	TERMS AND DEFINITIONS
SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS	WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO	HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT IF TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL.	ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND YIELD LESS THAN 180 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (AASHTO 1206, ASTM D-1586). SOIL	POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.	SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EDUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE	AQUIFER - A WATER BEARING FORMATION OR STRATA.
CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH	ANGULARITY OF GRAINS	OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS; ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	WEATHERED WILD NON-COASTAL PLAIN MATERIAL THAT WOULD VIELD SPT N VALUES > 160	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC.
VERY STAFF, GRAV, SILTY CUAN, MOST WITH INTERBEDDED FINE SAND LARENS, HONLY PLASTIC, A-7-6	MINERALOGICAL COMPOSITION	ROCK (WR) BLOWS PER FOOT IF TESTED.	ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL
SOIL LEGEND AND AASHTO CLASSIFICATION GENERAL GRANULAR MATERIALS SILT-CLAY MATERIALS ACCOUNTS MATERIALS	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS	CRYSTALLINE ROCK (CR) FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD STREFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE,	AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.
CLASS. (≤ 35% PASSING *200) (> 35% PASSING *200) UNGARIL MATERIALS	WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.	J. GREISS, GABBRU, SCHISI, ETC.	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5 CLASS. A-1-a A-1-b A-2-4 A-2-5 A-2-5 A-2-5 A-2-7 A-6, A-7	COMPRESSIBILITY	NORTH STITLLINE SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED, ROCK TYPE	COLLUYIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.
CLASS. A-1-a A-1-b A-2-4 A-2-5 A-2-6 A-2-7 A-3 A-6, A-7 SYMBOL 8000000000000000000000000000000000000	SLIGHTLY COMPRESSIBLE LIQUID LIMIT LESS THAN 31 MODERATELY COMPRESSIBLE LIQUID LIMIT EQUAL TO 31-50	COASTAL PLAIN COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL
55556656	HIGHLY COMPRESSIBLE LIOUID LIMIT GREATER THAN 50 PERCENTAGE OF MATERIAL	SEDIMENTARY ROCK SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.	LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
2 PASSING 10 50 MX GRANULAR SILT- CLAY MUCK, CLAY OF A	OPCANIC MATERIAL GRANULAR SILT - CLAY	WEATHERING	<u>DIKE</u> - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.
* 40 30 MX 50 MX 51 MN PEAT SOILS PEAT SOILS PEAT SOILS SOILS	URGANIC MATERIAL SOILS SOILS OTHER MATERIAL TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRACE 1 - 18%	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER	DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE
LIDING LIDING	LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 10 - 20%	HAMMER IF CRYSTALLINE. VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN,	HORIZONTAL.
PLASTIC INDEX 6 MX NP 18 MX 12 MX 12 MX 12 MN 16 MX 141 MN 16 MX 11 MN SOILS WITH LITTLE OR HIGHLY	MODERATELY ORGANIC	(V SLI.) CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF	DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
GROUP INDEX 0 0 0 4 MX 8 MX 12 MX 16 MX No MX MODERATE ORGANIC	GROUND WATER	OF A CRYSTALLINE NATURE. SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE
USUAL TYPES STONE FRAGS. FINE SILTY OR CLAYEY SILTY CLAYEY DRGANIC	WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING	(SLI,) 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR	SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
DF MAJOR GRAVEL, AND SAND GRAVEL AND SAND SOILS SOILS MATTER	STATIC WATER LEVEL AFTER 24 HOURS	CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
GEN. RATING AS A EXCELLENT TO GOOD FAIR TO POOR POOR POOR UNSUITABLE	∇PW PERCHED WATER, SATURATED ZONE, DR WATER BEARING STRATA	(MOD.) GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL.
SUBGRADE	SPRING OR SEEP	DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY
PI OF A-7-5 SUBGROUP IS ≤ LL - 30; PI OF A-7-6 SUBGROUP IS > LL - 30	<u> </u>	MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, IN GRANITOID ROCKS, ALL FELDSPARS DULL	THE STREAM. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN
CONSISTENCY OR DENSENESS RANGE OF STANDARD RANGE OF UNCONFINED	MISCELLANEOUS SYMBOLS ET ROADWAY EMRANKMENT (RE) SET CET TEXT SOUTHER SAMPLE	SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION, ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK, ROCK GIVES "CLUNK" SDUND WHEN STRUCK.	THE FIELD.
PRIMARY SOIL TYPE COMPACTNESS OR CONSISTENCY PENETRATION RESISTENCE (N-VALUE) (TONS/FT2)	ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION ROADWAY EMBANKMENT (RE) OPT DNT TEST BORING DESIGNATIONS	IF TESTED, WOULD YIELD SPT REFUSAL	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
CENERALLY VERY LOOSE <4	S - BULK SAMPLE AUGER BORING	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KADLINIZED TO SOME	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO
GRANULAR LUUSE 4 TO 100 N/A	SS - SPLIT SPOON ARTIFICIAL FILL (AF) OTHER A SAMPLE	EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, YIELDS SPT N VALUES > 100 BPF	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
MATERIAL (NON-COHESIVE) DENSE 30 TO 50	THAN ROADWAY EMBANKMENT	VERY SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT	MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN
	INFERRED SOIL BOUNDARY SAMPLE	(V SEV.) THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING, SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR	SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN
GENERALLY SOFT 2 TO 4 0.25 TO 0.50	MONITORING WELL RS - ROCK SAMPLE	VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. IF TESTED, VIELDS SPT N VALUES < 100 BPF	INTERVENING IMPERVIOUS STRATUM.
SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0 MATERIAL STIFF 8 TO 15 1 TO 2	PIEZOMETER INSTALLATION RT - RECOMPACTED TRIAXIAL SOME F. SAMPLE	COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS, QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS, SAPROLITE IS	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
(COHESIVE) VERY STIFF 15 TO 30 2 TO 4 HARD >30 >4	SLOPE INDICATOR	ALSO AN EXAMPLE.	ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND
TEXTURE OR GRAIN SIZE	ROCK STRUCTURES RATIO SAMPLE	ROCK HARDNESS	EXPRESSED AS A PERCENTAGE,
	SOUNDING ROD SPT NEFURAL	VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK, BREAKING OF HAND SPECIMENS REQUIRES	SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.
U.S. STD. SIEVE SIZE 4 10 40 60 200 270 OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	THE OF I REPUBL	SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK. HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY, HARD HAMMER BLOWS REQUIRED	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND
BOULDER COBBLE GRAVEL COARSE FINE SILT CLAY	ABBREVIATIONS AR - AUGER REFUSAL HI HIGHLY ## - MOISTURE CONTENT	TO DETACH HAND SPECIMEN.	RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
(BLDR.) (COB.) (GR.) (CSE. SD.) (F SD.) (SL.) (CL.)	BT - BORING TERMINATED MED MEDIUM V - VERY	MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 8.25 INCHES DEEP CAN BE	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR
GRAIN MM 305 75 2.0 0.25 0.05 0.005	CL CLAY MICA MICACEDUS VST - VANE SHEAR TEST CPT - CONE PENETRATION TEST MOD MODERATELY WEA WEATHERED	HARD EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	SLIP PLANE.
SIZE IN. 12 3	CSE COARSE NP - NON PLASTIC 7- UNIT WEIGHT	MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH
SOIL MOISTURE - CORRELATION OF TERMS	DMT - DILATOMETER TEST ORG ORGANIC 7d- DRY UNIT WEIGHT DPT - DYNAMIC PENETRATION TEST PMT - PRESSUREMETER TEST	HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.
SOIL MOISTURE SCALE FIELD MOISTURE GUIDE FOR FIELD MOISTURE DESCRIPTION	e - VOID RATIO SAP SAPROLITIC	SOFT CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY	F - FINE SD SAND, SANDY FOSS FOSSILIFEROUS SL SILT, SILTY	FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	OF STRATUM AND EXPRESSED AS A PERCENTAGE.
(SAT.) FROM BELOW THE GROUND WATER TABLE	FRAC FRACTURED, FRACTURES SLI SLIGHTLY FRAGS FRAGMENTS TCR - TRICONE REFUSAL	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH	STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE
PLASTIC PLASTIC PROVIDE TO	THOUSE THOUSENED THE	SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.	TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
RANGE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	EQUIPMENT USED ON SUBJECT PROJECT	FRACTURE SPACING BEDDING	<u>IOPSOIL (TS.)</u> - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.
"" PLL PLASTIC LIMIT	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE:	TERM SPACING TERM THICKNESS VERY THICKLY BEDDED > 4 FEET	BENCH MARK:
OM OPTIMUM MOISTURE - MOIST - (M) SOLID; AT OR NEAR OPTIMUM MOISTURE	CLAY BITS	WERY WIDE MURE THAN 10 FEET THICKLY BEDDED 1.5 - 4 FEET	ELEVATION: FT.
SL SHRINKAGE LIMIT	4 C MURILE B-	MODERATELY CLOSE 1 TO 3 FEET HINNLY BEDDED 0.16 - 1.5 FEET VERY THINNLY BEDDED 0.16 - 1.5 FEET	
REOUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE		CLOSE 0.16 TD 1 FEET THICKLY LAMINATED 0.008 - 0.03 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED < 0.008 FEET CHOICE CO.008 FEET	NOTES:
PLASTICITY	A HOLLOW AUGERS	INDURATION (S.SOSO FEET	
PLASTICITY INDEX (PI) DRY STRENGTH		FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	
NDNPLASTIC 0-5 VERY LOW		FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS;	
LOW PLASTICITY 6-15 SLIGHT MED. PLASTICITY 16-25 MEDIUM	CASING W/ ADVANCER HAND TOOLS:	GENILE BLOW BY HAMMER DISINIEGRATES SAMPLE.	
HIGH PLASTICITY 26 OR MORE HIGH	PORTABLE HOIST TRICONE STEEL TEETH POST HOLE DIGGER	MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	
COLOR	TRICONE TUNG,-CARB. HAND AUGER SOUNDING ROD	INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE;	
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY).	CORE BIT SOUNDING ROD VANE SHEAR TEST	DIFFICULT TO BREAK WITH HAMMER.	
MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	

EARTHWORK SUMMARIES (COMBINED FOR CABARRUS AVE & POWDER ST)

Volumes in Cubic Yards DATE 15-Nov-11

PROJECT_	B-3421		COUNTY_	Cabarr	rus County		DATE	15-Nov-11	CON	IPILED BY: _	JLT	SHEET	3	of 8	SHEETS
				EXCAVATION				EMBAN	KMENT		WAS7		WASTE	E	
LINE	STATION	STATION	TOTAL (UNCL.)	ROCK	UNDERCUT	UNSUIT. UNCLASS.	SUITABLE UNCLASS.	TOTAL	ROCK	EARTH	EMB. +20%	BORROW	ROCK	SUITABLE	UNSUIT
Ť	10+69.59	16+67.35	19				19	16,711		16,711	20,053	20,034			
-L- BRIDGE															
-L-	19+29.10	24+75.00	174				174	5,147	,	5,147	6,176	6,002			
-Y2-	10+20.00	12+38.53	440				440	77		77	92			348	
INTERSECTION W -Y2-	/ITH -L- 12+76.72	16+27.10	634				634	57		57	68			566	
	TOTALS		1,267				1,267	21,992		21,992	26,389	26,036		914	
Estimate	d loss due to Clear.	& Grub.	-125				-125					125			
Use	Waste in lieu of Bor	row										-914		-914	F
F	PROJECT TOTAL		1,142				1,142	21,992		21,992	26,389	25,247		C)
Est. 5% to	replace Topsoil on I	Borrow Pits										1,262			
	GRAND TOTAL		1,142		0		1,142	21,992		21,992	26,389	26,509			
	SAY		1,280				·					29,200			

NOTE: EARTHWORK QUANTITIES ARE CALCULATED BY THE ROADWAY DESIGN UNIT. THESE EARTHWORK QUANTITIES ARE BASED IN PART ON SUBSURFACE DATA PROVIDED BY THE GEOTECHNICAL ENGINEERING UNIT.

 403 YD^3 **Pavement Structure Volume =**

> $1,000 \text{ YD}^3$ (Per CFI Lettery Dated Sept. 29, 2008) Est. Undercut =

 850 YD^3 Est. Shallow Undercut Contingency = (Per Geotech Report Dated August 14, 2008) Est. Class IV Subgrade Stabilization Contingency = 1,700 **Tons** (Per Geotech Report Dated August 14, 2008)

 $2,600 \text{ YD}^2$ (Per Geotech Report Dated August 14, 2008) (Per Roadside Environmental Unit) Est. Geotextile for Soil Stabilization Contingency =



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

MICHAEL F. EASLEY
GOVERNOR

LYNDO TIPPETT SECRETARY

August 11, 2008

STATE PROJECT:

33048.1.1 (B-3421)

FEDERAL PROJECT:

BRSTP-1002(7)

COUNTY:

Cabarrus

DESCRIPTION:

Bridge No. 266 on SR 1002 (Cabarrus Ave.) over Southern Railway

SUBJECT:

Geotechnical Report - Inventory

PROJECT DESCRIPTION

The project is located in the City of Concord, Cabarrus County. It is in an urban area where there has been considerable alteration of the natural terrain. It is a bridge replacement project with upgrades to the existing roadway. Three retaining walls are also proposed. The geotechnical investigation consisted of four Standard Penetration Test borings, one at each proposed wall location and one near the proposed bridge. The borings were performed with a CME-550 drill rig using 8" hollow stem augers or casing. The borings were conducted in June of 2008.

AREAS OF SPECIAL GEOTECHNICAL INTEREST

Near the beginning of the project, we encountered alluvial soils associated with the floodplain of Irish Buffalo Creek. The floodplain has been filled over with roadway and artificial embankment soils. The sediments consist of soft to medium stiff silty and sandy clays, and silty sands.

Numerous areas of artificial fill were encountered. These fills are associated with buildings, parking lots, etc. The fills appear to be moderately well compacted and contain a variety of soils. We did not encounter any debris or any evidence of unsuitable materials.

PHYSIOGRAPHY AND GEOLOGY


The project area is in the Charlotte Geologic Belt, near the edge of the Concord Plutonic Suite. We did not obtain rock core samples or note any outcrop. Residual soil descriptions are most consistent with altered mafic volcanics. The typical soil profile includes a surface layer of red-brown clay, moist, with low to medium plasticity. Subsoils are clayey sandy silts or silty sands. Hardness/density generally increases rapidly with depth. All test borings reached hard soils or weathered rock at depths of 10' to 20'. Three of the four borings encountered groundwater, at depths between eight and 14


feet. The borings were conducted outside of the existing roadway embankment, so the collar elevations were well below the proposed grade. The measured groundwater elevations were 20' to 30' below the proposed grade.


Respectfully submitted


Clint Little

Regional Geological Engineer









NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAY MATERIALS & TESTS UNIT SOILS LABORATORY

T. I. P. No.	B-3421					
	REPORT ON SA	AMPLES OF	SOILS FOR Q	UALIT	Y	
Project	3304811	County	CABARRUS		Owner	
Date: Sampled	6/10/08	Received	6/16/08		Reported	6/18/08
Sampled from				Ву	C C MURI	RAY
Submitted by	N WAINAINA				1995	Standard Specifications
746578 TO 74659	90					

746578 TO 746590 8/11/08

TEST RESULTS

Proj. Sample No.	SS-1	SS-2	SS-3	SS-4	SS-5	SS-6
Lab. Sample No.	746578	746579	746580	746581	746582	746583
Retained #4 Sieve	% -	_	_	-	-	_
Passing #10 Sieve	% 98	98	100	100	100	99
Passing #40 Sieve	% 81	83	100	98	96	82
Passing #200 Sieve	% 37	39	97	51	61	22

MINUS NO. 10 FRACTION

SOIL MORTAR - 100%							
Coarse Sand Ret - #60	%	31.8	27.2	0.6	6.3	10.7	38.0
Fine Sand Ret - #270	%	36.7	40.1	4.3	53.3	34.0	46.0
Silt 0.05 - 0.005 mm	%	15.3	14.5	34.3	20.2	18.7	9.9
Clay < 0.005 mm	%	16.2	18.2	60.8	20.3	36.5	6.1
Passing #40 Sieve	%	-	-	_	_	_	-
Passing #200 Sieve	%	-	-	_	-	-	-

L. L.		30	32	45	23	35	20
P. I.		6	6	20	4	15	NP
AASHTO Classification	1	A-4(0)	A-4(0)	A-7-6(22)	A-4(0)	A-6(7)	A-2-4(0)
Station		11+20	11+20	11+20	11+20	11+20	21+70
OFFSET	4	46 RT	46 RT	46 RT	46 RT	46 RT	30 RT
ALIGNMENT		L	L	L	L	L	L
Depth (Ft)		4.10	9.10	14.10	19.10	24.10	3.60
	to	5.60	10.60	15.60	20.60	25.60	5.10

cc: C C MURRAY
Soils File

Soils Engineer Page 1

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAY

MATERIALS & TESTS UNIT SOILS LABORATORY

T. I. P. No.	B-3421	_					
	REPORT ON SAM	MPLES OF	SOILS FO	R QUALITY	Y		
Project	3304811	County	CABARRU	JS	Owner		
Date: Sampled	6/10/08	Received	6/16/08		Reported	6/18/08	
Sampled from		•		By	C C MURI		
Submitted by	N WAINAINA			_ Dy _	***************************************	Standard Spe	ecifications
746578 TO 74659 8/11/08	90	T ì	EST RESUL	LTS			
Proj. Sample No	•	SS-7	SS-8	SS-9	SS-10	SS-11	SS-12
Lab. Sample No		746584	746585	746586	746587	746588	746589
Retained #4 Si	eve %	2	-	-		4	-
Passing #10 Si	eve %	91	96	100	97	89	95
Passing #40 Si		66	70	85	68	70	70
Passing #200 Si	eve %	29	45	54	40	42	38
		MINUS	5 NO. 10 FRA	ACTION			
SOIL MORTAR	- 100%						
Coarse Sand 1	Ret - #60 %	40.6	35.7	24.9	37.7	32.4	39.7
Fine Sand Re	t - #270 %	32.7	21.1	27.6	27.0	24.3	24.1
Silt 0.05 - 0.0	05 mm %	12.5	10.8	25.2	23.2	18.9	11.9
Clay < 0.005	mm %	14.2	32.4	22.3	12.2	24.3	24.3
Passing #40 Si			-	-	-	_	-
Passing #200 Si	eve %	-	-	-	-	-	-
L. L.		23	37	48	43	30	27
P. I.	,	2	20	15	4	11	11
AASHTO Classi	fication	A-2-4(0)	A-6(5)	A-7-5(7)	A-5(0)	A-6(1)	A-6(1)
Station		21+70	16+55	16+55	16+55	14+20	14+20
OFFSET		30 RT	CL	CL	CL	70 RT	70 RT
ALIGNMENT		L	L	L	L	L	L
Depth (Ft)		8.60	14.00	9.00	14.00	3.90	8.90

10.10

to

15.50

10.50

15.50

Soils Engineer

5.40

Page 2

10.40

M & T Form 503

Soils Engineer

Page 3

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAY MATERIALS & TESTS UNIT SOILS LABORATORY

T. I. P. No.	B-3421						
	REPORT ON SAM	MPLES OF	SOILS FOR	QUALIT	Y		
Project	3304811	County	CABARRU	S	Owner		
Date: Sampled	6/10/08	Received	6/16/08		— Reported	6/18/08	
Sampled from		-		By	C C MURF	 RAY	
Submitted by	N WAINAINA	······································		•	1995	Standard Spe	ecifications
746578 TO 74659 8/11/08	00	· ·	EST RESUL	rc			
Proj. Sample No.		SS-13	LSI RESUL	10		T	T
Lab. Sample No.		746590	-				
Retained #4 Sie		-			+		
Passing #10 Sie		100					
Passing #40 Sie		98					
Passing #200 Si	eve %	60					
		MINUS	S NO. 10 FRA	CTION			
SOIL MORTAR	- 100%		T				
Coarse Sand F	Ret - #60 %	5.3					
Fine Sand Ret	- #270 %	47.6					
Silt 0.05 - 0.00	05 mm %	24.8					
Clay < 0.005 1		22.3		······································			
Passing #40 Sie		-		***************************************			
Passing #200 Si	eve %	-					
		7					
L. L.		38					
P. I.		10					
AASHTO Classi	fication	A-4(5)				<u> </u>	
Station		14+20					
OFFSET		70 RT					
ALIGNMENT		L					
Depth (Ft)		13.90					
	to	15.40					