



NC 99 VIN MAP

PROJECT REFERENCE NO.	SHEET NO.
2CRJ0071.3	1



PROJECT NO.	SHEET NO.	TOTAL NO.
2CR.10071.3	3	


SUMMARY OF QUANTITIES

PROJECT NO	COUNTY	MAP NO	ROUTE	DESCRIPTION	TYP NO	FINAL SURFACE TESTING REQUIRED	LENGTH MI	WIDTH FT	AGGREGATE SHOULDER BORROW TON	INCIDENTAL STONE BASE TON	SHOULDER RECONSTRUCTION SMI	INCIDENTAL MILLING SY	BASE COURSE, B25.0B TONS	INTERMEDIATE COURSE, I19.0B TONS	SURFACE COURSE, S9.5B TONS	ASPHALT BINDER FOR PLANT MIX TONS	TEMPORARY SILT FENCE LF	STONE FOR EROSION CONTROL, CLASS B TON	WATTLE LF	POLY-ACRYLAMIDE (PAM) LB	SEEDING & MULCHING ACR
2CR.10071.3	Beaufort	1	NC 99	WIDEN STRENGTHEN & RESURFACE FROM INTERSECTION OF NC 99 & SR 1722 TO BEGIN BRIDGE APPROACH OF PANTEGO CREEK BRIDGE	1	YES	6.82	26	4,640	2,728	13.64	1,466	8,049	16,437	9,658	1,723	400	10	150	25	8
TOTAL FOR PROJ NO. 2CR.10071.3							6.82		4,640	2,728	13.64	1,466	8,049	16,437	9,658	1,723	400	10	150	25	8

THERMOPLASTIC AND PAINT QUANTITIES

PROJECT NO	COUNTY	MAP NO	ROUTE	DESCRIPTION	LENGTH	WIDTH	4399000000-N	4685000000-E	4686000000-E	4710000000-E	4810000000-E		4835000000-E	4905000000-N
							TEMPORARY TRAFFIC CONTROL LS	4" X 90 M WHITE THERMO LF	4" X 120 M YELLOW THERMO LF	24" X 120 M WHITE THERMO LF	4" WHITE PAINT LF	4" YELLOW PAINT LF	24" WHITE PAINT LF	SNOWPLOWABLE PAVEMENT MARKERS EA
2CR.10071.3	Beaufort	1	NC 99	WIDEN STRENGTHEN & RESURFACE FROM INTERSECTION OF NC 99 & SR 1722 TO BEGIN BRIDGE APPROACH OF PANTEGO CREEK BRIDGE	6.82	26	*	73,383	45,012	25	73,383	45,012	25	400
TOTAL FOR PROJ NO. 2CR.10071.3					6.82		1	73,383	45,012	25	73,383	45,012	25	400
											118,395			

PROJECT REFERENCE NO.	SHEET NO.
2CR.10071.3	4



SHOULDER WEDGE DETAIL


30-MAY-2012 09:26
 C:\User\p\porter\Documents\mtac\shoulderwedgedetail8aug2011.dgn
 p\porter

CONTRACT STANDARDS AND DEVELOPMENT UNIT Office 919-707-8950 FAX 919-260-4119	
SHOULDER WEDGE DETAIL	
ORIGINAL BY: T. SPELL	DATE: 7-19-11
MODIFIED BY:	DATE:
CHECKED BY:	DATE:
FILE SPEC.: s:\user\details\stand\shoulderwedgedetail.dgn	

NOTES: Less than 5' - 10' undisturbed buffer from ROW, ditchline, water feature, or drainage inlet, add BMP.


BMP Options: Wattle or Silt Fence

EROSION CONTROL DETAIL




NOT TO SCALE


WATTLE WITH POLYACRYLAMIDE (PAM) DETAIL



ISOMETRIC VIEW



**CROSS SECTION
VEE DITCH**



**CROSS SECTION
TRAPEZOIDAL DITCH**

NOTES:

USE MINIMUM 12 IN. DIAMETER EXCELSIOR WATTLE.

USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.

ONLY INSTALL WATTLE(S) TO A HEIGHT IN DITCH SO FLOW WILL NOT WASH AROUND WATTLE AND SCOUR DITCH SLOPES AND AS DIRECTED.

INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO BOTTOM OF DITCH.



PROVIDE STAPLES MADE OF 0.125 IN. DIAMETER STEEL WIRE FORMED INTO A U SHAPE NOT LESS THAN 12" IN LENGTH.

INSTALL STAPLES APPROXIMATELY EVERY 1 LINEAR FOOT ON BOTH SIDES OF WATTLE AND AT EACH END TO SECURE IT TO THE SOIL.

INSTALL MATTING IN ACCORDANCE WITH SECTION 1631 OF THE STANDARD SPECIFICATIONS.

PRIOR TO POLYACRYLAMIDE (PAM) APPLICATION, OBTAIN A SOIL SAMPLE FROM PROJECT LOCATION, AND FROM OFFSITE MATERIAL, AND ANALYZE FOR APPROPRIATE PAM FLOCCULANT TO BE APPLIED TO EACH WATTLE.

INITIALLY APPLY 2 OUNCES OF ANIONIC OR NEUTRALLY CHARGED PAM OVER WATTLE WHERE WATER WILL FLOW AND 1 OUNCE OF PAM ON MATTING ON EACH SIDE OF WATTLE. REAPPLY PAM AFTER EVERY RAINFALL EVENT THAT IS EQUAL TO OR EXCEEDS 0.50 IN.



TOP VIEW