


WBS: 17BP.7.P.4 (PART 1) & 17BP.7.P.1 (PART 2)

CONTRACT: C203270











STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
GUILFORD COUNTY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.7.P.4 / 17BP.7.P.1	1	
STATE PROJECT NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.7.P.4		PE	
17BP.7.P.4		CONSTR	
17BP.7.P.1		PE	
17BP.7.P.1		CONSTR	

LOCATION: BRIDGE #12 ON SR 1970 (EAST KIVETT DR.) OVER NORFOLK SOUTHERN RAILWAY (REHAB AND PAINT)
 BRIDGE #15 ON US 220 (WENDOVER AVE.) OVER I-85 (REHAB ONLY)
 BRIDGE #36 ON NC 150 (OAK RIDGE RD.) OVER ABANDONED RAILROAD GRADE (REHAB AND PAINT)
 BRIDGE #57 ON SR 1398 (FREEMAN MILL RD.) OVER NC 6 (WEST LEE ST.) & US 70A/29A (REHAB AND PAINT)
 BRIDGE #169 ON SR 1129 (GROOMETOWN RD.) OVER I-85 & US 70/29 (REHAB ONLY)
 BRIDGE #277 ON US 421 SBL OVER BIG ALAMANCE CREEK (REHAB AND PAINT)
 BRIDGE #278 ON US 421 NBL OVER BIG ALAMANCE CREEK (REHAB ONLY)
 BRIDGE #292 ON US 220 (WENDOVER AVENUE.) OVER US 220 SBL & SR 1452 (PAINT ONLY)
 BRIDGE #334 ON BESSEMER AVENUE OVER US 220/70/29 (REHAB AND PAINT)



TYPE OF WORK: BRIDGE PRESERVATION- SUBSTRUCTURE AND DECK REPAIR OF EXISTING BRIDGE STRUCTURES
 CLEANING AND PAINTING OF EXISTING BRIDGE STRUCTURES



DESIGN DATA

#12 ADT 2011=8,900
 #15 ADT 2011=27,000
 #36 ADT 2011=6,700
 #57 ADT 2009=21,500
 #169 ADT 2011=8,400
 #277 ADT 2009=8,000
 #278 ADT 2009=8,000
 #292 ADT 2011=55,000
 #334 ADT 2011=17,000

PROJECT LENGTH

PROJECT LENGTH #12 = 0.080 MI
 PROJECT LENGTH #15 = 0.035 MI
 PROJECT LENGTH #36 = 0.030 MI
 PROJECT LENGTH #57 = 0.030 MI
 PROJECT LENGTH #169 = 0.030 MI
 PROJECT LENGTH #277 = 0.039 MI
 PROJECT LENGTH #278 = 0.039 MI
 PROJECT LENGTH #292 = 0.034 MI
 PROJECT LENGTH #334 = 0.032 MI

Prepared in the Office of:
STRUCTURES MANAGEMENT UNIT
 NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

2012 STANDARD SPECIFICATIONS


LETTING DATE:
 June 18, 2013

RICK NELSON, PE
 PROJECT ENGINEER



FARZIN ASEFNIA, PE
 PROJECT DESIGN ENGINEER

CONTRACT NO: C203270 WBS: 17BP.7.P.4 (PART 1) & 17BP.7.P.1 (PART 2)



STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS


GUILFORD COUNTY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.7.P.4 / 17BP.7.P.1	1A	
STATE PROJECT NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.7.P.4		PE	
17BP.7.P.4		CONSTR	
17BP.7.P.1		PE	
17BP.7.P.1		CONSTR	

LOCATION: BRIDGE #12 ON SR 1970 (EAST KIVETT DR.) OVER NORFOLK SOUTHERN RAILWAY
 BRIDGE #15 ON US 220 (WENDOVER AVE.) OVER I-85
 BRIDGE #36 ON NC 150 (OAK RIDGE RD.) OVER ABANDONED RAILROAD GRADE
 BRIDGE #57 ON SR 1398 (FREEMAN MILL RD.) OVER NC 6 (WEST LEE ST.) & US 70A/29A
 BRIDGE #169 ON SR 1129 (GROOMETOWN RD.) OVER I-85 & US 70/29
 BRIDGE #277 ON US 421 SBL OVER BIG ALAMANCE CREEK
 BRIDGE #278 ON US 421 NBL OVER BIG ALAMANCE CREEK
 BRIDGE #292 ON US 220 (WENDOVER AVENUE.) OVER US 220 SBL & SR 1452
 BRIDGE #334 ON BESSEMER AVENUE OVER US 220/70/29

TYPE OF WORK: BRIDGE PRESERVATION- SUBSTRUCTURE AND DECK REPAIR OF EXISTING BRIDGE STRUCTURES
 CLEANING AND PAINTING OF EXISTING BRIDGE STRUCTURES

SHT#	DESCRIPTION
1	COMBINED TITLE SHEET
1A	INDEX OF SHEETS
2	SUMMARY OF QUANTITIES
3	TITLE SHEET (17BP.7.P.4)
S-1 THRU S-63	STRUCTURAL REHABILITATION PLANS (17BP.7.P.4)
TMP-1 THRU TMP-18	TRAFFIC CONTROL PLANS (17BP.7.P.4)
4	TITLE SHEET (17BP.7.P.1)
TMP-1 THRU TMP-6B	TRAFFIC CONTROL PLANS (17BP.7.P.1)



Prepared in the Office of:
STRUCTURES MANAGEMENT UNIT
 NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
 2012 STANDARD SPECIFICATIONS

LETTING DATE: June 18, 2013	RICK NELSON, PE PROJECT ENGINEER
--------------------------------	-------------------------------------

FARZIN ASEFNIA P.E.
 DESIGN ENGINEER

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
ROADWAY SUMMARY OF QUANTITIES FOR CONTRACT - C203270


ItemNumber	Sec #	Quantity	Unit	Description
0000100000-N	800	Lump Sum		MOBILIZATION
1330000000-E	607	4,534	SY	INCIDENTAL MILLING
1525000000-E	610	510	TON	ASPHALT CONC SURFACE COURSE, TYPE SF9.5A
1575000000-E	620	34	TON	ASPHALT BINDER FOR PLANT MIX
4400000000-E	1110	892	SF	WORK ZONE SIGNS (STATIONARY)
4405000000-E	1110	830	SF	WORK ZONE SIGNS (PORTABLE)
4410000000-E	1110	60	SF	WORK ZONE SIGNS (BARRICADE MOUNTED)
4415000000-N	1115	8	EA	FLASHING ARROW BOARD
4420000000-N	1120	6	EA	PORTABLE CHANGEABLE MESSAGE SIGN
4430000000-N	1130	850	EA	DRUMS
4435000000-N	1135	20	EA	CONES
4445000000-E	1145	40	LF	BARRICADES (TYPE III)
4450000000-N	1150	160	HR	FLAGGER
4480000000-N	1165	6	EA	TMA
4510000000-N	SP	616	HR	LAW ENFORCEMENT
4805000000-N	1205	4	EA	COLD APPLIED PLASTIC PAVEMENT MARKING SYMBOL, TYPE ** (II)
4847000000-E	1205	7,480	LF	POLYUREA PAVEMENT MARKING LINES (4", *****) (STANDARD GLASS BEADS)
4847100000-E	1205	1,260	LF	POLYUREA PAVEMENT MARKING LINES (6", *****) (STANDARD GLASS BEADS)
4900000000-N	1251	35	EA	PERMANENT RAISED PAVEMENT MARKERS
8161000000-E	420	119,486	SF	GROOVING BRIDGE FLOORS
8296000000-N	442	Lump Sum		POLLUTION CONTROL
8559000000-E	SP	522	SY	CLASS II, SURFACE PREPARATION
8566000000-E	SP	1	SY	CLASS III, SURFACE PREPARATION
8660000000-E	SP	114.5	CF	CONCRETE REPAIRS
8664000000-E	SP	590	CF	SHOTCRETE REPAIRS

ItemNumber	Sec #	Quantity	Unit	Description
8678000000-E	SP	324.3	LF	EPOXY RESIN INJECTION
8692000000-N	SP	Lump Sum		FOAM JOINT SEALS
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM CLEANING & REPAINTING BRIDGE #12
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM CLEANING & REPAINTING BRIDGE #277
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM CLEANING & REPAINTING BRIDGE #292
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM CLEANING & REPAINTING BRIDGE #334
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM CLEANING & REPAINTING BRIDGE #36
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM CLEANING & REPAINTING BRIDGE #57
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM PAINTING CONTAINMENT FOR BRIDGE #12
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM PAINTING CONTAINMENT FOR BRIDGE #277
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM PAINTING CONTAINMENT FOR BRIDGE #292
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM PAINTING CONTAINMENT FOR BRIDGE #334
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM PAINTING CONTAINMENT FOR BRIDGE #36
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM PAINTING CONTAINMENT FOR BRIDGE #57
8860000000-N	SP	Lump Sum		GENERIC STRUCTURE ITEM PARTIAL REMOVAL OF EXISTING STRUCTURE
8881000000-E	SP	669.7	CY	GENERIC STRUCTURE ITEM LATEX MOD CONC OVERLAY - VERY EARLY STRENGTH

ItemNumber	Sec #	Quantity	Unit	Description
8889000000-E	SP	1,000	LB	GENERIC STRUCTURE ITEM STRUCTURAL STEEL FOR GIRDER REPAIR
8892000000-E	SP	1,181	SF	GENERIC STRUCTURE ITEM BRIDGE JOINT DEMOLITION
8892000000-E	SP	3,892	SF	GENERIC STRUCTURE ITEM EPOXY COATING
8893000000-E	SP	14,394	SY	GENERIC STRUCTURE ITEM HYDRO-DEMOLITION OF BRIDGE DECK
8893000000-E	SP	14,394	SY	GENERIC STRUCTURE ITEM PLACING & FINISHING LATEX MOD CONC OVERLAY - VERY EARLY STRENGTH
8893000000-E	SP	14,394	SY	GENERIC STRUCTURE ITEM SCARIFYING BRIDGE DECK
8897000000-N	SP	19	EA	GENERIC STRUCTURE ITEM BRIDGE JACKING
8897000000-N	SP	27	EA	GENERIC STRUCTURE ITEM TEMPORARY WORK PLATFORM

WBS: 17BP.7.P.4

CONTRACT: C203270



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS








GUILFORD COUNTY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.7.P.4	3	
STATE PROJECT NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.7.P.4		PE	
17BP.7.P.4		CONSTR	

LOCATION: BRIDGE #12 ON SR 1970 (EAST KIVETT DR.) OVER NORFOLK SOUTHERN RAILWAY
 BRIDGE #15 ON US 220 (WENDOVER AVE.) OVER I-85
 BRIDGE #36 ON NC 150 (OAK RIDGE RD.) OVER ABANDONED RAILROAD
 BRIDGE #57 ON SR 1398 (FREEMAN MILL RD.) OVER NC 6 (WEST LEE ST.) & US 70A/29A
 BRIDGE #169 ON SR 1129 (GROOMETOWN RD.) OVER I-85 & US 70/29
 BRIDGE #277 ON US 421 SBL OVER BIG ALAMANCE CREEK
 BRIDGE #278 ON US 421 NBL OVER BIG ALAMANCE CREEK
 BRIDGE #334 ON BESSEMER AVENUE OVER US 220/70/29



TYPE OF WORK: BRIDGE PRESERVATION- SUBSTRUCTURE AND DECK REPAIR OF EXISTING BRIDGE STRUCTURES



DESIGN DATA

#12 ADT 2011=8900
 #15 ADT 2011=27000
 #36 ADT 2011=6700
 #57 ADT 2009=21500
 #169 ADT 2011=8400
 #277 ADT 2009=8000
 #278 ADT 2009=8000
 #334 ADT 2011=17000

PROJECT LENGTH

PROJECT LENGTH #12 = 0.080 MI
 PROJECT LENGTH #15 = 0.035 MI
 PROJECT LENGTH #36 = 0.030 MI
 PROJECT LENGTH #57 = 0.030 MI
 PROJECT LENGTH #169 = 0.030 MI
 PROJECT LENGTH #277 = 0.039 MI
 PROJECT LENGTH #278 = 0.039 MI
 PROJECT LENGTH #334 = 0.032 MI

Prepared in the Office of:
STRUCTURES MANAGEMENT UNIT
 NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
 2012 STANDARD SPECIFICATIONS

LETTING DATE: June 18, 2013	RICK NELSON, PE PROJECT ENGINEER
--------------------------------	-------------------------------------

FARZIN ASEFNIA, PE
PROJECT DESIGN ENGINEER

TOTAL BILL OF MATERIAL

GUILFORD COUNTY BRIDGE NO.	17BP.7.P.4														17BP.7.P.1							
	INCIDENTAL MILLING	ASPHALT CONCRETE SURFACE COURSE, TYPE SF9.5A	GROOVING BRIDGE FLOORS	CLASS II, SURFACE PREPARATION	CLASS III, SURFACE PREPARATION	CONCRETE REPAIRS	SHOTCRETE REPAIRS	EPOXY RESIN INJECTION	FOAM JOINT SEALS	PARTIAL REMOVAL OF EXISTING STRUCTURE	LATEX MODIFIED CONCRETE- VERY EARLY STRENGTH	EPOXY COATING	BRIDGE JOINT DEMOLITION	SCARIFYING BRIDGE DECK	HYDRO- DEMOLITION OF BRIDGE DECK	PLACING & FINISHING LATEX MODIFIED CONCRETE-VERY EARLY STRENGTH	TEMPORARY WORK PLATFORM	BRIDGE JACKING	POLLUTION CONTROL	CLEANING & REPAINTING OF BRIDGE *___	PAINTING CONTAINMENT FOR BRIDGE *___	STRUCTURAL STEEL FOR GIRDER REPAIR*
	SO. YDS.	TONS	SO. FT.	SO. YDS.	SO. YDS.	CU. FT.	CU. FT.	LIN. FT.	LUMP SUM	LUMP SUM	CU. YDS.	SO. FT.	SO. FT.	SO. YDS.	SO. YDS.	SO. YDS.	EACH	EACH	LUMP SUM	LUMP SUM	LUMP SUM	LBS.
12	289	32	29,360	191	---	7	95.5	144.5	LUMP SUM	---	174.6	1,020	210	3,592	3,592	3,592	5	6	---	LUMP SUM	LUMP SUM	---
15	1,673	194	31,488	35	---	5	23.5	72	LUMP SUM	---	157.2	590	215	3,773	3,773	3,773	4	4	---	LUMP SUM	LUMP SUM	---
36	235	26	4,814	---	---	---	---	---	LUMP SUM	---	21.0	---	70	604	604	604	---	---	---	LUMP SUM	LUMP SUM	---
57	512	56	11,698	56	---	---	45	2	LUMP SUM	LUMP SUM	56.0	555	136	1,378	1,378	1,378	3	---	---	LUMP SUM	LUMP SUM	---
169	1,202	132	21,307	188	---	---	30	47.8	LUMP SUM	---	156.0	171	165	2,493	2,493	2,493	4	---	---	LUMP SUM	LUMP SUM	---
277	244	27	7,455	34	---	100.5	13.5	39	LUMP SUM	---	38.4	506	145	921	921	921	4	7	---	LUMP SUM	LUMP SUM	---
278	229	26	5,956	---	---	2	5.5	3	LUMP SUM	---	28.9	295	107	732	732	732	3	2	---	LUMP SUM	LUMP SUM	---
292	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	LUMP SUM	LUMP SUM	---
334	150	17	7,408	18	1	---	377	16	LUMP SUM	---	37.6	755	133	901	901	901	4	---	---	LUMP SUM	LUMP SUM	---
TOTAL	4,534	510	119,486	522	1	114.5	590	324.3	LUMP SUM	LUMP SUM	669.7	3,892	1,181	14,394	14,394	14,394	27	19	LUMP SUM	LUMP SUM	LUMP SUM	1,000

* FOR INFORMATION ONLY. ACTUAL QUANTITY WILL BE DETERMINED IN THE FIELD.

17BP.7.P.4 &
PROJECT NO. 17BP.7.P.1
GUILFORD COUNTY
STATION: _____



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH


**STRUCTURE
TOTAL BILL
OF MATERIAL**

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-1
1			3			TOTAL SHEETS
2			4			63

DRAWN BY : J. YANNACCONE DATE : 3/13
CHECKED BY : F. ASEFNIA DATE : 3/13

← TO CENTENNIAL ST


→ TO COLLEGE DR




PLAN OF SPANS

NOTES

- EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK.
- EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.
- INCIDENTAL MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE.
- THE CONTRACTOR SHALL PROVIDE A METHOD OF HANDLING UNEXPECTED BLOW THROUGH OF THE DECK, SEE "TYPICAL "BLOW THRU" CONTAINMENT AND FORMWORK" DETAIL.
- THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS, SEE MANAGING HYDRO-DEMOLITION WATER SPECIAL PROVISIONS.
- FOR OVERLAY SURFACE PREPARATION, SEE SPECIAL PROVISIONS.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.
- FOR PROTECTION OF RAILWAY INTERESTS, SEE SPECIAL PROVISIONS.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.
- FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLAN SHEET.
- LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.
- DURING CONSTRUCTION, BERMS OR APPROPRIATE MEASURES SHALL BE USED TO ENSURE HYDRO-DEMOLITION WATER DOES NOT FLOW OR MIGRATE INTO ACTIVE TRAVEL LANES.



DETAIL FOR LATEX MODIFIED CONCRETE OVERLAY




TYP. "BLOW THRU" CONTAINMENT AND FORMWORK

A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.

SUBMIT DETAILS OF PROPOSED FORM WORK FOR APPROVAL PRIOR TO BEGINNING WORK.

COST FOR INSTALLING AND REMOVING FORM WORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.



PROJECT NO. 17BP.7.P.4
COUNTY: GUILFORD
DECK REPAIR BRIDGE NO. 12
SHEET 1 OF 10

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH


PLAN VIEW OF BRIDGE #12, KIVETT DRIVE OVER SOUTHERN R.R.
56' CL. ROADWAY

REVISIONS				SHEET NO.	
NO.	BY	DATE	NO.	BY	DATE
2			3		
			4		


TOTAL SHEETS 63




DRAWN BY: C. BRIGHT DATE: 10/12
CHECKED BY: F. ASEFNIA DATE: 10/12



TYPICAL SECTION
(SPAN A)



TYPICAL SECTION
(SPANS B, C & D)



TYPICAL SECTION
(SPAN E)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 2 OF 10


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

TYPICAL SECTION




REVISIONS						HEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			


DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



SECTION A-A
(EXISTING JOINT)



SECTION A-A
(MINIMUM EXISTING JOINT DEMOLITION)




SECTION A-A
(PROPOSED JOINT)


NOTES

FOR FOAM JOINT SEAL, SEE SPECIAL PROVISIONS.
 THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.
 NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2" AT BENTS.
 THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINT FOR THE FOAM JOINT SEAL IN LIEU OF SAWING THE JOINT.
 NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL FOR THE EXISTING JOINT IN THE CURB, MEDIAN AND SIDEWALK TO BE DETERMINED BY THE ENGINEER.
 GRADE DIFFERENCE BETWEEN PROPOSED BRIDGE LMC OVERLAY AND EXISTING PAVEMENT SHALL BE ADJUSTED IN THE APPROACH SLAB OVERLAY. SEE SECTIONS A-A & C-C.
 BACKER ROD SIZE TO BE DETERMINED BY THE ENGINEER.


NOTE: RETAIN ALL EXISTING REINFORCING STEEL. CLEAN AND REPAIR AS NEEDED.




SECTION B-B
(EXISTING JOINT)




SECTION B-B
(PREPOSED JOINT PRE-SAWED DIMENSIONS)




SECTION B-B
(PROPOSED JOINT PRE-SAWED DIMENSIONS)




SECTION B-B
(PROPOSED JOAM JOINT SEAL EXPANSION)




PLAN




SECTION C-C
(MINIMUM EXISTING DEMOLITION)



SECTION C-C
(PROPOSED)



SECTION D-D



SECTION @ MEDIAN

ELASTOMERIC CONCRETE	
BENTS	39.3 (CU. FT.)
* TOTAL	39.3 (CU. FT.)
* BASED ON THE MINIMUM BLOCKOUT SHOWN.	




PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 3 OF 10

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


JOINT DETAILS

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			

DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



END BENT 1



END BENT 2*

* NO DAMAGE OBSERVED ON BENT 2, HOWEVER IF SOME DAMAGE IS FOUND BY THE ENGINEER SEE NOTE ON THIS SHEET CONCERNING ADDITIONAL REPAIRS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-10.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AND PILE CAPS AT END BENT 1.

REPAIRS END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
SHOTCRETE REPAIRS				
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
TOP OF CAP	43.8	27.5		
PILE CAP	0	0		
CONCRETE REPAIRS	10.9	7.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP (VERTICAL, FACE)		40		
PILE CAP		0		
EPOXY COATING		SO. FT		SO. FT
TOP OF CAP AND PILE CAPS		230		

REPAIRS END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
SHOTCRETE REPAIRS				
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
TOP OF CAP	0	0		
PILE CAP	0	0		
CONCRETE REPAIRS	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP (VERTICAL, FACE)		0		
PILE CAP		0		
EPOXY COATING		SO. FT		SO. FT
TOP OF CAP AND PILE CAPS		0		

VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 4 OF 10


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

END BENTS




REVISIONS						SHEET NO. S-5
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			

DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



SPAN 'B' FACE



SPAN 'A' FACE

REPAIR QUANTITY TABLE

REPAIRS BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	20.0	9.0		
CAP (HORIZONTAL, CORNER)	11.0	7.0		
COLUMN	6.2	4.0		
STRUT (VERTICAL FACE)	0	0		
STRUT (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		19		
COLUMN		5		
STRUT		0		
EPOXY COATING		SO. FT		SO. FT
TOP FACE OF CAP		395		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-10.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 1.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 5 OF 10


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 1




REVISIONS						SHEET NO. S-6
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			

DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



SPAN 'C' FACE*

* NO DAMAGE OBSERVED ON BENT 2, HOWEVER IF SOME DAMAGE IS FOUND BY THE ENGINEER SEE NOTE ON THIS SHEET CONCERNING ADDITIONAL REPAIRS.



SPAN 'B' FACE*

REPAIR QUANTITY TABLE

REPAIRS BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
COLUMN	0	0		
STRUT (VERTICAL FACE)	0	0		
STRUT (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0		
COLUMN		0		
STRUT		0		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 6 OF 10


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 2




REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			

DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



1.5 SQ. FT. SHOTCRETE REPAIR

SPAN 'D' FACE



6 SQ. FT. SHOTCRETE REPAIR

3 SQ. FT. SHOTCRETE REPAIR

SPAN 'C' FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
COLUMN	10.5	6.5		
STRUT (VERTICAL FACE)	0	0		
STRUT (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION			LN. FT	LN. FT
CAP			0	
COLUMN			0	
STRUT			0	

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.


FOR STRUCTURE REPAIRS, SEE SHEET S-10.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 7 OF 10


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 3


REVISIONS						SHEET NO. S-8
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			



DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



SPAN 'E' FACE



SPAN 'D' FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 4	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	1.0	0.5		
CAP (HORIZONTAL, CORNER)	6.2	4		
COLUMN	52.0	33		
STRUT (VERTICAL FACE)	0	0		
STRUT (HORIZONTAL, CORNER)	6.0	4		
EPOXY RESIN INJECTION				
		LN. FT		LN. FT
CAP		4.0		
COLUMN		44.0		
STRUT		32.5		
EPOXY COATING				
		SO. FT		SO. FT
TOP FACE OF CAP		395		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-10.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 4.


PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 8 OF 10

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


BENT 4




REVISIONS						EVENT NO.
NO.	BY	DATE	NO.	BY	DATE	S-9
1			3			TOTAL SHEETS
2			4			63



BENT CAP & COLUMN REPAIR DETAIL




SECTION L-L




SECTION M-M


* CONCRETE SHALL BE REMOVED UNTIL SOUND CRETE IS FOUND, MIN. OF 1"




OVERHANG REPAIR DETAIL



END BENT CAP REPAIR DETAIL



SECTION K-K



SECTION J-J



PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 9 OF 10

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


**CAP & COLUMN
 REPAIR DETAILS**

REVISIONS						SHEET NO. S-10
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			



DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12

← TO CENTENNIAL ST

TO COLLEGE DR →




**DISTANCE TO BE FIELD DETERMINED BY THE ENGINEER


-  DECK SCARIFICATION AND HYDRODEMOLITION
-  INCIDENTAL MILLING

PLAN


C1 PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.




TYPICAL ROADWAY SECTION
(WEST BRIDGE APPROACH)



TYPICAL ROADWAY SECTION
(EAST BRIDGE APPROACH)



TYPICAL ROADWAY MILLING SECTION
(WEST BRIDGE APPROACH)
(MILL TO 2" DEPTH)



TYPICAL ROADWAY MILLING SECTION
(EAST BRIDGE APPROACH)
(MILL TO 2" DEPTH)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 12
 SHEET 10 OF 10


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

PLAN VIEW OF BRIDGE
 #12, KIVETT DRIVE
 OVER SOUTHERN R.R.
 56' CL. ROADWAY



REVISIONS						SHEET NO. S-11
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			


DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12





APPROX. AREA: CLASS II REPAIR
 BRIDGE JOINT DEMOLITION

NOTES

- EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK.
- EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.
- INCIDENTAL MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE.
- THE CONTRACTOR SHALL PROVIDE A METHOD OF HANDLING UNEXPECTED BLOW THROUGH OF THE DECK, SEE "TYPICAL "BLOW THRU" CONTAINMENT AND FORMWORK" DETAIL.
- THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS, SEE MANAGING HYDRO-DEMOLITION WATER SPECIAL PROVISION.
- FOR OVERLAY SURFACE PREPARATION, SEE SPECIAL PROVISIONS.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR SCARIFYING BRIDGE DECK, SEE SPECIAL PROVISIONS.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.
- FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLAN SHEETS.
- LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.
- DURING CONSTRUCTION, BERMS OR APPROPRIATE MEASURES SHALL BE USED TO ENSURE HYDRO-DEMOLITION WATER DOES NOT FLOW OR MIGRATE INTO ACTIVE TRAVEL LANES.



DETAIL FOR LATEX MODIFIED CONCRETE OVERLAY



TYP. "BLOW THRU" CONTAINMENT AND FORMWORK


A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.
 SUBMIT DETAILS OF PROPOSED FORM WORK FOR APPROVAL PRIOR TO BEGINNING WORK.
 COST FOR INSTALLING AND REMOVING FORM WORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 1 OF 9




STATE OF NORTH CAROLINA					
DEPARTMENT OF TRANSPORTATION					
RALEIGH					
PLAN VIEW OF BRIDGE					
#15, ON US 220					
OVER I -85					
100' CL. ROADWAY SKEW 58°-32'					
REVISIONS					SHEET NO.
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		
					TOTAL SHEETS
					63

DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



TYPICAL SECTION
(SPANS A & D)



TYPICAL SECTION
(SPANS B & C)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 2 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

TYPICAL SECTION



REVISIONS						HEET NO.
NO.	BY	DATE	NO.	BY	DATE	S-13
1			3			TOTAL SHEETS
2			4			63


DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12

NOTES


FOR FOAM JOINT SEAL, SEE SPECIAL PROVISIONS.
 THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.
 NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2 1/2" AT BENTS.
 THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINT FOR THE FOAM JOINT SEAL IN LIEU OF SAWING THE JOINT.
 THE BACKER ROD SIZE SHALL BE DETERMINED BY THE ENGINEER.

ELASTOMERIC CONCRETE	
BENTS	40.3 (CU. FT.)
* TOTAL	40.3 (CU. FT.)


* BASED ON THE MINIMUM BLOCKOUT SHOWN.



SECTION A-A
(EXISTING JOINT)




SECTION A-A
(PROPOSED JOINT)




SECTION A-A
(PROPOSED JOINT)


* ALL LOOSE AND UNSOUND CONCRETE SHALL BE REMOVED. IF THE EMBEDDED PORTION OF THE EXISTING WATERSTOP IS EXPOSED DURING REMOVAL, THE ENTIRE WATERSTOP SHALL BE REMOVED.




SECTION B-B
(EXISTING JOINT)



SECTION B-B
(MINIMUM EXISTING JOINT DEMOLITION)




SECTION B-B
(PROPOSED JOINT PRE-SAWED DIMENSIONS)




SECTION B-B
(PROPOSED JOINT SEAL EXPANSION)


NOTE: RETAIN ALL EXISTING REINFORCING STEEL. CLEAN AND REPAIR AS REQ'D.




SECTION C-C
(EXISTING JOINT)



SECTION C-C
(PROPOSED JOINT)



PLAN



SECTION D-D

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 3 OF 9



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

JOINT DETAILS

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S-14
1			3			TOTAL SHEETS
2			4			63



DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



* NO DAMAGE OBSERVED ON END BENT 2, HOWEVER IF SOME DAMAGE IS FOUND BY THE ENGINEER, SEE NOTE ON THIS SHEET CONCERNING ADDITIONAL REPAIRS.

NOTE:
 REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.
 FOR STRUCTURE REPAIRS, SEE SHEET S-19.
 EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AND PILE CAPS AT END BENT 1.

REPAIR QUANTITY TABLE					
REPAIRS END BENT 1	QUANTITIES				
	ESTIMATE		ACTUAL		
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	DEPTH FT	VOLUME CF
CAP (VERTICAL)	0	0			
CAP (HORIZONTAL, CORNER)	19.0	12.0			
PILE CAP	0	0			
EPOXY RESIN INJECTION		LN. FT			LN. FT
CAP (VERTICAL, FACE)		6			
PILE CAP		0			
EPOXY COATING	215 SQ. FT.				

REPAIR QUANTITY TABLE					
REPAIRS END BENT 2	QUANTITIES				
	ESTIMATE		ACTUAL		
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	DEPTH FT	VOLUME CF
CAP (VERTICAL)	0	0			
CAP (HORIZONTAL, CORNER)	0	0			
PILE CAP	0	0			
EPOXY RESIN INJECTION		LN. FT			LN. FT
CAP (VERTICAL, FACE)		0			
PILE CAP		0			

VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 4 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


END BENTS

REVISIONS				SHEET NO.
NO.	BY	DATE	NO.	DATE
1			3	
2			4	

TOTAL SHEETS: 63




DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



EAST END

NORTH FACE



WEST END

SOUTH FACE

REPAIRS BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
SHOTCRETE REPAIRS				
CAP (VERTICAL FACE)	9.5	4.0		
CAP (HORIZONTAL, CORNER)	3.0	2.0		
COLUMN (VERTICAL FACE)	0	0		
COLUMN (HORIZONTAL, CORNER)	0	0		
CONCRETE REPAIRS	10.1	5.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		3		
COLUMN		43		
EPOXY COATING	375 SO. FT.			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-19.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 1.


PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 5 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 BENT 1




REVISIONS						SHEET NO. S-16	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				

DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



EAST END

NORTH FACE



WEST END

SOUTH FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.2	0.5		
CAP (HORIZONTAL, CORNER)	0	0		
COLUMN (VERTICAL FACE)	1.2	1.0		
COLUMN (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0		
COLUMN		0		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-19.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 6 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 2




REVISIONS						SHEET NO. S-17	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				

DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



EAST END

NORTH FACE



WEST END

SOUTH FACE

REPAIRS BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
SHOTCRETE REPAIRS				
CAP (VERTICAL FACE)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
COLUMN (VERTICAL FACE)	7.0	4.0		
COLUMN (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0		
COLUMN		20		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-19.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 7 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 3




REVISIONS						SHIRT NO.
NO.	BY	DATE	NO.	BY	DATE	S-18
1			3			TOTAL SHEETS
2			6			63


DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



BENT CAP & COLUMN REPAIR DETAIL




SECTION L-L




SECTION M-M


* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1" MIN.)




OVERHANG REPAIR DETAIL



END BENT CAP REPAIR DETAIL



SECTION K-K



SECTION J-J

DAMAGED AREA

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 8 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH



CAP & COLUMN REPAIR DETAILS



REVISIONS						SHEET NO.	
NO.	BY	DATE	NO.	BY	DATE	S-19	
1			3			TOTAL SHEETS	
2			4			63	


DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12




-  DECK SCARIFICATION AND HYDRO-DEMOLITION
-  INCIDENTAL MILLING

PLAN

C1 PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.



TYPICAL ROADWAY SECTION



TYPICAL ROADWAY MILLING SECTION
(MILL TO 2" DEPTH)




PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 15
 SHEET 9 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 ROADWAY TYPICAL
 SECTION AND
 MILLING DETAILS

REVISIONS						SHEET NO. S-20
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			


DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12

NOT TO SCALE




NOTES

- EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK.
- EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.
- INCIDENTAL MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE.
- THE CONTRACTOR SHALL PROVIDE A METHOD OF HANDLING UNEXPECTED BLOW THROUGH OF THE DECK, SEE "TYPICAL 'BLOW THRU' CONTAINMENT AND FORMWORK" DETAIL.
- THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS SEE, MANAGING HYDRO-DEMOLITION WATER SPECIAL PROVISION.
- FOR OVERLAY SURFACE PREPARATION, SEE SPECIAL PROVISIONS.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR SCARIFYING BRIDGE DECK, SEE SPECIAL PROVISIONS.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.
- FOR PROTECTION OF RAILWAY INTERESTS, SEE SPECIAL PROVISIONS.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.
- FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLAN SHEETS.
- LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.
- DURING CONSTRUCTION, BERMS OR APPROPRIATE MEASURES SHALL BE USED TO ENSURE HYDRO-DEMOLITION WATER DOES NOT FLOW OR MIGRATE INTO ACTIVE TRAVEL LANES.




DETAIL FOR LATEX MODIFIED CONCRETE OVERLAY



TYP. "BLOW THRU" CONTAINMENT AND FORMWORK

A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.
 SUBMIT DETAILS OF PROPOSED FORM WORK FOR APPROVAL PRIOR TO BEGINNING WORK.
 COST FOR INSTALLING AND REMOVING FORM WORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.



PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 36
 SHEET 1 OF 3


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

PLAN VIEW OF BRIDGE #36, ON NC 150 OVER ABANDONED RAILWAY
 34' CL. ROADWAY 26°-37'-27" SKEW


REVISIONS				SHEET NO. S-21
NO.	BY	DATE	TOTAL SHEETS 63	
1		3		
2		4		



DRAWN BY: C. BRIGHT DATE: 09/12
 CHECKED BY: J. YANNAACONE DATE: 10/12




TYPICAL SECTION




SECTION A-A

**EXISTING APPROACH AND SHOULDER ASPHALT CONCRETE PAVING TO BE MILLED A MINIMUM DEPTH OF 2". PROVIDE ADEQUATE NEW ASPHALT CONCRETE THICKNESS TO PROVIDE SMOOTH TRANSITION TO APPROACH SLAB, AS SHOWN. NEW ASPHALT THICKNESS MAY EXCEED 2" DUE TO SETTLEMENT OF THE APPROACH AND SHOULDER ASPHALT.

* ALL LOOSE AND UNSOUND CONCRETE SHALL BE REMOVED. IF THE EMBEDDED PORTION OF THE EXISTING WATERSTOP IS EXPOSED DURING REMOVAL, THE ENTIRE WATERSTOP SHALL BE REMOVED.




SECTION B-B
(EXISTING JOINT)




SECTION B-B
(MINIMUM EXISTING JOINT DEMOLITION)

* WATERSTOP TO BE CUT FLUSH WITH JOINT


NOTE: RETAIN ALL EXISTING REINFORCING STEEL. CLEAN AND REPAIR AS REQUIRED.



SECTION B-B
(PROPOSED FOAM JOINT SEAL PRE-SAWED DIMENSIONS)



SECTION B-B
(PROPOSED FOAM JOINT SEAL EXPANSION)



PLAN

NOTES

FOR FOAM JOINT SEAL, SEE SPECIAL PROVISIONS.


THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.

NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2 1/2" AT BENTS.


THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINT FOR THE FOAM JOINT SEAL IN LIEU OF SAWING THE JOINT.

ELASTOMERIC CONCRETE	
BENTS	14.5 (CU. FT.)
* TOTAL	14.5 (CU. FT.)

* BASED ON THE MINIMUM BLOCKOUT SHOWN.



SECTION D-D




PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 36
 SHEET 2 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

TYPICAL SECTION
 &
 JOINT DETAILS

REVISIONS						SHEET NO. S-22
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			


DRAWN BY: C. BRIGHT DATE: 09/12
 CHECKED BY: J. YANNAACONE DATE: 10/12




- DECK SCARIFICATION AND HYDRODEMOLITION
- ASPHALT MILLING

PLAN

C1 PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.



TYPICAL ROADWAY SECTION



TYPICAL ROADWAY MILLING SECTION
(MILL TO 2" DEPTH)




PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 36
 SHEET 3 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
ROADWAY TYPICAL SECTION AND MILLING DETAILS

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S-23
1			3			TOTAL SHEETS
2			4			63

NOT TO SCALE

DRAWN BY: C. BRIGHT DATE: 09/12
 CHECKED BY: J. YANACCONO DATE: 10/12





APPROX. AREA:
CLASS II REPAIR

BRIDGE JOINT
DEMOLITION

NOTES

- EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK.
- EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.
- INCIDENTAL MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE.
- THE CONTRACTOR SHALL PROVIDE A METHOD OF HANDLING UNEXPECTED BLOW THROUGH OF THE DECK, SEE "TYPICAL "BLOW THRU" CONTAINMENT AND FORMWORK" DETAIL.
- THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS, SEE MANAGING HYDRO-DEMOLITION WATER SPECIAL PROVISION.
- FOR OVERLAY SURFACE PREPARATION, SEE SPECIAL PROVISIONS.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR SCARIFYING BRIDGE DECK, SEE SPECIAL PROVISIONS.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.
- FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLAN SHEET.
- LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.
- DURING CONSTRUCTION, BERMS OR APPROPRIATE MEASURES SHALL BE USED TO ENSURE HYDRO-DEMOLITION WATER DOES NOT FLOW OR MIGRATE INTO ACTIVE TRAVEL LANES.
- FOR PARTIAL REMOVAL OF EXISTING STRUCTURE, SEE SPECIAL PROVISIONS.

PLAN OF SPANS



TYP. "BLOW THRU" CONTAINMENT AND FORMWORK

A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.

SUBMIT DETAILS OF PROPOSED FORM WORK FOR APPROVAL PRIOR TO BEGINNING WORK.

COST FOR INSTALLING AND REMOVING FORM WORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 57
 SHEET 1 OF 7


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

PLAN VIEW OF BRIDGE
 #57, ON FREEMAN MILL RD
 OVER NC 6 (LEE ST.)
 68' CL. ROADWAY 66°-48' SKEW

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			



DRAWN BY: C. BRIGHT DATE: 09/12
 CHECKED BY: F. ASEFNIA DATE: 09/12




TYPICAL SECTION

OVERHANG DIAPHRAGMS TO BE REMOVED LOW SIDE OF BRIDGE. SEE SHEET 6 OF 7.


NOTES
 FOR FOAM JOINT SEAL, SEE SPECIAL PROVISIONS.
 THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.
 NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2 1/2" AT BENTS.
 THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINT FOR THE FOAM JOINT SEAL IN LIEU OF SAWING THE JOINT.
 BACKER ROD WIDTH SHALL BE FIELD DETERMINED BY THE ENGINEER AFTER THE JOINT HAS BEEN CLEANED.

ELASTOMERIC CONCRETE	
BENTS	25.4 (CU. FT.)
* TOTAL	25.4 (CU. FT.)


* BASED ON THE MINIMUM BLOCKOUT SHOWN.




SECTION A-A (EXISTING JOINT)




SECTION A-A (PROPOSED JOINT)




SECTION B-B (EXISTING JOINT)



SECTION B-B (PROPOSED JOINT)




SECTION D-D (EXISTING JOINT)




SECTION D-D (PROPOSED JOINT)

NOTE: RETAIN ALL EXISTING REINFORCING STEEL. CLEAN AND REPAIR AS REQ'D.




SECTION E-E




PLAN


* ALL LOOSE AND UNSOUND CONCRETE SHALL BE REMOVED. IF THE EMBEDDED PORTION OF THE EXISTING WATERSTOP IS EXPOSED DURING REMOVAL, THE ENTIRE WATERSTOP SHALL BE REMOVED.




SECTION C-C (EXISTING JOINT)



SECTION C-C (MINIMUM EXISTING JOINT DEMOLITION)



SECTION C-C (PROPOSED FOAM JOINT SEAL PRE-SAWED DIMENSIONS)




SECTION C-C (PROPOSED FOAM JOINT SEAL EXPANSION)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 57
 SHEET 2 OF 7

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
TYPICAL SECTION & JOINT DETAILS					
SHEET NO. S-25					
TOTAL SHEETS 63					
REVISIONS					
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		




DRAWN BY: C BRIGHT DATE: 09/12
 CHECKED BY: F. ASEFNIA DATE: 09/12



END BENT 1

ESTIMATED REPAIR AREA



END BENT 2*

* NO DAMAGE OBSERVED ON END BENT 2. HOWEVER IF DAMAGE IS FOUND BY THE ENGINEER, SEE NOTE ON THIS SHEET CONCERNING ADDITIONAL REPAIRS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-29.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AND PILE CAPS AT END BENT 1.

REPAIRS END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
SHOTCRETE REPAIRS				
CAP (VERTICAL)	13.3	6.0		
CAP (HORIZONTAL, CORNER)	0.7	0.5		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP (VERTICAL, FACE)		0		
PILE CAP		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP AND PILE CAPS		143		

REPAIRS END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
SHOTCRETE REPAIRS				
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP (VERTICAL, FACE)		0		
PILE CAP		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP AND PILE CAPS		0		

VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 57
 SHEET 3 OF 7


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

END BENTS



REVISIONS						SHEET NO. S-26
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			


DRAWN BY: CLB DATE: 10/11
 CHECKED BY: DCM DATE: 11/11



EAST END

SPAN 'B' FACE

ESTIMATED REPAIR AREA



WEST END

SPAN 'A' FACE

REPAIR QUANTITY TABLE

REPAIRS BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	7.5	3.5		
CAP (HORIZONTAL, CORNER)	23.7	15.0		
COLUMN (VERTICAL FACE)	0	0		
COLUMN (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		2		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP		206		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL. TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-29.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 1.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 57
 SHEET 4 OF 7


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 1




REVISIONS						SHEET NO. S-27	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				

DRAWN BY: CLB DATE: 10/11
 CHECKED BY: DCM DATE: 11/11



EAST END

SPAN 'C' FACE



WEST END

SPAN 'B' FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	13.0	5.5		
CAP (HORIZONTAL, CORNER)	1.5	1.0		
COLUMN (VERTICAL FACE)	0.6	0.5		
COLUMN (HORIZONTAL, CORNER)	18.5	13.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0		
COLUMN		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP		206		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-29.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 2.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 57
 SHEET 5 OF 7


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 2


REVISIONS						DRYER NO.
NO.	BY	DATE	NO.	BY	DATE	S-28
1			3			TOTAL SHEETS
2			4			63




DRAWN BY: CLB DATE: 10/11
 CHECKED BY: DCM DATE: 11/11



BENT CAP & COLUMN REPAIR DETAIL




SECTION L-L




SECTION M-M


* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1" MIN.)




OVERHANG REPAIR DETAIL



END BENT CAP REPAIR DETAIL



SECTION K-K




SECTION J-J

DAMAGED AREA

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 57
 SHEET 6 OF 7


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
**CAP & COLUMN
 REPAIR DETAILS**



REVISIONS				SHEET NO.	
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		


TOTAL SHEETS: **63**

DRAWN BY: CLB DATE: 10/11
 CHECKED BY: DCM DATE: 11/11




- DECK SCARIFICATION AND HYDRODEMOLITION
- INCIDENTAL MILLING

PLAN



TYPICAL ROADWAY SECTION

C1 PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.




TYPICAL ROADWAY MILLING SECTION
(MILL TO 2" DEPTH)

NOT TO SCALE


PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 57
 SHEET 7 OF 7

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 ROADWAY TYPICAL
 SECTION AND
 MILLING DETAILS

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			



DRAWN BY: CLB DATE: 10/11
 CHECKED BY: DCM DATE: 11/11



NOTES

EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK.

EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.

INCIDENTAL MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE.

THE CONTRACTOR SHALL PROVIDE A METHOD OF HANDLING UNEXPECTED BLOW THROUGH OF THE DECK, SEE "TYPICAL 'BLOW THRU' CONTAINMENT AND FORMWORK" DETAIL.

THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS SEE, MANAGING HYDRO-DEMOLITION WATER SPECIAL PROVISION.

FOR OVERLAY SURFACE PREPARATION, SEE SPECIAL PROVISIONS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR SCARIFYING BRIDGE DECK, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.


IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.

FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLAN SHEETS.


LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.

DURING CONSTRUCTION, BERMS OR APPROPRIATE MEASURES SHALL BE USED TO ENSURE HYDRO-DEMOLITION WATER DOES NOT FLOW OR MIGRATE INTO ACTIVE TRAVEL LANES.

PLAN



DETAIL FOR LATEX MODIFIED CONCRETE OVERLAY-VES




TYP. "BLOW THRU" CONTAINMENT AND FORMWORK

A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.

SUBMIT DETAILS OF PROPOSED FORM WORK FOR APPROVAL PRIOR TO BEGINNING WORK.

COST FOR INSTALLING AND REMOVING FORM WORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.



ELEVATION


PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 169
 SHEET 1 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 PLAN VIEW OF BRIDGE
 #169, ON SR 1129
 OVER I-85
 70' CL. ROADWAY 49°-03' SKEW


REVISIONS						SHEET NO. S-31 TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE	
1			3			
2			4			




DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12




TYPICAL SECTION
(SPANS A & D)



TYPICAL SECTION
(SPANS A & D)



TYPICAL SECTION
(SPANS B & C)



TYPICAL SECTION
(SPANS B & C)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 169
 SHEET 2 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

TYPICAL SECTION
 &
 JOINT DETAILS




REVISIONS						SHEET NO. S-32	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				

DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12




SECTION A-A
(EXISTING JOINT)




SECTION A-A
(MINIMUM EXISTING JOINT DEMOLITION)


NOTE: RETAIN ALL EXISTING REINFORCING STEEL. CLEAN AND REPAIR AS NEEDED.



SECTION A-A
(PROPOSED JOINT)




SECTION B-B
(EXISTING JOINT)




SECTION B-B
(MINIMUM EXISTING JOINT DEMOLITION)

* ALL LOOSE AND UNSOUND CONCRETE SHALL BE REMOVED. IF THE EMBEDDED PORTION OF THE EXISTING WATERSTOP IS EXPOSED DURING REMOVAL, THE ENTIRE WATERSTOP SHALL BE REMOVED.




SECTION B-B
(PROPOSED FOAM JOINT SEAL PRE-SAWED DIMENSIONS)




SECTION B-B
(PROPOSED FOAM JOINT SEAL EXPANSION)

NOTES

FOR FOAM JOINT SEAL, SEE SPECIAL PROVISIONS.
THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.
NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2 1/2" AT BENTS.
THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINT FOR THE FOAM JOINT SEAL IN LIEU OF SAWING THE JOINT.



PLAN



SECTION D-D

ELASTOMERIC CONCRETE		
BENT 1	15.5	(CU. FT.)
BENT 3	15.5	(CU. FT.)
* TOTAL	31.0	(CU. FT.)

* BASED ON THE MINIMUM BLOCKOUT SHOWN.

PROJECT NO. 17BP.7.P.4
COUNTY: GUILFORD
DECK REPAIR BRIDGE NO. 169
SHEET 3 OF 9

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH


JOINT DETAILS

REVISIONS					
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		


SHEET NO. S-33
TOTAL SHEETS 63



DRAWN BY: C BRIGHT DATE: 10/12
CHECKED BY: F. ASEFNIA DATE: 10/12



END BENT #1



END BENT #2

▨ ESTIMATED REPAIR AREA

REPAIR QUANTITY TABLE				
REPAIRS END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP (VERTICAL, FACE)		9		
PILE CAP		0		

REPAIR QUANTITY TABLE				
REPAIRS END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	8.5	5.0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP (VERTICAL, FACE)		0		
PILE CAP		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP AND PILE CAPS			171	

NOTE:
 REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.
 FOR STRUCTURE REPAIRS, SEE SHEET S-38.
 EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AND PILE CAPS AT END BENT 2.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 169
 SHEET 4 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

END BENTS

70' CL. ROADWAY 49°-03' SKEW


REVISIONS				SHEET NO.
NO.	BY	DATE	NO.	DATE
1			3	
2			4	

TOTAL SHEETS: **63**




DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12

VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.



EAST END

NORTH FACE



WEST END

SOUTH FACE

▨ ESTIMATED REPAIR AREA

REPAIRS BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
SHOTCRETE REPAIRS				
CAP (VERTICAL FACE)	2.0	1.0		
CAP (HORIZONTAL, CORNER)	1.8	1.0		
COLUMN (VERTICAL FACE)	10.2	6.5		
COLUMN (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		3		
COLUMN		14		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.


FOR STRUCTURE REPAIRS, SEE SHEET S-38.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 169
 SHEET 5 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 1

70' CL. ROADWAY 49°-03' SKEW




REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			


DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12




EAST END



NORTH FACE



WEST END



SOUTH FACE

▨ ESTIMATED REPAIR AREA

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-38.

REPAIRS BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
COLUMN (VERTICAL FACE)	0	0		
COLUMN (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		3		
COLUMN		0		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 169
 SHEET 6 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


BENT 2

70' CL. ROADWAY 49°-03' SKEW



REVISIONS						SHEET NO. S-36	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				

DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.
FOR STRUCTURE REPAIRS, SEE SHEET S-38.

REPAIRS BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0	0		
CAP (HORIZONTAL, CORNER)	24.9	16.0		
COLUMN (VERTICAL FACE)	0.25	0.5		
COLUMN (HORIZONTAL, CORNER)	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		15.8		
COLUMN		3.0		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 169
 SHEET 7 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 3


70' CL. ROADWAY 49°-03' SKEW

REVISIONS						SHEET NO. S-37
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			






BENT CAP & COLUMN REPAIR DETAIL




SECTION L-L




SECTION M-M


* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1\"/>




OVERHANG REPAIR DETAIL



END BENT CAP REPAIR DETAIL



SECTION K-K



SECTION J-J

* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1\"/>

 DAMAGED AREA


PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 169
 SHEET B OF 9



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
**CAP & COLUMN
 REPAIR DETAILS**




REVISIONS						SHIRT NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			

DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12




-  ASPHALT MILLING, DECK SCARIFICATION AND HYDRODEMOLITION
-  INCIDENTAL MILLING

PLAN




TYPICAL ROADWAY SECTION

C1 PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.



TYPICAL BRIDGE MILLING SECTION
(MILL TO 2" DEPTH OR BRIDGE DECK SURFACE)




TYPICAL ROADWAY MILLING SECTION
(MILL TO 2" DEPTH)

NOT TO SCALE


PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 169
 SHEET 9 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 ROADWAY TYPICAL
 SECTION AND
 MILLING DETAILS

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			




DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



NOTES

- EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK.
- EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.
- INCIDENTAL MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE.
- THE CONTRACTOR SHALL PROVIDE A METHOD OF HANDLING UNEXPECTED BLOW THROUGH OF THE DECK, SEE "TYPICAL "BLOW THRU" CONTAINMENT AND FORMWORK" DETAIL.
- THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS SEE, MANAGING HYDRO-DEMOLITION WATER SPECIAL PROVISION.
- FOR OVERLAY SURFACE PREPARATION, SEE SPECIAL PROVISIONS.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR SCARIFYING BRIDGE DECK, SEE SPECIAL PROVISIONS.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.
- FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLAN SHEETS.
- LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.
- DURING CONSTRUCTION, BERMS OR APPROPRIATE MEASURES SHALL BE USED TO ENSURE HYDRO-DEMOLITION WATER DOES NOT FLOW OR MIGRATE INTO ACTIVE TRAVEL LANES.




TYP. "BLOW THRU" CONTAINMENT AND FORMWORK


A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.

SUBMIT DETAILS OF PROPOSED FORM WORK FOR APPROVAL PRIOR TO BEGINNING WORK.

COST FOR INSTALLING AND REMOVING FORM WORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.



DETAIL FOR LATEX MODIFIED CONCRETE OVERLAY




PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 277
 SHEET 1 OF 8

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

PLAN VIEW OF BRIDGE #277, ON US 421 OVER BIG ALAMANCE CREEK
 40' CL. ROADWAY

REVISIONS						SHEET NO. S-40
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			

DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



TYPICAL SECTION

NOTES

FOR FOAM JOINT SEAL, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.


NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2 1/2" AT BENTS.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINT FOR THE FOAM JOINT SEAL IN LIEU OF SAWING THE JOINT.


BACKER ROD WIDTH SHALL BE FIELD DETERMINED BY THE ENGINEER AFTER THE JOINT HAS BEEN CLEANED.

ELASTOMERIC CONCRETE	
BENTS	27.1 (CU. FT.)
* TOTAL	27.1 (CU. FT.)


* BASED ON THE MINIMUM BLOCKOUT SHOWN.




SECTION A-A
(EXISTING JOINT)



SECTION A-A
(PROPOSED JOINT)




PLAN




SECTION D-D


* ALL LOOSE AND UNSOUND CONCRETE SHALL BE REMOVED. IF THE EMBEDDED PORTION OF THE EXISTING WATERSTOP IS EXPOSED DURING REMOVAL, THE ENTIRE WATERSTOP SHALL BE REMOVED.




SECTION B-B
(EXISTING JOINT)



SECTION B-B
(MINIMUM EXISTING JOINT DEMOLITION)



SECTION B-B
(PROPOSED JOINT PRE-SAWED DIMENSIONS)



SECTION B-B
(PROPOSED FOAM JOINT SEAL EXPANSION)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 277
 SHEET 2 OF 8

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


TYPICAL SECTION & JOINT DETAILS

REVISIONS				SHEET NO.
NO.	BY	DATE	NO.	DATE
1			3	
2			4	


TOTAL SHEETS: 63



DRAWN BY: C. BRIGHT DATE: 10/2012
 CHECKED BY: F. ASEFNIA DATE: 10/2012



END BENT 1
SPAN A FACE



END BENT 2 *
SPAN D FACE

* NO DAMAGE OBSERVED ON BENT 2, HOWEVER IF SOME DAMAGE IS FOUND BY THE ENGINEER, SEE NOTE ON THIS SHEET CONCERNING ADDITIONAL REPAIRS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-46.

REPAIR QUANTITY TABLE				
REPAIRS END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP (VERTICAL, FACE)		24		
PILE CAP		0		

REPAIR QUANTITY TABLE				
REPAIRS END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP (VERTICAL, FACE)		0		
PILE CAP		0		

VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 277
 SHEET 3 OF 8


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

END BENTS




REVISIONS						SHEET NO. S-42
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			

DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



END VIEW

SPAN 'B' FACE



END VIEW

SPAN 'A' FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	1.8	1.0		
CAP (HORIZONTAL, CORNER)	9.0	5.5		
COLUMN (VERTICAL FACE)	2.0	1.0		
COLUMN (HORIZONTAL, CORNER)	0	0		
CONCRETE REPAIRS	91.0	91.5		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP		0		
COLUMN		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP		134		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-46.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 1.

ESTIMATED REPAIR AREA


PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 277
 SHEET 4 OF 8

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 1




REVISIONS						SHEET NO. S-43	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				



END VIEW

SPAN 'C' FACE



END VIEW

SPAN 'B' FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	1.6	0.5		
CAP (HORIZONTAL, CORNER)	0.1	0.5		
COLUMN (VERTICAL FACE)	0	0		
COLUMN (HORIZONTAL, CORNER)	0	0		
CONCRETE REPAIRS	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0		
COLUMN		0		
EPOXY COATING		SQ. FT.		SQ. FT.
TOP OF CAP		186		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-46.


EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 2.

ESTIMATED REPAIR AREA


PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 277
 SHEET 5 OF 8

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 2




REVISIONS						SHEET NO. S-44	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				



END VIEW

SPAN 'D' FACE



END VIEW

SPAN 'C' FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0	0		
CAP (HORIZONTAL, CORNER)	4.5	3.0		
COLUMN (VERTICAL FACE)	3.4	2.0		
COLUMN (HORIZONTAL, CORNER)	0	0		
CONCRETE REPAIRS	14.3	9.0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP		4		
COLUMN		11		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP		186		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-46.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 3.

ESTIMATED REPAIR AREA

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 277
 SHEET 6 OF 8


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 3




REVISIONS						SHEET NO. S-45
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			


DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



BENT CAP & COLUMN REPAIR DETAIL




SECTION L-L




SECTION M-M


* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1\"/>




OVERHANG REPAIR DETAIL



END BENT CAP REPAIR DETAIL




SECTION K-K



SECTION J-J

* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1\"/>

 DAMAGED AREA

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 277
 SHEET 7 OF 8


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
**CAP & COLUMN
 REPAIR DETAILS**

REVISIONS					
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		

SHEET NO.
S-46
 TOTAL SHEETS
63




DRAWN BY: C BRIGHT DATE: 02/12
 CHECKED BY: F. ASEFNIA DATE: 10/12




- DECK SCARIFICATION AND HYDRODEMOLITION
- INCIDENTAL MILLING

PLAN

C1 PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.



TYPICAL ROADWAY SECTION




TYPICAL ROADWAY MILLING SECTION
(MILL TO 2" DEPTH)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 277
 SHEET 8 OF 8

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
ROADWAY TYPICAL SECTION AND MILLING DETAILS


REVISIONS						SHEET NO. S-47
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			



NOT TO SCALE

DRAWN BY: J. YANNACONE DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12


28-MAR-2013 13:36
 S:\PMS\POC\Squad C\Preservation\Projects\17BP.7.P.4\DCN Files\277_SD_PL_TS_BT.dgn
 jayannacone




PLAN OF SPANS

NOTES


- EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK.
- EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.
- INCIDENTAL MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE.
- THE CONTRACTOR SHALL PROVIDE A METHOD OF HANDLING UNEXPECTED BLOW THROUGH OF THE DECK, SEE "TYPICAL 'BLOW THRU' CONTAINMENT AND FORMWORK" DETAIL.
- THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS, SEE MANAGING HYDRO-DEMOLITION WATER SPECIAL PROVISION.
- FOR OVERLAY SURFACE PREPARATION, SEE SPECIAL PROVISIONS.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR SCARIFYING BRIDGE DECK, SEE SPECIAL PROVISIONS.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.
- FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLAN SHEETS.
- LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.
- DURING CONSTRUCTION, BERMS OR APPROPRIATE MEASURES SHALL BE USED TO ENSURE HYDRO-DEMOLITION WATER DOES NOT FLOW OR MIGRATE INTO ACTIVE TRAVEL LANES.




DETAIL FOR LATEX MODIFIED CONCRETE OVERLAY



PLAN



ELEVATION



TYP. "BLOW THRU" CONTAINMENT AND FORMWORK

A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.

SUBMIT DETAILS OF PROPOSED FORM WORK FOR APPROVAL PRIOR TO BEGINNING WORK.

COST FOR INSTALLING AND REMOVING FORM WORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 278
 SHEET 1 OF 7


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 PLAN VIEW OF BRIDGE
 #278, ON US 421 OVER
 BIG ALAMANCE CREEK
 40' CL. ROADWAY

REVISIONS					
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		

SHEET NO. S-48
TOTAL SHEETS 63



DRAWN BY: C BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12




NOTES


- FOR FOAM JOINT SEAL, SEE SPECIAL PROVISIONS.
- THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.
- NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2" AT BENTS.
- THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINT FOR THE FOAM JOINT SEAL IN LIEU OF SAWING THE JOINT.
- BACKER ROD WIDTH SHALL BE FIELD DETERMINED BY THE ENGINEER AFTER THE JOINT HAS BEEN CLEANED.

ELASTOMERIC CONCRETE	
BENTS	20.8 (CU. FT.)
* TOTAL	20.8 (CU. FT.)


* BASED ON THE MINIMUM BLOCKOUT SHOWN.




SECTION A-A
(EXISTING JOINT)



SECTION A-A
(PROPOSED JOINT)




PLAN




SECTION D-D


* ALL LOOSE AND UNSOUND CONCRETE SHALL BE REMOVED. IF THE EMBEDDED PORTION OF THE EXISTING WATERSTOP IS EXPOSED DURING REMOVAL, THE ENTIRE WATERSTOP SHALL BE REMOVED.




SECTION B-B
(EXISTING JOINT)



SECTION B-B
(MINIMUM EXISTING JOINT DEMOLITION)



SECTION B-B
(PROPOSED JOINT PRE-SAWED DIMENSIONS)



SECTION B-B
(PROPOSED FOAM JOINT SEAL EXPANSION)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 278
 SHEET 2 OF 7

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

TYPICAL SECTION & JOINT DETAILS


REVISIONS				SHEET NO.	
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		

SHEET NO. S-49
 TOTAL SHEETS 63




DRAWN BY: C. BRIGHT DATE: 10/2012
 CHECKED BY: F. ASEFNIA DATE: 10/2012

NOTE: RETAIN ALL EXISTING REINFORCING STEEL. CLEAN AND REPAIR AS REQ'D.



END BENT 2
SPAN C SIDE

 ESTIMATED REPAIR AREA



END BENT 1
SPAN A SIDE

REPAIR QUANTITY TABLE				
REPAIRS END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL)	5.0	2.5		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP (VERTICAL, FACE)		0		
PILE CAP		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP AND PILE CAPS		111		

REPAIR QUANTITY TABLE				
REPAIRS END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP (VERTICAL, FACE)		0		
PILE CAP		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP AND PILE CAPS		0		

VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-53.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AND PILE CAPS AT END BENT 1.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 278
 SHEET 3 OF 7


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

END BENTS




REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-50
1			3			TOTAL SHEETS
2			4			63

DRAWN BY : C. BRIGHT DATE : 10/2012
 CHECKED BY : F. ASEFNIA DATE : 10/2012



SPAN 'B' FACE



SPAN 'A' FACE

REPAIRS END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL)	5.8	2.5		
CAP (HORIZONTAL, CORNER)	0.8	0.5		
PILE CAP	0	0		
CONCRETE REPAIRS	3.3	2.0		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP (VERTICAL, FACE)		3		
PILE CAP		0		
EPOXY COATING		SQ. FT.		SQ. FT.
TOP OF CAP AND PILE CAPS		184		

VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-53.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 1.

ESTIMATED REPAIR AREA

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 278
 SHEET 4 OF 7

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 1

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-51
1			3			TOTAL SHEETS
2			4			63



DRAWN BY : C. BRIGHT DATE : 10/2012
 CHECKED BY : F. ASEFNIA DATE : 10/2012


REPAIR QUANTITY TABLE				
REPAIRS END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL)	0	0		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP (VERTICAL, FACE)		0		
PILE CAP		0		

VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.


NOTE:
REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-53.

 ESTIMATED REPAIR AREA



SPAN 'B' FACE *



SPAN 'C' FACE *


* NO DAMAGE OBSERVED ON BENT 2. HOWEVER IF DAMAGE IS FOUND BY THE ENGINEER, SEE NOTE ON THIS SHEET CONCERNING ADDITIONAL REPAIRS.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 278
 SHEET 5 OF 7


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 2

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-52
1			3			TOTAL SHEETS 63
2			4			




DRAWN BY : C. BRIGHT DATE : 10/2012
 CHECKED BY : F. ASEFNIA DATE : 10/2012




BENT CAP & COLUMN REPAIR DETAIL


* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1" MIN.)




SECTION L-L



SECTION M-M




OVERHANG REPAIR DETAIL




END BENT CAP REPAIR DETAIL

* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1" MIN.)



SECTION K-K



SECTION J-J

DAMAGED AREA

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 278
 SHEET 6 OF 7

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

CAP & COLUMN REPAIR DETAILS






REVISIONS					SHEET NO. S-53
NO.	BY	DATE	NO.	BY	
1			3		TOTAL SHEETS 63
2			4		

DRAWN BY: C. BRIGHT DATE: 10/2012
 CHECKED BY: F. ASEFNIA DATE: 10/2012

← TO JULIAN


TO GREENSBORO →




-  DECK SCARIFICATION AND HYDRODEMOLITION
-  INCIDENTAL MILLING

PLAN

C1 PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.



TYPICAL ROADWAY SECTION



TYPICAL ROADWAY MILLING SECTION
(MILL TO 2" DEPTH)

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 278
 SHEET 7 OF 7

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 ROADWAY TYPICAL
 SECTION AND
 MILLING DETAILS


REVISIONS						SHEET NO. S-54
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			



NOT TO SCALE


DRAWN BY: J. YANNAKONE DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12

23-MAR-2013 13:36
 S:\PRS\POC\Squad C\Preservation\Projects\17BP.7.P.4\DDN Files\278-SD.PL-TS.BT.dgn
 jayannakone




APPROX. AREA: CLASS II REPAIR
 BRIDGE JOINT DEMOLITION

PLAN



ELEVATION




TYP. "BLOW THRU" CONTAINMENT AND FORMWORK

A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.

SUBMIT DETAILS OF PROPOSED FORM WORK FOR APPROVAL PRIOR TO BEGINNING WORK.

COST FOR INSTALLING AND REMOVING FORM WORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.



DETAIL FOR LATEX MODIFIED CONCRETE OVERLAY

NOTES

EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK.

EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER.

INCIDENTAL MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE.

THE CONTRACTOR SHALL PROVIDE A METHOD OF HANDLING UNEXPECTED BLOW THROUGH OF THE DECK, SEE "TYPICAL 'BLOW THRU' CONTAINMENT AND FORMWORK" DETAIL.

THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS, SEE MANAGING HYDRO-DEMOLITION WATER SPECIAL PROVISION.

FOR OVERLAY SURFACE PREPARATION, SEE SPECIAL PROVISIONS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR SCARIFYING BRIDGE DECK, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.

FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLAN SHEETS.

LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG THE CENTERLINE OR EDGE OF TRAVEL LANES.

DURING CONSTRUCTION, BERMS OR APPROPRIATE MEASURES SHALL BE USED TO ENSURE HYDRO-DEMOLITION WATER DOES NOT FLOW OR MIGRATE INTO ACTIVE TRAVEL LANES.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 1 OF 9



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 PLAN VIEW OF BRIDGE
 #334, ON BESSEMER AVE.
 OVER NC 29
 48' CL. ROADWAY 97°-21" SKEW

REVISIONS					
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		

SHEET NO. S-55
 TOTAL SHEETS 63



DRAWN BY: C.L.B./ S.T.S. DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12




NOTES


FOR FOAM JOINT SEAL, SEE SPECIAL PROVISIONS.
 THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.
 NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2" AT BENTS.
 THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINT FOR THE FOAM JOINT SEAL IN LIEU OF SAWING THE JOINT.

ELASTOMERIC CONCRETE	
BENTS	25.0 (CU. FT.)
* TOTAL	25.0 (CU. FT.)


* BASED ON THE MINIMUM BLOCKOUT SHOWN.




SECTION A-A
(EXISTING JOINT)




SECTION A-A
(PROPOSED JOINT)




PLAN




SECTION B-B
(EXISTING JOINT)




SECTION B-B
(MINIMUM EXISTING JOINT DEMOLITION)



SECTION B-B
(PROPOSED JOINT PRE-SAWED)



SECTION B-B
(PROPOSED EVAZOTE JOINT SEAL EXPANSION)



SECTION D-D




PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 2 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
TYPICAL SECTION & JOINT DETAILS


REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			63
2			4			

DRAWN BY: C.L.B / S.T.S. DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12

NOTE: RETAIN ALL EXISTING REINFORCING STEEL. CLEAN AND REPAIR AS REQ'D.



END BENT 1
SPAN A VIEW



END BENT 2
SPAN D VIEW

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-61.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AND PILE CAPS AT END BENT 1.


REPAIR QUANTITY TABLE				
REPAIRS END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	18	8.0		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP (VERTICAL, FACE)		0		
PILE CAP		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP AND PILE CAPS		175		

REPAIR QUANTITY TABLE				
REPAIRS END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	29	13.0		
CAP (HORIZONTAL, CORNER)	0	0		
PILE CAP	0	0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP (VERTICAL, FACE)		0		
PILE CAP		0		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP AND PILE CAPS		175		

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 3 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


END BENTS



REVISIONS						SHEET NO. S-57
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			


VALUES IN CHARTS REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

DRAWN BY: C.L.B. / S.T.S. DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12



END VIEW

SPAN 'B' FACE



END VIEW

SPAN 'A' FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	32.2	14.5		
CAP (HORIZONTAL, CORNER)	140.1	88.0		
COLUMN (VERTICAL FACE)	10.0	6.0		
COLUMN (HORIZONTAL, CORNER)	9	6.5		
EPOXY RESIN INJECTION		LN. FT.		LN. FT.
CAP		0		
COLUMN		7		
EPOXY COATING		SO. FT.		SO. FT.
TOP OF CAP AND PILE CAPS		135		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.


FOR STRUCTURE REPAIRS, SEE SHEET S-61.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 1.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 4 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 1




REVISIONS						SHEET NO. S-58	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				

DRAWN BY: C.L.B/ S.T.S. DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12



END VIEW

SPAN 'C' FACE



END VIEW

SPAN 'B' FACE

REPAIRS BENT 2		QUANTITIES			
		ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF	
CAP (VERTICAL FACE)	24.6	11.0			
CAP (HORIZONTAL, CORNER)	130.0	82.0			
COLUMN (VERTICAL FACE)	10.3	6.5			
COLUMN (HORIZONTAL, CORNER)	56.1	40.5			
EPOXY RESIN INJECTION		LN. FT.		LN. FT.	
CAP		0			
COLUMN		3			
EPOXY COATING		SQ. FT.		SQ. FT.	
TOP OF CAP AND PILE CAPS		135			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT, SEE REPAIR DETAILS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-61.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 2.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 5 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 2




REVISIONS						SHEET NO. S-59
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			

DRAWN BY: C.L.B/ S.T.S. DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12



END VIEW

SPAN 'C' FACE



END VIEW

SPAN 'D' FACE

REPAIR QUANTITY TABLE				
REPAIRS BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	13.0	6.0		
CAP (HORIZONTAL, CORNER)	109.0	69.0		
COLUMN (VERTICAL FACE)	0	0		
COLUMN (HORIZONTAL, CORNER)	36.0	26.0		
EPOXY RESIN INJECTION			LN. FT.	LN. FT.
CAP		0		
COLUMN		6		
EPOXY COATING			SO. FT.	SO. FT.
TOP OF CAP AND PILE CAPS		135		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 1" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTE:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

FOR STRUCTURE REPAIRS, SEE SHEET S-61.

EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP AT BENT 3.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 6 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT 3




REVISIONS						SHEET NO. S-60
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			


DRAWN BY: C.L.B./ S.T.S. DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12



BENT CAP & COLUMN REPAIR DETAIL




SECTION L-L




SECTION M-M


* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1" MIN.)




OVERHANG REPAIR DETAIL



END BENT CAP REPAIR DETAIL



SECTION K-K



SECTION J-J

* CONCRETE SHALL BE REMOVED UNTIL SOUND CONCRETE IS FOUND. (1" MIN.)






PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 7 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
**CAP & COLUMN
 REPAIR DETAILS**


REVISIONS						SHEET NO. S-61
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 63
2			4			

DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12




 DECK SCARIFICATION AND HYDRO-DEMOLITION
 INCIDENTAL MILLING

PLAN



TYPICAL ROADWAY SECTION

C1 PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF 9.5A AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.



TYPICAL ROADWAY MILLING SECTION
(MILL TO 2" DEPTH)

NOT TO SCALE




PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 8 OF 9


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 ROADWAY TYPICAL
 SECTION AND
 MILLING DETAILS

REVISIONS						HEET NO.
NO.	BY	DATE	NO.	BY	DATE	S-62
1			3			TOTAL SHEETS
2			4			63

DRAWN BY: C. BRIGHT DATE: 10/12
 CHECKED BY: F. ASEFNIA DATE: 10/12



PLAN VIEW
(UNDERSIDE)



SECTION A-A


REPAIRS SPANS A THRU D	QUANTITIES			
	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
SHOTCRETE REPAIRS				
DIAPHRAGMS	—	5.0		
GIRDERS	0	0		
UNDERSIDE OF DECK & OVERHANGS	2.68	0.39		
EPOXY RESIN INJECTION		LN. FT		LN. FT
DIAPHRAGMS		0		
GIRDERS		0		
UNDERSIDE OF DECK & OVERHANGS		0		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF LOOSE CONCRETE, MIN. OF 1" BEHIND REBAR. SEE REPAIR DETAILS.

PROJECT NO. 17BP.7.P.4
 COUNTY: GUILFORD
 DECK REPAIR BRIDGE NO. 334
 SHEET 9 OF 9

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

BENT DIAPHRAGM
 REPAIRS



REVISIONS						SHEET NO. S-63	TOTAL SHEETS 63
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				


DRAWN BY: C.L.B./M.J.W. DATE: 11/12
 CHECKED BY: F. ASEFNIA DATE: 11/12

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

TRANSPORTATION MANAGEMENT PLAN

GUILFORD COUNTY

DIVISION 7



DECK PRESERVATION

BRIDGE #12 – SR 1970 (E. KIVETT DR.) OVER RAILROAD

BRIDGE #15 – US 220 OVER I-85 BUS/US 70/US 29

BRIDGE #36 – NC 150 (OAK RIDGE RD.) OVER RAILROAD

BRIDGE #57 – SR 1398 (FREEMAN MILL RD.) OVER NC 6

BRIDGE #169 – SR 1129 (GROOMETOWN RD.) OVER I-85

BRIDGE #277 – US 421 SOUTHBOUND OVER BIG ALAMANCE CREEK

BRIDGE #278 – US 421 NORTHBOUND OVER BIG ALAMANCE CREEK

BRIDGE #334 – E. BESSEMER AVENUE OVER US 29


INDEX OF SHEETS

SHEET NO.	TITLE
TMP-1	TITLE SHEET AND INDEX OF SHEETS
TMP-1A	LEGEND AND LIST OF ROADWAY STANDARD DRAWINGS
TMP-2	GENERAL NOTES
TMP-3	VICINITY MAPS & PHASING
TMP-4	GUILFORD #12 - E. KIVETT DR. EASTBOUND RIGHT LANE WORK AREA
TMP-5	GUILFORD #12 - E. KIVETT DR. EASTBOUND LEFT LANE WORK AREA
TMP 6-6A	GUILFORD #15 - US 220 NORTHBOUND RIGHT LANE WORK AREA
TMP-6B	GUILFORD #15 - EXIT 35B DETOUR ROUTE
TMP 7-7A	GUILFORD #15 - US 220 NORTHBOUND LEFT LANE WORK AREA
TMP 8-8A	GUILFORD #15 - US 220 SOUTHBOUND RIGHT LANE WORK AREA
TMP-8B	GUILFORD #15 - EXIT 35A DETOUR ROUTE
TMP-9	GUILFORD #15 - US 220 SOUTHBOUND LEFT LANE WORK AREA
TMP 10-10A	GUILFORD #57 - SR 1398 NORTHBOUND RIGHT LANE WORK AREA
TMP 11-11A	GUILFORD #57 - SR 1398 SOUTHBOUND RIGHT LANE WORK AREA
TMP 12-12A	GUILFORD #57 - SR 1398 LEFT LANE WORK AREA
TMP-13	GUILFORD #169 - SR 1129 NORTHBOUND RIGHT LANE WORK AREA
TMP-14	GUILFORD #169 - SR 1129 SOUTHBOUND RIGHT LANE WORK AREA
TMP-15	GUILFORD #169 - SR 1129 LEFT LANE WORK AREA
TMP-16	GUILFORD #334 - BESSEMER AVE. EASTBOUND RIGHT LANE WORK AREA
TMP-17	GUILFORD #334 - BESSEMER AVE. WESTBOUND RIGHT LANE WORK AREA
TMP-18	GUILFORD #334 - BESSEMER AVE. LEFT LANE WORK AREA


TRAFFIC MANAGEMENT STRATEGY

PROPOSED BRIDGE WORK WILL BE PERFORMED USING A COMBINATION OF DAY AND TIME RESTRICTED LANE CLOSURES. REFER TO SHEET TMP-3 FOR PHASING.

I:\20\2012\TrafficControl\WBS 17BP.7.P.4 Guilford\TOP\Plan Sheets\17BP.7.P.4.TC.TMP-DI.TITLE.dgn



PLAN PREPARED FOR NCDOT STRUCTURES MANAGEMENT UNIT
RALEIGH, NC



PLAN PREPARED BY:
Stantec Consulting Services Inc.
801 Jones Franklin Road-Suite 300
Raleigh, NC 27606
Tel. 919.851.6966
Fax. 919.851.7024
www.stantec.com

BETSY L. WATSON, P.E.

TRAFFIC ENGINEER

GEORGE KARAGEORGE

SR. TRANSPORTATION DESIGNER

APPROVED *Betsy L. Watson*
DATE: 11/28/12



SEAL



WBS 17BP.7.P.4

SHEET NO.
TMP-1


LEGEND




SIGNALS




PAVEMENT MARKINGS



PAVEMENT MARKING SYMBOLS



PAVEMENT MARKERS



ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:



STD. NO.	TITLE
1101.01	WORK ZONE ADVANCE WARNING SIGNS
1101.02	TEMPORARY LANE CLOSURES
1101.04	TEMPORARY SHOULDER CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1110.02	PORTABLE WORK ZONE SIGNS
1115.01	FLASHING ARROW BOARDS
1130.01	DRUMS
1135.01	CONES
1145.01	BARRICADES
1150.01	FLAGGING DEVICES
1165.01	WORK VEHICLE LIGHTING SYSTEMS AND TMA DELINEATION
1205.01	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS
1205.02	PAVEMENT MARKINGS - TWO LANE AND MULTILANE ROADWAYS
1250.01	RAISED PAVEMENT MARKERS - INSTALLATION SPACING
1251.01	RAISED PAVEMENT MARKERS - (PERMANENT AND TEMPORARY)

I:\2012\LAN TrafficControl\WBS 17BP.7.P.4 Guilford\TCF\Plan Sheets\17BP.7.P.4.TC.TMP.01A.RDHYSTDSLEGEND.dgn



Stantec Consulting Services Inc.
 801 Jones Franklin Road
 Suite 300
 Raleigh, NC 27606
 Tel: (919) 851-6868
 Fax: (919) 851-7024
 www.stantec.com
 License No. F-0672

APPROVED: _____ DATE: _____



**LEGEND
&
ROADWAY STANDARD DRAWINGS**

GENERAL NOTES

PROJ. REFERENCE NO.	SHEET NO.
WBS 17BP.7.P.4	TMP-2

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE PROJECT EXCEPT WHEN OTHERWISE NOTED IN THE PLAN OR DIRECTED BY THE ENGINEER.

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRED OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING, OR REMOVAL OF DEVICES AS DIRECTED BY THE ENGINEER.

LANE CLOSURE TIME RESTRICTIONS

A) DO NOT CLOSE OR NARROW TRAVEL LANES AS FOLLOWS:

ROAD NAME/BRIDGE #	DAY AND TIME RESTRICTIONS
US220/#15, SR 1970 E. KIVETT DR/#12, SR 1398 FREEMAN MILL RD/#57, SR 1129 GROOMETOWN RD/#169, E. BESSEMER AVE/#334, US 29/#334	6:00 A.M. - 7:00 P.M. MONDAY-SUNDAY
US 421/#277,#278 NC 150 OAK RIDGE RD/#36	6:00 A.M. - 9:00 A.M. MONDAY-FRIDAY AND 4:00 P.M. - 7:00 P.M. MONDAY-FRIDAY

B) DO NOT CLOSE OR NARROW A LANE OF TRAFFIC, DETAIN AND/OR ALTER THE TRAFFIC FLOW ON OR DURING HOLIDAYS, HOLIDAY WEEKENDS, OR ANY OTHER TIME WHEN TRAFFIC IS UNUSUALLY HEAVY, INCLUDING THE FOLLOWING SCHEDULES:

ROAD NAME
ALL ROADS

HOLIDAY & HOLIDAY WEEKEND LANE CLOSURE TIME RESTRICTIONS

- 1) FOR ANY UNEXPECTED OCCURRENCE THAT CREATES UNUSUALLY HIGH TRAFFIC VOLUMES, AS DIRECTED BY THE ENGINEER.
 - 2) FOR NEW YEAR'S, BETWEEN THE HOURS OF 6:00 A.M. DECEMBER 31ST TO 7:00 P.M. JANUARY 2ND. IF NEW YEAR'S DAY IS ON A FRIDAY, SATURDAY, SUNDAY, OR MONDAY THEN UNTIL 7:00 P.M. THE FOLLOWING TUESDAY.
 - 3) FOR EASTER, BETWEEN THE HOURS OF 6:00 A.M. THURSDAY AND 7:00 P.M. MONDAY.
 - 4) FOR MEMORIAL DAY, BETWEEN THE HOURS OF 6:00 A.M. FRIDAY TO 7:00 P.M. TUESDAY.
 - 5) FOR INDEPENDENCE DAY, BETWEEN THE HOURS OF 6:00 A.M. THE DAY BEFORE INDEPENDENCE DAY AND 7:00 P.M. THE DAY AFTER INDEPENDENCE DAY. IF INDEPENDENCE DAY IS ON A FRIDAY, SATURDAY, SUNDAY OR MONDAY; THEN BETWEEN THE HOURS OF 6:00 A.M. THE THURSDAY BEFORE INDEPENDENCE DAY AND 7:00 P.M. THE TUESDAY AFTER INDEPENDENCE DAY.
 - 6) FOR LABOR DAY, BETWEEN THE HOURS OF 6:00 A.M. FRIDAY AND 7:00 P.M. TUESDAY.
 - 7) FOR THANKSGIVING DAY, BETWEEN THE HOURS OF 6:00 A.M. TUESDAY TO 7:00 P.M. MONDAY.
 - 8) FOR CHRISTMAS, BETWEEN THE HOURS OF 6:00 A.M. THE FRIDAY BEFORE THE WEEK OF CHRISTMAS DAY AND 7:00 P.M. THE FOLLOWING TUESDAY AFTER THE WEEK OF CHRISTMAS.
- C) ROAD CLOSURES ARE NOT PERMITTED AT ANY TIME, EXCEPT WHEN SPECIFIED IN THE PLAN OR ALLOWED BY THE ENGINEER.

AT BRIDGE #15 THE RAMPS AT EXITS 35A AND 35B FROM I-85 BUSINESS TO US 220 WILL BE PERMITTED TO BE CLOSED AS SHOWN ON SHEETS TMP-6B AND TMP-8B.

DO NOT CLOSE RAMPS AT EXITS 35A AND 35B AS FOLLOWS:

DAY AND TIME RESTRICTIONS
6:00 A.M. - 7:00 P.M. MONDAY-SUNDAY

D) DO NOT STOP TRAFFIC AS FOLLOWS:

ROAD NAME	DAY AND TIME RESTRICTIONS	DURATION AND OPERATION
ALL ROADS	6:00 A.M. - 7:00 P.M. MONDAY-SUNDAY	15 MIN. DURING HYDRO-DEMOLITION

LANE AND SHOULDER CLOSURE REQUIREMENTS

- E) LANE CLOSURES ARE REQUIRED WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN ANY PORTION OF A TRAVEL LANE. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL LANE.
- F) INSTALL ALL LANE CLOSURES ACCORDING TO THE PLANS, ROADWAY STANDARD DRAWINGS (1101.02), OR AS DIRECTED BY THE ENGINEER.
- G) REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED OR AS DIRECTED BY THE ENGINEER. COVER OR LAY DOWN SIGNS, AND TURN OFF ARROW BOARDS AND MESSAGE BOARDS.
- H) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.
- I) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.
- J) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO A DIVIDED FACILITY AND WITHIN 10 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

ROAD CLOSURES

- K) NOTIFY THE ENGINEER TWENTY ONE (21) CALENDAR DAYS PRIOR TO ANY ROAD CLOSURE.
- L) FURNISH AND INSTALL SIGNING AND DEVICES FOR ROAD CLOSURES ACCORDING TO THE TRAFFIC MANAGEMENT PLAN. COVER OR REMOVE ALL SIGNS AND DEVICES FOR ROAD CLOSURES WHEN NOT IN EFFECT.
- M) FURNISH AND INSTALL OFFSITE-DETOUR ROUTE SIGNING AS SHOWN IN THE TRAFFIC MANAGEMENT PLAN. COVER OR REMOVE OFFSITE-DETOUR SIGNING WHEN THE DETOUR IS NOT IN OPERATION. ALL DETOUR ROUTES MUST BE APPROVED BY THE ENGINEER PRIOR TO IMPLEMENTING.
- N) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.
- O) WHEN CLOSING A ROADWAY OR DRIVEWAY PLACE TYPE III BARRICADES COMPLETELY ACROSS THE ROADWAY OR FROM CURB TO CURB. ATTACH BARRICADE MOUNTED "ROAD CLOSED" SIGN R11-2 AT ALL CLOSURE LOCATIONS. IF LOCAL TRAFFIC IS TO BE MAINTAINED STAGGER THE BARRICADES TO ALLOW ACCESS.
- P) INSTALL SIGNS BEFORE BARRICADES WHEN CLOSING A ROADWAY TO TRAFFIC. REMOVE BARRICADES BEFORE SIGNS WHEN OPENING A ROADWAY TO TRAFFIC. INSTALL/REMOVE ROAD CLOSURE SIGNS AND BARRICADES IN A CONTINUOUS OPERATION AND WITHIN THE SAME CALENDAR DAY.

PAVEMENT MARKINGS AND MARKERS

Q) RECORD ALL LOCATIONS AND TYPES OF EXISTING PAVEMENT MARKINGS AS THEY WILL BE REPLACED IN THE SAME LOCATION ON THE NEW SURFACE.

R) UPON COMPLETION OF ALL OTHER CONSTRUCTION OPERATIONS INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE AS FOLLOWS:

ROAD NAME	MARKING	PAVEMENT MARKER
SR 1970	POLYUREA	NONE
US 220	POLYUREA	PERMANENT RAISED
NC 150	POLYUREA	PERMANENT RAISED
SR 1398	POLYUREA	PERMANENT RAISED
SR 1129	POLYUREA	NONE
US 421	POLYUREA	PERMANENT RAISED
BESSEMER AVE.	POLYUREA	NONE

S) FOR PAVEMENT MARKING SYMBOLS, ALPHANUMERIC CHARACTERS, DIAGONAL LINES AND STOP BARS USE THE FOLLOWING TYPE OF MARKING:

ON ASPHALT PAVEMENTS

1. THERMOPLASTIC HEATED IN PLACE, OR
2. THERMOPLASTIC EXTRUDED.
3. COLD APPLIED PLASTIC (TYPE 2) OR 3 OPTIONAL

ON CONCRETE PAVEMENTS

1. COLD APPLIED PLASTIC (TYPE 2) OR 3 OPTIONAL
2. THERMOPLASTIC HEATED IN PLACE (OPTIONAL)

T) DO NOT USE POLYUREA MARKING ON TYPE S9.5A SURFACE COURSE.




U) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.

V) REPLACE ANY PAVEMENT MARKINGS ERADICATED OR DAMAGED BY CONSTRUCTION OPERATIONS BEFORE OPENING LANES TO TRAFFIC.

MISCELLANEOUS


- W) USE LAW ENFORCEMENT TO MAINTAIN TRAFFIC THROUGH THE WORK AREA AND/OR INTERSECTIONS AS SHOWN IN THE PLANS OR AS DIRECTED BY THE ENGINEER. LOCATIONS SHOWN IN THE PLANS ARE APPROXIMATE AND MAY BE REVISED AS THE OFFICER OR THE ENGINEER DEEM NECESSARY.
- X) ALL DIMENSIONS AND STATIONS IN THE TRANSPORTATION MANAGEMENT PLAN AND PHASING ARE APPROXIMATE (+/-); FIELD ADJUST AS NECESSARY OR AS DIRECTED BY THE ENGINEER.
- Y) ENSURE THE OVERSIZE/OVERWEIGHT PERMIT UNIT (919) 733-4740 HAS BEEN ADVISED OF THE ONGOING TRAFFIC OPERATIONS THROUGH THE DIVISION OFFICE.
- Z) CHANGEABLE MESSAGE SIGN MESSAGES SHOWN ARE EXAMPLES. OTHER MESSAGES MAY BE USED AS CONDITIONS WARRANT. ALL MESSAGES AND LOCATIONS MUST BE APPROVED BY THE ENGINEER PRIOR TO INCORPORATING.
- AA) IN THE EVENT OF FALLING DEBRIS OR WATER USE LAW ENFORCEMENT TO DIRECT TRAFFIC BELOW THE BRIDGE.

I:\2020\TrafficControl\WBS 17BP.7.P.4\TrafficControl\Sheet\N7BP.7.P.4.TC.TMP.02.GENERALNOTES.dgn

 Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-8866 Fax. (919) 851-7024 www.stantec.com License No. F-0872	APPROVED: _____ DATE: _____ 		<h2 style="margin: 0;">GENERAL NOTES</h2>
---	--	---	---

PHASING

PROJ. REFERENCE NO.	SHEET NO.
WBS 17BP.7.P.4	TMP-3



GUILFORD CO. VICINITY MAPS

FOR BRIDGE #12 #36, #57, #277, #292, #334 PERFORM PAINTING OPERATIONS AFTER COMPLETION OF REHAB OPERATIONS. REFER TO PLANS FOR BRIDGE PAINTING PROJECT 17BP.7.P.1.

BRIDGE #12 - SR 1970 (E. KIVETT DR.) OVER RAILROAD
FOR CONSTRUCTION OF SR 1970 EASTBOUND, USE LEFT AND RIGHT LANE CLOSURES PER SHEETS TMP-4 AND TMP-5.

FOR CONSTRUCTION OF SR 1970 WESTBOUND, USE LEFT AND RIGHT LANE CLOSURES PER ROADWAY STANDARD DRAWING 1101.02 SHEET 3.

BRIDGE #15 - US 220 OVER I-85 BUSINESS/US 29/US 70
FOR CONSTRUCTION OF US 220 NORTHBOUND RIGHT LANE & RAMP LANE, USE RIGHT LANE CLOSURE WITH CLOSURE OF EXIT 35B RAMP PER SHEETS TMP-6, 6A, 6B.

FOR CONSTRUCTION OF US 220 NORTHBOUND LEFT LANE, USE LEFT LANE CLOSURE WITH CLOSURE OF EXIT 35B RAMP PER SHEETS TMP-7, 7A, 6B.

FOR CONSTRUCTION OF US 220 SOUTHBOUND RIGHT LANE AND RAMP LANE, USE RIGHT LANE CLOSURE WITH CLOSURE OF EXIT 35A RAMP PER SHEETS TMP-8, 8A, 8B.

FOR CONSTRUCTION OF US 220 SOUTHBOUND LEFT LANE, USE LEFT LANE CLOSURE WITH CLOSURE OF EXIT 35A PER SHEETS TMP-9, 8B.

BRIDGE #36 - NC 150 (OAK RIDGE RD.) OVER RAILROAD
FOR CONSTRUCTION OF NC 150 EASTBOUND, USE FLAGGING OPERATION PER ROADWAY STANDARD DRAWING 1101.02 SHEET 1.

FOR CONSTRUCTION OF NC 150 WESTBOUND, USE FLAGGING OPERATION PER ROADWAY STANDARD DRAWING 1101.02 SHEET 1.

BRIDGE #57 - SR 1398 (FREEMAN MILL RD.) OVER NC 6 (W. LEE ST.)
FOR CONSTRUCTION OF SR 1398 NORTHBOUND RIGHT LANE & SHOULDER, USE 2-LANE/2-WAY TRAFFIC PATTERN PER SHEETS TMP-10 AND 10A.

FOR CONSTRUCTION OF SR 1398 SOUTHBOUND RIGHT LANE & SHOULDER, USE 2-LANE/2-WAY TRAFFIC PATTERN PER SHEETS TMP-11 AND 11A.

FOR CONSTRUCTION OF SR 1398 INTERIOR LANES, USE 2-LANE/2-WAY TRAFFIC PATTERN PER SHEETS TMP-12 AND 12A.

BRIDGE #169 - SR 1129 (GROOMETOWN RD.) OVER I-85/US 29/US 70
FOR CONSTRUCTION OF SR 1129 NORTHBOUND RIGHT LANE & SHOULDER, USE 2-LANE/2-WAY TRAFFIC PATTERN PER SHEET TMP-13.

FOR CONSTRUCTION OF SR 1129 SOUTHBOUND RIGHT LANE & SHOULDER, USE 2-LANE/2-WAY TRAFFIC PATTERN PER SHEET TMP-14.

FOR CONSTRUCTION OF SR 1129 LEFT LANES (INTERIOR WORK AREAS), USE SHEET TMP-15.

BRIDGE #277 - US 421 OVER BIG ALAMANCE CREEK
FOR CONSTRUCTION OF US 421 SOUTHBOUND, USE LEFT AND RIGHT LANE CLOSURES PER ROADWAY STANDARD DRAWING 1101.02 SHEET 3.

BRIDGE #278 - US 421 WESTBOUND OVER BIG ALAMANCE CREEK
FOR CONSTRUCTION OF US 421 NORTHBOUND, USE LEFT AND RIGHT LANE CLOSURES PER ROADWAY STANDARD DRAWING 1101.02 SHEET 3.

BRIDGE #334 - BESSEMER AVENUE OVER US 29/US 70/US 220
FOR CONSTRUCTION OF BESSEMER AVE. EASTBOUND RIGHT LANE, USE RIGHT LANE CLOSURE PER SHEET TMP-16.



FOR CONSTRUCTION OF BESSEMER AVE. WESTBOUND RIGHT LANE, USE RIGHT LANE CLOSURE PER SHEET TMP-17.

FOR CONSTRUCTION OF BESSEMER AVE. LEFT LANES, USE LEFT LANE CLOSURES PER SHEET TMP-18.



I:\2020\TrafficControl\WBS 17BP.7.P.4 Guilford\TC\Plan Sheets\17BP.7.P.4.TC.TMP.03.VICINITY MAP & PHASING.dgn



Stantec Consulting Services Inc.
601 Jones Franklin Road
Suite 300
Raleigh, NC 27606
Tel. (919) 851-6886
Fax. (919) 851-7024
www.stantec.com
License No. F-0672





**VICINITY MAPS
&
PHASING**






1/20/2012
 UN:\TrafficControl\WBS 17BP.7.P.4 Guilfo-d\TCP\plan Sheets\17BP.7.P.4.TC.TMP.04.BRIDGE.12.EB.RT.WORKAREA.dgn
 c:\u

<p>Stantec</p>	Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-8896 Fax. (919) 851-7024 www.stantec.com License No. F-0672	APPROVED: _____	DATE: _____	<p>DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK ZONE TRAFFIC CONTROL</p>	GUILFORD CO. BRIDGE #12 SR 1970 (E. KIVETT DR.) EASTBOUND RIGHT LANE WORK AREA
		SEAL 			



1/26/2012 10:10:00 AM C:\Users\jw\Documents\Projects\17BP.7.P.4\17BP.7.P.4.TC.TMP.05.BRIDGE.12_EB.L1.WORKAREA.dgn

<p>Stantec Consulting Services Inc. 801 James Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. P-0572</p>	APPROVED: _____	DATE: _____	<p>GUILFORD CO. BRIDGE #12</p> <p>SR 1970 (E. KIVETT DR.)</p> <p>EASTBOUND LEFT LANE</p> <p>WORK AREA</p>




11/20/2012
 US Traffic Control Plans
 Guilford
 17BP.7.P.4 GuilfordTrafficControlPlans\17BP.7.P.4.TC.TMP.06.BRIDGE.15.NB.RT.WORKAREA.dgn

 Stantec <small>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. P-0672</small>	APPROVED: _____ DATE: _____ 		GUILFORD CO. BRIDGE #15 US 220 NORTHBOUND RIGHT LANE WORK AREA




MESSAGE NO. 2
MESSAGE NO. 1
FOLLOW
EXIT 35C
CLOSED
EXIT 35B
MESSAGE NO. 35B
CHANGEABLE MESSAGE SIGN


SEE SHEET TMP-6B
FOR DETOUR

MATCHLINE - SEE PREVIOUS SHEET



11/25/2012
C:\Users\jacob\Documents\17BP.7.P.4_Guilford\TrafficControl\WBS 17BP.7.P.4_Guilford\TrafficControl\Plan Sheets\17BP.7.P.4_IC_TMP_06A_BRIDGE_US_NB_RT_WORKAREA.dgn



 Stantec	Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672	APPROVED: _____ DATE: _____  SEAL ROBERT L. WATSON PROFESSIONAL ENGINEER STATE OF NORTH CAROLINA License No. 12512	 DIVISION OF HIGHWAYS NORTH CAROLINA DEPARTMENT OF TRANSPORTATION TRAFFIC CONTROL	GUILFORD CO. BRIDGE #15 US 220 NORTHBOUND RIGHT LANE WORK AREA
---	--	---	--	---



- (A)** DETOUR NORTH 220 ↑ M4-8 24" X 12" M3-1 24" X 12" M1-4 M6-3 21" X 15"
- (B)** DETOUR NORTH 220 → M4-8 24" X 12" M3-1 24" X 12" M1-4 M6-1 21" X 15"
- (C)** DETOUR NORTH 220 ← M4-8 24" X 12" M3-1 24" X 12" M1-4 M6-1 L 21" X 15"
- (D)** DETOUR NORTH 220 ↗ M4-8 24" X 12" M3-1 24" X 12" M1-4 M6-2 21" X 15"
- (E)** DETOUR NORTH 220 ← M4-8 24" X 12" M3-1 24" X 12" M1-4 M5-1 21" X 15"
- (F)** DETOUR NORTH 220 ↗ M4-8 24" X 12" M3-1 24" X 12" M1-4 M5-2 R 21" X 15"


I:\2017\2017\TrafficControl\WBS 17BP.7.P.4 Guilford\TC\Plan Sheets\N7BP.7.P.4.TC.TMP_06B_BRIDGE_15_NB_RT_DETOUTR.dgn
 11/29/2017 10:51:03 AM

<p>Stantec Consulting Services Inc. 901 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6963 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 		GUILFORD CO. BRIDGE #15 EXIT 35B DETOUR ROUTE
	SEAL: _____		




I:\2012\2012\LEN Traffic\TrafficControl\WBS 17BP.7.P.4 Guilford\TCPlan Sheets\17BP.7.P.4.TC.TMP-07.BRIDGE.15.NE.L1.T.#ORKAREA.dgn
 11/20/2012 10:51:12 AM


<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-8566 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 		GUILFORD CO. BRIDGE #15 US 220 NORTHBOUND LEFT LANE WORK AREA
--	---------------------------------	--	--



SEE SHEET TMP-6B
FOR DETOUR




MATCHLINE - SEE PREVIOUS SHEET








I:\20\2002\US\TrafficControl\WBS 17BP.7.P.4 Guilford\TC\Plan Sheets\17BP.7.P.4.TC.TMP_07A_BRIDGE_US_NB.L1.WORKAREA.dgn
 Guilford

<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 		GUILFORD CO. BRIDGE #15 US 220 NORTHBOUND LEFT LANE WORK AREA




11/29/2012
 C:\Users\j\Documents\TrafficControl\WBS_17BP.7.P.4_Guilford\TIC\Plan_Sheets\17BP.7.P.4_TC_TMP_08_BRIDGE_15_SB_RT_WORKAREA.dgn
 17BP.7.P.4

 Stantec Stantec Consulting Services Inc. 601 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0572	APPROVED: _____ DATE: _____ 		GUILFORD CO. BRIDGE #15 US 220 SOUTHBOUND RIGHT LANE WORK AREA
	MESSAGE NO. 1: US 220 S CLOSED MESSAGE NO. 2: EXIT 35A DETOUR MESSAGE NO. 3: FOLLOW DETOUR MESSAGE NO. 4: EXIT 35B UNAVAILABLE MESSAGE SIGN		



I:\2017\202\202\TrafficControl\WBS 17BP.7.P.4 Guilford\TDP\Plan Sheets\17BP.7.P.4.TC_TMP_08A_BRIDGE_15_SB_RT_WORKAREA.dgn
 1/22/2017 10:51:11 AM
 User: jgallagher

<p>Stantec Consulting Services Inc. 601 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION TRAFFIC CONTROL</p>	GUILFORD CO. BRIDGE #15 US 220 SOUTHBOUND RIGHT LANE WORK AREA
	SEAL 		




- | | | |
|---|---|---|
| <p>(A) DETOUR M4-8 24" X 12"</p> <p>SOUTH M3-3 24" X 12"</p> <p>220 M1-4</p> <p>↑ M6-3 21" X 15"</p> | <p>(B) DETOUR M4-8 24" X 12"</p> <p>SOUTH M3-3 24" X 12"</p> <p>220 M1-4</p> <p>← M6-1 L 21" X 15"</p> | <p>(C) DETOUR M4-8 24" X 12"</p> <p>SOUTH M3-3 24" X 12"</p> <p>220 M1-4</p> <p>↗ M5-2 R 21" X 15"</p> |
| <p>(D) DETOUR M4-8 24" X 12"</p> <p>SOUTH M3-3 24" X 12"</p> <p>220 M1-4</p> <p>↗ M6-2 21" X 15"</p> | <p>(E) DETOUR M4-8 24" X 12"</p> <p>SOUTH M3-3 24" X 12"</p> <p>220 M1-4</p> <p>← M5-1 21" X 15"</p> | |


11/20/2012
 L:\TrgAffia\TrgAffia\Contractor\WBS 17BP.7.P.4 Guilford\TC\Plan Sheets\17BP.7.P.4.TC.TMP-08B.BRIDGE.15.SB.DETOUR.dgn
 Reulen

<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27608 Tel: (919) 851-6865 Fax: (919) 851-7024 www.stantec.com License No. F-0872</p>	APPROVED: _____ DATE: _____ 		GUILFORD CO. BRIDGE #15 EXIT 35A DETOUR ROUTE
	SEAL 		

SIGNING IN ADVANCE OF LEFT LANE CLOSURE




1/20/2012
 US Traffic Control WBS 17BP.7.P.4 Guilford\TC\Plan Sheets\17BP.7.P.4.TC.TMP.09.BRIDGE.US.SB.L1.WORKAREA.dgn
 caulien




Startec
 Startec Consulting Services Inc.
 801 Jones Franklin Road
 Suite 300
 Raleigh, NC 27606
 Tel. (919) 851-8866
 Fax. (919) 851-7024
 www.startec.com
 License No. F-0672


APPROVED: _____ DATE: _____
 SEAL
 NORTH CAROLINA PROFESSIONAL ENGINEER
 STATE OF NORTH CAROLINA
 1/28/12



GUILFORD CO. BRIDGE #15
US 220 SOUTHBOUND
LEFT LANE WORK AREA




SIGNING IN ADVANCE OF RIGHT LANE CLOSURE



11/20/2012 10:41:10 AM \\franklin\Projects\17BP.7.P.4_Guilford\TDCP\Plan_Sheets\17BP.7.P.4_TC_TMP_ID_BRIDGE_57_NB_RT_WORKAREA.dgn


<p>Stantec Consulting Services Inc. 801 Jonas Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	<p>APPROVED: _____ DATE: _____</p>	<p>DIVISION OF HIGHWAYS NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK AREA ZONE TRAFFIC CONTROL</p>	<p>GUILFORD CO. BRIDGE #57 SR 1398 (FREEMAN MILL RD.) NORTHBOUND RIGHT LANE WORK AREA</p>
	<p>SEAL</p>		




11/20/2012 10:17:00 AM C:\Users\jfranklin\Documents\17BP.7.P.4_Guilford\TC\Plan_Sheets\17BP.7.P.4_TC_TMP_10A_BRIDGE_57_NB_RT_WORKAREA.dgn

MATCHLINE - SEE PREVIOUS SHEET

<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel: (919) 851-6956 Fax: (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS DEPARTMENT OF TRANSPORTATION NORTH CAROLINA</p>	<p>GUILFORD CO. BRIDGE #57 SR 1398 (FREEMAN MILL RD.) NORTHBOUND RIGHT LANE WORK AREA</p>
	SEAL 		




SIGNING IN ADVANCE OF LEFT LANE CLOSURE






11/20/2012 10:28:11 AM C:\TrafficControl\WBS 17BP.7.P.4 Guilford\TCP\Plan Sheets\17BP.7.P.4_TC_TMP_ILBRIDGE.57_SS_RT_WORKAREA.dgn



<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0872</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION LONG RANGE TRAFFIC CONTROL</p>	<p>GUILFORD CO. BRIDGE #57 SR 1398 (FREEMAN MILL RD.) SOUTHBOUND RIGHT LANE WORK AREA</p>
	SEAL 		



I:\2025\2\LAN\TrafficControl\WBS 17BP.7.P.4 Guilford\TCN\Plan Sheets\17BP.7.P.4.TC.TMP.11A.BRIDGE.57.SB.RT.WORKAREA.dwg
 C:\Users\lan\Documents\17BP.7.P.4 Guilford\TCN\Plan Sheets\17BP.7.P.4.TC.TMP.11A.BRIDGE.57.SB.RT.WORKAREA.dwg

MATCHLINE - SEE PREVIOUS SHEET


 Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6896 Fax. (919) 851-7024 www.stantec.com License No. F-0672	APPROVED: _____ DATE: _____ 		GUILFORD CO. BRIDGE #57 SR 1398 (FREEMAN MILL RD.) SOUTHBOUND RIGHT LANE WORK AREA
	[Handwritten signature and date: Betsy L. Haddon, 1/28/11]		



1/25/2012 11:29 AM \\fs1\projects\17BP.7.P.4\TrafficControl\WBS 17BP.7.P.4\TrafficControl\Plan Sheets\17BP.7.P.4.TC.TMP.12.BRIDGE.57.LT.WORKAREA.dgn

MATCHLINE - SEE NEXT SHEET


<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	<p>APPROVED: _____ DATE: _____</p>		<p>GUILFORD CO. BRIDGE #57 SR 1398 (FREEMAN MILL RD.) LEFT LANE WORK AREA</p>
	<p>SEAL</p> <p><i>Jeffrey L. Watson</i> 1/28/12</p>		



1/29/2012
 C:\TrafficControl\WBS 17BP.7.P.4 Guilford\TC\Plan Sheets\17BP.7.P.4.TC.TMP_12A.BRIDGE_57.LT.WORKAREA.dgn
 P:\TrafficControl\WBS 17BP.7.P.4 Guilford\TC\Plan Sheets\17BP.7.P.4.TC.TMP_12A.BRIDGE_57.LT.WORKAREA.dgn


MATCHLINE - SEE PREVIOUS SHEET

<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6868 Fax. (919) 851-7024 www.stantec.com License No. F-6672</p>	APPROVED: _____ DATE: _____			<p>GUILFORD CO. BRIDGE #57 SR 1398 (FREEMAN MILL RD.) LEFT LANE WORK AREA</p>
	<p>SEAL</p> <p><i>Gregory L. Watson</i> 11/28/12</p>			







11/20/2012
 U:\TrafficControl\WBS 17BP.7.P.4 Guilford\TCP\Plan Sheet\SYTBP.7.P.4.TC.TMP.13.BRIDGE.169.SR.1129.NB.RT.WORKAREA.dgn
 Toulmin

<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6968 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK ZONE TRAFFIC CONTROL</p>	<p>GUILFORD CO. BRIDGE #169 SR 1129 (GROOMETOWN RD.) NORTHBOUND RIGHT LANE WORK AREA</p>
	SEAL 		



1/20/2012
 C:\Users\jfrancis\Documents\WBS 17BP.7.P.4 Guilford\TCPIP\Plan Sheets\17BP.7.P.4.TC.TMP.14.BRIDGE.169.SR.1129.S5.P1.WORKAREA.dgn
 Guilford




 Stantec Stantec Consulting Services Inc. 801 Jones Franklin Road, Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-6672	APPROVED: _____ DATE: _____ 		GUILFORD CO. BRIDGE #169 SR 1129 (GROOMETOWN RD.) SOUTHBOUND RIGHT LANE WORK AREA
	SEAL _____		




11/28/2012
 D:\Projects\TrafficControl\WBS 17BP.7.P.4_GulfCo-TrafficControl\Sheets\TMP.7.P.4.TC_TMP_15_BRIDGE_169_SR_1129_L1_WORKAREA.dgn
 COLLIER

<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6886 Fax. (919) 851-7224 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION NORTH CAROLINA TRAFFIC CONTROL</p>	<p>GUILFORD CO. BRIDGE #169 SR 1129 (GROOMTOWN RD.) LEFT LANE WORK AREA</p>
	SEAL: <i>Best L. Wason</i> 11/28/12		



I:\2012\2012\UK\OFFICE\TrafficControl\WBS 17BP.7.P.4 Guilford\TC\Plan Sheets\16.BRIDGE.334_EB_RT_WORKAREA.dgn



<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-8866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK ZONE TRAFFIC CONTROL</p>	<p>GUILFORD CO. BRIDGE #334 BESSEMER AVE. EASTBOUND RIGHT LANE WORK AREA</p>
	<p>SEAL</p>		



11/28/2012 10:45 AM C:\FILES\T-COFFICE\CONTRACTS\WBS 17BP.7.P.4 Guilford\T-COFFICE\CONTRACTS\WBS 17BP.7.P.4 TC_TMP_17_BRIDGE_334_MB_RT_WORKAREA.dgn




Stantec
Stantec Consulting Services Inc.
801 Jones Franklin Road
Suite 300
Raleigh, NC 27606
Tel. (919) 851-6666
Fax. (919) 851-7024
www.stantec.com
License No. F-0672



APPROVED: _____ DATE: 11/28/12
SEAL: [Professional Engineer Seal for Beth A. Watson, License No. 29449]

DIVISION OF HIGHWAY
STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
TRAFFIC CONTROL

GUILFORD CO. BRIDGE #334
BESSEMER AVE. WESTBOUND
RIGHT LANE WORK AREA




11/20/2012
 C:\Users\jg\Documents\17BP.7.P.4_GulfportVTC\Plan Sheets\17BP.7.P.4_TC_TMP_18_BRIDGE_334.L.L.LANE_WORKAREA.dgn
 11/20/2012 11:04:49 AM



<p>Stantec</p>	Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6968 Fax. (919) 851-7024 www.stantec.com License No. F-0672	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK ZONE TRAFFIC CONTROL</p>	<p>GUILFORD CO. BRIDGE #334</p> <p>BESSEMER AVE. LEFT LANE WORK AREA</p>

PROJECT: 17BP.7.P.1

CONTRACT: C203270










STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS

GUILFORD COUNTY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.7.P.1	4	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.7.P.1		PE	
17BP.7.P.1		CONSTR	

LOCATION: BRIDGE #12, ON SR 1970 (EAST KIVETT DR.) OVER NORFOLK SOUTHERN RAILWAY
 BRIDGE #36, ON NC 150 (OAK RIDGE RD.) OVER SOUTHERN RAILWAY (ABANDONED)
 BRIDGE #57, ON SR 1398 (FREEMAN MILL RD.) OVER NC 6
 BRIDGE #277, ON US 421 EBL OVER BIG ALAMANCE CREEK
 BRIDGE #292, ON US 220 (WENDOVER AVE.) ACROSS US 220 SBL & SR 1452
 BRIDGE #334, ON BESSEMER AVENUE ACROSS US 29

TYPE OF WORK: BRIDGE PRESERVATION - CLEANING & PAINTING OF EXISTING BRIDGE STRUCTURES



DESIGN DATA

#12 ADT 2011	=	8,900
#36 ADT 2011	=	6,700
#57 ADT 2009	=	21,500
#277 ADT 2009	=	8,000
#292 ADT 2011	=	55,000
#334 ADT 2011	=	17,000

PROJECT LENGTH

GUILFORD BRIDGE #12	=	.080 MILE
GUILFORD BRIDGE #36	=	.030 MILE
GUILFORD BRIDGE #57	=	.030 MILE
GUILFORD BRIDGE #277	=	.039 MILE
GUILFORD BRIDGE #292	=	.034 MILE
GUILFORD BRIDGE #334	=	.032 MILE

Prepared in the Office of:
STRUCTURES MANAGEMENT UNIT
 NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

2012 STANDARD SPECIFICATIONS	
LETTING DATE: June 18, 2013	RICK NELSON, PE PROJECT ENGINEER

NORTH CAROLINA
 PROFESSIONAL ENGINEER
 SEAL
 20103
 FARZIN ASEFANIA
 PROJECT DESIGN ENGINEER


FARZIN ASEFANIA, P.E.
 PROJECT DESIGN ENGINEER

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

TRANSPORTATION MANAGEMENT PLAN


GUILFORD COUNTY

DIVISION 7




BRIDGE PAINTING

- GUILFORD BRIDGE #12 – SR 1970 OVER SOUTHERN RAILROAD**
- GUILFORD BRIDGE #36 – NC 150 OVER SOUTHERN RR (ABANDONED)**
- GUILFORD BRIDGE #57 – SR 1398 OVER NC 6**
- GUILFORD BRIDGE #277 – US 421 EB OVER BIG ALAMANCE CREEK**
- GUILFORD BRIDGE #292 – US 220 OVER US 220 SB**
- GUILFORD BRIDGE #334 – BESSEMER AVENUE OVER US 29**



PLAN PREPARED FOR NCDOT BRIDGE MANAGEMENT UNIT
RALEIGH, NC



INDEX OF SHEETS

SHEET NO.	TITLE
TMP-1	TITLE SHEET, INDEX OF SHEETS, & TRAFFIC MANAGEMENT STRATEGY
TMP-1A	LEGEND & ROADWAY STANDARD DRAWINGS
TMP-2	GENERAL NOTES
TMP-3	PHASING
TMP-4	BRIDGE #57 NC 6/W LEE ST.-LEFT & CENTER LANE CLOSURES
TMP-4A	BRIDGE #57 NC 6/W LEE ST.-RIGHT LANE CLOSURES
TMP-5	BRIDGE #292 BATTLEGROUND AVE-LEFT LANE CLOSURES
TMP-5A	BRIDGE #292 BATTLEGROUND AVE-RIGHT LANE CLOSURES
TMP-6	BRIDGE #334 US 29-LEFT LANE CLOSURES
TMP-6A	BRIDGE #334 US 29-LEFT LANE CLOSURES WITH SHIFT
TMP-6B	BRIDGE #334 HEADQUARTERS DR. RAMP CLOSURE & DETOUR ROUTE

TRAFFIC MANAGEMENT STRATEGY

BRIDGE PAINTING OPERATIONS WILL BE ACCOMPLISHED USING TIME RESTRICTED LANE CLOSURES. REFER TO SHEET TMP-3 FOR PHASING.




PLAN PREPARED BY:
Stantec Consulting Services Inc.
801 Jones Franklin Road-Suite 300
Raleigh, NC 27606
Tel. 919.851.6866
Fax. 919.851.7024
www.stantec.com

BETSY L. WATSON, P.E. *TRAFFIC ENGINEER*
GEORGE KARAGEORGE *SR. TRANSPORTATION DESIGNER*

APPROVED: *Betsy L. Watson*
DATE: 12/15/11






















SEAL




SHEET NO.
TMP-1

WBS 17BP.7.P.1





LEGEND

-  DIRECTION OF TRAFFIC FLOW
-  DIRECTION OF PEDESTRIAN TRAFFIC FLOW
-  WORK AREA
-  PAVEMENT REMOVAL
-  NORTH ARROW
-  TYPE III BARRICADE
-  CONE
-  DRUM
-  SKINNY DRUM
-  TUBULAR MARKER
-  CHANGEABLE MESSAGE SIGN (CMS)
-  FLAGGER
-  FLASHING ARROW BOARD (TYPE C)
-  LAW ENFORCEMENT
-  TRUCK MOUNTED ATTENUATOR (TMA)
-  PORTABLE CONCRETE BARRIER (PCB)
-  TEMPORARY CRASH CUSHION
-  TEMPORARY SHORING
-  WORK ZONE SIGN-PORTABLE
-  WORK ZONE SIGN-STATIONARY
-  WORK ZONE SIGN-STATIONARY OR PORTABLE




SIGNALS

-  EXISTING
-  PROPOSED
-  TEMPORARY




PAVEMENT MARKINGS

-  EXISTING PAVEMENT MARKING (GRAY)
-  SKIP LINES
-  MINI-SKIP LINES
-  SOLID LINES

PAVEMENT MARKING SYMBOLS

-  PAVEMENT MARKING SYMBOLS
-  EXISTING PAVEMENT MARKING SYMBOLS (HOLLOW)
-  PAVEMENT MARKING ALPHANUMERIC CHARACTERS

PAVEMENT MARKERS

-  CRYSTAL/CRYSTAL
-  CRYSTAL/RED
-  YELLOW/YELLOW

ROADWAY STANDARD DRAWINGS


THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:


<u>STD. NO.</u>	<u>TITLE</u>
1101.01	WORK ZONE ADVANCE WARNING SIGNS
1101.02	TEMPORARY LANE CLOSURES
1101.04	TEMPORARY SHOULDER CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1110.02	PORTABLE WORK ZONE SIGNS
1115.01	FLASHING ARROW BOARDS
1130.01	DRUMS
1135.01	CONES
1145.01	BARRICADES
1150.01	FLAGGING DEVICES
1165.01	WORK VEHICLE LIGHTING SYSTEMS AND TMA DELINEATION
1180.01	SKINNY - DRUM

I2/14/2011
U:\TrafficControl\WBS 17BP.7.P.1\GulfFord Painting\TCP\Plan Sheets\17BP.7.P.1.TC.TMP.01A.RDWAYSTDLEGEND.dgn
dkar cgs0179e



Stantec Consulting Services Inc.
801 Jones Franklin Road
Suite 300
Raleigh, NC 27606
Tel. (919) 851-6866
Fax. (919) 851-7024
www.stantec.com
License No. F-0572

APPROVED: _____ DATE: _____
SEAL  12/15/11



LEGEND
&
ROADWAY STANDARD DRAWINGS

GENERAL NOTES

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE PROJECT EXCEPT WHEN OTHERWISE NOTED IN THE PLAN OR DIRECTED BY THE ENGINEER.

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRED OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING, OR REMOVAL OF DEVICES AS DIRECTED BY THE ENGINEER.

LANE CLOSURE TIME RESTRICTIONS

A) DO NOT CLOSE OR NARROW TRAVEL LANES AS FOLLOWS:

ROAD NAME	DAY AND TIME RESTRICTIONS
E. KIVETT DR. FREEMAN MILL RD. WEST LEE ST. (NC 9) BATTLEGROUND AVE. WENDOVER AVE. N. OHENRY BLVD. E. BESSEMER AVE.	6:00 A.M. - 7:00 P.M. MONDAY-SUNDAY (EVERY DAY)
NC 150 US 421	6:00 A.M. - 9:00 A.M. MONDAY THRU FRIDAY, AND 4:00 P.M. - 7:00 P.M. MONDAY THRU FRIDAY

HOLIDAY & HOLIDAY WEEKEND LANE CLOSURE TIME RESTRICTIONS

B) DO NOT CLOSE OR NARROW TRAVEL LANES DURING HOLIDAYS AND HOLIDAY WEEKENDS AS FOLLOWS:

- ROAD NAME**
ALL ROADS
- FOR ANY UNEXPECTED OCCURRENCE THAT CREATES UNUSUALLY HIGH TRAFFIC VOLUMES, AS DIRECTED BY THE ENGINEER.
 - FOR NEW YEAR'S, BETWEEN THE HOURS OF 6:00 A.M. DECEMBER 31st TO 7:00 P.M. JANUARY 2nd. IF NEW YEAR'S DAY IS ON A FRIDAY, SATURDAY, SUNDAY, OR MONDAY THEN UNTIL 7:00 P.M. THE FOLLOWING TUESDAY.
 - FOR EASTER, BETWEEN THE HOURS OF 6:00 A.M. THURSDAY AND 7:00 P.M. MONDAY.
 - FOR MEMORIAL DAY, BETWEEN THE HOURS OF 6:00 A.M. FRIDAY TO 7:00 P.M. TUESDAY.
 - FOR INDEPENDENCE DAY, BETWEEN THE HOURS OF 6:00 A.M. THE DAY BEFORE INDEPENDENCE DAY AND 7:00 P.M. THE DAY AFTER INDEPENDENCE DAY. IF INDEPENDENCE DAY IS ON A FRIDAY, SATURDAY, SUNDAY OR MONDAY; THEN BETWEEN THE HOURS OF 6:00 A.M. THE THURSDAY BEFORE INDEPENDENCE DAY AND 7:00 P.M. THE TUESDAY AFTER INDEPENDENCE DAY.
 - FOR LABOR DAY, BETWEEN THE HOURS OF 6:00 A.M. FRIDAY AND 7:00 P.M. TUESDAY.
 - FOR THANKSGIVING DAY, BETWEEN THE HOURS OF 6:00 A.M. TUESDAY TO 7:00 P.M. MONDAY.
 - FOR CHRISTMAS, BETWEEN THE HOURS OF 6:00 A.M. THE FRIDAY BEFORE THE WEEK OF CHRISTMAS DAY AND 7:00 P.M. THE FOLLOWING TUESDAY AFTER THE WEEK OF CHRISTMAS.

ROAD CLOSURE TIME RESTRICTIONS

C) DO NOT CLOSE ROADS AS FOLLOWS:

ROAD NAME	DAY AND TIME RESTRICTIONS
RAMPS FROM ARNOLD ST AND BESSEMER AVE (HEADQUARTERS DR) ONTO US 29	6:00 A.M. - 7:00 P.M. MONDAY-SUNDAY (EVERY DAY)

LANE AND SHOULDER CLOSURE REQUIREMENTS

- LANE CLOSURES ARE REQUIRED WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN ANY PORTION OF A TRAVEL LANE. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL LANE.
- INSTALL ALL LANE CLOSURES ACCORDING TO THE PLANS, ROADWAY STANDARD DRAWINGS (1101.02), OR AS DIRECTED BY THE ENGINEER.
- REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED OR AS DIRECTED BY THE ENGINEER. COVER OR LAY DOWN SIGNS, AND TURN OFF ARROW BOARDS AND MESSAGE SIGNS.
- INSTALL LANE CLOSURES WITH THE TRAFFIC FLOW, BEGINNING WITH DEVICES ON THE UPSTREAM SIDE OF TRAFFIC. REMOVE LANE CLOSURES AGAINST THE TRAFFIC FLOW, BEGINNING WITH DEVICES ON THE DOWNSTREAM SIDE OF TRAFFIC.
- WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.
- WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.
- WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO A DIVIDED FACILITY AND WITHIN 10 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.
- UNLESS OTHERWISE SHOWN IN THE PLANS, PLACE ARROW BOARDS ON THE ROADWAY SHOULDER. IF SHOULDERS DO NOT EXIST, PLACE ARROW BOARDS WITHIN THE MERGE TAPER BEHIND THE CHANNELIZING DEVICES OF THE LANE CLOSURE. IF NEEDED, EXTEND LANE CLOSURES TO PROVIDE STOPPING SIGHT DISTANCE TO THE ARROW BOARD (REFER TO ROADWAY STANDARD DRAWING 1101.11 SHEET 2).
- PLACE LANE CLOSURE DRUMS IN TAPERS AT A MAXIMUM SPACING EQUAL IN FEET TO THE POSTED SPEED LIMIT (MPH). ALONG BUFFER SPACES AND WORK AREAS SPACE DRUMS AT A MAXIMUM SPACING EQUAL IN FEET TO TWICE THE POSTED SPEED LIMIT (MPH). IN ALL CASES, CHANNELIZING DEVICES ARE TO BE SPACED IN SUCH A MANNER AS TO POSITIVELY ACHIEVE THE INTENDED VISUAL CHANNELIZATION. CHANNELIZING DEVICES SHOULD BE LATERALLY OFFSET 3 FT INSIDE THE CLOSED LANE AS ROOM PERMITS.
- WHENEVER TAPERS ARE TO BE USED IN CLOSE PROXIMITY TO AN INTERCHANGE RAMP, CROSSROADS, CURVES, OR OTHER INFLUENCING FACTORS, THE LENGTH OF STANDARD TAPERS MAY BE ADJUSTED.




ROAD CLOSURES

- NOTIFY THE ENGINEER TWENTY ONE (21) CALENDAR DAYS PRIOR TO ANY ROAD CLOSURE.
- FURNISH AND INSTALL SIGNING AND DEVICES FOR ROAD CLOSURES ACCORDING TO THE TRAFFIC MANAGEMENT PLAN. COVER OR REMOVE ALL SIGNS AND DEVICES FOR ROAD CLOSURES WHEN NOT IN EFFECT.
- FURNISH AND INSTALL OFFSITE-DETOUR ROUTE SIGNING AS SHOWN IN THE TRAFFIC MANAGEMENT PLAN. COVER OR REMOVE OFFSITE-DETOUR SIGNING WHEN THE DETOUR IS NOT IN OPERATION. ALL DETOUR ROUTES MUST BE APPROVED BY THE ENGINEER PRIOR TO IMPLEMENTING.
- WHEN CLOSING A ROADWAY OR DRIVEWAY PLACE TYPE III BARRICADES COMPLETELY ACROSS THE ROADWAY OR FROM CURB TO CURB. ATTACH BARRICADE MOUNTED "ROAD CLOSED" SIGN R11-2 AT ALL CLOSURE LOCATIONS. IF LOCAL TRAFFIC IS TO BE MAINTAINED STAGGER THE BARRICADES TO ALLOW ACCESS.
- INSTALL SIGNS BEFORE BARRICADES WHEN CLOSING A ROADWAY TO TRAFFIC. REMOVE BARRICADES BEFORE SIGNS WHEN OPENING A ROADWAY TO TRAFFIC. INSTALL/REMOVE ROAD CLOSURE SIGNS AND BARRICADES IN A CONTINUOUS OPERATION AND WITHIN THE SAME CALENDAR DAY.

MISCELLANEOUS

- LAW ENFORCEMENT MAY BE USED TO MAINTAIN TRAFFIC THROUGH THE WORK AREA AND/OR INTERSECTIONS AS DIRECTED BY THE ENGINEER. LOCATIONS SHOWN IN THE PLANS ARE APPROXIMATE AND MAY BE REVISED AS THE OFFICER OR THE ENGINEER DEEM NECESSARY.
- ALL DIMENSIONS AND STATIONS IN THE TRAFFIC MANAGEMENT PLAN AND PHASING ARE APPROXIMATE (+/-); FIELD ADJUST AS NECESSARY OR AS DIRECTED BY THE ENGINEER.
- ENSURE THE OVERSIZE/OVERWEIGHT PERMIT UNIT (919) 733-4740 HAS BEEN ADVISED OF THE ONGOING TRAFFIC OPERATIONS THROUGH THE DIVISION OFFICE.
- CHANGEABLE MESSAGE SIGN MESSAGES SHOWN ARE EXAMPLES. OTHER MESSAGES MAY BE USED AS CONDITIONS WARRANT. ALL MESSAGES AND LOCATIONS MUST BE APPROVED BY THE ENGINEER PRIOR TO INCORPORATING.
- DO NOT PERFORM WORK FROM THE ROADWAY ON TOP OF ANY BRIDGE, UNLESS SPECIFICALLY ALLOWED IN THE PLAN OR BY THE ENGINEER.

I:\15\2011\11\15\TrafficControl\WBS 17BP.7.P.1\Guilford Painting\TCP\Plan Sheets\17BP.7.P.1.TC.TMP-02 - GENERAL NOTES.dgn

 Stantec Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0572	APPROVED: _____ DATE: _____ 		GENERAL NOTES
---	--	---	---------------

PHASING

DURING BRIDGE PAINTING OPERATIONS USE LANE CLOSURES WHEN
REQUIRED AS OUTLINED BELOW:

BRIDGE #12 SR 1970 (E KIVETT DR) OVER SOUTHERN RR

USE RIGHT LANE CLOSURES PER ROADWAY STANDARD DRAWING 1101.02
SHEET 3 OF 15.

BRIDGE #36 NC 150 (OAK RIDGE RD) OVER SOUTHERN RR (ABANDONED)

USE FLAGGER LANE CLOSURES PER ROADWAY STANDARD DRAWING 1101.02
SHEET 1 OF 15.

BRIDGE #57 SR 1398 (FREEMAN MILL RD) OVER NC 6 (W LEE ST)

USE LANE CLOSURES PER SHEETS TMP-4, 4A.

BRIDGE #277 US 421 EASTBOUND OVER BIG ALAMANCE CREEK

USE LANE CLOSURES PER ROADWAY STANDARD DRAWING 1101.02 SHEET 3
OF 15 OR ROADWAY STANDARD DRAWING SHEET 6 OF 15.

BRIDGE #292 US 220 (W WENDOVER AVE) OVER US 220 SOUTHBOUND &
BATTLEGROUND AVE




USE LANE CLOSURES PER SHEETS TMP-5,5A.


BRIDGE #334 BESSEMER AVE OVER US 29/70/220 (N OHENRY BLVD)

USE LANE CLOSURES PER SHEETS TMP-6,6A


WHEN WORKING IN THE RIGHT AND ENTRANCE RAMP LANES CLOSE THE
ENTRANCE RAMP FROM ARNOLD ST. AND BESSEMER AVE. (HEADQUARTERS
DR.) PER SHEET TMP-6B.

12/14/2011
U:\TrafficControl\WBS 17BP.7.P.1\Gulford Painting\TCP\Plan Sheets\17BP.7.P.1.TC.TMP.03.PHASING.dgn
gkarogor


 <p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	<p>APPROVED: _____ DATE: _____</p> <div style="text-align: center;">  <p>SEAL Patsy L. Watson 12/15/11</p> </div>		<p>PHASING</p>
--	--	---	----------------




12/14/2011
 U:\TrafficControl\WBS 17BP.7.P.1\Gulford Painting\TCP\Plan Sheets\17BP.7.P.1.TC.TMP.04.GULFORD.57.dgn
 dkarageorge






 Stantec <small>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</small>	APPROVED: _____ DATE: _____ 	 DIVISION OF HIGHWAYS NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK ZONE TRAFFIC CONTROL	BRIDGE #57 NC 6/W LEE ST. LEFT & CENTER LANE CLOSURES



12/14/2011
 U:\TrafficControl\WBS 17BP.7.P.1\GulfFord\Painting\TCF\Plan Sheets\17BP.7.P.1.TC.TMP_04A_GULFORD_57.dgn
 gkarageorge






 Stantec <small>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</small>	APPROVED: _____ DATE: _____ 		BRIDGE #57 NC 6/W LEE ST RIGHT LANE CLOSURES



<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK ZONE TRAFFIC CONTROL</p>	BRIDGE #292 BATTLEGROUND AVE LEFT LANE CLOSURES
	SEAL: _____ 12/15/11		



12/14/2011
 U:\TrafficControl\WBS 17BP.7.P.1\Gulliford Pointing\TCP\Plan Sheets\17BP.7.P.1.TC.TMP_05.GULLIFORD_292.dgn
 dkarcg00r.g0

12/14/2011
 I:\TrafficControl\WBS\17BP.7.P.1\Gullford\Painting\TCP\Plan Sheets\17BP.7.P.LTC.TMP_05A_GULLFORD_292.dgn
 gkarageorge




<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION TRUCK ZONE TRAFFIC CONTROL</p>	<p>BRIDGE #292</p> <p>BATTLEGROUND AVE</p> <p>RIGHT LANE CLOSURES</p>

12/14/2011 10:42 AM C:\Users\jgarcia\Documents\TrafficControl\WBS 17BP-7.P.1\Gulford\Painting\TOP\Plan Sheets\17BP-7.P.1.LC.TMP-06.GULFORD_334.dgn



 Stantec	Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-8866 Fax. (919) 851-7024 www.stantec.com License No. F-0672	APPROVED: _____ DATE: _____ SEAL 12/15/11	 BRIDGE #334 US 29/70/220/N OHENRY BLVD LEFT LANE CLOSURES
--------------------	--	---	---



SIGNING IN ADVANCE OF LEFT LANE CLOSURE
PLACE SIGNS ON THE RIGHT SIDE OF THE ROADWAY

MESSAGE NO. 1 ROAD WORK AHEAD CHANGABLE MESSAGE SIGN	MESSAGE NO. 2 LEFT LANE CLOSED	MESSAGE NO. 1 LEFT LANE CLOSED CHANGABLE MESSAGE SIGN	MESSAGE NO. 2 MERGE LANE RIGHT	MESSAGE NO. 1 LEFT LANE CLOSED CHANGABLE MESSAGE SIGN	MESSAGE NO. 2 MERGE LANE RIGHT
--	-----------------------------------	---	-----------------------------------	---	-----------------------------------


1500' 500' 500' 500' 500'

BEGINNING OF MERGE TAPER

12/14/2011
Us:\Traffic\TrafficControl\WBS\17BP.7.P.1\Gulford\Painting\TCP\Plan Sheets\17BP.7.P.1.TC.TMP.06A.GULFORD_334.dgn
gkara@geogear.com

<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6866 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION ZONE TRAFFIC CONTROL</p>	<p align="center">BRIDGE #334 US 29/70/220/N OHENRY BLVD LEFT LANE CLOSURES WITH SHIFT</p>

12/14/2011
 U:\TrafficControl\WBS 17BP.7.P.1\Cullford Printing\TCP\Plan Sheets\7BP.7.P.1.TC.TMP_06B_CULLFORD_334.dgn
 gkaragiorge



<p>Stantec Consulting Services Inc. 801 Jones Franklin Road Suite 300 Raleigh, NC 27606 Tel. (919) 851-6886 Fax. (919) 851-7024 www.stantec.com License No. F-0672</p>	APPROVED: _____ DATE: _____ 	<p>DIVISION OF HIGHWAYS NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK ZONE TRAFFIC CONTROL</p>	BRIDGE #334 HEADQUARTERS DR. RAMP CLOSURE & DETOUR ROUTE
	SEAL <i>R. L. Watson</i> 10/15/11		