

SIGN NUMBER: 101B
TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
M1_4	43	98.3	36	36
NC362	132.1	98.3	36	36
Type A Arrow	85.2	10.8	22.5	35.4

MAT'L: 0.125" ALUMINUM

NO. Z BARS: 6
LENGTH: 190.0

NOTES:
1. Legend and border shall be direct applied Grade C reflective sheeting.
2. Shields shall be Grade C refelective sheeting on 0.032" aluminum and demountable.
3. Background shall be Grade C reflective sheeting.

DESIGN BY: TRT
PROJECT ID: R-2514D

CHECKED BY: ADK/CAJ
DIV: 02

DATE: October 2014

16'-6"

13.7"
12"E

10.7"
15"E

29.7"
15"E

32.7"
12"E

15'-6"

160.3"

98.3"

141.3"

17.9"

162.2"

17.9"

BORDER
R=12"
TH=2"

Spacing Factor is 1 unless specified otherwise

Letter spacings are to start of next letter																										Series/Size Text Length
	N		O	R	T	H																				E 2000
31.1	12.2	3.1	12.8	11	11	9.7	107																			59.9
	B	U	S	I	N	E	S	S																		E 2000
17.9	12.1	12.1	12.1	5.3	12.8	10.7	11.4	9.7	93.8																	86.3
	N		O	R	T	H																				E 2000
120.2	12.2	3.1	12.8	11	11	9.7	17.9																			59.9
	P	o	l	l	o	c	k	s	v	i	l	l	e													EM 2000
18.4	15.4	15.8	9.6	8.2	14.4	15.5	13.8	13.8	17	9.6	9.6	8.2	10.6	18.4												161.3
	T	r	e	n	t	o	n																			EM 2000
51.3	15.7	10.4	15.5	15.4	12	15.8	10.6	51.3																		95.4

SIGN NUMBER: 103B
TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
M1_4	43	90.8	36	36
NC362	132.1	90.8	36	36

MAT'L: 0.125" ALUMINUM

NO. Z BARS: 6
LENGTH: 190.0

NOTES:
1. Legend and border shall be direct applied Grade C reflective sheeting.
2. Shields shall be Grade C refelective sheeting on 0.032" aluminum and demountable.
3. Background shall be Grade C reflective sheeting.

DESIGN BY: TRT
PROJECT ID: R-2514D

CHECKED BY: ADK/CAJ
DIV: 02

DATE: October 2014

16'-6"

13.7"
12"E

10.7"
15"E

30.7"
15"E

33.7"
12"E

15'-0"

154.3"

65.7"

134.3"

17.9"

162.2"

17.9"

BORDER
R=12"
TH=2"

Spacing Factor is 1 unless specified otherwise

Letter spacings are to start of next letter																										Series/Size Text Length
	N		O	R	T	H																				E 2000
31.1	12.2	3.1	12.8	11	11	9.7	107																			59.9
	B	U	S	I	N	E	S	S																		E 2000
17.9	12.1	12.1	12.1	5.3	12.8	10.7	11.4	9.7	93.8																	86.3
	N		O	R	T	H																				E 2000
120.2	12.2	3.1	12.8	11	11	9.7	17.9																			59.9
	P	o	l	l	o	c	k	s	v	i	l	l	e													EM 2000
18.4	15.4	15.8	9.6	8.2	14.4	15.5	13.8	13.8	17	9.6	9.6	8.2	10.6	18.4												161.3
	T	r	e	n	t	o	n																			EM 2000
51.3	15.7	10.4	15.5	15.4	12	15.8	10.6	51.3																		95.4
	1		M	I	L	E																				E 2000
72.7	4.5	15	12	4.4	9.2	7.5	72.7																			52.6

SIGN NUMBER: 102B
TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
M1_4	43	91	36	36
NC362	132.1	91	36	36

MAT'L: 0.125" ALUMINUM

NO. Z BARS: 6
LENGTH: 190.0

NOTES:
1. Legend and border shall be direct applied Grade C reflective sheeting.
2. Shields shall be Grade C refelective sheeting on 0.032" aluminum and demountable.
3. Background shall be Grade C reflective sheeting.

DESIGN BY: TRT
PROJECT ID: R-2514D

CHECKED BY: ADK/CAJ
DIV: 02

DATE: October 2014

16'-6"

13.5"
12"E

10.5"
15"E

29.7"
15"E

32.7"
12"E

15'-0"

154.5"

65.7"

134.5"

17.9"

162.2"

17.9"

BORDER
R=12"
TH=2"

Spacing Factor is 1 unless specified otherwise

Letter spacings are to start of next letter																										Series/Size Text Length
	N		O	R	T	H																				E 2000
31.1	12.2	3.1	12.8	11	11	9.7	107																			59.9
	B	U	S	I	N	E	S	S																		E 2000
17.9	12.1	12.1	12.1	5.3	12.8	10.7	11.4	9.7	93.8																	86.3
	N		O	R	T	H																				E 2000
120.2	12.2	3.1	12.8	11	11	9.7	17.9																			59.9
	P	o	l	l	o	c	k	s	v	i	l	l	e													EM 2000
18.4	15.4	15.8	9.6	8.2	14.4	15.5	13.8	13.8	17	9.6	9.6	8.2	10.6	18.4												161.3
	T	r	e	n	t	o	n																			EM 2000
51.3	15.7	10.4	15.5	15.4	12	15.8	10.6	51.3																		95.4
	1/2		M	I	L	E																				E 2000
64	22	15	12	4.4	9.2	7.5	64																			70.1

SIGN NUMBER: 104B,109B
TYPE: A
QUANTITY: 2

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
M1_4	48	42.8	36	36

MAT'L: 0.125" ALUMINUM

NO. Z BARS: 3
LENGTH: 124.0

NOTES:
1. Legend and border shall be direct applied Grade C reflective sheeting.
2. Shields shall be Grade C reflective sheeting on 0.032" aluminum and demountable.
3. Background shall be Grade C reflective sheeting.
4. Proposed Support Spacing for Signs 104B and 109B is 8.00'.

DESIGN BY: TRT
PROJECT ID: R-2514D

CHECKED BY: ADK/CAJ
DIV: 02

DATE: October 2014

11'-0"

13.5"
12"E

10.5"
15"E

30.7"
15"E

33.7"
12"E

9'-6"

82.5"

15"E

134.3"

17.9"

86.3"

22.85"

BORDER
R=12"
TH=2"

Spacing Factor is 1 unless specified otherwise

Letter spacings are to start of next letter																										Series/Size Text Length
	B	U	S	I	N	E	S	S																		E 2000
22.9	12.1	12.1	12.1	5.3	12.8	10.7	11.4	9.7	22.9																	86.3
	1		M	I	L	E																				E 2000
39.7	4.5	15	12	4.4	9.2	7.5	39.7																			52.6

TIP NO.
R-2514D

SHEET NO.
SIGN-4C

APPROVED:

DocuSigned by:
Charles A Johnson III
7802AD68CBF4F8

DATE: 2/2/2015

SEAL

NORTH CAROLINA
PROFESSIONAL
SEAL
20675
ENGINEER
CHARLES A. JOHNSON III

