2603

80

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

PROJECT REFERENCE NO.		SHEET NO.
R-2603		PMP-I
APPROVED:	Pocusigned by: Ron king	
DATE:	13E7AF7B9AA4448 0/2015	
SEAL		

PAVEMENT MARKING PLAN WILKES COUNTY

LOCATION: NC 268 FROM MULTI-LANES EAST OF NC 18 TO SR 1966 (AIRPORT ROAD)

ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

CONCIDENCE / LYMNI OF THESE PERMOT			
STD. NO.	<u>TITLE</u>		
1205.01	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS		
1205.02	PAVEMENT MARKINGS - TWO-LANE AND MULTILANE ROADWAYS		
1205.04	PAVEMENT MARKINGS - INTERSECTIONS		
1205.05	PAVEMENT MARKINGS - TURN LANES		
1205.06	PAVEMENT MARKINGS - LANE DROPS		
1205.08	PAVEMENT MARKINGS - SYMBOLS AND WORD MESSAGES		
1205.09	PAVEMENT MARKINGS - PAINTED ISLANDS		
1205.12	PAVEMENT MARKINGS - BRIDGES		
1205.13	PAVEMENT MARKINGS - LANE REDUCTIONS		
1250.01	RAISED PAVEMENT MARKERS - INSTALLATION SPACING		
1251.01	RAISED PAVEMENT MARKERS - PERMANENT AND TEMPORARY		
1253.01	RAISED PAVEMENT MARKERS - SNOWPLOWABLE		
1261.01	GUARDRAIL AND BARRIER DELINEATORS - INSTALLATION SPACING		
1261.02	GUARDRAIL AND BARRIER DELINEATORS - TYPES AND MOUNTING		
1262.01	GUARDRAIL END DELINEATION		
1264.01	OBJECT MARKERS - TYPES		
1264.02	OBJECT MARKERS - INSTALLATION		

INDEX

SHEET NO.

DESCRIPTION

PMP-1 PMP-2 PMP-3

PAVEMENT MARKING PLAN TITLE PAVEMENT MARKING SCHEDULE SHEET CROSSWALK PAVEMENT MARKING GUIDANCE DETAIL

PMP-4-18

PAVEMENT MARKING DETAIL

GENERAL NOTES

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

A) INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE AS FOLLOWS:

ROAD NAME

MARKING Polyurea w/Highly Reflective Elements

Snowplowable (Raised on Bridge Decks

and Match Existing on Y-lines)

- B) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.
- C) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS.
- D) PASSING ZONES WILL BE DETERMINED IN THE FIELD AND MUST BE APPROVED BY THE ENGINEER.
- E) STOP BAR LOCATION AT NON-SIGNALIZED INTERSECTIONS MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER.
- F) REMOVE ALL RESIDUE AND SURFACE LAITANCE BY ACCEPTABLE METHODS ON CONCRETE BRIDGE DECKS PRIOR TO PLACING POLYUREA PAVEMENT MARKING MATERIAL
- G) UNLESS OTHERWISE SPECIFIED. HEATED-IN-PLACE THERMOPLASTIC MAY BE USED IN LIEU OF EXTRUDED THERMOPLASTIC FOR STOP BARS, SYMBOLS, CHARACTERS AND DIAGONALS. IF HEATED-IN-PLACE IS USED, IT SHALL BE PAID FOR USING THE EXTRUDED THERMOPLASTIC PAY ITEM.
- H) SEE ROADWAY PLANS FOR ALTERNATE CURB RAMP DESIGNS WHEN INDICATED ON PAVEMENT MARKING DETAIL SHEETS.

PLAN PREPARED BY: N.C.D.O.T. SIGNING AND DELINEATION UNIT

K. L. JORDAN SIGNING & DELINEATION REGIONAL ENGINEER

J. G. MARTINEZ SIGNING & DELINEATION PROJECT DESIGN ENGINEER/TECHNICIAN

