

NOTE: SEE SHEET 2A FOR PLAN SHEET LAYOUT AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-3159	1	12
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
38331.1.1	STPNHS-0052(31)	P.E. RW & UTIL.	

CONTENTS

LINE	STATION	PLAN	PROFILE	XSECT
-L-	7+75.00 to 21+00.00	4-5	8	
-Y2-	10+00.00 to 12+36.06	4	8	
-RPA-	10+00.00 to 21+61.41	7,4	9	
-LPA-	10+00.00 to 19+05.77	4	9	
-RPC-	10+00.00 to 20+71.61	6,4	10	
-LPC-	10+00.00 to 17+41.46	4	10	
-Y3-	10+00.00 to 16+09.98	6,4	11	
-Y7-	10+00.00 to 18+53.57	7	11	

SOIL TEST RESULTS 12

ROADWAY
SUBSURFACE INVESTIGATION

PROJ. REFERENCE NO. 38331.1.1 (B-3159) F.A. PROJ. STPNHS-0052(31)
COUNTY DAVIDSON
PROJECT DESCRIPTION BRIDGE NO. 27 OVER US 29-64-70 /I-85 BUS.
ON NC 8 /US 52

INVENTORY

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING, AND DESIGN AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N.C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 250-4088. NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOGS, ROCK CORES, OR SOIL TEST DATA ARE PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU UNPLACED TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION, AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

PERSONNEL

J.K. STICKNEY


C.L. SMITH

INVESTIGATED BY J.E. BEVERLY

CHECKED BY C.B. LITTLE

SUBMITTED BY C.B. LITTLE

DATE APRIL 2014



ID: B-3159

CONTRACT:

DRAWN BY: J.K. McCLURE

NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N.C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IS IT CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THE PROJECT.

NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

PROJECT REFERENCE NO.
38331.1(B-3159) SHEET NO.
2

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS





SOIL DESCRIPTION		GRADATION		ROCK DESCRIPTION		TERMS AND DEFINITIONS																																																																																																																																																																																												
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (ASHTO T208, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:</p> <p style="text-align: center;"><i>VERY STIFF, GRAY, SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>		<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED)</p> <p>GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>		<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT IF TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>		<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.</p> <p>AQUIFER - A WATER BEARING FORMATION OR STRATA.</p> <p>ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.</p> <p>ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC.</p> <p>ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.</p> <p>CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.</p> <p>COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.</p> <p>CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.</p> <p>DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.</p> <p>DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.</p> <p>FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.</p> <p>FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.</p> <p>FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL.</p> <p>FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.</p> <p>FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.</p> <p>JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.</p> <p>LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.</p> <p>LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.</p> <p>MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.</p> <p>PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.</p> <p>RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.</p> <p>ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.</p> <p>SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.</p> <p>SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.</p> <p>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS IN OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.</p> <p>STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.</p> <p>STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.</p> <p>TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																																												
SOIL LEGEND AND AASHTO CLASSIFICATION		MINERALOGICAL COMPOSITION		WEATHERING																																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">GENERAL CLASS.</th> <th colspan="7">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="7">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="3">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>SYMBOL</th> <th>A-1</th> <th>A-1-b</th> <th>A-3</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th></th> <th></th> <th></th> </tr> <tr> <td>% PASSING</td> <td></td> <td>50</td> <td>30</td> <td>30</td> <td>50</td> <td>50</td> <td>50</td> <td>50</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td></td> <td></td> <td></td> </tr> <tr> <td>LIQUID LIMIT</td> <td></td> <td>50</td> <td>30</td> <td>30</td> <td>50</td> <td>50</td> <td>50</td> <td>50</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td></td> <td></td> <td></td> </tr> <tr> <td>PLASTIC INDEX</td> <td></td> <td>6</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>GROUP INDEX</td> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td></td> <td>GRAVEL AND SAND</td> <td>FINE SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td>SAND</td> <td></td> <td></td> <td></td> </tr> <tr> <td>GEN. RATING AS A SUBGRADE</td> <td></td> <td colspan="7">EXCELLENT TO GOOD</td> <td colspan="7">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td>UNSATURABLE</td> <td></td> <td></td> <td></td> </tr> </table>		GENERAL CLASS.		GRANULAR MATERIALS (≤ 35% PASSING #200)							SILT-CLAY MATERIALS (> 35% PASSING #200)							ORGANIC MATERIALS			GROUP CLASS.	SYMBOL	A-1	A-1-b	A-3	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7				% PASSING		50	30	30	50	50	50	50	10	10	10	10	10	10	10	10				LIQUID LIMIT		50	30	30	50	50	50	50	10	10	10	10	10	10	10	10				PLASTIC INDEX		6	0	0	0	0	0	0	0	0	0	0	0	0	0	0				GROUP INDEX		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0				USUAL TYPES OF MAJOR MATERIALS		GRAVEL AND SAND	FINE SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND				GEN. RATING AS A SUBGRADE		EXCELLENT TO GOOD							FAIR TO POOR							FAIR TO POOR	POOR	UNSATURABLE				<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p>		<p>WEATHERED ROCK (WR) - NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.</p> <p>CRYSTALLINE ROCK (CR) - FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p> <p>NON-CRYSTALLINE ROCK (NCR) - FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.</p> <p>COASTAL PLAIN SEDIMENTARY ROCK (CP) - COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.</p>		<p>SLIGHTLY COMPRESSIBLE MODERATELY COMPRESSIBLE HIGHLY COMPRESSIBLE</p> <p>LIQUID LIMIT LESS THAN 31 LIQUID LIMIT EQUAL TO 31-50 LIQUID LIMIT GREATER THAN 50</p>		<p>PERCENTAGE OF MATERIAL</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>>10%</td> <td>>20%</td> <td>HIGHLY</td> </tr> <tr> <td></td> <td></td> <td></td> <td>35% AND ABOVE</td> </tr> </table>		ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	>10%	>20%	HIGHLY				35% AND ABOVE
GENERAL CLASS.		GRANULAR MATERIALS (≤ 35% PASSING #200)							SILT-CLAY MATERIALS (> 35% PASSING #200)							ORGANIC MATERIALS																																																																																																																																																																																		
GROUP CLASS.	SYMBOL	A-1	A-1-b	A-3	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																																		
% PASSING		50	30	30	50	50	50	50	10	10	10	10	10	10	10	10																																																																																																																																																																																		
LIQUID LIMIT		50	30	30	50	50	50	50	10	10	10	10	10	10	10	10																																																																																																																																																																																		
PLASTIC INDEX		6	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																																																																																																		
GROUP INDEX		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																																																																																																		
USUAL TYPES OF MAJOR MATERIALS		GRAVEL AND SAND	FINE SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND	SAND																																																																																																																																																																																		
GEN. RATING AS A SUBGRADE		EXCELLENT TO GOOD							FAIR TO POOR							FAIR TO POOR	POOR	UNSATURABLE																																																																																																																																																																																
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																															
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																																																																																															
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																																																																																															
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																																																																																															
HIGHLY ORGANIC	>10%	>20%	HIGHLY																																																																																																																																																																																															
			35% AND ABOVE																																																																																																																																																																																															
CONSISTENCY OR DENSENESS		MISCELLANEOUS SYMBOLS		ROCK HARDNESS																																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td><4 4 TO 10 10 TO 30 30 TO 50 >50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td><2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30</td> <td><0.25 0.25 TO 0.50 0.5 TO 1.0 1 TO 2 2 TO 4 >4</td> </tr> </table>		PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	<4 4 TO 10 10 TO 30 30 TO 50 >50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	<2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30	<0.25 0.25 TO 0.50 0.5 TO 1.0 1 TO 2 2 TO 4 >4	<p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</p> <p>INFERRED SOIL BOUNDARY</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP & DIP DIRECTION OF ROCK STRUCTURES</p> <p>SPT TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>CONE PENETROMETER TEST</p> <p>SOUNDING ROD</p>		<p>VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</p> <p>HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p> <p>MODERATELY HARD CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p> <p>MEDIUM HARD CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p> <p>SOFT CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p> <p>VERY SOFT CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</p>																																																																																																																																																																																		
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																																															
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	<4 4 TO 10 10 TO 30 30 TO 50 >50	N/A																																																																																																																																																																																															
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	<2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30	<0.25 0.25 TO 0.50 0.5 TO 1.0 1 TO 2 2 TO 4 >4																																																																																																																																																																																															
TEXTURE OR GRAIN SIZE		ABBREVIATIONS		FRACTURE SPACING		BEDDING																																																																																																																																																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table>		U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	<p>AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS - FOSSILIFEROUS FRAC - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI - HIGHLY</p> <p>MED. - MEDIUM MICA - MICA MOD. - MODERATELY ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL W - MOISTURE CONTENT V - VERY</p> <p>VST - VANE SHEAR TEST WEA. - WEATHERED W - UNIT WEIGHT W_d - DRY UNIT WEIGHT</p> <p>SAMPLE ABBREVIATIONS S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL RATIO CBR - CALIFORNIA BEARING RATIO</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>> 4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>		TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	> 4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET																																																																																																																																																			
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																												
	4.76	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																																												
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																																															
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	> 4 FEET																																																																																																																																																																																															
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																															
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																															
CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																															
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																															
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																															
SOIL MOISTURE - CORRELATION OF TERMS		EQUIPMENT USED ON SUBJECT PROJECT		INDURATION																																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>		SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>DRILL UNITS:</p> <p>MOBILE B- _____</p> <p>BK-51 _____</p> <p>CME-45C _____</p> <p>CME-550 _____</p> <p>PORTABLE MOIST _____</p> <p>_____</p> <p>_____</p> <p>_____</p>		<p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>																																																																																																																																																																															
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																																
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																																
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																
PLASTICITY		COLOR		NOTES:																																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>0-5</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>LOW PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>		NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	0-5	0-5	VERY LOW	LOW PLASTICITY	6-15	SLIGHT	MED. PLASTICITY	16-25	MEDIUM	HIGH PLASTICITY	26 OR MORE	HIGH	<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>		<p>SOIL STRATIGRAPHY IS THROUGH THE BORINGS FOR PROFILES.</p> <p>BORING ELEVATIONS OBTAINED FROM THE B3159.LS.TIN.TIN FILE.</p>																																																																																																																																																																															
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																																
0-5	0-5	VERY LOW																																																																																																																																																																																																
LOW PLASTICITY	6-15	SLIGHT																																																																																																																																																																																																
MED. PLASTICITY	16-25	MEDIUM																																																																																																																																																																																																
HIGH PLASTICITY	26 OR MORE	HIGH																																																																																																																																																																																																
COLOR		FRAC. SPACING		INDURATION		NOTES:																																																																																																																																																																																												
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>		<p>FRAC. SPACING</p> <p>VERY WIDE MORE THAN 10 FEET</p> <p>WIDE 3 TO 10 FEET</p> <p>MODERATELY CLOSE 1 TO 3 FEET</p> <p>CLOSE 0.16 TO 1 FEET</p> <p>VERY CLOSE LESS THAN 0.16 FEET</p>		<p>INDURATION</p> <p>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>		<p>BENCH MARK:</p> <p>_____</p> <p>ELEVATION: _____ FT.</p>																																																																																																																																																																																												

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-3159	2A	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
38331.1.1	STPNHS-0052(31)	PE	

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

DAVIDSON COUNTY

LOCATION: BRIDGE NO. 27 OVER US 29-64-70 / I-85 BUS ON NC 8 / US 52
TYPE OF WORK: GRADING, DRAINAGE, PAVING, RETAINING WALL,
& STRUCTURE




CLEARING ON THIS PROJECT SHOULD BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD ____.
THIS IS A FULL CONTROLLED-ACCESS PROJECT WITH ACCESS TO BE SHOWN ON PLANS.
THIS PROJECT IS WITHIN THE CITY LIMITS OF LEXINGTON.

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

TIP PROJECT: B-3159

CONTRACT:



DESIGN DATA

ADT 2009 =	23,900
ADT 2035 =	28,600
DHV =	10 %
D =	60 %
T =	5 % *
V =	40 MPH
* TTST =	2 DUAL 3
FUNC CLASS =	ARTERIAL
	STATEWIDE TIER

PROJECT LENGTH

LENGTH ROADWAY OF TIP PROJECT B-3159 =	0.259 MILES
LENGTH STRUCTURE OF TIP PROJECT B-3159 =	0.030 MILES
TOTAL LENGTH OF TIP PROJECT B-3159 =	0.289 MILES

Prepared In the Office of:
DIVISION OF HIGHWAYS
1000 Birch Ridge Dr., Raleigh NC, 27610

2012 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: JUNE 20, 2014

LETTING DATE: JUNE 16, 2015

TONY HOUSER, PE
PROJECT ENGINEER


BRUCE PAYNE, PE
PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER

SIGNATURE: _____

ROADWAY DESIGN ENGINEER

SIGNATURE: _____



08-APR-2014 11:05 C:\Projects\3159_CEO_RDWY-DAVIDSON\PlanProf\B3159_GEO_inv_orig-rdy-tsh_002A.dgn jimc@ncdot.gov



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

PAT MCCRORY
GOVERNOR

ANTHONY J. TATA
SECRETARY

April 14, 2014

STATE PROJECT: 38331.1.1 (B-3159)
F.A. PROJECT: STPNHS-0052(31)
COUNTY: Davidson
DESCRIPTION: Bridge No. 27 over US 29-64-70 / I-85 Business on NC 8 / US 52
SUBJECT: Geotechnical Report – Inventory

This report presents the findings for the proposed interchange surrounding bridge # 27 in Davidson County. The bridge lies at the intersection of NC 8 / US 52 and US 29-64-70 / I-85 Business.

The geotechnical field investigation was conducted in the month of February 2014 with the addition of two PDEA borings from May 2010. An ATV mounted CME 550X drill machine equipped with automatic drop hammer was utilized to perform test borings. The following survey lines are addressed in this report.

Line	Station
-L-	7+75 to 21+00
-Y2-	10+00 to 12+36.06
-RPA-	10+00 to 21+61.41
-LPA-	10+00 to 19+05.77
-RPC-	10+00 to 20+71.61
-LPC-	10+00 to 17+41.46
-Y3-	10+00 to 16+09.98
-Y7-	10+00 to 18+53.57

Areas of Special Geotechnical Interest:

1. *Groundwater:*

Groundwater was encountered in several borings during the course of this investigation, however in only 2 instances was groundwater at or above proposed grade. Following is a list of those locations:

Boring Location	Groundwater Elevation
-LPA- 15+35, 25.3' RT	774.1'
-LPC- 11+43, 38' LT	764.5'

2. *Crystalline Rock:*

Rock was not encountered during the course of this investigation.

3. *High PI Soils: (PI's 28 and greater)*

High PI clay soils were only encountered in one instance. An A-7-5 clay with a PI value of 45 was noted at -LPA- station 15+35, 8' RT. Depth range of the soil is 0 – 12 feet which puts it above proposed grade, however it may exist in the proposed side slope cuts around this vicinity.

4. *Alluvial Soils:*

There are no alluvial soils present on the project.

Physiography / Geology:

The project area is located in east-central Davidson County within the city limits of Lexington. Topography is predominantly flat with the area surrounded by business structures and traversed by major highways, ramps and loops.

Geologically the site lies in the Carolina Slate Belt with residual soil types originating from metamorphic mafic rock types of Paleozoic Era (PzZm).

Soil Properties:

1. *Residual Soils:*

These soils are derived from in place weathering of parent materials. They occur in a variety of consistencies, classifications, and stratigraphic sequences. Residual soils are further subdivided into clays, silts, and sands. In most instances residual soils in this area are micaceous with mica amounts ranging from trace to high.

Clays are common soils within this area. They are found as surface soils and at depth. Boring and sample data indicates they consist of medium stiff to stiff, trace to very micaceous, silty sandy clay. AASHTO classifications were A-7-5 and A-7-6. Clay soils appear well drained with a plasticity index range from 18 to 45. Corresponding liquid limit ranges were between 46 and 85.

Silts are also common and consist of soft to hard, some to very micaceous, clayey sandy silt. AASHTO classifications are A-4, and A-5. Silts were only noted below 7 feet.

MAILING ADDRESS:
NC DEPARTMENT OF TRANSPORTATION
DIRECTOR OF PRECONSTRUCTION
1538 MAIL SERVICE CENTER
RALEIGH NC 27699-1538

TELEPHONE: 919-707-2540
FAX: 919-715-5361
WEBSITE: WWW.NCDOT.GOV


LOCATION:
TRANSPORTATION BUILDING
1 SOUTH WILMINGTON STREET
RALEIGH NC

Sands consist of loose to dense, some mica, clayey silty sand and clayey sand with corresponding AASHTO classifications of A-2-4, and A-2-6. Sands occur at multiple depth ranges.

2. *Fill Soils:*

Roadway embankment fill soils are present beneath the existing roads, loops and ramps associated with the interchange. Roadway fill soils were medium stiff to stiff sandy silty clay with the A-6 AASHTO classification.

Respectfully Submitted,



J. E. Beverly
Project Engineering Geologist

NAD 83/NSRS 2007
-Y3-

-L-
 PI Sta 18+64.71 Δ = 13° 50' 42.1" (LT)
 D = 10' 44' 58.8" L = 128.79'
 T = 64.71' R = 533.00'
 SE = SEE PLANS

-RPC-
 PI Sta 19+97.13 Δ = 14° 36' 42.4" (RT)
 D = 10' 44' 58.8" L = 135.93'
 T = 68.33' R = 533.00'
 SE = SEE PLANS

-RPC-
 PI Sta 18+23.72 Δ = 22° 17' 00.9" (LT)
 D = 12' 54' 16.0" L = 172.68'
 T = 87.45' R = 444.00'
 SE = .08

-RPA-
 PI Sta 18+86.35 Δ = 48° 51' 27.7" (LT)
 D = 12' 54' 16.0" L = 378.61'
 T = 201.68' R = 444.00'
 SE = .08

-Y3-
 PI Sta 12+87.78 Δ = 60° 06' 55.5" (LT)
 D = 21' 42' 10.6" L = 276.99'
 T = 152.78' R = 264.00'
 SE = .08

-Y3-
 PI Sta 15+39.19 Δ = 61° 27' 14.0" (RT)
 D = 26' 46' 25.4" L = 229.53'
 T = 127.20' R = 214.00'
 SE = SEE PLANS

-Y-
 PI Sta 25+58.78 Δ = 30° 35' 22.0" (RT)
 D = 1' 00' 18.7" L = 3,043.15'
 T = 1,558.78' R = 5,700.00'
 SE = EXIST

-Y2-
 PI Sta 11+41.11 Δ = 36° 43' 40.6" (RT)
 D = 26' 46' 25.4" L = 137.18'
 T = 71.04' R = 214.00'
 SE = SEE PLANS

BEGIN TIP PROJECT B-3159
-L- POT STA 7+75.00
-L- POT STA 7+00.00

JOHN L. PALMER AND WIFE
 MADELINE R. PALMER
 DB 224 PG 477
 DB 615 PG 444
 PB 4 PG 68

JBL PROPERTIES, LLC
 DB 1510 PG 469


JACK C. CHILDERS
 DB 1009 PG 158
 DB 908 PG 161
 DB 910 PG 2

BODDIE-NOELL ENTERPRISES, INC.
 DB 666 PG 820

RIFFLE OIL COMPANY, INC.
 DB 1309 PG 1309

BILLIE S. PARKER
 DB 127 PG 1505

LEE BARKER AND WIFE
 S. J. BARKER
 49 PG 323
 VPG 89



-LPC-
 PI Sta 10+81.05 Δ = 1° 26' 15.2" (LT)
 D = 1' 00' 42.0" L = 142.10'
 T = 71.05' R = 5,663.48'
 SE = .08

-LPC-
 PI Sta 12+77.76 Δ = 0° 50' 41.6" (S)
 D = 44' 00' 40.8" L = 184.00'
 LT = 125.66'
 ST = 66.51'

-LPC-
 PI Sta 14+48.63 Δ = 86° 19' 20.1" (LT)
 D = 47' 44' 47.3" L = 180.79'
 T = 112.53' R = 120.00'
 SE = .08

-LPC-
 PI Sta 15+81.88 Δ = 43° 55' 36.4" (S)
 D = 184.00' L = 126.67'
 LT = 64.99' ST = 64.99'

-LPA-
 PI Sta 10+02.32 Δ = 0° 02' 46.5" (RT)
 D = 0° 59' 48.8" L = 4.64'
 T = 2.32' R = 5,747.48'
 SE = .02


-LPA-
 PI Sta 10+65.97 Δ = 35° 08' 29.1" (S)
 D = 184.00' L = 125.17'
 LT = 61.33' ST = 61.33'

-LPA-
 PI Sta 15+84.35 Δ = 109° 21' 47.2" (LT)
 D = 38' 11' 49.9" L = 286.31'
 T = 211.71' R = 150.00'
 SE = .08

-LPA-
 PI Sta 17+22.57 Δ = 35° 08' 29.1" (S)
 D = 184.00' L = 125.17'
 LT = 61.33' ST = 61.33'

NOTES:
 SEE SHEET 8 FOR L-P PROFILE
 SEE SHEET 9 FOR RPA PROFILE
 SEE SHEET 9 FOR LPA PROFILE
 SEE SHEET 10 FOR -RPC- PROFILE
 SEE SHEET 10 FOR -LPC- PROFILE
 SEE SHEET 2 FOR BRIDGE DETAIL
 SEE SHEET 2 FOR INTERSECTION DETAILS
 SEE SHEET 3-1, 5-7 FOR STRUCTURES PLANS
 SEE SHEET W-1 - W-4 FOR WALL PLANS

REVISIONS
 1/2013 (REV) DESIGN REVISION - REMOVED RETAINING WALL #3 FROM ALONG -Y-
 08-APR-2014 10:56:00 GEO. ROWAY, DAVIDSON, CADDD, CE TECH.PlanProf.B3159.GED.rv.004.dgn



8/17/99
 08-APP-2014
 C:\projects\83159\83159.dgn
 08-APP-2014
 C:\projects\83159\83159.dgn

m proposed intersection
 rive is 40' wide. New curb



 fore proposed intersection

 ce is 50' wide. New curb
 rance. New curb and gutter

 -L- PC Sta. 21+43.74
 St. This will close the existing

PRELIMINARY PLANS
 DO NOT USE FOR CONSTRUCTION
 ENGLISH SCALE
 1"=100'
 January 7, 2014


PROJECT REFERENCE NO.	SHEET NO.
B-3159	5
BY SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	



- ① PB 8 PG 94
GEORGE V. HANNAH
AND WIFE
PATRICIA W. HANNAH
DB 579 PG 81
- ② DRY CREEK PROPERTIES, INC.
DB 1375 PG 1278
- ③ BOBBY R. CALLICUTT
AND WIFE
BETTY B. CALLICUTT
DB 627 PG 842
DB 639 PG 223
- ④ THOMAS P. MAJNEY
DB 877 PG 101
- ⑤ R. TYLER FREEMAN
AND WIFE
ESTHER S. FREEMAN
DB 497 PG 184
- ⑥ GEORGE TOMMY PLOTT
DB 1253 PG 1981

-L-

PI Sta 19+97.13	PI Sta 21+68.66
$\Delta = 14' 36" 42.4" (RT)$	$\Delta = 0' 57" 06.7" (LT)$
$D = 10' 44" 58.8"$	$D = 1' 54" 35.5"$
$L = 135.93'$	$L = 49.84'$
$T = 68.33'$	$T = 24.92'$
$R = 533.00'$	$R = 3,000.00'$
SE = SEE PLANS	SE = SEE PLANS



SIDEWALK / ISLANDS
NOTES:
 SEE SHEET 8 FOR -L- PROFILE
 SEE SHEET 2 FOR INTERSECTION DETAIL

-RPC-			-Y-		
PI Sta 11+97.82	PI Sta 13+50.37	PI Sta 15+01.75	PI Sta 25+58.78		
$\Theta_s = 8^\circ 58' 47.7"$	$\Delta = 17^\circ 41' 38.5" (RT)$	$\Theta_s = 8^\circ 58' 47.7"$	$\Delta = 30^\circ 35' 22.0" (RT)$		
Ls = 184.00'	D = 9' 45' 38.8"	Ls = 184.00'	D = 1' 00' 18.7"		
LT = 122.82'	L = 181.28'	LT = 122.82'	L = 3,043.15'		
ST = 61.48'	T = 91.37'	ST = 61.48'	T = 1,558.78'		
	R = 587.00'		R = 5,700.00'		
	SE = .08		SE = EXIST		


NAD 83/NSRS 2007

B-3159 DESIGN REVISION

- ① Additional drive and of 7th St/NCB and gutter added
- ② Right turn lane

BEGIN CONSTRUCTION
-Y3- POT Sta. 10+00.00

BEGIN CONSTRUCTION
-Y- POC Sta. 11+50.00




02-APR-2014 13:50
 C:\Projects\B3159\DWG\B3159_GEO_INV_006.dwg
 8/17/99

PAVEMENT REMOVAL
 NOTES:
 SEE SHEET 10 FOR -RPC- PROFILE
 SEE SHEET 11 FOR -Y3- PROFILE

-RPA- Pls Sta 11+97.82 $\Delta s = 8' 58" 47.7"$ $Ls = 184.00'$ $LT = 122.82'$ $ST = 61.48'$	-RPA- Pls Sta 13+24.10 $\Delta = 12' 39" 25.3" (RT)$ $D = 9' 45" 38.8"$ $L = 129.67'$ $T = 65.10'$ $R = 587.00'$ $SE = .08$	-RPA- Pls Sta 14+50.15 $\Delta s = 8' 58" 47.7"$ $Ls = 184.00'$ $LT = 122.82'$ $ST = 61.48'$	-Y7- Pls Sta 16+37.49 $\Delta = 77' 12" 46.1" (RT)$ $D = 19' 05" 54.9"$ $L = 404.29'$ $T = 239.54'$ $R = 300.00'$ $SE = .06$	-Y- Pls Sta 25+58.78 $\Delta = 30' 35" 22.0" (RT)$ $D = 1' 00" 18.7"$ $L = 3,043.15'$ $T = 1,558.78'$ $R = 5,700.00'$ $SE = EXIST$
--	---	--	--	--

-RPA-
 Pls Sta 18+86.35
 $\Delta = 48' 51" 27.7" (LT)$
 $D = 12' 54" 16.0"$
 $L = 378.61'$
 $T = 201.68'$
 $R = 444.00'$
 $SE = .08$



NAD 83/NSRS 2007



REVISIONS
 1/20/13 (AEV) DESIGN REVISION - REMOVED RETAINING WALL #3 FROM ALONG -Y-.



08-APR-2014 13:59 G:\PROJECTS\13059\GEO\PCWY\DAVIDSON\CADD\GETECH\PlanPrcf\B3159_GEO_inv_007.dgn

NOTES:
 SEE SHEET 9 FOR -RPA- PROFILE.
 SEE SHEET 11 FOR -Y7- PROFILE.





05-APR-2014 10:34:44 C:\Users\jacobson\Documents\PROJECTS\B3159\B3159.dgn
 L:\Projects\B3159\B3159.dgn
 5/28/19

PROJECT REFERENCE NO. B-3159	SHEET NO. 9
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	



08-APR-2014 10:22
 C:\p\projects\B3159\ROADWAY\DAVIDSON\CAADD.GEOTECH\PLAN\PROF\B3159_GEO.plt -RPA\LPA_009.dgn
 5/28/19





5/28/99

08-APR-2014 10:48 AM C:\PROJ\B3159\CADD\GEO\TECH\PLAN\RPC\LPC\RPC&LPC.dgn

5/28/99

D:\APP-2014\05159\GEO\RDWY\DAVIDSON\CADD\GEO\RDWY\B3159_GEO.plt...Y3&Y7_011.dgn

PROJECT REFERENCE NO. B-3159	SHEET NO. 11
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	



SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC	Line or Boring ID
							C.SAND	F.SAND	SILT	CLAY	10	40	200			
SS-1	26 RT	16+00	4.8-5.8	A-2-6(1)	37	20	55.5	14.1	8.2	22.1	73	39	24	-	-	LPC
SS-2	25 RT	14+40	4.6-5.6	A-7-5(10)	65	18	15.9	35.0	20.9	28.2	100	92	55	-	-	RPC
SS-3	25 RT	14+40	9.6-10.6	A-5(0)	42	NP	21.1	41.6	23.1	14.1	100	89	44	-	-	RPC
SS-4	25 RT	14+40	24.6-25.6	A-4(0)	31	NP	19.5	45.3	23.1	12.1	100	92	44	-	-	RPC
SS-5	60 RT	17+30	4.6-5.6	A-7-5(19)	67	25	12.7	23.3	25.8	38.2	100	95	69	-	-	RPC
SS-12	67 LT	36+00	4.4-5.4	A-7-5(14)	57	17	10.3	25.6	30.0	34.2	100	95	71	-	-	Y
SS-13	67 LT	36+00	9.4-10.4	A-7-6(13)	46	18	10.9	20.1	26.8	42.3	100	95	73	-	-	Y
SS-17	87 LT	30+85	9.2-10.2	A-5(3)	49	8	21.9	32.6	27.4	18.1	94	80	48	-	-	Y
SS-19	8 RT	15+35	4.3-5.3	A-7-5(40)	85	45	11.1	13.5	11.1	64.4	100	94	78	-	-	LPA
SS-20	8 RT	15+35	9.3-10.3	A-7-6(16)	46	26	11.9	25.4	14.5	48.3	100	96	68	-	-	LPA
SS-21	8 RT	15+35	14.3-15.3	A-5(3)	45	5	4.2	49.3	32.4	14.1	100	99	57	-	-	LPA
THE FOLLOWING SAMPLES ARE FROM PROJECT 38331.1.1 (B-3159) PDEA																
SS-1	76 LT	12+67	9.7-10.7	A-2-4(0)	39	3	30.2	44.3	19.4	6.1	98	82	33	-	-	B-1 (-L-)
SS-2	76 LT	12+67	19.7-20.7	A-2-4(0)	25	NP	18.6	62.7	16.7	2.0	100	92	32	-	-	B-1 (-L-)
SS-3	6 LT	14+07	4.9-5.9	A-6(7)	39	21	18.6	35.5	19.4	26.5	99	91	52	-	-	B-2 (-L-)
SS-4	6 LT	14+07	9.9-10.9	A-2-4(0)	37	3	25.7	48.0	18.2	8.2	100	88	34	-	-	B-2 (-L-)