NOTES

Drawings NCDOT" dated January

Specifications for Roads and

2. Do not program signal for late

unless otherwise directed by

3. Phase 1 and/or phase 5 may be

4. The order of phase 3 and phase

5. Disconnect existing loops 2C, 2D,

current ITS and Signals Design

night flashing operation

Structures" dated January 2012.

1. Refer to "Roadway Standard

2012 and "Standard

the Engineer.

6C, and 6D.

Section.

presence mode.

7. In the event of loop

4 may be reversed.

6. Set all detector units to

replacement, refer to the

Manual and submit a Plan of

Record to the Signal Design

to obstruct sight distance of vehicles turning right on red.

countdown the flashing "Don't

be removed at the direction of

11. Existing lane control signs may

12. Pavement markings are existing.

operation only. Coordinated signal system timing values

13. Maximum times shown in timing

chart are for free-run

supersede these values.

**LEGEND** 

**EXISTING** 

8. Locate new cabinet so as not

9. Omit "WALK" and flashing

"DON'T WALK" with no

10. Program pedestrian heads to

pedestrian calls.

Walk" time only.

the Engineer.

<u>PROPOSED</u>

lagged.



17,011													UASIS	2070	LUUP	& DEI	EU	IOR	ΤIΛ	STAL	_LAII	ON CF	1AK	ı
PHASE													I	NDUCTI	VE LO	0PS		DET	ECT	OR F	ROGRA	MMING	ì	
SIGNAL FACE	Ø 1 + 5	6	2 2 + + 5 6	3		FLASH							LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTENSION FULL TIME DELAY	STRETCH TIME	I DELAY TIME	<	NEW CARD
11	-	<b>←</b>   •	R	<del>}                                    </del>	- <del>                                    </del>	<del></del>							1 A	6X40	0	2-4-2	-	1	Υ	Y -	-	-	-	Υ
21, 22	R	R	G C	R	R	Y							2A, 2B	6X6	300	EXIST	-	2	Υ	Υ -	-	-	T-	Υ
31	R	R I	₹   F	? G	_ R	R							2C, 2D	6X6	90	EXIST	-			) ISC	ONNEC <sup>-</sup>	-	<u> </u>	-
32	R	R	$R \mid F$	≀ G	R	R							3A	6X60	0	2-4-2	-	3	Υ	Υ -	-	3	-	Υ
41	R	R I	₹ F	R	G	. R							3B	6X60	0	2-4-2	_	3	Y	Υ -	-	10		Y
42	R	R	7 F	R	G	R	1						4A	6X40	0	2-4-2	_	4	Y	Y -	_	3	<u></u> -	Y
51	-	<del>-R</del> -	<b>—</b>   <del>∢</del>	<del>}                                    </del>	- <del>- R</del>	<del></del>							4B	6X40	0	2-4-2	-	4	Y	Υ -	_	10	┷	Y
61, 62	R	G	₹ (	+	+	+	1						5A	6X40	+5	2-4-2	_	5	Y	Y -	_	_	-	Y
P31, P32		DW C	_	-	+	DRK	W - Walk						6A,6B	6X6	300	EXIST	-	6	<u> </u>	Y -	_	_	<u>↓-</u>	Y
	+		_	+	+	+-	1 0" 0011 1	Walk					6C,6D	6X6	90	EXIST	_	<u> </u>	!	)ISC	ONNEC.	-	<u> </u>	-
P61, P62	DW	WL	W	/ DW	JUW	טאא	DRK – Dark						S1	6X6	+215	EXIST	-			_   -	_	_	Y	Y
								ii	H .		!!! i		S2	6X6	+215	EXIST	_	_	'	-   -	_	_	Y	Y
<u>SIGNA</u>		AC	<u>E</u> :	[ . D	<u> </u>			ļi	11				S3	6X6	+230	EXIST	_		<u> </u>	_   -	_	-	Y	
All Heads L.E.D.							35 	ii	' 1	::		S4	6X6	+230	EXIST	-	_	_	-   -	_	_	Υ	Υ	

- Existing Loops

SR 1278 (S. College Dr.)

Y G 21, 22 32 42 P31, P32 P61, P62 Disconnect

SR 1278 (S. College Dr.)

Disconnect

Existing Loops ——

45 MPH -3% Grade

61,62

TIE-

12"

	OASIS	2070	TIMING	G CHART	Ī						
	PHASE										
FEATURE	1	2	3	4	5	6					
Min Green 1 *	7	12	7	7	7	12					
Extension 1 *	2.0	6.0	2.0	2.0	2.0	6.0					
Max Green 1 *	15	60	25	25	15	60					
Yellow Clearance	3.0	4.8	4.1	3.6	3.0	4.7					
Red Clearance	2.8	1.2	2.4	2.6	3.1	1.0					
Red Revert	2.0	2.0	2.0	2.0	2.0	2.0					
Walk 1 *	-	-	7	-	-	7					
Don't Walk 1	-	-	28	-	-	14					
Seconds Per Actuation *	-	1.5	-	-	-	1.5					
Max Variable Initial *	-	34	-	-	-	34					
Time Before Reduction *	-	15	-	-	-	15					
Time To Reduce *	-	30	-	-	-	30					
Minimum Gap	-	3.0	-	-	-	3.0					
Recall Mode**	-	SOFT RECALL	-	-	-	SOFT RECALL					
Vehicle Call Memory	-	YELLOW	-	-	-	YELLOW					
Dual Entry	-	-	-	-	-	-					
Simultaneous Gap	ON	ON	ON	ON	ON	ON					


\* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

$\bigcirc$	Traffic Signal Head	<b></b>
<b>O</b>	Modified Signal Head	N/A
<del>_</del>	Sign	<u> </u>
<b>↓</b>	Pedestrian Signal Head With Push Button & Sign	<b>+</b>
$\bigcirc$	Type II Signal Pedestal	•
	Signal Pole with Guy	
	Signal Pole with Sidewalk Guy	
0	- Metal Pole with Mastarm	
	Inductive Loop Detector	$\subset = = = = = = = = = = = = = = = = = = =$
	Controller & Cabinet	K K M
	Junction Box	
	2-in Underground Conduit	
N/A	Right of Way	
$\longrightarrow$	Directional Arrow	$\longrightarrow$
N/A	Curb Ramp	
$\langle \! \Delta \! \rangle$	Street Name Sign (D3-1)	$\triangle$
B	No U Turn Sign (R3-4)	$^{lack}$
<b>(C)</b>	Combined Through and Left Arrow Sign (R3-6L)	0
	Combined Through and Right Arrow Sign (R3-6R)	

Signal Upgrade SR 1278 (S. College Drive)

SR 1300 (E. Green Drive) Guilford County Division 7 High Point June 2014 PREPARED BY: R.N. Zinser PLAN DATE:

'50 N.Greenfield Pkwy.Garner.NC 27529 PREPARED BY: T. L. AVERETE REVIEWED BY: REVISIONS INIT. DATE



SEAL

**←** - - - **← ≻** 01+6 PHASING DIAGRAM DETECTION LEGEND DETECTED MOVEMENT UNDETECTED MOVEMENT (OVERLAP) UNSIGNALIZED MOVEMENT ← − − > PEDESTRIAN MOVEMENT

02+6

02+5

45 MPH -2% Grade (E)

<sup>\*\*</sup> May be changed to Min Recall by Time of Day at discretion of City Traffic Engineer.