


TIP NO.	SHEET NO.
W-5206AM	PMP-1A
APPROVED: <u>Steve Miller</u> <small>DocuSigned by: Steve Miller BFB0C1CEEB48</small>	
DATE: 9/25/2015	
SEAL	



**PAVEMENT MARKING SCHEDULE**

SYMBOL	DESCRIPTION	
TU	WHITE DIAGONAL	<u>THERMOPLASTIC(12", 90 MILS)</u>
		<u>THERMOPLASTIC(24", 120 MILS)</u>
T2	WHITE STOPBAR	
T3	WHITE CROSSWALK LINE	
		<u>THERMOPLASTIC(4", 120 MILS)</u>
T8	2 FT. - 6 FT./SP WHITE MINISKIP	
T9	2 FT. - 6 FT./SP YELLOW MINISKIP	
TC	10 FT. WHITE SKIP	
TD	3 FT. - 9 FT./SP WHITE MINISKIP	
TE	WHITE SOLID LANE LINE	
TI	YELLOW DOUBLE CENTER	
		<u>THERMOPLASTIC(4", 90 MILS)</u>
TA	WHITE EDGELINE	
TB	YELLOW EDGELINE	
		<u>THERMOPLASTIC(8", 90 MILS)</u>
TN	WHITE GORELINE	
TP	YELLOW DIAGONAL	
		<u>THERMOPLASTIC PAVEMENT MARKING SYMBOLS (90 MILS)</u>
UA	LEFT TURN ARROW	
UB	RIGHT TURN ARROW	
UC	STRAIGHT ARROW	
UE	COMBO.STRAIGHT/RIGHT	
UT	U-TURN ARROW	
		<u>SNOWPLOWABLE RAISED PAVEMENT MARKERS</u>
ME	YELLOW & YELLOW	
MF	CRYSTAL & RED	

**GENERAL NOTES**

- THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.
- A) INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE AS FOLLOWS:
 

ROAD NAME	MARKING	MARKER
NC24/NC87(BRAGG BLVD)	THERMOPLASTIC	SNOWPLOWABLE RAISED
NC24/NC210	THERMOPLASTIC	SNOWPLOWABLE RAISED
-Y- LINES	THERMOPLASTIC	SNOWPLOWABLE RAISED
  - B) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.
  - C) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS.
  - D) PASSING ZONES WILL BE DETERMINED IN THE FIELD AND MUST BE APPROVED BY THE ENGINEER.
  - E) STOP BAR LOCATION AT NON-SIGNALIZED INTERSECTIONS MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER.
  - F) UNLESS OTHERWISE SPECIFIED, HEATED-IN-PLACE THERMOPLASTIC MAY BE USED IN LIEU OF EXTRUDED THERMOPLASTIC FOR STOP BARS, SYMBOLS, CHARACTERS AND DIAGONALS. IF HEATED-IN-PLACE IS USED, IT SHALL BE PAID FOR USING THE EXTRUDED THERMOPLASTIC PAY ITEM.

**ROADWAY STANDARD DRAWING**

- THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:
- | STD. NO. | TITLE  |
|----------|--|
| 1205.01  | PAVEMENT MARKINGS - LINE TYPES AND OFFSETS               |
| 1205.02  | PAVEMENT MARKINGS - TWO-LANE AND MULTILANE ROADWAYS      |
| 1205.04  | PAVEMENT MARKINGS - INTERSECTIONS                        |
| 1205.05  | PAVEMENT MARKINGS - TURN LANES                           |
| 1205.09  | PAVEMENT MARKINGS - PAINTED ISLANDS                      |
| 1250.01  | RAISED PAVEMENT MARKERS - INSTALLATION SPACING           |
| 1253.01  | RAISED PAVEMENT MARKERS - SNOWPLOWABLE                   |
| 1261.01  | GUARDRAIL AND BARRIER DELINEATORS - INSTALLATION SPACING |
| 1261.02  | GUARDRAIL AND BARRIER DELINEATORS - TYPES AND MOUNTING   |

9/14/2015 8:17:58 AM G:\Transportation\TR14.011.00 W-5206AM Pavement Marking\PMP-1A.dgn