

**This electronic collection of documents is provided  
for the convenience of the user  
and is Not a Certified Document –**

**The documents contained herein were originally issued  
and sealed by the individuals whose names and license  
numbers appear on each page, on the dates appearing  
with their signature on that page.**

**This file or an individual page  
shall not be considered a certified document.**



GEOTECHNICAL ENGINEER

ENGINEER

SEAL 028893




Michael Stephens

9/14/2016

DATE

SIGNATURE

DATE



### SOLDIER PILE WALL WITH PRECAST PANEL - TYPICAL SECTIONS

AT THE CONTRACTOR'S OPTION, CONNECT COPING TO PANELS WITH DOWELS OR EXTEND COPING DOWN BACK OF PANELS AND PILES.  
 \*SEE CONCRETE DITCH BEHIND WALL DETAILS.  
 \*\*SEE PLANS FOR FINISHED GRADE OR END BENT SLOPE DETAILS.

#### NOTES:

- FOR SOLDIER PILE RETAINING WALLS, SEE SOLDIER PILE RETAINING WALLS PROVISION.
- DRILLED-IN H-PILES ARE REQUIRED FOR RETAINING WALL NO. 2.
- AT THE CONTRACTORS OPTION USE A SOLDIER PILE RETAINING WALL WITH PRECAST CONCRETE PANELS THAT MEET SECTION 1077 OF THE STANDARD SPECIFICATIONS FOR RETAINING WALL NO. 2.
- PAINT GALVANIZED H-PILES GRAY IN ACCORDANCE WITH ARTICLE 442-12 OF THE STANDARD SPECIFICATIONS FOR RETAINING WALL NO. 2.
- AT THE CONTRACTOR OPTION USE A SOLDIER PILE RETAINING WALL WITH A CAST-IN-PLACE REINFORCED CONCRETE FACE FOR RETAINING WALL NO. 2.
- BEFORE BEGINNING SOLDIER PILE WALL DESIGN FOR RETAINING WALL NO. 2, SURVEY WALL LOCATION AND SUBMIT A REVISED WALL PROFILE VIEW (WALL ENVELOPE) FOR REVIEW. DO NOT START WALL DESIGN OR CONSTRUCTION UNTIL THE REVISED WALL ENVELOPE IS ACCEPTED.

DESIGN RETAINING WALL NO. 2 FOR THE FOLLOWING:

- H = DESIGN HEIGHT + WALL EMBEDMENT
- DESIGN LIFE = 100 YEARS
- MINIMUM WALL EMBEDMENT ELEVATION = 3,042 FT
- MINIMUM PILE PENETRATION INTO ROCK = 10 FT
- IN-SITU ASSUMED MATERIAL PARAMETERS FOR COLLUVIUM, ALLUVIUM AND FILL IN-SITU ASSUMED MATERIAL PARAMETERS ABOVE ELEVATION 3062 FT  
 UNIT WEIGHT,  $\gamma = 120$  LB/CF  
 FRICTION ANGLE,  $f = 32$  DEGREES  
 COHESION,  $c = 0$  LB/SF
- IN-SITU ASSUMED MATERIAL PARAMETERS FOR RESIDUAL ABOVE ELEVATION 3,055 FT:  
 UNIT WEIGHT,  $\gamma = 125$  LB/CF  
 FRICTION ANGLE,  $f = 34$  DEGREES  
 COHESION,  $c = 0$  LB/SF
- IN-SITU ASSUMED MATERIAL PARAMETERS FOR PARTIALLY WEATHER ROCK ABOVE ELEVATION 3050 FT:  
 UNIT WEIGHT,  $\gamma = 135$  LB/CF  
 FRICTION ANGLE,  $f = 38$  DEGREES  
 COHESION,  $c = 0$  LB/SF
- IN-SITU ASSUMED MATERIAL PARAMETERS ROCK:  
 UNIT WEIGHT,  $\gamma = 150$  LB/CF  
 FRICTION ANGLE,  $f = 45$  DEGREES  
 COHESION,  $c = 0$  LB/SF

PREPARED BY: MHS	DATE: 9/14/16
REVIEWED BY: SCC	DATE: 9/14/16

### SOLDIER PILE WALL WITH CAST-IN-PLACE FACE - TYPICAL SECTION

\*SEE CONCRETE DITCH BEHIND WALL DETAILS.  
 \*\*SEE PLANS FOR FINISHED GRADE OR END BENT SLOPE DETAILS.

PROJECT NO.: **B-5380**

**AVERY** COUNTY


STATION: **12+65.00 -L- to 13+50.00 -L-**

SHEET 2 OF 3

**NORTH CAROLINA**  
**DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**

**GEOTECHNICAL**  
**ENGINEERING UNIT**

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	
1	MHS	7-12-16	3	-	-	W-2
2	-	-	4	-	-	



**NOTES:**

- FOR SOIL NAIL RETAINING WALLS, SEE SOIL NAIL RETAINING WALLS PROVISION.
- BEFORE BEGINNING SOIL NAIL WALL DESIGN FOR RETAINING WALL NO.2, SURVEY WALL LOCATION AND SUBMIT A REVISED WALL PROFILE VIEW (WALL ENVELOPE) FOR REVIEW. DO NOT START WALL DESIGN OR CONSTRUCTION UNTIL THE REVISED WALL ENVELOPE IS ACCEPTED.
- DESIGN RETAINING WALL NO.2 FOR THE FOLLOWING:
- 1) H = DESIGN HEIGHT + EMBEDMENT
  - 2) DESIGN LIFE = 100 YEARS
  - 3) MINIMUM EMBEDMENT DEPTH = 2 FT
  - 4) IN-SITU ASSUMED MATERIAL PARAMETERS FOR COLLUVIUM, ALLUVIUM AND FILL IN-SITU ASSUMED MATERIAL PARAMETERS ABOVE ELEVATION 3062 FT  
 UNIT WEIGHT,  $\gamma = 120$  LB/CF  
 FRICTION ANGLE,  $f = 32$  DEGREES  
 COHESION,  $c = 0$  LB/SF
  - 5) IN-SITU ASSUMED MATERIAL PARAMETERS FOR RESIDUAL ABOVE ELEVATION 3,055 FT:  
 UNIT WEIGHT,  $\gamma = 125$  LB/CF  
 FRICTION ANGLE,  $f = 34$  DEGREES  
 COHESION,  $c = 0$  LB/SF
  - 6) IN-SITU ASSUMED MATERIAL PARAMETERS FOR PARTIALLY WEATHER ROCK ABOVE ELEVATION 3050 FT:  
 UNIT WEIGHT,  $\gamma = 135$  LB/CF  
 FRICTION ANGLE,  $f = 38$  DEGREES  
 COHESION,  $c = 0$  LB/SF
  - 7) IN-SITU ASSUMED MATERIAL PARAMETERS ROCK:  
 UNIT WEIGHT,  $\gamma = 150$  LB/CF  
 FRICTION ANGLE,  $f = 45$  DEGREES  
 COHESION,  $c = 0$  LB/SF
- DRILLING OPERATIONS WILL LIKELY ENCOUNTER COLLUVIAL/ALLUVIAL BOULDERS, CONTRACTOR SHALL USE DRILLING TECHNIQUES THAT WILL MAINTAIN HOLE STABILITY AND ALLOW ALL NAILS TO BE INSTALLED TO THEIR REQUIRED DESIGN DEPTHS.
- (1) VERIFICATION TEST AND (2) PROOF TESTS WILL BE REQUIRED UNLESS OTHERWISE DIRECTED BY THE GEOTECHNICAL OPERATIONS ENGINEER.

**SOIL NAIL WALL - TYPICAL SECTION**

\*SEE CONCRETE DITCH BEHIND WALL DETAILS.  
 \*\*SEE PLANS FOR FINISHED GRADE OR END BENT SLOPE DETAILS.

PROJECT NO.: **B-5380**  
**AVERY** COUNTY  
 STATION: **12+65.00 -L- to 13+50.00 -L-**  
 SHEET 3 OF 3

**NORTH CAROLINA**  
**DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**

**GEOTECHNICAL**  
**ENGINEERING UNIT**

**SOIL NAIL OPTION FOR**  
**RETAINING WALL #2**

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	
1	-	-	3	-	-	W-3
2	-	-	4	-	-	

PREPARED BY: MHS	DATE: 9/14/16
REVIEWED BY: SCC	DATE: 9/14/16

