

GRADE POINT ELEV. @ STATION 14+59.3 -L- = 5.23  
 BED ELEV. @ STATION 14+59.3 -L- = -4.30  
 ROADWAY SLOPES VARIES 2:1 TO 4:1  
 FOR UTILITY INFORMATION SEE UTILITY PLANS AND SPECIAL PROVISIONS

**LOCATION SKETCH**

**TOTAL STRUCTURE QUANTITIES**

CLASS A CONCRETE		
BARREL @	3.79	CY/FT 759.16 C.Y.
WING ETC.		29.53 C.Y.
TOTAL		788.69 C.Y.
REINFORCING STEEL		
BARREL		124,206 LBS.
WINGS ETC.		2229 LBS.
TOTAL		126,435 LBS.
CULVERT EXCAVATION*		
		1 LS
FOUNDATION CONDITIONING MATERIAL 546 TONS		
RIP RAP CLASS II 31 TON		
GEOTEXTILE FABRIC 28 S.Y.		
1 1/2' GALVANIZED STEEL PIPE 145 L.F.		

\*PAYMENT FOR REMOVAL OF EXISTING CULVERT SHALL BE INCLUDED IN THE LUMP SUM PRICE BID FOR CULVERT EXCAVATION.

**HYDRAULIC DATA**

DESIGN DISCHARGE = 3000 CFS  
 FREQUENCY OF DESIGN FLOOD = 50 YR.  
 DESIGN HIGH WATER ELEVATION = 6.8 FT.  
 DRAINAGE AREA = 4.0 SQ. MI.  
 BASE DISCHARGE (Q100) = 3300 CFS  
 BASE HIGH WATER ELEVATION = 6.89 FT.

**OVERTOPPING FLOOD DATA**

OVERTOPPING DISCHARGE = <1700 CFS  
 FREQUENCY OF OVERTOPPING FLOOD = <5 YR.  
 OVERTOPPING FLOOD ELEVATION = 5.4 FT.

**NOTES:**

ASSUMED LIVE LOAD = HL-93 OR ALTERNATE LOADING.  
 DESIGN FILL = 1.5 FEET  
 FOR OTHER DESIGN DATA AND NOTES, SEE STANDARD NOTE SHEET SN.  
 THE 18 INCH DIAMETER PIPE, AND 15 INCH DIAMETER PIPE THROUGH THE SIDEWALL OF THE CULVERT SHALL BE LOCATED BY THE ENGINEER. THE REINFORCING STEEL SHALL BE FIELD BENT AS NECESSARY TO CLEAR PIPES.  
 THE 36 INCH DIAMETER PIPE, AND 15 INCH DIAMETER PIPE THROUGH THE WING WALLS SHALL BE LOCATED BY THE ENGINEER. THE REINFORCING STEEL SHALL BE FIELD BENT AS NECESSARY TO CLEAR PIPES.  
 TRAFFIC ON FRONT STREET AND BURNETT BOULEVARD SHALL BE MAINTAINED AT VARIOUS STAGES OF CONSTRUCTION. IN ORDER TO MAINTAIN TRAFFIC, THE CULVERT SHALL BE CONSTRUCTED IN SECTIONS AS DIRECTED BY THE ENGINEER, AND IN ACCORDANCE WITH THE TRAFFIC CONTROL PLANS.

STEEL IN THE BOTTOM SLAB MAY BE SPLICED AT THE PERMITTED CONSTRUCTION JOINT AT THE CONTRACTOR'S OPTION. EXTRA WEIGHT OF THE STEEL DUE TO THE SPLICES WILL BE PAID FOR BY THE CONTRACTOR.

TRANSVERSE CONSTRUCTION JOINTS SHALL BE USED IN THE BARREL, SPACED TO LIMIT THE POURS TO A MAXIMUM OF 70 FEET. LOCATION OF JOINTS SHALL BE SUBJECT TO THE APPROVAL OF THE ENGINEER.

ONE PERMITTED CONSTRUCTION JOINT WILL BE ALLOWED IN THE END CURTAIN WALL.

FOR CULVERT DIVERSION DETAILS AND PAY ITEMS, SEE EROSION CONTROL PLANS.

A 3 FOOT STRIP OF FILTER FABRIC SHALL BE ATTACHED TO THE FILL FACE OF THE WING COVERING THE ENTIRE LENGTH OF THE EXPANSION JOINT.

NO PRECAST REINFORCED BOX CULVERT OPTION WILL BE ALLOWED.

BED MATERIAL PLACED BETWEEN SILLS IN THE CULVERT SHALL PROVIDE A CONTINUOUS LOW FLOW CHANNEL BETWEEN THE LOWER SILLS. THE MATERIAL SHALL BE EXCAVATED FROM THE STREAM OR FLOODPLAIN AT THE PROJECT SITE DURING CONSTRUCTION. ONLY MATERIAL THAT IS EXCAVATED FROM THE STREAM BED MAY LINE THE LOWER SILLS. RIPRAP MAY BE USED TO SUPPLEMENT NATIVE MATERIAL IN THE HIGH SILL BARREL. IF RIPRAP IS USED, NATIVE MATERIAL SHALL BE PLACED TO FILL ALL VOIDS AND PROVIDE A LEVEL SURFACE FOR ANIMAL PASSAGE. NATIVE MATERIAL IS SUBJECT TO APPROVAL BY THE ENGINEER AND MAY BE SUBJECT TO PERMIT CONDITIONS.

THE ENGINEER SHALL CHECK THE LENGTH OF THE CULVERT BEFORE STAKING IT OUT TO VERIFY THAT IT WILL PROPERLY TAKE CARE OF THE FILL.

**NOTES (CONTINUED):**

DIMENSIONS FOR THE WING LAYOUT AS WELL AS ADDITIONAL REINFORCING STEEL EMBEDDED IN BARREL SHOWN ON WING SHEETS.

3" Ø WEEP HOLES INDICATED TO BE IN ACCORDANCE WITH THE SPECIFICATIONS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.


FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

THE SCOUR CRITICAL ELEVATION IS THE AS-BUILT BOTTOM OF CULVERT FLOOR SLAB ELEVATION. SCOUR CRITICAL ELEVATIONS ARE USED TO MONITOR POSSIBLE SCOUR PROBLEMS DURING THE LIFE OF THE STRUCTURE.

CONCRETE IN CULVERTS TO BE POURED IN THE FOLLOWING ORDER:

1. WING FOOTINGS AND CULVERT FLOOR SLAB INCLUDING 4 INCHES OF VERTICAL WALLS.
2. THE REMAINING PORTIONS OF THE WALLS AND WINGS TO FULL HEIGHT.
3. ROOF SLABS AND HEAD WALLS.
4. CONSTRUCTION JOINTS SHALL BE PERMITTED IN ORDER TO CONSTRUCT CULVERT IN ACCORDANCE WITH THE VARIOUS TRAFFIC CONTROL STAGES.


CONTRACTOR SHALL SUBMIT TO THE ENGINEER FOR APPROVAL, A DETAILED DEMOLITION PLAN FOR THE REMOVAL OF THE EXISTING CONCRETE CULVERT.



**PROFILE ALONG CULVERT**

PROJECT NO. 17BP.3.R.28  
 NEW HANOVER COUNTY  
 STATION: 14+60.69 -L-

REPLACES CULVERT NO. 640028



9/28/2016

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

TRIPLE 12 FT. X 7 FT.  
 CONCRETE BOX CULVERT  
 90°(-L-) 60°(-Y-) SKEW

DRAWN BY : C. DESROCHERS  
 CHECKED BY : M. PAYNE  
 DATE : MAY 2014  
 DATE : MAY 2014

28-SEP-2016 14:26  
 \*\*\*\*\*DCN\*\*\*\*\*  
 PAYN5628 AT LUS290333

**ATKINS** 1616 E. MILLBROOK ROAD, SUITE #310  
 RALEIGH, NORTH CAROLINA 27609  
 (919) 876-6888 NCBES #F-0326

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	C-2
1			3			TOTAL SHEETS
2			4			11