

## NOTES

REPAIR LOCATIONS AND ESTIMATED QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR UNDERSIDE OF DECK AND DIAPHRAGM REPAIRS, SEE "OVERHANG, DIAPHRAGM AND BRIDGE RAIL REPAIR DETAILS" SHEET.

- \* CLASS II SURFACE PREPARATION, CLASS III SURFACE PREPARATION AND CONCRETE FOR DECK REPAIR ARE NOT ANTICIPATED. TOKEN PAY ITEMS ARE INDICATED FOR PRICING PURPOSES IN CASE UNANTICIPATED CLASS II OR CLASS III AREAS ARE
- OUANTITY HAS BEEN INCREASED DUE TO THE POTENTIAL FOR FURTHER DETERIORATION SINCE THE FIELD INSPECTION BY STRUCTURES MANAGEMENT UNIT.

AS-BUILT REPAIR QUANTITY TABLE				
TOP OF DECK REPAIRS				
	ESTIMATE		ACTUAL	
SCARIFYING BRIDGE DECK	184 SY			
HYDRO-DEMOLITION OF BRIDGE DECK	184 SY			
CLASS II SURFACE PREPARATION	20.0 SY *			
CLASS III SURFACE PREPARATION	0.5 SY *			
BRIDGE JOINT DEMOLITION	24.7 SF			
CONCRETE FOR DECK REPAIR	3.0 CF *			
CONCRETE REPAIRS (RAIL AND CURB)	3.0 CF			
UNDERSIDE OF DECK REPAIRS				
SHOTCRETE REPAIRS	ESTIMATE		ACTUAL	
	AREA SF	VOLUME CF	AREA SF	VOLUME CF
UNDERSIDE OF DECK	0.0	0.0		
OVERHANG DIAPHRAGMS	0.0	0.0		
UNDERSIDE OF OVERHANG	27.3	17.2♦		
INTERIOR DIAPHRAGMS	7.4	4.7 ♦		

VALUES IN CHARTS REPRESENT ESTIMATED UNDERSIDE OF DECK REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE MINIMUM OF 1" BEHIND REBAR AND MINIMUM 2" CLEAR TO SAWCUT. SEE REPAIR DETAILS.

0.8 0.5 ♦

ESTIMATE

3.0 LF

ACTUAL

OUTSIDE FACE OF DECK

UNDERSIDE EPOXY RESIN INJECTION

APPROX. CLASS II AREA

APPROX.CLASS III AREA

BRIDGE JOINT DEMOLITION

UNDERSIDE REPAIR

DIAPHRAGM REPAIR TEST LOCATION

ERI EPOXY RESIN INJECTION

BUNCOMBE COUNTY 421 BRIDGE NO.

SHEET 3 OF 3 John Manhamaccont

SEAL

32492

· CACINEER

YANNA

1/21/2017

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

> PLAN OF SPANS SPAN C

REVISIONS SHEET NO S-19 DOCUMENT NOT CONSIDERE FINAL UNLESS ALL SIGNATURES COMPLETED

CL BRIGHT DATE : \_\_05/16\_ DRAWN BY : DATE : \_\_07/16 CHECKED BY :

ASPHALT THICKNESS

(INCH)

43/4"

51/2"

5"

INFORMATION IN CHART TAKEN FROM DECK EVALUATION

NFORMATION IN CHART TAKEN FROM DECK EVALUATION
DATED 4/25/2016.

★ CONCRETE COVER FOR TOP BARS IN THE DECK IS PER THE
EXISTING BRIDGE PLANS.

■ CONCRETE COMPRESSIVE STRENGTH COULD NOT BE TESTED DUE TO
THE PRESENCE OF ASPHALT OVERLAY.

TEST LOCATION

#3

CONCRETE COVER

(INCH)

11/2" \*

11/2" ★

11/2" ★

CONCRETE STRENGTH

(PSI)