NOTES: REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE. FOR REPAIRS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET. SPAN B CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP FACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISION. SPAN A BOTTOM OF CAP DAMAGED AREA ---- EPOXY RESIN INJECTION 1.0 SF - SHOTCRETE REPAIR SPAN B SPAN A 1.0 SF - SHOTCRETE REPAIR 1.0 SF SHOTCRETE REPAIR APPROX. GROUND LINE I-5892 PROJECT NO._ BUNCOMBE COUNTY 422 ELEVATION BRIDGE NO._ (SPAN B FACE) END VIEW SHEET 2 OF 4 DocuSigned by: John STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION BENT 1 SEAL 7 32492 BENT 1 SPAN B FACE YANNA 1/21/2017 REVISIONS SHEET NO. DATE: S-37 DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED CL BRIGHT DATE : 05/16 DRAWN BY : . CHECKED BY : ___ S. WANCE DATE : 10/16