DocuSign Envelope ID: 956C06C0-4D4E-4CC1-BF42-406845214163

501 505 507 517 520

1 - 24 X 12

1 - 24 X 24

ONE "U" POST PER SIGN

510 523

2 - 24 X 12

2 - 24 X 24

2 - 21 X 15

TWO "U" POSTS PER SIGN

502 508 516 521

1 - 24 X 12

1 - 24 X 24

ONE "U" POST PER SIGN

511 524

2 - 24 X 12

2 - 24 X 24

2 - 21 X 15

TWO "U" POSTS PER SIGN

503 509 512 522 525

1 - 21 X 15

1 - 24 X 24

ONE "U" POST PER SIGN

513 526

2 - 24 X 12

2 - 24 X 24

2 - 21 X 15

TWO "U" POSTS PER SIGN

504 514 527



2 - 24 X 12

2 - 24 X 24

2 - 21 X 15

TWO "U" POSTS PER SIGN

515 519



2 - 24 X 12

2 - 24 X 24

1 - 21 X 21
1 - 21 X 15

TWO "U" POSTS PER SIGN

506 518



2 - 24 X 12

2 - 24 X 24

1 - 21 X 21
1 - 21 X 15

TWO "U" POSTS PER SIGN

TIP NO.	SHEET NO.
R-3100B	SIGN-3A

APPROVED: DocuSigned by: Betsy L. Watson 35E67BB34F8743F...

DATE: 9/19/2016

SEAL

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Stantec

SIGN NUMBER: U-TURN DETAIL
TYPE: F
QUANTITY: 4

SIGN WIDTH: 21"
HEIGHT: 21"
TOTAL AREA: 3.1 Sq.Ft.

BORDER TYPE: FLUSH
RADII: 1.5"
WIDTH: 0.63"
RECESS: 0.38"

NO. Z BARS:
LENGTH:

BACKG COLOR: White
COPY COLOR: Black

SYMBOL	X	Y	WID	HT
U-TURN ARROW	3.6	3.5	12.7	13.9

MAT'L: 0.063" (1.6MM) ALUMINUM

DESIGN BY: RRH
CHECKED BY: BLW
PROJECT ID: R-3100B
DIV: 12
DATE: Sep 05, 2016

USE NOTES

1. Legend and border shall be direct applied non-reflective sheeting.
2. Background shall be Grade C reflective sheeting.



Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter	Series/Size Text Length