

STATE	STATE PROJECT REFERENCE NO.	SHEET	TOTAL SHEETS
N.C.	U-3633	1	27
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
37649.1.1	STP-0273(1)	P.E.	
		RW & UTIL.	

NOTE: SEE SHEET 2A FOR PLAN SHEET LAYOUT AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

**ROADWAY
SUBSURFACE INVESTIGATION**

PROJ. REFERENCE NO. 37649.1.1 (U-3633) F.A. PROJ. STP-0273(1)
COUNTY GASTON
PROJECT DESCRIPTION MOUNT HOLLY-NC 273 (SOUTH MAIN ST.)
FROM TUCKASEEGE RD. TO HIGHLAND ST.
AT SOUTH MAIN ST.

INVENTORY

CONTENTS

LINE	STATION	PLAN	PROFILE	XSECT
-L-	18+65.00 to 90+00.00	4-9	11-13	18-24
-Y-	15+50.00 to 28+82.00	10,4	14	
-Y1-	10+39.49 to 10+75.00	4	14	
-Y2-	10+22.61 to 19+37.50	4	15	
-Y4-	10+37.65 to 10+80.00	5	15	
-Y5-	16+00.00 to 19+50.00	5	15	
-Y6-	10+45.64 to 11+50.00	5	15	
-Y7-	17+20.00 to 17+50.86	6	16	
-DRI-	10+49.50 to 12+00.00	6	16	
-DR2-	10+49.50 to 12+00.00	6	16	
-Y8-	10+37.51 to 10+75.00	7	16	
-Y10-	10+41.39 to 11+00.00	7	16	
-Y11-	14+00.00 to 22+73.00	8	17	
-Y12-	11+00.00 to 15+25.00	8	17	

SAMPLE SHEET 25

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING, AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N.C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 250-4088. NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOGS, ROCK CORES, OR SOIL TEST DATA ARE PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

PERSONNEL

C.G. MURRAY

J.E. ESTEP


M.R. MOORE

INVESTIGATED BY J.P. ROGERS

CHECKED BY C.B. LITTLE

SUBMITTED BY C.B. LITTLE

DATE MARCH 2012



CONTRACT: ID: U-3633

DRAWN BY: J.K. McClure /JP ROGERS

NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N.C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IT IS CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THE PROJECT.

NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

PROJECT REFERENCE NO. 37649.11(U-3633) SHEET NO. 2

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION				GRADATION				ROCK DESCRIPTION				TERMS AND DEFINITIONS																																																										
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE: <i>VERY STIFF, GRAY, SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HEAVY PLASTIC, A-7-6</i></p>				<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p style="text-align: center;">ANGULARITY OF GRAINS</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>				<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT IF TESTED, WOULD YIELD SPT REFUSAL, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>				<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (IN OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SCREC) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																										
SOIL LEGEND AND AASHTO CLASSIFICATION				MINERALOGICAL COMPOSITION				WEATHERING				TERMS AND DEFINITIONS																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">GENERAL CLASS.</th> <th colspan="3">GRANULAR MATERIALS (< 35% PASSING #200)</th> <th colspan="3">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="3">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>SYMBOL</th> <th>A-1</th> <th>A-2</th> <th>A-3</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-4, A-5</th> <th>A-6, A-7</th> </tr> <tr> <td></td> <td></td> <td>A-1-a</td> <td>A-1-b</td> <td>A-2-1</td> <td>A-2-2</td> <td>A-2-3</td> <td>A-2-4</td> <td>A-2-5</td> <td>A-2-6</td> <td>A-2-7</td> <td>A-2-8</td> </tr> </table>				GENERAL CLASS.		GRANULAR MATERIALS (< 35% PASSING #200)			SILT-CLAY MATERIALS (> 35% PASSING #200)			ORGANIC MATERIALS			GROUP CLASS.	SYMBOL	A-1	A-2	A-3	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7			A-1-a	A-1-b	A-2-1	A-2-2	A-2-3	A-2-4	A-2-5	A-2-6	A-2-7	A-2-8	<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p> <p style="text-align: center;">COMPRESSIBILITY</p> <p>SLIGHTLY COMPRESSIBLE LIQUID LIMIT LESS THAN 31 MODERATELY COMPRESSIBLE LIQUID LIMIT EQUAL TO 31-50 HIGHLY COMPRESSIBLE LIQUID LIMIT GREATER THAN 50</p> <p style="text-align: center;">PERCENTAGE OF MATERIAL</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>>10%</td> <td>>20%</td> <td>HIGHLY</td> </tr> <tr> <td></td> <td></td> <td></td> <td>35% AND ABOVE</td> </tr> </table>				ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	>10%	>20%	HIGHLY				35% AND ABOVE	<p>FRESH - ROCK FRESH, CRYSTALLINE BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> <p>VERY SLIGHT (V SL.) - ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> <p>SLIGHT (SL.) - ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> <p>MODERATE (MOD.) - SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> <p>MODERATELY SEVERE (MOD. SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL</i></p> <p>SEVERE (SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, YIELDS SPT N VALUES < 100 BPF</i></p> <p>VERY SEVERE (V SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS. WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, YIELDS SPT N VALUES < 100 BPF</i></p> <p>COMPLETE - ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>			
GENERAL CLASS.		GRANULAR MATERIALS (< 35% PASSING #200)			SILT-CLAY MATERIALS (> 35% PASSING #200)			ORGANIC MATERIALS																																																														
GROUP CLASS.	SYMBOL	A-1	A-2	A-3	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7																																																											
		A-1-a	A-1-b	A-2-1	A-2-2	A-2-3	A-2-4	A-2-5	A-2-6	A-2-7	A-2-8																																																											
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																			
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																			
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																			
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																			
HIGHLY ORGANIC	>10%	>20%	HIGHLY																																																																			
			35% AND ABOVE																																																																			
<p>PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30</p> <p style="text-align: center;">CONSISTENCY OR DENSENESS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td><4 4 TO 10 10 TO 30 30 TO 50 >50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td><2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30</td> <td><0.25 0.25 TO 0.50 0.5 TO 1.0 1 TO 2 2 TO 4 >4</td> </tr> </table>				PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	<4 4 TO 10 10 TO 30 30 TO 50 >50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	<2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30	<0.25 0.25 TO 0.50 0.5 TO 1.0 1 TO 2 2 TO 4 >4	<p style="text-align: center;">MISCELLANEOUS SYMBOLS</p> <p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION SOIL SYMBOL ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT INFERRED SOIL BOUNDARY INFERRED ROCK LINE ALLUVIAL SOIL BOUNDARY DIP & DIP DIRECTION OF ROCK STRUCTURES</p> <p>SPT TEST BORING AUGER BORING CORE BORING MONITORING WELL PIEZOMETER INSTALLATION SLOPE INDICATOR INSTALLATION CONE PENETROMETER TEST SOUNDING ROD</p>				<p style="text-align: center;">ROCK HARDNESS</p> <p>VERY HARD - CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</p> <p>HARD - CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p> <p>MODERATELY HARD - CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p> <p>MEDIUM HARD - CAN BE GROUDED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p> <p>SOFT - CAN BE GROUDED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p> <p>VERY SOFT - CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</p>																																																		
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																			
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	<4 4 TO 10 10 TO 30 30 TO 50 >50	N/A																																																																			
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	<2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30	<0.25 0.25 TO 0.50 0.5 TO 1.0 1 TO 2 2 TO 4 >4																																																																			
<p style="text-align: center;">TEXTURE OR GRAIN SIZE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <td>BOULDER (BLDR.)</td> <td>COBBLE (COB.)</td> <td>GRAVEL (GR.)</td> <td>COARSE SAND (CSE, SD.)</td> <td>FINE SAND (F, SD.)</td> <td>SILT (SL.)</td> <td>CLAY (CL.)</td> </tr> <tr> <td>GRAIN SIZE MM</td> <td>305</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> <tr> <td>GRAIN SIZE IN.</td> <td>12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>				U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE, SD.)	FINE SAND (F, SD.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE MM	305	75	2.0	0.25	0.05	0.005	GRAIN SIZE IN.	12	3					<p style="text-align: center;">ABBREVIATIONS</p> <p>AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS - FOSSILIFEROUS FRAC - FRACTURED, FRACTURES FRAGS - FRAGMENTS HI - HIGHLY</p> <p>MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL W - MOISTURE CONTENT V - VERY</p> <p>VST - VANE SHEAR TEST WEA. - WEATHERED W - UNIT WEIGHT W_d - DRY UNIT WEIGHT</p> <p style="text-align: center;">SAMPLE ABBREVIATIONS</p> <p>S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO</p>																															
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																
	4.76	2.00	0.42	0.25	0.075	0.053																																																																
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE, SD.)	FINE SAND (F, SD.)	SILT (SL.)	CLAY (CL.)																																																																
GRAIN SIZE MM	305	75	2.0	0.25	0.05	0.005																																																																
GRAIN SIZE IN.	12	3																																																																				
<p style="text-align: center;">SOIL MOISTURE - CORRELATION OF TERMS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td rowspan="2">LL - LIQUID LIMIT PL - PLASTIC LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>				SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p style="text-align: center;">EQUIPMENT USED ON SUBJECT PROJECT</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> <tr> <td><input type="checkbox"/> MOBILE B- <input type="checkbox"/> BK-51 <input type="checkbox"/> CME-45C <input type="checkbox"/> CME-550 <input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> CLAY BITS <input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER <input type="checkbox"/> 8" HOLLOW AUGERS <input type="checkbox"/> HARD FACED FINGER BITS <input type="checkbox"/> TUNG.-CARBIDE INSERTS <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER <input type="checkbox"/> TRICONE _____ * STEEL TEETH <input type="checkbox"/> TRICONE _____ * TUNG.-CARB. <input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL <input type="checkbox"/> -B <input type="checkbox"/> -N <input type="checkbox"/> -H HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST</td> </tr> </table>				DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> MOBILE B- <input type="checkbox"/> BK-51 <input type="checkbox"/> CME-45C <input type="checkbox"/> CME-550 <input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> CLAY BITS <input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER <input type="checkbox"/> 8" HOLLOW AUGERS <input type="checkbox"/> HARD FACED FINGER BITS <input type="checkbox"/> TUNG.-CARBIDE INSERTS <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER <input type="checkbox"/> TRICONE _____ * STEEL TEETH <input type="checkbox"/> TRICONE _____ * TUNG.-CARB. <input type="checkbox"/> CORE BIT	<input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL <input type="checkbox"/> -B <input type="checkbox"/> -N <input type="checkbox"/> -H HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST																																											
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																				
LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																				
	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																				
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																				
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																				
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																				
<input type="checkbox"/> MOBILE B- <input type="checkbox"/> BK-51 <input type="checkbox"/> CME-45C <input type="checkbox"/> CME-550 <input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> CLAY BITS <input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER <input type="checkbox"/> 8" HOLLOW AUGERS <input type="checkbox"/> HARD FACED FINGER BITS <input type="checkbox"/> TUNG.-CARBIDE INSERTS <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER <input type="checkbox"/> TRICONE _____ * STEEL TEETH <input type="checkbox"/> TRICONE _____ * TUNG.-CARB. <input type="checkbox"/> CORE BIT	<input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL <input type="checkbox"/> -B <input type="checkbox"/> -N <input type="checkbox"/> -H HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST																																																																				
<p style="text-align: center;">PLASTICITY</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table> <p style="text-align: center;">COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>				NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p style="text-align: center;">FRACTURE SPACING</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table> <p style="text-align: center;">BEDDING</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>> 4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table> <p style="text-align: center;">INDURATION</p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>				TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FEET	VERY CLOSE	LESS THAN 0.16 FEET	TERM	THICKNESS	VERY THICKLY BEDDED	> 4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET																						
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																				
LOW PLASTICITY	0-5	VERY LOW																																																																				
MED. PLASTICITY	6-15	SLIGHT																																																																				
HIGH PLASTICITY	16-25	MEDIUM																																																																				
	26 OR MORE	HIGH																																																																				
TERM	SPACING																																																																					
VERY WIDE	MORE THAN 10 FEET																																																																					
WIDE	3 TO 10 FEET																																																																					
MODERATELY CLOSE	1 TO 3 FEET																																																																					
CLOSE	0.16 TO 1 FEET																																																																					
VERY CLOSE	LESS THAN 0.16 FEET																																																																					
TERM	THICKNESS																																																																					
VERY THICKLY BEDDED	> 4 FEET																																																																					
THICKLY BEDDED	1.5 - 4 FEET																																																																					
THINLY BEDDED	0.16 - 1.5 FEET																																																																					
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																					
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																					
THINLY LAMINATED	< 0.008 FEET																																																																					
<p style="text-align: center;">INSTRUMENTS</p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>				<p style="text-align: center;">BENCH MARK:</p> <p style="text-align: right;">ELEVATION: _____ FT.</p> <p>NOTES: SOIL STRATIGRAPHY IS THROUGH THE BORINGS FOR PROFILES AND CROSS-SECTIONS. BORING ELEVATIONS OBTAINED FROM THE U3633_PS_TIN_110615.TIN FILE.</p>																																																																		

05/08/99

See Sheet 1-A For Index of Sheets
See Sheet 1-B For Conventional Symbols
See Sheet 1-C For Survey Control Sheet



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

GASTON COUNTY


**LOCATION: MOUNT HOLL - NC 273 (SOUTH MAIN STREET) FROM
TUCKASEEGE ROAD TO HIGHLAND STREET AT A&G DRIVE**

**TYPE OF WORK: WIDENING, GRADING, DRAINAGE, PAVING, RESURFACING,
CULVERT, & GUARDRAIL.**


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-3633	2A	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
37649.1.1	STP-0273(1)	PE	
37649.1.2	STP-0273(1)	R/W	
37649.1.3	STP-0273(1)	UTIL	



TIP PROJECT: U-3633



VICINITY MAP




BEGIN T.I.P. PROJECT U-3633
-L- STA. 18 + 65.00

END T.I.P. PROJECT U-3633
-L- STA. 90 + 00.00

THIS IS NOT A CONTROL OF ACCESS PROJECT
THIS PROJECT IS WITHIN THE MOUNT HOLLY MUNICIPAL BOUNDARIES
CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

CONTRACT:



DESIGN DATA

ADT 2014 =	26,800
ADT 2035 =	42,300
DHV =	10 %
D =	55 %
T =	4 % *
V =	50 MPH
* TTST =	2 DUAL 2
FUNC CLASS =	URBAN COLLECTOR
REGIONAL TIER	

PROJECT LENGTH

LENGTH ROADWAY T.I.P. PROJECT U-3633 =	1.346 MI
LENGTH STRUCTURE T.I.P. PROJECT U-3633 =	0.005 MI
TOTAL LENGTH OF T.I.P. PROJECT U-3633 =	1.351 MI

Prepared in the Office of:

DIVISION OF HIGHWAYS
1000 Birch Ridge Dr., Raleigh NC, 27610

2012 STANDARD SPECIFICATIONS


RIGHT OF WAY DATE: MARCH 19, 2013	JASON MOORE, PE PROJECT ENGINEER
LETTING DATE: NOVEMBER 18, 2014	NYA BOAYUE, PE PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER


SIGNATURE: _____ P.E.

ROADWAY DESIGN ENGINEER

SIGNATURE: _____ P.E.



28-MAR-2012 07:51
C:\Projects\U3633_GEO_RDWY_GASTON\CADD_GEO\TECH\Plan\Prof\U3633_GEO Inv_002A_RDWY_GASTON.dgn
jmculture AT GEH257466



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PURDUE
GOVERNOR

Eugene A. Conti, Jr.
SECRETARY

April 25, 2012

STATE PROJECT: 37649.1.1 (U-3633)
FEDERAL PROJECT: STP-0273(1)
COUNTY: Gaston
DESCRIPTION: Mt. Holly – NC 273 (South Main Str.) from Tuckaseege Rd. to Highland Str. at South Main Str.
SUBJECT: Geotechnical Report – Inventory

PROJECT DESCRIPTION

This project is located in eastern Gaston County near the Town of Mt. Holly. The scope of this project is to widen existing NC 273 from two to four lanes from Tuckaseege Road to Highland Street. The project begins approximately 1.5 miles north of I-85. This segment of NC 273 serves as a major thruway from I-85 into Mt. Holly. The following alignments were investigated:

- L- Station 18+65.00 to 90+00.00 (1.35 miles)
- Y- 15+50.00 to 28+82.00 (0.25 miles)
- Y1- 10+39.49 to 10+75.00 (0.01 miles)
- Y2- 10+22.61 to 19+37.50 (0.18 miles)
- Y4- 10+37.65 to 10+80.00 (0.01 miles)
- Y5- 16+00.00 to 19+50.00 (0.07 miles)
- Y6- 10+45.64 to 11+50.00 (0.02 miles)
- Y7- 17+20.00 to 17+50.86 (0.01 miles)
- DR1- 10+49.50 to 12+00.00 (0.03 miles)
- DR2- 10+49.50 to 12+00.00 (0.03 miles)
- Y8- 10+37.51 to 10+75.00 (0.01 miles)

MAILING ADDRESS:
NC DEPARTMENT OF TRANSPORTATION
GEOTECHNICAL ENGINEERING UNIT
1589 MAIL SERVICE CENTER
RALEIGH NC 27699-1589

TELEPHONE: 919-707-6850
FAX: 919-250-4237
WEBSITE:
www.ncdot.gov/doh/preconstruct/highway/geotech

LOCATION:
CENTURY CENTER COMPLEX
ENTRANCE B-2
1020 BIRCH RIDGE DRIVE
RALEIGH NC

- Y10- 10+41.39 to 11+00.00 (0.01 miles)
- Y11- 14+00.00 to 22+73.00 (0.17 miles)
- Y12- 11+00.00 to 15+25.00 (0.08 miles)

The total length of lines investigated is 2.23 miles. The investigation phase of this project was conducted in February 2012. Due to the presence of existing traffic, existing utilities, and design considerations, the field investigation was accomplished with a hand auger, 1/2" bridge rod, and visual reconnaissance. No Standard Penetration Tests were performed within the project corridor during this investigation. 22 soil samples were submitted to the Materials and Tests Unit for laboratory analysis. Rock outcrops were observed within the project corridor on both the east and west side of existing NC 273. Where readily apparent, these outcrops were noted on the planview sheets of the attached inventory report.

AREAS OF SPECIAL GEOTECHNICAL INTEREST

Pond: A pond is located adjacent to the project corridor at the following location:

Line	Station(s)	Offset
-L-	38+00	75' Left

Crystalline Rock: Crystalline rock was encountered within 10' of proposed grade in the following cut section:

Line	Station(s)	Offset
-L-	47+50 to 51+75	Left

Please refer to the cross sections contained in the attached inventory report for a graphical depiction of this area.

Alluvial Soils: Fites Creek and an unnamed tributary serve as the primary drainage outlets for this project. The unnamed tributary is on the eastern side of existing NC 273 and flows almost entirely on severely weathered crystalline rock and crystalline rock. The alluvial soil that was encountered within the project corridor was found immediately adjacent to Fites Creek. Based on field classification, these soils are sandy silts (A-4).

SOIL PROPERTIES

Residual Soils

All residual soils on the project are derived from the metamorphosed quartz diorite and tonalite (mqd) rocks encountered within the project corridor. The dominant residual soil types encountered are silty and sandy clay (A-7-6, A-6), silty sand (A-2-4, A-1-b) and sandy silt (A-4).



Respectfully submitted,

John P. Rogers
Project Geological Engineer

8/17/99

25-MAR-2012 10:56:33 GEO_RDWY_GASTON.CADD_GEOITCHYPlanProj\U3633_GEO_INV_004_GASTON.dgn

PROJECT REFERENCE NO. U-3633		SHEET NO. 4	
RAW SHEET NO.		HYDRAULICS ENGINEER	
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR A/W ACQUISITION		PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	




-L-	-L-	-Y2-
PI Sta 16+35.20	PI Sta 28+35.58	PI Sta 17+47.34
$\Delta = 20' 56' 29.0''$ (LT)	$\Delta = 28' 38' 49.7''$ (RT)	$\Delta = 33' 26' 13.0''$ (RT)
D = 3'16' 26.6"	D = 4'16' 32.9"	D = 15'16' 43.9"
L = 639.62'	L = 669.98'	L = 218.84'
T = 323.42'	T = 342.15'	T = 112.64'
R = 1750.00'	R = 1340.00'	R = 375.00'
SE = 04	SE = 06	SE = SEE PLANS

- EXIST. SIGNAL TO BE UPGRADED
- MONOLITHIC CONC. ISLAND
- PAVEMENT REMOVAL
- SEE SHEET 2-C FOR TRAFFIC DIAGRAM
- SEE SHEET 11 FOR -L- PROFILE
- SEE SHEET 14 FOR -Y- PROFILE
- SEE SHEET 14 FOR -Y1- PROFILE
- SEE SHEET 15 FOR -Y2- PROFILE

8/17/99
23 MAR 2012 11:33 AM
C:\PROJECTS\2012\033\GEO.ROWY_GASTON.CADD_GEO\TECH\Plan\Prof\U3633_GEO.tny.005_GASTON.dgn

PROJECT REFERENCE NO.	SHEET NO.
U-3633	5
RAW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR A/W ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	

-Y5-	-Y6-
PI Sta 19+08.42	PI Sta 12+40.37
$\Delta = 22^{\circ}04'06.7''$ (RT)	$\Delta = 49^{\circ}00'33.9''$ (LT)
D = 8'48'53.0"	D = 2'37'15.8"
L = 250.36'	L = 226.67'
T = 126.75'	T = 120.79'
R = 650.00'	R = 265.00'
SE = SEE PLANS	SE = SEE PLANS




MATCHLINE SEE SHEET 4 - L- STA. 29+00.00

MATCHLINE SEE SHEET 6 - L- STA. 43+00.00

MONOLITHIC CONC. ISLAND
PAVEMENT REMOVAL
SEE SHEET 2-C FOR TRAFFIC DIAGRAM
SEE SHEET 11 FOR -L- PROFILE
SEE SHEET 15 FOR -Y4- PROFILE
SEE SHEET 15 FOR -Y5- PROFILE
SEE SHEET 15 FOR -Y6- PROFILE

REVISIONS

8/17/99



MATCHLINE SEE SHEET 5 -L- STA. 43+00.00

MATCHLINE SEE SHEET 7 -L- STA. 57+00.00


-DRI-	-DR2-	-DR2-
PI Sta 11+92.11	PI Sta 11+79.38	PI Sta 11+62.28
Δ = 11° 51' 18.0" (RT)	Δ = 18° 22' 12.0" (LT)	Δ = 20° 52' 15.9" (RT)
D = 14' 19" 26.2"	D = 114' 35" 29.6"	D = 114' 35" 29.6"
L = 82.76'	L = 16.03'	L = 18.21'
T = 41.53'	T = 8.08'	T = 9.21'
R = 400.00'	R = 50.00'	R = 50.00'

MONOLITHIC CONC. ISLAND
 SEE SHEET 2-C FOR TRAFFIC DIAGRAM
 SEE SHEET 12 FOR -L- PROFILE
 SEE SHEET 16 FOR -Y7- PROFILE
 SEE SHEET 16 FOR -DRI- PROFILE
 SEE SHEET 16 FOR -DR2- PROFILE

CO:\PR-2012\113633_GEO.RDWAY_GASTON\CADD\GEO\CH\Plan\Prof\U3633.GEO.lyr_006_GASTON.dgn
 8/17/99
 11:36:33 AM
 11/17/99

8/17/99
 REVISIONS
 23-MAR-2012 11:57:33 GEO_RDWY_GASTON.CADD_GEDTECH.PlanProf\U3633_GED.unv.007.GASTON.dgn
 23-MAR-2012 11:57:33 GEO_RDWY_GASTON.CADD_GEDTECH.PlanProf\U3633_GED.unv.007.GASTON.dgn

PROJECT REFERENCE NO. U-3633	SHEET NO. 7
RAW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR A/W ACQUISITION PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	




-L-	-Y8-	-Y10-
PI Sta 61+311.3	PI Sta 10+96.16	PI Sta 12+207.5
Δ = 27° 57' 46.0" (RT)	Δ = 20° 00' 09.8" (RT)	Δ = 6° 44' 58.8" (LT)
D = 3' 00' 56.0"	D = 28' 38' 52.4"	D = 1' 36' 50.3"
L = 927.28'	L = 69.82'	L = 418.20'
T = 473.07'	T = 35.27'	T = 209.34'
R = 1,900.00'	R = 200.00'	R = 3,550.00'
SE = 04	SE = SEE PLANS	SE = SEE PLANS

MONOLITHIC CONC. ISLAND
 SEE SHEET 2-C FOR TRAFFIC DIAGRAM
 SEE SHEET 12 FOR -L- PROFILE
 SEE SHEET 16 FOR -Y8- PROFILE
 SEE SHEET 16 FOR -Y9- PROFILE
 SEE SHEET 16 FOR -Y10- PROFILE

INCOMPLETE PLANS
DO NOT USE FOR A/W ACQUISITION

PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION



REVISIONS

MATCHLINE SEE SHEET 7 -L- STA. 70+50.00

MATCHLINE SEE SHEET 9 -L- STA. 84+50.00

23-MAR-2012 13:39 GEO_RDWY_GASTON.CADD_GEOI_TCH.PlanProf/U3633_GEO...v.v.008.GASTON.dgn

-L-	-YII-	-YII-	-YII-	-YII-	-YII-
PI Sta 73+71.29	PI Sta 13+48.15	PI Sta 18+64.38	PI Sta 20+59.32	PI Sta 11+44.05	PI Sta 13+73.66
$\Delta = 24' 18" 53.7' (RT)$	$\Delta = 4' 21" 22.3' (RT)$	$\Delta = 21' 58" 02.1' (RT)$	$\Delta = 6' 41" 48.6' (RT)$	$\Delta = 13' 45" 26.5' (RT)$	$\Delta = 50' 03" 15.6' (RT)$
$\phi = 3' 34" 51.6'$	$D = 0' 50" 51.3'$	$D = 19' 05" 54.9'$	$D = 6' 59" 14.2'$	$D = 22' 55" 05.9'$	$D = 19' 05" 54.9'$
L = 679.00'	L = 513.96'	L = 115.02'	L = 95.84'	L = 60.03'	L = 262.08'
T = 344.69'	T = 257.11'	T = 58.23'	T = 47.98'	T = 30.16'	T = 140.07'
R = 1,600.00'	R = 6,760.00'	R = 300.00'	R = 820.00'	R = 250.00'	R = 300.00'
SE = 03	SE = SEE PLANS	SE = SEE PLANS	SE = SEE PLANS	SE = SEE PLANS	SE = SEE PLANS

- ★ EXIST. SIGNAL TO BE UPGRADED
- MONOLITHIC CONC. ISLAND
- PAVEMENT REMOVAL
- SEE SHEET 2-C FOR TRAFFIC DIAGRAM
- SEE SHEET 13 FOR -L- PROFILE
- SEE SHEET 17 FOR -YII- PROFILE
- SEE SHEET 17 FOR -Y12- PROFILE

8/17/99


23 MAR 2012 11:32:33 GEO_RDWY_GASTON.CADD_GEOTECH.PlanProj\U3633-GEO.rwy_009_GASTON.dgn

PROJECT REFERENCE NO. U-3633	SHEET NO. 9
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR A/W ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	



REVISIONS

MATCHLINE SEE SHEET 9 -L- STA. 84 + 50.00



END T.I.P. PROJECT U-3633
-L- POC STA. 90 + 00.00

-L-
PI Sta 92+48.97
$\Delta = 43^{\circ} 29' 33.6''$ (LT)
$D = 7^{\circ} 57' 27.9''$
$L = 546.54'$
$T = 287.20'$
$R = 720.00'$
$SE = 04$


★ EXIST. SIGNAL TO BE UPGRADED
 SEE SHEET 13 FOR -L- PROFILE

8/17/99

28-MAR-2012 09:03:03 GEO. RDWY_GASTON.CADD_GEO.TECH.PlanProf\U3633_CED.rwy_010_GASTON.dgn

-Y2-	-Y2-
PI Sta 10+52.76	PI Sta 12+21.75
$\Delta = 42^\circ 34' 00.4" (RT)$	$\Delta = 11^\circ 39' 47.3" (LT)$
D = 69' 52' 22.4"	D = 4' 29' 37.6"
L = 60.92'	L = 259.54'
T = 31.94'	T = 130.22'
R = 82.00'	R = 1275.00'
SE = SEE PLANS	SE = SEE PLANS

PROJECT REFERENCE NO.	SHEET NO.
U-3633	10
RAW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR A/W ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	



-Y-	-Y-
PI Sta 17+36.52	PI Sta 21+17.78
$\Delta = 15^\circ 55' 18.9" (RT)$	$\Delta = 28^\circ 45' 24.5" (RT)$
D = 4' 46' 28.7"	D = 9' 32' 57.5"
L = 333.47'	L = 301.4'
T = 167.82'	T = 153.8'
R = 1,200.00'	R = 600.00'
SE = SEE PLANS	SE = SEE PLANS

SEE SHEET 10 FOR -Y- PROFILE
SEE SHEET 15 FOR -Y2- PROFILE

REVISIONS

MATCHLINE SEE SHEET 4 -Y- STA. 14+00.00


MATCHLINE SEE SHEET 4 -Y- STA. 21+00.00

5/28/99


26-MAR-2012 11:58:33 G:\GEO\CADD_GASTON\Projects\U3633\GEO\REF\011-017.ROWY_GASTON.dgn

PROJECT REFERENCE NO. U-3633	SHEET NO. 11
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	

-L- NC 273 (BEATTY DR)





-L- NC 273 (SOUTH MAIN ST)



5/28/99

20-APR-2012 14:42 C:\p\projects\13633\GEO-ROWY-GASTON\GASTON\GASTON.dgn


PROJECT REFERENCE NO. U-3633	SHEET NO. 12
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	




5/28/99

-L- NC 273 (SOUTH MAIN ST)

PROJECT REFERENCE NO. U-3633	SHEET NO. 13
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	



-L- NC 273 (SOUTH MAIN ST)




25-MAR-2012 11:48:33 GEO. RDWY_GASTON\CADD_GEOTECH\Plan\pof\U36333_GED_pfl&pfl-011-017_RDWY_GASTON.dgn

5/28/99


-Y- BELMONT-MT HOLLY RD/SOUTH MAIN ST.

PROJECT REFERENCE NO. U-3633	SHEET NO. 14
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	



-Y- BELMONT-MT HOLLY RD/SOUTH MAIN ST.

-YI- LOWE ST.




26-MAR-2016 11:51:53 GEO_RDWY_GASTON\CADD_GEO\TECH\PI\Proj\U3633_GEO_RDWY_GASTON.dgn

5/28/99

PROJECT REFERENCE NO. U-3633	SHEET NO. 15
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	


-Y2- OLD NC 273

-Y4- SUNSET DR.



-Y5- WEST/EAST CATAWBA DR.

-Y6- FOREST HILLS DR.





25-MAR-2012 10:52:33 GEO_RDWY_GASTON_CADD_GEOTECH\Plan\pof\U3633\GEO_RDWY_GASTON.dgn

5/28/99

25-MAR-2012 11:53:23 GEO. RDWY_GASTON\CADD_GEOTECH\Plan\pof\U3633_GEO.pf1&p1.011-017.RDWY_GASTON.dgn


PROJECT REFERENCE NO. U-3633	SHEET NO. 16
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	




5/28/99

-Y11- RANKIN AVE/TUCKASEEGE RD.

PROJECT REFERENCE NO. U-3633	SHEET NO. 17
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR ACQUISITION	
PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	




-Y12- SOUTH MAIN ST.




26-MAR-2012 11:53:33 GEO. RDWY. GASTON\CADD_GEO\TECH\Plan\Proj\U3633_GEO.pfl\011-017.RDWY_GASTON.dgn


26-MAR-2012 15:46 C:\Projects\U3633\GEO\RDWY_GASTON\CADD_GEDTECH\sec\U3633_Geo_xa.L.RDWY_GASTON.dgn




8/23/99
26-MAR-2012 15:47
C:\Projects\U3633\GEO\RDWY_GASTON\CADD_GEDTECH\Geo_xat.L_RDWY_GASTON.dgn
imcolur AT BEH257486




26-MAR-2012 15:47 C:\Projects\U3633\GEO\RDWY_GASTON\CADD_GEOTECH\Xsec\U3633_Geo_xa.L.RDWY_GASTON.dgn




26-MAR-2012 15:50 C:\Projects\U3633\GASTON\CADD\GASTON\RDWY_GASTON\Geo_xsl\RDWY_GASTON.dgn




-L-




PROJ. REFERENCE NO.	SHEET NO.
U-3633	22




50+00.00



49+50.00






51+00.00

50+50.00

-L-



Station	Ground Elevation (ft)	Proposed Roadway Elevation (ft)	Notes
52+00.00	609.68	613.23	Proposed roadway elevation
51+50.00	610.74	614.40	Proposed roadway elevation
51+75	622.89	627.91	End of rock location
51+50	615.06	615.06	Proposed roadway elevation
51+25	612.39	612.39	Proposed roadway elevation
51+00	595.99	598.37	Proposed roadway elevation

SOIL TEST RESULTS																
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC	Line or Boring ID
							C.SAND	F.SAND	SILT	CLAY	10	40	200			
S-1	CL	23+00	0.0-2.0	A-7-5(21)	57	23	11.2	9.3	20.6	58.9	100	93	80	-	-	L
MS-1	CL	23+00	0.0-2.0	-	-	-	-	-	-	-	-	-	-	30.3	-	L
S-2	CL	23+00	2.0-4.0	A-7-6(11)	45	16	13.4	14.0	32.0	40.6	94	87	69	-	-	L
MS-2	CL	23+00	2.0-4.0	-	-	-	-	-	-	-	-	-	-	26.8	-	L
S-3	CL	23+00	4.0-6.0	A-7-5(22)	59	20	3.7	11.0	42.7	42.6	100	98	86	-	-	L
MS-3	CL	23+00	4.0-6.0	-	-	-	-	-	-	-	-	-	-	36.7	-	L
S-4	65 RT	42+15	1.0-4.0	A-6(2)	28	11	20.1	26.8	28.7	24.4	92	82	50	-	-	L
MS-4	65 RT	42+15	1.0-4.0	-	-	-	-	-	-	-	-	-	-	18.5	-	L
S-5	25 RT	52+50	2.0-3.0	A-4(1)	29	9	35.3	19.9	22.4	22.3	100	79	45	-	-	L
MS-5	25 RT	52+50	2.0-3.0	-	-	-	-	-	-	-	-	-	-	18.6	-	L
S-6	25 RT	52+50	3.0-6.0	A-4(3)	31	4	3.9	22.5	53.3	20.3	100	99	75	-	-	L
MS-6	25 RT	52+50	3.0-6.0	-	-	-	-	-	-	-	-	-	-	33.0	-	L
S-7	15 RT	57+90	2.0-4.0	A-7-5(18)	60	23	19.5	9.9	25.9	44.7	100	87	71	-	-	L
MS-7	15 RT	57+90	2.0-4.0	-	-	-	-	-	-	-	-	-	-	30.7	-	L
S-8	65 RT	67+50	1.0-4.0	A-6(4)	31	14	39.4	12.2	18.0	30.5	100	76	49	-	-	L
MS-8	65 RT	67+50	1.0-4.0	-	-	-	-	-	-	-	-	-	-	16.1	-	L
S-9	40 LT	75+50	1.0-6.0	A-4(0)	33	6	32.5	23.4	23.9	20.3	100	85	45	-	-	L
S-10	40 RT	88+00	1.0-9.0	A-2-4(0)	25	NP	50.2	30.9	14.9	4.1	96	67	19	-	-	L
S-11	50 LT	82+50	1.0-6.0	A-7-5(22)	61	17	1.8	7.7	37.7	52.8	100	99	91	-	-	L
S-12	55 LT	44+00	1.0-4.0	A-7-6(20)	53	25	5.7	18.3	33.4	42.6	100	98	77	-	-	L
MS-12	55 LT	44+00	1.0-4.0	-	-	-	-	-	-	-	-	-	-	33.6	-	L
S-13	65 LT	35+00	1.0-9.0	A-1-b(0)	25	3	59.9	19.8	13.2	7.1	88	48	18	-	-	L