

SURFACING SCHEDULE

ITEM NO	DESCRIPTION	
C1	PROP. APPROX. 1 1/4" ASPHALT CONCRETE S COURSE, TYPE SF9.5A, AT AN AVERAGE RATE SQ. YD	
C2	PROP. APPROX. 1 1/2" ASPHALT CONCRETE S COURSE, TYPE S9.5B, AT AN AVERAGE RATE SQ. YD	
DI	PROP. ASPHALT CONCRETE INTERMEDIATE C TYPE I19.0B, AT VARIABLE DEPTH AT LOCATION AS DIRECTRED BY PROJECT ENGINEER (1	
R1	MILLED EDGELINE RUMBLE STRIPS 1/2" IN DE IN LOCATIONS AS DIRECTED BY PROJECT EN	
R2	MILLED CENTERLINE RUMBLE STRIPS 12" WIL IN LOCATIONS AS DIRECTED BY PROJECT EN	
٧١	MILLED ASPHALT PAVEMENT 1 1/2" IN DEPTH AS DIRECTED BY PROJECT ENGINEER	
т	SHOULDER RECONSTRUCTION	
U	EXISTING ASPHALT	
x	ASPHALT CURB. *SEE SPECIAL PROVISION	

PROJECT REF	SHEET NO.	
2018CPT.1.0	19	
STATE PROJECT	F.A. PROJECT NO	DESCRIPTION

DN

CONCRETE SURFACE ERAGE RATE OF 137.5 LBS. PER

CONCRETE SURFACE RAGE RATE OF 168 LBS. PER

RMEDIATE COURSE ,(WEDGING) AT LOCATIONS

INEER (114 lbs/sy per 1" depth)

PS 1/2" IN DEPTH 8" WIDE

PROJECT ENGINEER

RIPS 12" WIDTH 1/2" IN DEPTH

PROJECT ENGINEER

2" IN DEPTH IN LOCATIONS