

**This electronic collection of documents is provided  
for the convenience of the user  
and is Not a Certified Document –**

**The documents contained herein were originally issued  
and sealed by the individuals whose names and license  
numbers appear on each page, on the dates appearing  
with their signature on that page.**

**This file or an individual page  
shall not be considered a certified document.**

REFERENCE: R-5719

PROJECT: 50473

SEE SHEET 3 FOR PLAN SHEET LAYOUT  
AT TIME OF INVESTIGATION

**STATE OF NORTH CAROLINA**  
DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5719	1	65

**ROADWAY**  
**SUBSURFACE INVESTIGATION**

COUNTY WAYNE  
PROJECT DESCRIPTION DIVISION 4 - US 117 AND  
SR 1135 (COUNTRY CLUB ROAD) INTERCHANGE

**INVENTORY**

**CONTENTS**

<u>LINE</u>	<u>STATION</u>	<u>PLAN</u>	<u>PROFILE</u>
-L-	10+00 TO 68+00	4 TO 8	11 TO 15
-RAMP A-	10+00 TO 25+12	7, 9	16
-RAMP B-	10+00 TO 29+94	5, 6, 9	17
-RAMP C-	10+00 TO 26+24	5, 6, 10	18
-RAMP D-	10+00 TO 29+55	7, 8, 10	19
-Y I-	10+00 TO 26+35	6, 9, 10	20

**CROSS SECTIONS**

<u>LINE</u>	<u>STATION</u>	<u>SHEETS</u>
-L-	10+00 TO 25+00	21 TO 28
-L-	37+00	29
-L-	38+00	30
-L-	40+00	31
-L-	42+00	32
-L-	57+50 TO 68+00	32 TO 38
-RAMP A-	23+50 TO 24+50	39
-RAMP B-	10+00 TO 14+50	40 TO 43
-RAMP C-	10+00 TO 14+00	44 TO 47
-RAMP C-	23+50 TO 25+50	48 TO 49
-RAMP D-	26+50 TO 29+00	50 TO 52
-Y I-	11+00 TO 14+50	53 TO 55
-Y I-	16+00 TO 19+50	55 TO 58
-Y I-	24+00 TO 26+00	59 TO 60

**APPENDICES**

<u>APPENDIX</u>	<u>TITLE</u>	<u>SHEETS</u>
A	LABORATORY RESULTS	61 TO 62
B	CPT LOGS	63 TO 65

**CAUTION NOTICE**

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

- DUGGINS, W. T.  
EKLUND, M. A.  
SMITH, E. H.  
LEE, D. K.  
LEE, S.  
ALEXANDER, M. J.

INVESTIGATED BY TERRACON CONSULTANTS  
DRAWN BY ALEXANDER, M. J.  
CHECKED BY RIGGS, A. F.  
SUBMITTED BY TERRACON CONSULTANTS  
DATE JANUARY 2017



SIGNATURE \_\_\_\_\_ DATE \_\_\_\_\_


**DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED**



NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
**GEOTECHNICAL ENGINEERING UNIT**  
**SUBSURFACE INVESTIGATION**  
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																																														
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</p>										<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOADED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																														
SOIL LEGEND AND AASHTO CLASSIFICATION										ANGULARITY OF GRAINS										WEATHERED ROCK (WR)										CRYSTALLINE ROCK (CR)																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (&gt; 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> </tr> <tr> <th>SYMBOL</th> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> </tr> <tr> <th>% PASSING #10 #40 #200</th> <td>50 MX 30 MX 15 MX</td> <td>50 MX 25 MX</td> <td>51 MN 35 MX 35 MX</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td>36 MN 36 MN</td> <td colspan="2">GRANULAR SOILS</td> <td colspan="2">SILT-CLAY SOILS</td> <td>MUCK, PEAT</td> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <td colspan="2">-</td> <td>NP</td> <td>40 MX 41 MN 10 MX 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td>40 MX 41 MN 11 MN 11 MN</td> <td colspan="2">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="2">HIGHLY ORGANIC SOILS</td> <td></td> </tr> <tr> <th>GROUP INDEX</th> <td colspan="2">0</td> <td>0</td> <td>4 MX</td> <td>8 MX</td> <td>12 MX</td> <td>16 MX</td> <td>NO MX</td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td colspan="2">STONE FRAGS. GRAVEL, AND SAND</td> <td>FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <td colspan="5">EXCELLENT TO GOOD</td> <td colspan="5">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td colspan="5">UNSUITABLE</td> </tr> <tr> <td colspan="10">PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS &gt; LL - 30</td> <td colspan="10"></td> <td colspan="10"></td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	SYMBOL	[Pattern]					[Pattern]					[Pattern]					% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX 35 MX	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	GRANULAR SOILS		SILT-CLAY SOILS		MUCK, PEAT	MATERIAL PASSING #40 LL PI	-		NP	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS			GROUP INDEX	0		0	4 MX	8 MX	12 MX	16 MX	NO MX									USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS										GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSUITABLE					PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																														<p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>										<p>NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES &gt; 100 BLOWS PER FOOT IF TESTED.</p>										<p>FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p>									
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																																																	
GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																																													
SYMBOL	[Pattern]					[Pattern]					[Pattern]																																																																																																																																																																																																	
% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX 35 MX	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	36 MN 36 MN	GRANULAR SOILS		SILT-CLAY SOILS		MUCK, PEAT																																																																																																																																																																																												
MATERIAL PASSING #40 LL PI	-		NP	40 MX 41 MN 10 MX 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	40 MX 41 MN 11 MN 11 MN	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS																																																																																																																																																																																														
GROUP INDEX	0		0	4 MX	8 MX	12 MX	16 MX	NO MX																																																																																																																																																																																																				
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS																																																																																																																																																																																																				
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSUITABLE																																																																																																																																																																																															
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																																																																																																																																																																																																												
MINERALOGICAL COMPOSITION										COMPRESSION										NON-CRYSTALLINE ROCK (NCR)										COASTAL PLAIN SEDIMENTARY ROCK (CP)																																																																																																																																																																														
<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>										<p>SLIGHTLY COMPRESSIBLE LL &lt; 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL &gt; 50</p>										<p>FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.</p>										<p>COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.</p>																																																																																																																																																																														
PERCENTAGE OF MATERIAL										GROUND WATER										WEATHERING										MISCELLANEOUS SYMBOLS																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>&gt; 10%</td> <td>&gt; 20%</td> <td>HIGHLY</td> </tr> <tr> <td></td> <td></td> <td></td> <td>35% AND ABOVE</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY				35% AND ABOVE	<p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING</p> <p>STATIC WATER LEVEL AFTER 24 HOURS</p> <p>PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA</p> <p>SPRING OR SEEP</p>										<p>FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> <p>VERY SLIGHT (V SL.) ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> <p>SLIGHT (SL.) ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> <p>MODERATE (MOD.) SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> <p>MODERATELY SEVERE (MOD. SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL</p> <p>SEVERE (SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES &gt; 100 BPF</p> <p>VERY SEVERE (V SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES &lt; 100 BPF</p> <p>COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>										<p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</p> <p>INFERRED SOIL BOUNDARY</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP &amp; DIP DIRECTION OF ROCK STRUCTURES</p> <p>SPT DMT TEST</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>CONE PENETROMETER TEST</p> <p>SOUNDING ROD</p> <p>TEST BORING WITH CORE</p> <p>SPT N-VALUE</p>																																																																																																																																																						
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																																									
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																																																																																																									
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																																																																																																									
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																																																																																																									
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY																																																																																																																																																																																																									
			35% AND ABOVE																																																																																																																																																																																																									
TEXTURE OR GRAIN SIZE										RECOMMENDATION SYMBOLS										ROCK HARDNESS										ABBREVIATIONS																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>GRAIN SIZE</th> <th>MM</th> <th>305</th> <th>75</th> <th>2.0</th> <th>0.25</th> <th>0.05</th> <th>0.005</th> </tr> <tr> <td></td> <td>IN.</td> <td>12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005		IN.	12	3					<p>UNDERCUT</p> <p>SHALLOW UNDERCUT</p> <p>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</p> <p>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</p> <p>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</p>										<p>VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</p> <p>HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p> <p>MODERATELY HARD CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p> <p>MEDIUM HARD CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p> <p>SOFT CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p> <p>VERY SOFT CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</p>										<p>AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI. - HIGHLY</p> <p>MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY</p> <p>VST - VANE SHEAR TEST WEA. - WEATHERED W - UNIT WEIGHT W<sub>d</sub> - DRY UNIT WEIGHT</p> <p>SAMPLE ABBREVIATIONS S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO</p>																																																																																																																																		
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																																						
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																																																						
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																																						
GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005																																																																																																																																																																																																					
	IN.	12	3																																																																																																																																																																																																									
SOIL MOISTURE - CORRELATION OF TERMS										EQUIPMENT USED ON SUBJECT PROJECT										FRACTURE SPACING										BEDDING																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PLASTIC RANGE (PI)</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PLASTIC RANGE (PI)	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>DRILL UNITS:</p> <p><input type="checkbox"/> CME-45C</p> <p><input type="checkbox"/> CME-55</p> <p><input type="checkbox"/> CME-550</p> <p><input type="checkbox"/> VANE SHEAR TEST</p> <p><input type="checkbox"/> PORTABLE HOIST</p> <p><input checked="" type="checkbox"/> DIEDRICH D-50</p> <p><input checked="" type="checkbox"/> ACKER RENEGADE</p> <p>ADVANCING TOOLS:</p> <p><input type="checkbox"/> CLAY BITS</p> <p><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</p> <p><input type="checkbox"/> 8" HOLLOW AUGERS</p> <p><input type="checkbox"/> HARD FACED FINGER BITS</p> <p><input type="checkbox"/> TUNG-CARBIDE INSERTS</p> <p><input checked="" type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</p> <p><input checked="" type="checkbox"/> TRICONE <input type="checkbox"/> 2 1/16" STEEL TEETH</p> <p><input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.</p> <p><input checked="" type="checkbox"/> 3/4" HOLLOW STEM AUGERS</p> <p><input checked="" type="checkbox"/> TRICONE <input type="checkbox"/> 3/8" STEEL TEETH</p> <p>HAMMER TYPE:</p> <p><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</p> <p>CORE SIZE:</p> <p><input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N</p> <p>HAND TOOLS:</p> <p><input type="checkbox"/> POST HOLE DIGGER</p> <p><input checked="" type="checkbox"/> HAND AUGER</p> <p><input type="checkbox"/> SOUNDING ROD</p> <p><input type="checkbox"/> VANE SHEAR TEST</p>										<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table>										TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET	<p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>																																																																																																																																			
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																										
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																																										
PLASTIC RANGE (PI)	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																										
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																																										
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																										
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																																																									
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																																									
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																									
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																									
CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																									
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																									
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																									
PLASTICITY										INDURATION										BENCH MARK: N/A - SEE NOTES										ELEVATION: N/A FEET																																																																																																																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NON PLASTIC</th> <th colspan="2">PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td></td> <td>0-5</td> <td></td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>6-15</td> <td></td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>16-25</td> <td></td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>26 OR MORE</td> <td></td> <td>HIGH</td> </tr> </table>										NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH		0-5		VERY LOW	SLIGHTLY PLASTIC	6-15		SLIGHT	MODERATELY PLASTIC	16-25		MEDIUM	HIGHLY PLASTIC	26 OR MORE		HIGH	<p>REPORT PREPARED USING PROVIDED TIN FILE (r5719_ls.tnl.tin)</p>										NOTES:										DATE: 8-15-14																																																																																																																																																										
NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																																																																																																																																									
	0-5		VERY LOW																																																																																																																																																																																																									
SLIGHTLY PLASTIC	6-15		SLIGHT																																																																																																																																																																																																									
MODERATELY PLASTIC	16-25		MEDIUM																																																																																																																																																																																																									
HIGHLY PLASTIC	26 OR MORE		HIGH																																																																																																																																																																																																									
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>																				<p>FIAD - FILLED IMMEDIATELY AFTER DRILLING</p>																																																																																																																																																																																								

**TIP PROJECT: R-5719**



**VICINITY MAP**



STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**WAYNE COUNTY**

**LOCATION: US-117 AND SR-1135 (COUNTRY CLUB RD.) INTERCHANGE**

**TYPE OF WORK: GRADING, DRAINAGE, PAVING, STRUCTURE**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5719	3	65
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
50473.1.FD1		PE	



THIS PROJECT IS NOT WITHIN ANY MUNICIPAL BOUNDARIES  
CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD III  
THIS IS A CONTROLLED ACCESS PROJECT WITH ACCESS BEING LIMITED TO INTERCHANGES.

**INCOMPLETE PLANS**  
DO NOT USE FOR R/W ACQUISITION  
**PRELIMINARY PLANS**  
DO NOT USE FOR CONSTRUCTION

**CONTRACT:**

<p><b>GRAPHIC SCALES</b></p> <p>0 50 100 PLANS</p> <p>0 50 100 PROFILE (HORIZONTAL)</p> <p>0 10 20 PROFILE (VERTICAL)</p>	<p><b>DESIGN DATA</b></p> <p>ADT 2015 = 14400 ADT 2040 = 27700 K = 9 % D = 55 % T = 11 % * V = 70 MPH *TTST=8% DUAL=3%</p>	<p><b>PROJECT LENGTH</b></p> <p>LENGTH ROADWAY TIP PROJECT R-5719 = 1.076 MI LENGTH STRUCTURE TIP PROJECT R-5719 = 0.022 MI TOTAL LENGTH TIP PROJECT R-5719 = 1.098 MI</p>	<p>Prepared in the Office of: <b>DIVISION OF HIGHWAYS</b> 1000 Birch Ridge Dr., Raleigh NC, 27610</p>	<p>HYDRAULICS ENGINEER</p> <p>SIGNATURE: _____ P.E.</p>	
			<p>2012 STANDARD SPECIFICATIONS</p> <p>RIGHT OF WAY DATE: AUGUST 2016</p> <p>LETTING DATE: JUNE 2017</p>	<p>T.M. LITTLE, PE PROJECT ENGINEER</p> <p>D.R. ETHRIDGE PROJECT DESIGN ENGINEER</p>	

Date: January 2017  
 WBS Number: 50473  
 TIP Number: R-5719  
 County: Wayne  
 Description: US 117 and SR 1135 (Country Club Road) Interchange Improvements

**Subject: Roadway Geotechnical Report - Inventory**

**Project Description**

The project is located along the existing US 117 corridor between Goldsboro and Mt. Olive in Wayne County. On US 117 (-L-), the project begins approximately 0.6 miles south of the existing at-grade intersection of US 117 and SR 1135 (-Y1-) and continues north along US 117 for approximately 1.1 miles. The -L- alignment is proposed to cross over the -Y1- alignment on dual single-span structures. The proposed interchange also includes ramps in all four quadrants of the interchange on new location. On SR 1135 (-Y1-), the project begins approximately 0.2 miles west of the existing intersection and continues east for approximately 0.3 miles. The -Y1- alignment is proposed to remain in the same location and at nearly the same grade. The project corridor is in a rural setting and much of the surrounding land is undeveloped.

The geotechnical subsurface investigation was performed from January through May of 2016. Standard penetration test (SPT) borings were advanced using Diedrich D-50 and Acker Renegade rotary drill rigs equipped with recently calibrated automatic hammers. SPT borings were advanced utilizing wash boring and hollow stem auger drilling techniques to advance the borings to the necessary depths. Representative soil samples were collected in the field for visual classification and selected samples were submitted for laboratory analysis by Terracon’s soil testing laboratory. Two Shelby tube samples were taken near the proposed structures for consolidation testing. Laboratory testing was performed in general accordance with the AASHTO specifications. In addition to the soil test borings performed along the corridor, a Pagani TG73-200 rig was utilized to perform four cone penetrometer (CPT) soundings. Supplemental hand auger borings were performed during October 2016. Excavated soils were visually classified in the field by a trained geologist. Select representative samples were submitted for laboratory analysis by Terracon’s soil testing laboratory.

The following alignments were investigated by soil testing and visual reconnaissance:

<u>Alignment</u>	<u>Stations</u>
-L-	10+00 to 68+00
-RAMP A-	10+00 to 25+12
-RAMP B-	10+00 to 29+94
-RAMP C-	10+00 to 26+24
-RAMP D-	10+00 to 29+55
-Y 1-	10+00 to 26+35

**Physiography and Geology**

The site is located within the Inner Coastal Plain Physiographic and Geologic Province of North Carolina in Wayne County. The Coastal Plain Province is characterized by subdued topographic features. The existing elevations along the investigated corridor range from approximately 125 feet to 150 feet. In general, the topography at this site is slightly rolling with gentle slopes.

The project is located in the Inner Coastal Plain Physiographic Province with geology consisting of a wedge of unconsolidated sands, silt, and clays interbedded with occasional limestone strata, which rests atop crystalline basement rocks. Based on previous mapping (N.C. Geologic Map 1985) and our knowledge of the local geology, the site falls within the Cretaceous age Black Creek Formation. However, based on our site visit and subsurface conditions encountered, the near surface soils appear to be recent Coastal Plain deposits of alluvial origin and are consistent with interbedded sands, clayey sands and clays typical of Undivided Coastal Plain soils. This type of deposition has resulted in a highly variable subsurface profile along the project alignments. The Undivided Coastal Plain deposits overlie the denser, darker soils belonging to the Black Creek Formation. The Black Creek Formation soils are described as gray to black lignitic clay with thin beds and laminae of fine-grained micaceous sand and contains thin beds and laminae of fine-grained micaceous sand and thick lenses of cross-bedded sand. Glauconitic, fossiliferous clayey sand lenses are common in the upper part.

**Soil Properties**

Soils encountered during this investigation are separated into three categories based on their origin. The soils encountered consist of roadway embankment fill, Undivided Coastal Plain deposited soils and Formational soils.

Roadway embankment soils were encountered at the following approximate locations:

<u>Alignment</u>	<u>Stations</u>
-L-	10+00 to 16+50
-L-	18+23 to 21+26
-L-	48+79 to 68+00
-RAMP A-	10+00 to 14+40
-RAMP B-	10+00 to 10+30
-RAMP D-	10+00 to 15+79

The roadway embankment soils encountered appear to be derived from the nearby existing cuts along the -L- alignment. The roadway embankment soils predominately consist of medium stiff to very stiff, moist to wet, sandy clay (A-6) and medium stiff, moist, highly plastic silty clay (A-7-6). Some loose, moist, silty sand (A-2-4) was also encountered in the borings advanced through the existing roadway embankments.

Roadway embankment fill consisting of moderately plastic sandy clay (A-6) and moderately to highly plastic silty clay (A-7-6) was encountered along -L- between 10+00 and 16+50, 18+20 and 21+35, and from 57+50 to 68+00. In general, the cohesive roadway embankment soil extends to boring termination depths ranging



from 4 to 10 feet. The plasticity indices of the cohesive roadway embankment soils range from 16 to 31 based on laboratory testing.

A majority of existing US 117 through the project was cut below natural ground. Therefore, Undivided Coastal Plain deposits are present at the surface and beneath the roadway embankment soils and asphalt pavement sections. The Undivided Coastal Plain soils can be generalized as alternating layers of silt, clay, and sand extending to the maximum depths of exploration. The near surface Undivided Coastal Plain deposits along the -L-, -RAMP-, and -Y 1- alignments are generally medium stiff to stiff and consists of moist to wet, sandy silt (A-4), sandy clay (A-6) and moderately to highly plastic silty clay (A-7-6). These cohesive soils were encountered at or near the existing ground surface on a majority of the project. The cohesive soils are interbedded with laterally discontinuous, saturated, very loose to medium dense, silty and clayey sand (A-2-4 and A-2-6, respectively). The Undivided Coastal Plain soils encountered deeper than approximately 10 feet below existing grades were generally very soft to soft cohesive soils and very loose to loose granular soils which extend to the top of the Black Creek Formation.

Undivided Coastal Plain soils consisting of moderately plastic sandy clay (A-6) and moderately to highly plastic silty clay (A-7-6) were encountered at or near the existing ground surface between -L- 16+50 and 24+30. The plasticity indices of the cohesive soils range from 17 to 23 based on laboratory testing. The cohesive soils extend to approximately 10 feet below existing grades and are underlain by saturated, very loose to medium dense silty to clayey sand (A-2-4 and A-2-6, respectively) and fine sand (A-3) based on borings advanced to 15 feet below the existing ground surface.

Undivided Coastal Plain soils consisting of moderately plastic sandy clay (A-6) was encountered near the existing ground surface on -RAMP A- between 23+55 and 25+12 or existing SR 1135. The moderately plastic sandy clay extends to a depth of approximately 2 feet below existing grades and is underlain by moist and loose fine sand (A-3).

The Undivided Coastal Plain soils consisting of moderately plastic sandy clay encountered on the -L- alignment continue along the -RAMP B- and -RAMP C- alignments. Moderately plastic sandy clay was encountered near the existing ground surface between -RAMP B- 10+00 and 14+50 and on -RAMP C- between 10+00 and 14+00. Plasticity indices for these soils ranged from 20 to 23 based on laboratory testing.

Undivided Coastal Plain soils consisting of slightly to moderately plastic sandy clay (A-6) were encountered near proposed grade on -RAMP C- between 23+50 and 25+15. The slightly to moderately plastic sandy clay is underlain by soft to medium stiff, moist to wet, sandy silt (A-4).

Undivided Coastal Plain soils consisting of slightly to moderately plastic sandy clay (A-6) and highly plastic silty clay (A-7-6) were encountered on -RAMP D- between 26+70 and 29+30 near existing SR 1135. The sandy clay was encountered near the surface and transitions to highly plastic silty clay at depths of approximately 3 to 5 feet below existing grades between -RAMP D- 26+66 and 29+30. The plasticity indices of the cohesive soils range from 15 to 35 based on laboratory testing.

Undivided Coastal Plain soils consisting of moderately plastic sandy clay (A-6) was encountered along the -Y 1- alignment between 10+00 and 14+05. The cohesive soils extended to hand auger termination depth of 4 feet below the existing ground surface. Moderately plastic sandy clay (A-6) and highly plastic silty clay (A-7-6) were encountered along -Y 1- between 17+00 and 21+00. The cohesive soils extend to hand auger termination depth of 4 feet along -Y 1- although the borings along -L- encountered very loose to loose, saturated silty sand (A-2-4) approximately 18 feet below the existing ground surface. Moderately plastic sandy clay (A-6) and highly plastic silty clay (A-7-6) were encountered near the existing ground surface between 23+50 and 25+50. Some of this area coincides with the -RAMP C- and -RAMP D- alignments. The cohesive soils extend to boring termination depths ranging from 4 to 10 feet. The moderately plastic sandy clay and highly plastic silty clay are interbedded with sandy silt (A-4).

Formational soils of the Black Creek Formation were encountered in the deep borings along the -L- alignment between Elevation 94 and 60 feet. These soils are characterized by their black to gray color and consist of layers of loose to dense, saturated, silty to clayey sands (A-2-4 and A-2-6).

#### **Groundwater**

In general, the corridor drains to Brooks Swamp to the north and Lee Branch to the west. Groundwater was encountered during drilling and sampling along the -L- and -RAMP- alignments at depths ranging from 4 to 13 feet below existing grades. Groundwater was not encountered within 6 feet of proposed grades in the borings performed at the site. The depth of groundwater, beneath the ground surface, will fluctuate with seasonal precipitation and may occur a higher levels at other times of the year above less permeable clayey soils.

#### **Areas of Special Geotechnical Interest**

- 1) Plastic Soils - Moderately to highly plastic soils with plastic indices (PI) of 16 and greater were encountered near proposed subgrade at the following locations:

<u>Alignment</u>	<u>Stations</u>
-L-	10+00 to 24+30
-L-	57+75 to 68+00
-RAMP A-	23+75 to 24+92
-RAMP B-	10+00 to 13+15
-RAMP C-	10+00 to 13+70
-RAMP C-	23+90 to 25+05
-RAMP D-	26+70 to 29+30
-Y 1-	11+50 to 14+00
-Y 1-	17+00 to 21+00
-Y 1-	23+50 to 25+50

A discussion of these plastic soils is located above in the section titled "Soil Properties".

**UNDISTRUBED SAMPLES**


The following "Shelby" tube samples were taken to provide data for the in-situ strength of the soil.

<u>Sample No.</u>	<u>Location</u>	<u>Offset</u>	<u>Depth (ft.)</u>	<u>Test</u>
ST-1	38+83 -L-	68 ft. Left	13.5 - 15.0	Consolidation
ST-2	39+50 -L-	80 ft. Right	15.0 - 17.4	Consolidation



Sincerely,  
Terracon Consultants, Inc.



Matthew J. Alexander, PE  
Project Geotechnical Engineer




Abner F. Riggs, Jr., PE  
Senior Geotechnical Engineer

PROJECT REFERENCE NO. <i>R-5719</i>	SHEET NO. <b>4</b>
 <b>Terracon</b> Consulting Engineers & Scientists 2401 BRENTWOOD ROAD, SUITE 107 RALEIGH, NORTH CAROLINA 27604 PHONE: (919) 873-2211 FAX: (919) 873-9555 NC REGISTERED FIRM: F-0869	
 0 100 200 FEET	

KERMIT SHELTON PRICE  
CAROL PRICE KALEEL  
DB 1619 PG 663


UNDIVIDED COASTAL PLAIN




UNDIVIDED COASTAL PLAIN

KERMIT SHELTON PRICE  
CAROL PRICE KALEEL  
DB 1619 PG 663







MARGARET K. PRICE  
DB 085E PG 663



**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869



KENNETH EARL JOYNER  
 DB 1348 PG 844  
 PC F SLIDE 182

JOHN RICHARD BELL III & WIFE  
 DB 1213 PG 422  
 PC F SLIDE 182

CHRISTOPHER WORTH & WIFE  
 BRANDI WORTH  
 DB 2065 PG 580

MARGARET K. PRICE  
 DB 085E PG 663

MARGARET K. PRICE  
 DB 085E PG 663

TESSIE S. PIERCE  
 DB 848 PG 391  
 PC F PG 130

JAMES T. LOGAN  
 DB 1296 PG 326

MARGARET K. PRICE  
 DB 085E PG 663

MATCH LINE - RAMP B - STA. 18+00  
 SEE SHEET 5

MATCH LINE - L - STA. 29+00  
 SEE SHEET 5

MATCH LINE - RAMP C - STA. 16+50  
 SEE SHEET 5

MATCH LINE - RAMP C - STA. 23+00  
 SEE SHEET 10

MATCH LINE - RAMP B - STA. 27+00  
 SEE SHEET 9

MATCH LINE - Y 1 - STA. 17+50  
 SEE SHEET 9

MATCH LINE - L - STA. 42+00  
 SEE SHEET 7

MATCH LINE - Y 1 - STA. 22+00  
 SEE SHEET 10

UNDIVIDED COASTAL PLAIN

UNDIVIDED COASTAL PLAIN

UNDIVIDED COASTAL PLAIN

30+00 -L-

35+00 -L-

40+00

US-117 SOUTH

US-117 NORTH

US-117 SOUTH

US-117 NORTH

48" WW 15TBW

24" RCP

3" CABLE

30" RCP

30" RCP

15" RCP

15" RCP

15" RCP

18" RCP

15" RCP

15" RCP

15" RCP

30" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP

15" RCP



15" RCP

15" RCP


15" RCP

15" RCP

**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869




SOUTHERN WAYNE  
 RECREATION, INC.  
 DB 1551 PG 797






ROBERT H. SHACKELFORD  
 DB 949 PG 597

PROJECT REFERENCE NO.	SHEET NO.
R-5719	8
<b>Terracon</b>	
Consulting Engineers & Scientists	
2401 BRENTWOOD ROAD, SUITE 107 RALEIGH, NORTH CAROLINA 27604 PHONE: (919) 873-2211 FAX: (919) 873-9555 NC REGISTERED FIRM: F-0869	
 0 100 200 FEET	




MATCH LINE -L- STA. 56+00  
SEE SHEET 7



**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869



**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869



MATCH LINE -RAMP D- STA. 24+00  
SEE SHEET 7

ELMA M. LANE HEIRS  
DB 076E PG 280

UNDIVIDED  
COASTAL PLAIN

ELMA M. LANE HEIRS  
DB 076E PG 280

UNDIVIDED  
COASTAL PLAIN

-YI- POT 23+90.00 =  
-RAMP C- POT 26+24.35  
-RAMP D- POT 29+55.19

MATCH LINE -Y 1- STA. 22+00  
SEE SHEET 6

SR 1135 (COUNTRY CLUB ROAD)

UNDIVIDED  
COASTAL PLAIN

25+00 -RAMP\_C-

XEON ENTERPRISES INC.  
DB 2626 PG 821

DB 2626 PG 824  
XEON ENTERPRISES INC.



UNDIVIDED COASTAL PLAIN

MICHAEL BRENT WILLIAMS  
DB 2629 PG 415

SHIRLEY ANN PIGFORD  
DB 1750 PG 652  
DB 1398 PG 82

MATCH LINE -RAMP C- STA. 23+00  
SEE SHEET 6

GEORGE ALLEN FULGHUM  
& WIFE  
LYNNE W. FULGHUM  
DB 2430 PG 554



68' LT  
 BT  
 DRY  
 10/16

ROADWAY EMBANKMENT, ORANGE AND GRAY,  
 HIGHLY PLASTIC

S-1

67' LT  
 BT  
 DRY  
 10/16

MOIST, MEDIUM STIFF,  
 SILTY CLAY

UNDIVIDED COASTAL PLAIN, BROWN AND ORANGE,  
 MOIST, LOOSE, SILTY SAND AND FINE SAND

(A)



(A) UNDIVIDED COASTAL PLAIN, GRAY, TAN, ORANGE, AND  
 BROWN, MOIST TO WET, MEDIUM STIFF, SANDY CLAY



10+00 11+00 12+00 13+00 14+00 15+00 16+00 17+00 18+00 19+00 20+00



210  
200  
190  
180  
170  
160  
150  
140  
130  
120  
110  
100  
90  
80  
70  
60  
50  
40  
30  
20  
10




180  
170  
160  
150  
140  
130  
120  
110  
100  
90  
80  
70  
60  
50  
40  
30  
20  
10





(B) UNDIVIDED COASTAL PLAIN, ORANGE, TAN, AND GRAY, WET, VERY SOFT TO SOFT, SILTY CLAY









S-5  
S-6

65+RT

BT  
DRY  
10/16


ROADWAY EMBANKMENT, BROWN,  
MOIST, LOOSE, SILTY SAND



67+LT

BT  
DRY  
10/16


ROADWAY EMBANKMENT, ORANGE, BROWN, AND  
GRAY, MOIST, MEDIUM STIFF, SANDY CLAY AND SILTY CLAY

63+00    64+00    65+00    66+00    67+00    68+00









- (A) UNDIVIDED COASTAL PLAIN, BROWN, DRY TO MOIST, MEDIUM STIFF, SILTY CLAY
- (B) UNDIVIDED COASTAL PLAIN, BROWN, DRY TO MOIST, MEDIUM STIFF, SANDY CLAY



**-RAMP A-**








5/28/99






PROJECT REFERENCE NO. R-5719	SHEET NO. 18
---------------------------------	-----------------

**Terracon**  
Consulting Engineers & Scientists  
2401 BRENTWOOD ROAD, SUITE 107  
RALEIGH, NORTH CAROLINA 27604  
PHONE: (919) 873-2211 FAX: (919) 873-9555  
NC REGISTERED FIRM: F-0869












-Y 1-














PROJECT REFERENCE NO.	SHEET NO.
R-5719	23


**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604 160  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0889








150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80





PROJECT REFERENCE NO.	SHEET NO.
R-5719	26


**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0889



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150






150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80





PROJECT REFERENCE NO.	SHEET NO.
R-5719	28

**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869







150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150















150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80










PROJECT REFERENCE NO. R-5719 SHEET NO. 33


**Terracon**  
Consulting Engineers & Scientists  
2401 BRENTWOOD ROAD, SUITE 107  
RALEIGH, NORTH CAROLINA 27604  
PHONE: (919) 873-2211 FAX: (919) 873-9555  
NC REGISTERED FIRM: F-0869



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150










PROJECT REFERENCE NO.	SHEET NO.
R-5719	36


**Terracon**  
Consulting Engineers & Scientists  
2401 BRENTWOOD ROAD, SUITE 107  
RALEIGH, NORTH CAROLINA 27604  
PHONE: (919) 873-2211 FAX: (919) 873-9555  
NC REGISTERED FIRM: F-0889








150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80



PROJECT REFERENCE NO.	SHEET NO.
R-5719	38

**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869




75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40



PROJECT REFERENCE NO. R-5719 SHEET NO. 39

**Terracon**  
Consulting Engineers & Scientists  
2401 BRENTWOOD ROAD, SUITE 107  
RALEIGH, NORTH CAROLINA 27604  
PHONE: (919) 873-2211 FAX: (919) 873-9555  
NC REGISTERED FIRM: F-0869



UNDIVIDED COASTAL PLAIN, BROWN, DRY TO MOIST, MEDIUM STIFF, SANDY CLAY

TAN AND GRAY, MOIST, LOOSE, SAND

TAN AND GRAY, MOIST, MEDIUM STIFF, SANDY CLAY

BT  
FIAD  
05/16

24 + 50

UNDIVIDED COASTAL PLAIN, BROWN, DRY TO MOIST, MEDIUM STIFF, SANDY CLAY

TAN AND GRAY, MOIST, LOOSE, SAND

TAN AND GRAY, MOIST, MEDIUM STIFF, SANDY CLAY

24 + 00


UNDIVIDED COASTAL PLAIN, TAN AND GRAY, DRY TO MOIST, VERY LOOSE, SILTY SAND

TAN AND GRAY, MOIST, SOFT TO MEDIUM STIFF, SANDY SILT AND SILTY CLAY

23 + 50

-RAMP A-

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



S-4

11+04

BT  
 DRY  
 10/16

11+00

10+50

10+00


-RAMP B-

UNDIVIDED COASTAL PLAIN, TAN, GRAY AND RED, MOIST TO WET, VERY SOFT TO STIFF, SANDY CLAY

UNDIVIDED COASTAL PLAIN, TAN, GRAY AND RED, MOIST TO WET, VERY SOFT TO STIFF, SANDY CLAY


ROADWAY EMBANKMENT, TAN, ORANGE, AND GRAY,  
 DRY TO WET, STIFF TO VERY STIFF, SANDY CLAY

UNDIVIDED COASTAL PLAIN, TAN, GRAY AND RED, MOIST TO WET, VERY SOFT TO STIFF, SANDY CLAY




PROJECT REFERENCE NO.	SHEET NO.
R-5719	41


**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869







75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40














12+96

10  
 5  
 7  
 12  
 BT  
 FIAD  
 05/16

UNDIVIDED COASTAL PLAIN, TAN, GRAY AND ORANGE, MOIST TO WET, MEDIUM STIFF TO STIFF, SANDY CLAY AND SILTY CLAY

SEE LINE -L-

6:1

4.93:1

13+00

SEE LINE -L-



UNDIVIDED COASTAL PLAIN, TAN, GRAY AND ORANGE, MOIST TO WET, MEDIUM STIFF TO STIFF, SANDY CLAY AND SILTY CLAY


6:1

3.39:1

12+50

-RAMP C-






UNDIVIDED COASTAL PLAIN, GRAY AND TAN TO BROWN, MOIST TO WET, SOFT TO MEDIUM STIFF, SANDY CLAY, SANDY SILT, AND SILTY CLAY

24+50

UNDIVIDED COASTAL PLAIN, GRAY AND TAN TO BROWN, MOIST TO

WET, SOFT TO MEDIUM STIFF, SANDY CLAY, SANDY SILT, AND SILTY CLAY





BT  
FIAD  
05/16

24+00

UNDIVIDED COASTAL PLAIN, GRAY AND TAN TO BROWN, MOIST TO WET, SOFT TO MEDIUM STIFF, SANDY CLAY, SANDY SILT, AND SILTY CLAY

23+50


-RAMP C-





PROJECT REFERENCE NO.	SHEET NO.
R-5719	50

**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869




75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40



PROJECT REFERENCE NO.	SHEET NO.
R-5719	51

**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869




75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40





PROJECT REFERENCE NO.	SHEET NO.
R-5719	52



**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869












-Y /-



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40




PROJECT REFERENCE NO.	SHEET NO.
R-5719	56

**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869










PROJECT REFERENCE NO.	SHEET NO.
R-5719	58

**Terracon**  
 Consulting Engineers & Scientists  
 2401 BRENTWOOD ROAD, SUITE 107  
 RALEIGH, NORTH CAROLINA 27604  
 PHONE: (919) 873-2211 FAX: (919) 873-9555  
 NC REGISTERED FIRM: F-0869





SS-7

23+79  
 10  
 9  
 8  
 10  
 BT  
 FIAD  
 10/16

23+89  
 8  
 6  
 6  
 4  
 BT  
 FIAD  
 10/16

24+50

24+00

-Y /-

UNDIVIDED COASTAL PLAIN, ORANGE, GRAY, AND BROWN, MOIST TO WET, MEDIUM STIFF TO STIFF, SANDY CLAY, SANDY SILT, AND HIGHLY PLASTIC SILTY CLAY

UNDIVIDED COASTAL PLAIN, BROWN, DRY TO MOIST, LOOSE, SILTY SAND


UNDIVIDED COASTAL PLAIN, BROWN, DRY TO MOIST, LOOSE, SILTY SAND

SEE RAMP D

SEE RAMP C

SEE RAMP D

SEE RAMP C





NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT  
SUBSURFACE INVESTIGATION  
APPENDIX A  
LABORATORY RESULTS

REFERENCE: R-5719

PROJECT: 50473

**Terracon**  
Consulting Engineers & Scientists  
2401 BRENTWOOD ROAD, SUITE 107  
RALEIGH, NORTH CAROLINA 27604  
PHONE: (919) 873-2211 FAX: (919) 873-9555  
NC REGISTERED FIRM: F-0869

INITIALS

DATE

**LABORATORY TESTING SUMMARY**

PROJECT NUMBER: 50473

TIP: R-5719

COUNTY: WAYNE

DESCRIPTION: US 117 AND SR 1135 (COUNTRY CLUB ROAD) INTERCHANGE

Sample No.	Alignment	Station	Offset (feet)	Depth Interval (feet)	AASHTO Class.	L.L.	P.I.	% by Weight				% Retained #4 Sieve	% Passing (sieves)			% Moisture	% Organic
								Coarse Sand	Fine Sand	Silt	Clay		#10	#40	#200		
SS-1	-L-	23+50	CL	1.0 - 2.5	A-6 (8)	36	20	8.6	44.7	19.3	27.4	0	100	97	58	19.1	ND
SS-2	-L-	27+00	CL	1.0 - 2.5	A-6 (2)	26	11	9.3	50.7	16.7	23.3	0	100	97	49	12.0	ND
SS-3	-RAMP B-	29+50	27 RT	6.0 - 7.5	A-6 (11)	40	25	5.4	45.9	18.8	29.9	0	100	98	59	22.9	ND
SS-4	-RAMP C-	22+00	CL	1.0 - 2.5	A-6 (4)	26	14	8.0	50.8	15.8	25.4	0	100	97	53	18.2	ND
SS-5	-RAMP C-	25+50	CL	3.5 - 5.0	A-4 (0)	19	5	7.7	56.2	16.7	19.4	0	100	98	48	13.2	ND
SS-6	-RAMP D-	28+00	CL	3.5 - 5.0	A-6 (3)	31	15	8.7	56.3	10.9	24.1	1	98	95	44	16.1	ND
SS-7	-RAMP D-	29+00	CL	3.5 - 5.0	A-7-6 (18)	53	35	6.8	40.6	14.6	38.0	0	100	98	61	20.1	ND
ST-1	-L-	38+83	68 LT	13.5 - 15.0	A-4 (0)	25	NP	0.4	66.4	20.8	12.4	0	100	100	51	31.4	ND
ST-2	-L-	39+50	80 RT	15.0 - 17.4	A-4 (0)	24	6	21.5	52.3	12.1	14.1	0	100	91	38	19.2	ND
S-1	-L-	13+00	67 LT	0 - 4.0	A-7-6 (11)	45	31	4.3	49.9	10.9	34.9	0	100	100	50	21.1	ND
S-2	-L-	16+00	68 LT	0 - 4.0	A-6 (4)	33	17	4.9	55.6	17.1	22.4	0	100	98	48	15.4	ND
S-3	-L-	16+00	68 RT	1.5 - 4.0	A-2-4 (0)	30	10	26.7	52.8	1.6	18.9	0	97	85	22	ND	ND
S-4	-L-	22+00	70 LT	0 - 4.0	A-6 (5)	38	23	26.3	36.6	4.5	32.6	0	100	90	41	13.7	ND
S-5	-L-	63+00	65 RT	0 - 2.0	A-6 (5)	28	16	7.8	50.3	12.6	29.3	0	100	97	52	13.7	ND
S-6	-L-	63+00	65 RT	2.0 - 4.0	A-2-4 (0)	26	9	15.8	58.2	6.4	19.6	0	100	94	31	ND	ND
S-7	-Y1-	18+00	29 RT	1.0 - 3.0	A-7-6 (30)	59	43	5.1	31.0	16.4	47.5	0	100	99	72	23.0	ND
S-8	-Y1-	22+50	42 LT	3.0 - 4.0	A-6 (4)	28	16	8.6	50.6	12.7	28.1	0	100	97	50	15.2	ND
S-9	-Y1-	25+00	31 LT	1.0 - 4.0	A-4 (1)	26	9	5.8	61.4	12.4	20.4	0	100	99	45	14.1	ND

NP - NONPLASTIC  
 ND - NOT DETERMINED  
 LABORATORY TESTING OF SHELBY TUBE SAMPLES, ST-1 AND ST-2, WAS PERFORMED BY GEOTECHNICS.

*Stephanie H. Huffman*

Certified Lab Technician Signature

114-01-1203  
 Certification Number

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT  
SUBSURFACE INVESTIGATION  
APPENDIX B  
CPT LOGS

REFERENCE: R-5719


PROJECT: 50473

**Terracon**  
Consulting Engineers & Scientists  
2401 BRENTWOOD ROAD, SUITE 107  
RALEIGH, NORTH CAROLINA 27604  
PHONE: (919) 873-2211 FAX: (919) 873-9555  
NC REGISTERED FIRM: F-0869

INITIALS


DATE

# CPT LOG NO. C1




THIS BORING LOG IS NOT VALID IF SEPARATED FROM ORIGINAL REPORT. CPT REPORT R5719.CPT.GPJ TERRACON2015.GDT 3/1/16

# CPT LOG NO. C2



THIS BORING LOG IS NOT VALID IF SEPARATED FROM ORIGINAL REPORT. CPT REPORT R5719.CPT.GPJ TERRACON2015.GDT 3/1/16

### CPT LOG NO. C3



### CPT LOG NO. C4

