COMPUTED BY: D.R.ETHRIDGE DATE: 4/7/2017
CHECKED BY: DATE:

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

PROJECT NO.	SHEET NO.
U-5796	3D-1

Note: Invert Elevations indicated are for Bid Purposes only and shall not be used for project construction stakeout.
See "Standard Specifications For Roads and Structures, Section 300-5".

LIST OF PIPES, ENDWALLS, ETC. (FOR PIPES 48 INCHES & UNDER)

| STATION | LOCATION (LT, RT, OR CL)' | STRUCTURE NO. FROM | STRUCTURE NO. TO | TOP ELEVATION | INVERT ELEVATION | INVERT ELEVATION | SLOPE CRITICAL | SIDE DRAIN PIPE (RCP, CSP, CAAP, HDPE, or PVC) SIZE | | | | | | | | DO NOT USE RCP | DO NOT USE CSP | DO NOT USE CAAP | DO NOT USE HDPE | C.S. PIPE SIZE | | | | | | | | R.C. PIPE CLASS III SIZE | | | | | | | | R.C. PIPE CLASS IV SIZE | | | | | | | | 15" R.C. PIPE (CLASS V) | | | | | ENDWALLS STD. 838.01 OR STD. 838.11 (UNLESS NOTED OTHERWISE) CU. YARDS | | QUANTITIES FOR DRAINAGE STRUCTURES "TOTAL LF PIPE" QUANTITY SHALL BE COL. "A" + (1.3 X COL. "B") LIN. FT. | | | C.B. STD. 840.01 OR STD. 840.02 | FRAME, GRATES, AND HOOD STANDARD 840.03 TYPE OF GRATE | | | CONCRETE TRANSITIONAL SECTION | | GRATED D.I. TYPE "A" STD. 840.17 OR 840.26 | GRATED D.I. TYPE "B" STD. 840.18 OR 840.27 | GRATED D.I. TYPE "D" STD. 840.19 OR 840.28 | FRAME WITH TWO WIDE SLOT SAG GRATES STD. 840.22 | FRAME WITH TWO NARROW SLOT FLAT GRATES STD. 840.29 | | | | | | | | | | | FLOWABLE FILL (CY) | 15" CS PIPE ELBOWS, 0.064" THICK | | CONC. & BRICK PIPE PLUG, C.Y. STD. 840.71 | CONC. COLLARS CL. "B" C.Y. STD. 840.72 | PIPE REMOVAL LIN. FT. | REMARKS |
|---|---|---