

**WETHERILL ENGINEERING**  
 1223 Jones Franklin Rd.  
 Raleigh, N.C. 27606  
 License No. F-0377  
 Bus: 919 851 8077  
 Fax: 919 851 8107

TRANSPORTATION PLANNING/DESIGN - BRIDGE/STRUCTURE DESIGN  
 CIVIL/SITE DESIGN - GIS/GPS - CONSTRUCTION OBSERVATION

PROJECT REFERENCE NO. <b>1-5786</b>	SHEET NO. <b>2A-1</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER 6/6/2017 SEAL 21116 ENGINEER BOB A. MAY	PAVEMENT DESIGN ENGINEER 6/6/2017 SEAL 32142 ENGINEER COREY D. WELLS
Documented by: <i>Bob A. May</i> Documented by: <i>Corey D. Wells</i>	
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	

## PAVEMENT SCHEDULE

(FINAL PAVEMENT DESIGN)

A1	REPAIR OF JOINTED CONCRETE PAVEMENT SLABS (9" +/-).	R1	CONCRETE MEDIAN BARRIER TYPE T. (SEE SHT. 2C-15 FOR SPECIAL DETAIL)
C1	PROP. APPROX. 3½" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5D, AT AN AVERAGE RATE OF 196 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.	R2	PRECAST CONCRETE MEDIAN BARRIER STD. 854.04 (ANCHORED)
C2	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5D, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 2" IN DEPTH.	R3	PRECAST REINFORCED CONCRETE BARRIER (SINGLE FACED)
C3	PROP. APPROX. 2" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5D, AT AN AVERAGE RATE OF 224 LBS. PER SQ. YD.	T	EARTH MATERIAL
C4	PROP. APPROX. 1¾" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5D, AT AN AVERAGE RATE OF 196 LBS. PER SQ. YD.	T1	AGGREGATE SHOULDER BORROW
D1	PROP. APPROX. 4½" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0D, AT AN AVERAGE RATE OF 513 LBS. PER SQ. YD.	U	EXISTING PAVEMENT
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0D, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 2½" IN DEPTH OR GREATER THAN 5¼" IN DEPTH.	V	MILL ¾" OF EXISTING ASPHALT PAVEMENT
D3	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0D, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.	V1	VARIABLE DEPTH MILLING OF EXISTING ASPHALT PAVEMENT, VAR. 0" TO 1¾".
E1	PROP. APPROX. 5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.	V2	MILL 2" OF EXISTING ASPHALT PAVEMENT
E2	PROP. APPROX. 9" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 513 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.	Y	MILLED RUMBLE STRIPS
E3	PROP. APPROX. 5½" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 627 LBS. PER SQ. YD.	Z1	12" SELECT GRANULAR MATERIAL, CLASS III, TYPE 2

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.