



Temporary Rock Silt Check Type A
1.5ft. weir height

-L- POC Sta. 111+87.13 =
-Y4- POT Sta. 15+47.72
LAT V DITCH EST DDE = +/- 204 CY
SEE DETAIL 9

Temporary Rock Silt Check Type A
1.25ft. weir height

LAT 2' BASE DITCH EST DDE = +/- 311 CY
SEE DETAIL 11

FLOATING TURBIDITY CURTAIN
ROCK FILL EMBANKMENT
SEE DETAIL 28
SEE SHEET 3G-1 FOR GEOTECHNICAL SPECIAL DETAIL

Temporary Rock Silt Check Type A
1ft. weir height

LAT 2' BASE DITCH W/CL 1' RIP RAP EST DDE = +/- 407 CY
SEE DETAIL 11

Temporary Rock Silt Check Type A
2.25ft. weir height

NOTE:
INSTALL COIR FIBER MATTING ON DITCH SIDESLOPES FOR ALL PROPOSED DITCHES THAT WILL BE CONVEYING JURISDICTIONAL WATERS.

NOTE:
UTILIZE FABRIC INSERT INLET PROTECTION IN LIEU OF TYPE C INLET PROTECTION WHERE WATER MIGHT POND ON ROADWAY USED BY PUBLIC TRAFFIC.

SEE SHEET 2B-5 FOR INTERSECTION DETAILS
SEE SHEET 39 FOR -L- PROFILE
SEE SHEET 60 FOR -Y4- PROFILE
SEE SHEET 2B-8 FOR CURVE DATA
SEE SHEETS 2D-1 & 2D-2 FOR DITCH DETAILS
SEE SHEETS C-1 THRU C-X FOR CULVERT PLANS
SEE SHEET S-1 THRU S-X FOR NOISE WALL PLANS

MATCHLINE -L- STA 109+00 (SHEET 12)

MATCHLINE -L- STA 122+00 (SHEET 13)