

- 1. PROVIDE 1/4"HIGH BEAM BOLSTERS UPPER AT 4'-0"CTS. ATOP THE METAL STAY-IN-PLACE FORMS TO SUPPORT THE BOTTOM MAT OF "A" BARS. WHEN USING REMOVABLE FORMS, PROVIDE CONTINUOUS HIGH CHAIRS FOR METAL DECK (C.H.C.M.) @ 4'-0"CTS. WITH A HEIGHT TO SUPPORT THE BOTTOM MAT OF "A" BARS A CLEAR DISTANCE OF 21/2" ABOVE THE TOP OF THE REMOVABLE FORM.
- 2. LONGITUDINAL STEEL MAY BE SHIFTED SLIGHTLY, AS NECESSARY, TO AVOID INTERFERENCE WITH STIRRUPS IN PRESTRESSED CONCRETE GIRDERS.
- 3. METAL STAY-IN-PLACE FORMS SHALL NOT BE USED IN BAY 5 DUE TO THE CLOSURE POUR.
- 4. FOR INTERMEDIATE DIAPHRAGM DETAILS, SEE "INTERMEDIATE STEEL DIAPHRAGMS FOR 72" MODIFIED BULB TEE PRESTRESSED CONCRETE GIRDERS"

DESIGN
ENGINEER
OF RECORD: T. TOWNSEND DATE: 3-17

5. FOR END DIAPHRAGM SECTIONS AND DETAILS, SEE "SUPERSTRUCTURE DETAILS"SHEET.

3-17

4-17

DATE:

_ DATE : ___

DRAWN BY : ____TJT

CHECKED BY : AJP

