PMP-2C TIP NO. SHEET NO. APPROVED: Levin W. Bishy UNLESS OTHERWISE SPECIFIED, 4" WHITE LINE DATE: <u>11/16/2017</u> HI-VISIBILITY CROSSWALK MARKINGS SHALL BE USED AT MID-BLOCK CROSSINGS CURB & 6' MIN. FOR STANDARD **GUTTER** STOPBAR WIDTH SIDEWALK CROSSWALKS **REVISIONS** 4' MIN., SEE NOTE 3 STANDARD CROSSWALK DETAIL 'A' CLEAR SPACE, SEE NOTE 4 DETAIL 'A'- DUAL CURB RAMPS DETAIL 'B' **STOPBAR** CURB & **GUTTER** 4' MIN. SIDEWALK - 4' MIN. TO STOP BAR 2' MIN. STANDARD CROSSWALK LINES SEE NOTE 5 GUIDANCE DETAIL FOR CROSSWALK MARKINGS NOTES: 2' MIN. 1. USE THE DETAILS ABOVE AND THE FOLLOWING NOTES FOR GUIDANCE IN PLACING CROSSWALK MARKINGS NOT STATIONED ON THE DETAIL SHEETS OR WHEN FIELD ADJUSTMENTS REQUIRED MOVING STATIONED MARKINGS AS DIRECTED BY THE ENGINEER. REFER TO NCDOT ROADWAY STANDARD DRAWINGS, MUTCD AND ADA STANDARDS FOR ADDITIONAL GUIDANCE. 4' X 4' CLEAR SPACE, SEE NOTE 4 2. THE CROSSWALK MARKINGS SHOWN ON THE ABOVE DETAILS ARE FOR REFERENCE ONLY. ONLY INSTALL CROSSWALK MARKINGS WHERE SHOWN ON THE DETAIL SHEETS OR AS DIRECTED BY THE ENGINEER. THE CROSSWALK MARKING TYPE, STANDARD OR HI-VISIBILITY, SHALL BE INSTALL AS SPECIFIED ON THE DETAIL SHEETS OR AS DIRECTED BY THE ENGINEER. DETAIL 'B'- SINGLE DIAGONAL CURB RAMP 3. SET BACK DISTANCE FROM INSIDE CROSSWALK MARKING TO NEAREST EDGE OF TRAVEL IS 4' MIN. 4. BEYOND THE BOTTOM GRADE BRAKE, A CLEAR SPACE OF 4' X 4' MINIMUM SHALL BE PROVIDED WITHIN THE MARKINGS. 5. SINGLE DIAGONAL CURB RAMPS WITH FLARED SIDES SHALL HAVE A SEGMENT OF CURB 2 FEET LONG MINIMUM LOCATED ON EACH SIDE OF THE CURB RAMP AND WITHIN THE MARKED CROSSING, SEE DETAIL 'B'. CROSSWALK PAVEMENT MARKING **GUIDANCE DETAIL** 6. CURB RAMPS SHALL BE CONSTRUCTED IN ACCORDANCE TO THE LATEST NCDOT ROADWAY STANDARD DRAWINGS. PLANS PREPARED BY:

||/|6/20|7 ||5806_PM_PSH02C.dgn ||Kbisby

RUMMEL, KLEPPER & KAHL, LLP 900 RIDGEFIELD DRIVE SUITE 350 RALEIGH, NORTH CAROLINA 27609–3960 NC LICENSE NO. F–0112 • (919) 878–9560 PROJ. REFERENCE NO.

U-5806

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED